MIL-B-48088A (AR)
AMENDMENT 2
16 July 1987
SUPERSEDING
AMENDMENT 1
12 May 1983

MILITARY SPECIFICATION

BAG LOADING ASSEMBLY
FOR M36A2 PROPELLING CHARGE

This Amendment forms a part of Military Specification MIL-B-48088A(AR), dated 20 August 1981, and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1:

SPECIFICATIONS, FEDERAL:

Delete "PP-B-26" and substitute "PPP-B-26".

Delete "PPP-T-96" and substitute "PPP-T-97".

STANDARDS: Add the following new reference:

"FEDERAL

| | |
|---|---|
| FED-STD-101 | - Test Procedures for Packaging Materials". |

SPECIFICATIONS, MILITARY: Add the following new references:

| | |
|---|---|
| "MIL-B-117 | - Bag, Sleeve and Tubing - Interior Packaging |
| MIL-B-2427 | - Box, Ammunition Packing, Wood, Nailed |
| MIL-T-43036 | - Tape, Pressure-Sensitive Adhesive, Plastic Film, (For Sealing Fiber Containers and Cans) |
| MIL-F-50499 | - Filler Sheet Form (For Use in Ammunition Containers)". |



AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

PAGE 2

2.1, DRAWINGS:

Delete "76-1-1-39" and substitute "76-1-1039".

Delete "76-4-56" and substitute "76-4-59".

Add "76-4-56 - Box, Packing, Metal - Wood M17 for Smokeless Powder".

Add "8806652 - Marking and Sealing for Cylindrical Containers".

Add new paragraph as follows:

"3.5 Data requirements. The contractor shall generate data in accordance with the requirements of the data item description cited in 4.5.5.2.2".

PAGE 6

4.4.2.3:

Critical 1: Delete "*"

Critical 2: Delete in its entirety.

Major category, add new Major defect as follows:

"102 Weight of propellant 100% 3.2 4.5.2".

NOTES: Delete "* This inspection to be performed prior to the gross weight examination".

PAGE 7

4.4.2.4, Title: Add "74-4-56".

PAGE 8

4.4.2.5:

Title: Add "74-4-56".

Major 102: Delete "Gasket" and substitute "Cover".

Minor 201: Delete "seal" after car.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

Add new 4.5.2:

"4.5.2 Weight of propellant.

4.5.2.1 Manual method. The propellant shall be weighed or volumetrically dispensed into a tared container and then check weighed. The initial weighing or dispensing and check weighing shall be performed by different operators on different scales. Weight limits for check weighing should be established within the applicable weight requirements, depending on the accuracy and precision of the weighing system to assure compliance with the charge weight requirements. Any charge of bulk propellant failing to meet the applicable requirement shall be classified defective and removed from the lot.

4.5.2.2 Automated method. The contractor may elect to perform this operation with automated equipment and mandatory process controls. In such cases, process control plans in accordance with Data Item Description DI-P-1604 must be submitted to the Technical Agency (see 6.6) for approval of the automated operation.

5.1.1, Delete in its entirety and substitute the following:

"5.1.1 Level A. The bag loading assembies shall be packed in heat sealed barrier bags complying with Type I, Class E of MIL-B-117. The barrier bag size shall be 22 1/2 inches long by 22 1/2 inches wide, nominal. Approximately 15 pounds of propellant shall be packed in each bag and closed by means of heat sealing. Two heat sealed bags shall be packed in a wooden box (suggested inside box dimensions 14 1/2 X 14 1/2 X 7 1/4 inches) conforming to Grade A, Type I, Class 1 or 3 of MIL-B-2427. Both ends, sides, top and bottom of the wooden box shall be lined with 1/16 inch thick solid water resistance sheet material conforming to MIL-F-50449. The box shall be closed and strapped in accordance with MIL-B-2427. The net weight shall not exceed 30 pounds of propellant."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

5.1.1.1 Add new paragraph:

"5.1.1.1 Alternative level A. The bag loading assemblies shall be packed in propellant packing boxes M17, M18, M24, or M25 complying with dwg. 76-4-56, 76-4-59, 76-4-46 and 7549033 respectively. In lieu of air pressure test, two 4-mil conductive polyolefin or polyethylene bags can be used for all containers listed herein. Each bag must be individually tied and shall be a lay flat style bag made of conductive material in accordance with 5.1.2.1."

5.1.2 Delete in its entirety and substitute the following:

* "5.1.2 Level B. The bag loading assemblies shall be packed in a fiberboard carton conforming to requirements referenced on Drawing No. 7548645. The liner shall be a lay flat style bag made of conductive material in accordance with paragraph 5.1.2.1."

5.1.2.1 Add new paragraph:

"5.1.2.1 Liners. The liners shall be made of conductive polyethylene or polyolefin sheet with a thickness of .0004 inch minimum, surface resistivity shall not exceed 1000 ohms per centimeter, when tested in accordance with Method 4046 of FED-STD-101. The liner shall be closed by rolling down the top and taped with pressure tape made in accordance with PPP-T-97 or MIL-T-43036 to prevent unrolling or it may be heat sealed. Details not specified herein shall comply with PPP-B-26."

5.2.1 Delete in its entirety and substitute the following:

"5.2.1 Level A. Exterior containers shall be marked in accordance with dwg. 8796522. The data marking shall be "Propellant Explosive Class A."

5.2.2 Delete in its entirety and substitute the following:

"5.2.2 Alternative level A. The M17, M18 and M24 containers shall be marked in accordance with dwg. 8858848. The M25 container shall be marked in accordance with dwg. 8858577."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

5.2.3 Add new paragraph:

"5.2.3 Level B. The fiberboard carton or other container shall be marked in accordance with dwg. 9241693."



6.5 Add new paragraph:

"6.5 Data requirements. Deliverable data required by this specification to cited in following paragraph:

| PARAGRAPH | DATA REQUIREMENT | APPLICABLE DID |
|---|---|---|
| 4.5.2.2 | Manufacturing Method Reports (Modified) | DI-P-1604" |

6.6 Add new paragraph:

"6.6 Submission of process control plans for review. Submit plans as required to Commander, U.S. Army Armament, Munitions and Chemical Command, AMSMC-QAT-B, Picatinny Arsenal, NJ 07806-5000."

The margins of this amendment are marked with an asterick or vertical lines to indicated where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

(Project 1315-A890)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.