MIL-B-63299A(AR)
AMENDMENT 8
22 March 1988
SUPERSEDING
AMENDMENT 7
11 March 1988

MILITARY SPECIFICATION

BODY ASSEMBLY
MINE, ANTI-PERSONNEL: HE, M74

This Amendment forms a part of Military Specification MIL-B-63299A(AR), dated 15 December 1983, and is approved for use within the US Army Armament, Munitions and Chemical Command is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, Drawings: Delete "(See 6.7)" and substitute "(See 6.8)".

PRODUCT AND PACKAGING DRAWING: Delete "... DRAWING" and substitute "...DRAWINGS".

3.3.1 Delete "...(see 3.7)." and substitute "...(see 3.7.1)."

PAGE 4

3.5.2: Delete "...a torque of 35 inch pounds (in-lbs) min. without ..." and substitute "...a torque of 18 ± 2 inch pounds (in-lbs) min. without ..."

3.6d: Delete "Presence of shorting eyelet." and substitute "Presence of detonator and micropiston actuator flex cable shunts."

PAGE 8

4.3: Delete "Insert (Dwg. 9292629)" and substitute "Insert, Bushing (Dwg. 9381375)".

PAGE 18

4.4.2.4: Delete present Page 18 and substitute included Page 18.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.4	Insert, Bushing	1	1	9381375
				NEXT HIGHER ASSEMBLY: 9292680

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Diameter of hole		0.65%	3.2	Gage
204	Location of hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 33

4.4.2.19, Major 115: Delete "True position of O-ring groove diameter" and substitute "O-ring runout incorrect".

PAGE 37

4.4.2.21, Major 101: Delete in its entirety.

Add "Major 104: Any sensors not covered by potting 0.40% 3.2 Visual".

PAGE 41

4.4.2.24, Major 120: Delete "True position of O-ring groove diameter" and substitute "O-ring runout incorrect".

PAGE 46

* 4.4.2.28, Add: "Major 101 Conformal coating missing or improper 0.40% 3.2 Visual".

PAGE 47

4.4.2.29, Major 101: Delete in its entirety.

Add "Major 104: Any sensors not covered by potting 0.40% 3.2 Visual".

PAGE 53

4.4.2.34:

Critical 1: Change inspection method from "Visual" to "Gage".

Critical 4: Delete "Shorting eyelet missing" and substitute "Flex cable shunts missing or improper".

PAGE 54

4.4.2.34: Delete Major 109 in its entirety.

PAGE 56

4.4.2.35 Cont'd: Add "Major 110, Shim missing or incorrect, 0.40%, 3.2, Visual".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

PAGE 62

4.4.2.40: Delete in its entirety and substitute new PAGE 62, Paragraph 4.4.2.40 included.

PAGE 63

Add Page 63A, 4.4.2.41 included herein.

PAGE 65

4.5.1, line 30: Delete "DRSMC-QAT-I(D)" and substitute "AMSMC-QAT-I(D)".

PAGE 66

4.5.1 CONT., line 3: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

PAGE 73

6.3, line 3: Delete "DRSMC-QAT-I(D)" and substitute "AMSMC-QAT-I(D)".

6.4, line 3: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

6.6, line 4: Delete "DRSMC-QAT-M(D)" and substitute "AMSMC-QAT-M(D)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.40	Body Assembly	1 OF 2	9292689
			NEXT HIGHER ASSEMBLY ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	LOT ACCEPTANCE TESTS	1/			
Critical					
1	Unsafe after transportation-vibration		0-1	3.3.1 3.4	4.5.5 4.5.6.4, 2/
2	Premature arming			3.4	4.5.6.4
3	Premature detonation			3.4	4.5.6.4
4	Hazardous dud				
Major					
	PERFORMANCE TEST: LAUNCH/FUNCTION			3.4	4.5.6
105	Tripline (TL)/Breakwire (BW) mode				
106	Self Destruct (SD): normal/extended				
107	Antidisturbance (AD) mode				
108	Dud				
109	Early SD				

NOTES: 1/ See sheet 2. 2/ Acoustic sensor shall be used for monitoring.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.41	Shim, Shorting Bar				9381374
					NEXT HIGHER ASSEMBLY 9292680
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Length of legs, 2 places		0.65%	3.2	Gage
203	Width		0.65%	3.2	Gage
204	Diameter of hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.11	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A508)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:34Z
Check the source to verify that this is the current version before use.