MILITARY SPECIFICATION

CONTAINER, AMMUNITION, FIBERBOARD

This specification is approved for use within the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of an ammunition container designated as Container, Ammunition, Fiberboard.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement therto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9342677 - Container, Ammunition, Fiberboard

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.3 Other publications. The following documents forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-3951 - Commercial Packaging.

(ASTM Materials are available from ASTM, 1916 Race Street, Philadelphia, PA 19103.)

2.2 Order of precedence. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise-specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.1.1 Reworked material. No reworked material shall be used to make the product.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing (Dwg.) 9342677 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Free fall drop. The loaded (5 inert mines) container assembly shall show no evidence of broken, torn or loose parts which render the assembly unusable, after being dropped from a height of thirty-six (36) inches (in.) onto a one (1) in. minimum (min.) thick steel plate. Slight dents or crushing where the container assembly contacted the impact surface will be acceptable, provided usability of container is not affected. The closure shall not separate from container body. Test shall be conducted at temperature extremes of minus 25°F ± 5°F (minus 32°C) and +125°F ± 5°F (+52°C) and ambient temperature following conditioning at same temperature for four (4) hours minimum.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated, assembled and finished in a thorough workmanlike manner. All manufacturing, processing, and assembly operations shall be correctly performed. All parts and assemblies shall be clean, free from cuts, chips, dirt, grease, and other foreign matter which would affect their serviceability. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. Unless otherwise specified in-the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are-deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:35Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of six (6) assembled containers.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. Unless otherwise specified, all inspections shall be performed at ambient temperature conditions (see 6.6).

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48633(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Container, Ammunition, Fiberboard				9342677
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container, Ammunition, Fiberboard (Dwg. 9342677)				
	Examination for Defects	6		3.2	4.4.2.1
	Free Fall Drop Test	6		3.3	4.5.1

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105. Unless otherwise specified, all inspections shall be performed at ambient temperature conditions (see 6.6) .

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-48633(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Container, Ammunition, Fiberboard				9342677
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside dimensions for full depth		0.40%	3.2	Gage
102	Overall length, max		0.40%	3.2	Gage
103	Outside width		0.40%	3.2	Gage
104	Outside height		0.40%	3.2	Gage
105	Any component missing, damaged or improperly secured		0.40%	3.2	Visual
106	Closure improperly assembled/located		0.40%	3.2	Visual
107	Correct grade of fiberboard			3.2	Certification
Minor					
201	Poor workmanship		0.65%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1, and the test method paragraph (see 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection.

4.5.1 Free fall drop. After temperature conditioning for four (4) hours minimum, six (6) container assemblies, two (2) each at the temperatures specified in 3.3, with five (5) inert mines installed in each, shall be dropped freely from the specified height on the top (closure end), one side, 450 to one corner of the top, 450 diagonally to the opposite corner of the base and on the bottom (a total of five drops for each container assembly) . The simulated mines shall measure 4.75 - .025 in. diameter by 2.60 - .025 in. high (right circular cylinder), and weigh 4 ±1/4 pounds. Observation shall be made for compliance with the requirement.

5. PACKAGING

5.1 Preservation and packaging

5.1.1 Commercial. Unless otherwise specified by the procuring activity, the preservation and packaging shall be in accordance with ASTM-D-3951 except that the unit package must contain eight (8) fiberboard container assemblies.

5.2 Packing and marking.

5.2.1 Commercial. Unless otherwise specified by the procuring activity, all packing and marking shall be in accordance with ASTM-D-3951.

5.3 Shipping. When containers from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lot clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The Fiberboard Ammunition Container is intended for use as the interior unit packaging for the M74, M75 and M79 mines; and as a means of handling the mines during field loading operations of the M128 Dispenser (GEMSS).

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:35Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. (See MIL-A-48078). Submit equipment designs as required to Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Distribution of ammunition data cards and test data. Distribution of data cards and test data shall include the following: Commander, US Army Armament Research, Development and Engineering Center, AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.6 Temperature. Ambient temperature shall be defined as 700±100F-

6.7 Subject term (key word) listing.

Container
Ammunition
Fiberboard
Free fall drop

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A339)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Dover, NJ 07801-5001

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-48633 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:35Z
Check the source to verify that this is the current version before use.