MILITARY SPECIFICATION
CHARGE, PROPELLING, XM121, FOR CARTRIDGE 105MM, XM546 LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-60352 (MU) dated 7 December 1965 and is approved for use by all Departments and Agencies of the Department of Defense.

Title, paragraph 1.1 and paragraph 2.1, drawings, Army: Delete nomenclature "XM121" and "XM546" and substitute "M121" and "M546" respectively.

Paragraph 2.1, Specifications: Add the following:
"FEDERAL
PPP-B-26 Bag, Plastic, Polyethylene"

Paragraph 2.1, Standards: Add the following:
"FEDERAL
FED-STD-101 Preservation, Packaging, and Packing Materials; Test Procedures.
FED-STD-406 Plastics: Methods of Testing"
Under Military:
"MIL-STD-652 Propellants, Solid for Cannons; Requirements and Packing".

Paragraph 2.1, drawings, Army: Delete drawing "20-4-618" and substitute drawing "9217087". Add drawing "8858848 Marking Diagram and Sealing of Metal Lined Wooden Packing Boxes for Shipment of Propellants".

Paragraph 4.2.2.6, title: After the word "Drum" add "fiber or metal".

Paragraph 4.2.2.7:
Title: Delete the title in its entirety and subsitute: "Drum, fiber or metal, sealed (see dwg. 76-1-1039)".

Major Defect 102: Delete in its entirety and substitute: "102. Locking device damaged or improperly closed....Visual 07002".

Minor defect 201: After the word "positioned" add "when applicable".

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.

Paragraph 4.2.3.2: Delete in its entirety.

Paragraph 4.4.1: Delete in tis entirety and substitute the following paragraphs:

"4.4.1 Surface resistivity - The surface resistivity of the ployethylene bag shall not exceed ten to the third power ohms when tested in accordance with Methods 4041 and 4052 of FED-STD-406.

4.4.2 Electrostatic test - Electrostatic bleed-off shall not exceed 2.00 seconds when tested in accordance with Method 4046 of Federal Test Method Standard 101".

Paragraphs 5.1.1, 5.1.2 and 5.2: Delete in their entirety and substitute the following:

5.5.1 Level A.-The propelling charges shall be packed in a metal drum conforming to dwg. 76-1-1039. The drum shall contain two nominal .003 thick conductive polyethylene bags, one inside the other, which contain the charges and each bag shall be individually closed and tied. The bags shall be constructed in accordance with type II of Specification PPP-B-26 and shall meet the conductivity requirements of paragraph 4.4.

5.1.2 Level C.-The propelling charges shall be packed in fiber drums as specified in MIL-STD-652.

5.2 Marking.-The metal drums shall be marked in accordance with drawing 9217087. The fiber drums shall be marked as specified in MIL-STD-652 (see dwg. 8858848). The DOT marking shall be "PROPELLANT EXPLOSIVES, CLASS A."

Custodian:
Army - PA

Preparing Activity:
Army - PA

Project Number 1315-A039

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:30Z
Check the source to verify that this is the current version before use.