MIL-C-60559D(MU)
AMENDMENT 2
10 February 1975
SUPERSEDING
AMENDMENT 1
15 January 1971

MILITARY SPECIFICATION

CARTRIDGE, IMPULSE: M225

This amendment forms a part of Military Specification MIL-C-60559D(MU), dated 8 July 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 1.1, line 2, delete "XM176" and substitute "M176".

* Paragraph 2.2, delete reference to "ASA B46.1" in its entirety and substitute:

"ANSI B46.1 -Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI) 1430 Broadway, New York, N.Y. 10018)"

* Paragraph 3.4, delete in its entirety and substitute:

"3.4 Charge weight.-The amount of propellant charge by weight in any one cartridge shall be within two percent of the established charge weight."

* Paragraph 3.6.2, delete Table I and substitute:

"Table I

Temperature Degree Fahrenheit (F)	Average Grenade Range 1/ in feet Min	Max	Ignition Delay Milliseconds Max (See 6.2)
-20° to -25°F	100	150	20
65° to 75°F	100	150	20
125° to 130°F	100	150	20

1/ No grenade shall be launched to a distance less than 90 feet."

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:43Z
Check the source to verify that this is the current version before use.

* Paragraph 4.3.2, line 8, delete "ASA B46.1" and substitute "ANSI B46.1".

* Paragraph 4.3.2.3:

a. Under Major Defects add:

"106. Thickness of rupture area - - - - - - - - - Gage
107. Hardness of rupture area - - - - - - - - - Gage"

b. Delete Minor Defect No. "204" in its entirety.

Paragraph 4.3.2.4:

a. Under Major Defects, delete "101" and "102" and substitute the following:

"101. Diameter of body, max. - - - - - - - - - - -Gage
102. Diameter of head, max. - - - - - - - - - - -Gage"

b. Delete Major Defect No."103" in its entirety.

* c. Under Minor Defects, delete "201" and "202" and substitute the following:

"201. Diameter of body, min. - - - - - - - - - - -Gage
202. Diameter of head, min. - - - - - - - - - - -Gage"

* Paragraph 4.4.7.1, lines 5 and 6, delete "luancher" and substitute "launcher".

* Add Paragraphs 6.3 and 6.4:

"6.3 Loaded Assembly Hazard Information:

Explosive Hazard Classification - Class 1
Storage Compatibility - Group B, E or N
Department of Transportation (DOT) Hazard - Class C
DOT Marking (Small Arms Ammunition)

6.4 Hazard notice.-The cartridge described herein and certain of its components are flammable and/or explosive, consequently present hazards in manufacture, handling, storage and shipment. The contractor should recognize these hazards and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents."

Source: https://assist.dla.mil -- Downloaded: 20261O-23T00:43Z
Check the source to verify that this is the currentversion before use.

* The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1377 - A599

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:43Z
Check the source to verify that this is the current version before use.