MIL-P-48400A (AR)
Amendment 2
26 October 1977
Superseding
Amendment 1
22 September 1977

MILITARY SPECIFICATION

PROJECTILE, 60MM, HE, M720, METAL PARTS ASSEMBLY

This Amendment forms a part of Military Specification MIL-P-48400A (AR) dated 11 July 1977.

Page 2

Para. 2.1 add "TT-C-490- Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings
* Delete "9275526 - Cartridge, 60MM, HE, M720"
Add "9236378 - Body Loading Assembly" and "11722522 - Pellet, Booster" and "11751196 - Fin M27"

Page 4

* Paragraph 3.7.2, change Table I to read as specified.

Weight Interval	Fragment Size(grains)	Fragment Quantity
A	2 - 3	242 minimum
B	4 - 6	190 minimum
C	10 - 15	174 maximum

Page 5

* Delete Paragraph 3.9 in its entirety

Page 16

Para. 4.4.3.3 delete "The sample size and acceptance criteria shall be be in accordance with the assembly drawing and the requirements of the specifications listed thereon" and substitute "The sample size and acceptance criteria shall be in accordance with the assembly drawing and the requirements of TT-C-490".

FSC: 1310

Source: https://assistdla.mil -- Downloaded: 2026-10-22T19:25Z
Check the source to verify that this is the current version before use.

Page 17

* Paragraph 4.4.3.5.1, fifth sentence, change "The projectile assemblies shall be loaded and completely assembled with fuze in accordance with drawing 9275526 and MIL-C-48368" to read "The projectile bodies shall be loaded and assembled in accordance with 4.5.5.1.

Page 18

* Paragraph 4.4.3.5.2, fifth sentence, change "The projectile assemblies shall be loaded and completely assembled with fuze in accordance with drawing 9275526 and MIL-C-48368" to read "The projectile bodies shall be loaded and assembled in accordance with 4.5.5.1.

* Paragraph 4.4.3.6, fourth sentence, change "The projectile assemblies shall be loaded and completely assembled with fuze in accordance with drawing 9275526 and MIL-C-48368" to read "The projectile bodies shall be loaded and assembled in accordance with 4.5.5.2.

* Paragraph 4.4.3.7 delete in its entirety and substitute "4.4.3.7 Chemical Composition. - The chemical composition shall be as specified in ASTM-A322 as required on the applicable drawing when tested as specified in 4.5.6. The procedure for sampling shall be in accordance with ASTM-E350. Failure of any sample to meet the requirements is cause for rejection."

Page 20

Para. 4.5.3 delete "The procedures for testing the cleaning of components and the application of protective coating shall be in accordance with the requirements of the applicable drawings and the specifications listed thereon" and substitute "The procedures for testing the cleaning of components and the application of protective coating shall be in accordance with the requirements of the applicable drawing and the specifications listed thereon, and TT-C-490."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:25Z
Check the source to verify that this is the current version before use.

Page 21

* Paragraph 4.5.5.1, first sentence, delete "Prior to testing, the fuze shall be modified for static initiation by replacing the safe and arming mechanism with an adapter and inserting a No. 6 or No. 8 Electric Blasting Cap", and substitute "Load the projectile in accordance with drawing 9236378 and MIL-C-48368. At the forward end of the projectile insert a booster pellet (dwg no. 11722522) into fuze well cavity. Place a 1.25 inch OD x .24 inch ID x .75 inch thick cylindrical wooden plug over the booster pellet and insert a No. 6 Blasting Cap into the .24 inch diameter hole in the wooden plug. Seat the blasting cap on the booster pellet and secure the assembly with tape making certain the pellet and blasting cap are fully seated".

* Paragraph 4.5.5.2, add "Load projectile in accordance with drawing 9236378 and MIL-C-48368. Assemble a M27 fin (dwg 11751196) hand tight to aft end of loaded projectile. At forward end of projectile insert a booster pellet (dwg no. 11722522) into fuze well cavity. Place a 1.25 inch OD x .24 inch ID x .75 thick cylindrical wooden plug over the booster pellet and insert a No. 6 blasting cap into the .24 inch diameter hole in the plug. Seat the blasting cap on the booster pellet and secure the assembly with tape making certain the pellet and blasting cap are fully seated".

* Paragraph 4.5.6, shall be changed to read, "The chemical composition shall be determined in accordance with the test procedures specified in ASTM-E350."

Page 22

* Delete para. 6.3 in its entirety.

The margins of this Amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous Amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous Amendment.

Custodian:

Army - AR

Preparing Activity:

Army - AR

Project Number: 1310-A112

☆U.S. GOVERNMENT PRINTING OFFICE: 1978 — 703-122/864

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:25Z
Check the source to verify that this is the current version before use.