INCH-POUND

MIL-C-63239B (AR)
AMENDMENT 5
09 May 1995
SUPERSEDING
AMENDMENT 4
20 August 1993

MILITARY SPECIFICATION

CARTRIDGE, 40MM, PRACTICE, M781 METAL PARTS AND LOADING, ASSEMBLING AND PACKAGING

This Amendment forms a part of Military Specification MIL-C-63239B, dated 5 November 1984, and is approved for use by the US Army Armaments, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 3.3: Delete "The primer shall function without evidence of squibbing of hangfire."and substitute "The primer shall function without evidence of squibbing or hangfire."

* 3.4: Delete in its entirety and substitute the following:

"3.4 Functioning. The cartridge shall be considered to have functioned properly if, when fired, it gives no visual indication of separation or dye emission in flight and upon impact, does emit dye. At ambient temperature, the projectile shall have a mean velocity of 247 plus or minus (+/-) 7 feet per second (fps), when measured at 20 feet from the muzzle IAW 4.5.10, and a standard deviation no greater than 4.5 fps."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 5

4.3.1 Delete:

"Body and Band Assembly (when applicable)	9354247	25
Body (when applicable)	9352746	25
Rotating Band (when applicable)"	9352745	25

PAGE 6

4.3.3.1.b: Delete in its entirety and substitute the following:

"4.3.3.1b. Mean velocity or standard deviation fails to meet the applicable requirement (ambient only, informational in hot and cold phase)."

* 4.3.3.1c: Delete in its entirety and substitute the following:

"4.3.3.1c Any primer misfires, squibs, or hangfires in any temperature phase."

PAGE 7

Table I Delete:

"Rotating Band (DWg. 9352745) (when applicable) Examination for defects	25	4.4.2.2
Body (Dwg. 9352746) (when applicable) Examination for defects	25	4.4.2.3
Body and Band Assembly (Dwg. 9352747) (when applicable) Examination for defects	25	4.4.2.4"

PAGE 9

4.4.1c: Delete in its entirety and substitute the following:

"4.4.1c. Primers from one interfix lot number from one manufacturer."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 10

4.4.2.1: Delete "9354248 or" from next higher assembly block.

4.4.2.1: Add Major 105:

"105. Diameter between lobes (when applicable) (Dwg. 9322236-2)" 0.40% 3.2 Gage

PAGE 11

4.4.2.2: Delete in its entirety.

PAGE 12

4.4.2.3: Delete in its entirety.

PAGE 13

4.4.2.4: Delete in its entirety.

PAGE 14

4.4.2.5: Delete in its entirety.

PAGE 20

4.4.2.11: Add Major 107:

"107 Diameter of Windshield Snap Groove (when applicable) (Dwg. 9310344-2)" 0.40% 3.2 Gage

4.4.2.11: Delete existing Major 107 and substitute:

"107 Maximum Diameter of Windshield Snap Groove (when applicable) 0.40% 3.2 Gage

PAGE 23

* 4.4.2.14: Add Note 1 to Majors 101 and 102 and under notes add:

"1. When annular groove design is used (see Note 5 of Dwg 9322230), outer surface refers to the outer ring."

PAGE 30

Under paragraph block delete "4.4.2.13" and substitute "4.4.2.21".

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 33

4.4.3.6 Functioning, third line: Delete"...select tow-hundred..." and substitute "...select two hundred...".

* 4.4.3.6.4: Delete in its entirety and substitute the following:

"4.4.3.6.4 Rejection. Unless otherwise specified, the allowable number of failures are the total of all failures at all temperature phases. The lot shall be rejected if:"

* 4.4.3.6.4.a: Delete in its entirety and substitute the following:

"4.4.3.6.4a. Twelve (12) or more fail in flight or fail to function upon impact."

* Add to paragraph 4.4.3.6.4c. "Velocity measurements on projectiles not functioning properly shall be included in the mean velocity and standard deviation calculations."

* 4.4.3.6.4d: Delete in its entirety and substitute the following:

"4.4.3.6.4d. Any primer misfires, squibs, or hangfires in any temperature phase."

* 4.4.3.6.4f: Delete in its entirety and substitute the following:

"4.4.3.6.4f. Any projectile sticks in the gun bore in any temperature phase or fails to attain a minimum velocity of 144 fps. A projectile on which a velocity measurement was not obtained due to low velocity shall be cause for rejection of the lot."

PAGE 34

* 4.4.3.6.4h: Delete the following paragraph in its entirety: "If the launcher .... shall be rejected."

* 4.4.3.7.4: Delete in its entirety and substitute the following:

"4.4.3.7.4 Rejection. Unless otherwise specified, the allowable number of failures are the total of all failures at all temperature phases. The lot shall be rejected if:"

* 4.4.3.7.4a: Delete in its entirety and substitute the following:

"4.4.3.7.4a. Four (4) or more fail in flight or fail to function upon initial impact."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

* Add to paragraph 4.4.3.7.4c. "Velocity measurements on projectiles not functioning properly shall be included in the mean velocity and standard deviation calculations."

* 4.4.3.7.4.d: Delete in its entirety and substitute the following:

"4.4.3.7.4d. Any primer misfires, squibs, or hangfires in any temperature phase."

PAGE 35

* 4.4.3.7.4.f: Delete in its entirety and substitute the following:

"4.4.3.7.4f. Any projectile sticks in the gun bore in any temperature phase or fails to attain a minimum velocity of 144fps. A projectile on which a velocity measurement was not obtained due to low velocity shall be cause for rejection of the lot."

* 4.4.3.7.4h: Delete the following paragraph in its entirety: "If the launcher .... shall be rejected."

PAGE 39

* 4,5,10, second paragraph, (eighth line down): Delete ".0005" and substitute ".005."

PAGE 40

6.7: Delete: $S = \sqrt{\frac{(x-\bar{x})^2}{n-1}}$

and substitute:

$$S = \sqrt{\frac{\sum (x-\bar{x})^2}{n-1}}$$

PAGE 41

* Delete $(x-\bar{x})$ in line 4 and substitute: " $\sum (x-\bar{x})^2$= the sum of the squares.....individual value."

* 6.7.1: Delete "eiser" and substitute "easier."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assures no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian
Army-AR

Preparing activity:
Army-AR

(Project 1310-A552)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.