INCH-POUND

MIL-R-63997B(AR)
AMENDMENT 4
31 July 1993

SUPERSEDING
AMENDMENT 3
25 March 1992

MILITARY SPECIFICATION

RIFLE, 5.56MM: M16A2

This Amendment forms a part of MIL-R-93997B(AR), dated 12 December 1986, and is approved for use by U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 9

3.4.5, last line: Add the following sentence before the last sentence:

"The cyclic rate of fire measurement shall be taken on a three round burst, occurring on the sixth or seventh trigger pull l "

* 3.4.6: Delete in it's entirety and substitute the following:

"3.4.6 Targeting and accuracy. A series of 10 rounds fired from each rifle at a range of 91.4 meters shall be within the extreme spread and targeting area (heavy outline) specified in Figure I when the front and rear sights are set as follows. The normal rear sight peep (sight rotated fully rearward) shall be used with the rear sight set centrally in the slot for windage within plus or minus five (5) clicks. The top edge of the front sight post flange shall be set flush to .030 Inch below the bottom surface of the front sight slot. Ammunition shall be Government standard M855, 5.56mm ball cartridges conforming to Drawing 9342868 and shall have a vertical and horizontal standard deviation at 600 yards between 3.4 inches and 4.0 inches when measured in accordance with MIL-C-63989."

3.6: Add the following sentence at the end of the paragraph:

"The bar code label shall be firmly affixed to the lower receiver in the position specified on the applicable drawing, the bar coding shall be clearly defined and the number on the label shall agree with the serial number stamped on the receiver."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

PAGE 13

* 4.5.1.1.2, line 2: Delete “or a single shift’s production, whichever is larger.” and substitute “or a month's production, whichever is smaller.”

PAGE 27

4.5.2.2, DEFECT NO. 95: Delete the following:

“Lower Receiver. Missing or illegible receiver markings (serial number manufacturer’s identification, selector markings, etc.)“

and substitute:

‘Lower Receiver. Incorrect, dislocated, damaged, illegible or missing markings (serial number, bar code label, manufacturer’s identification, selector markings, etc.)”

PAGE 29

4.5.2.2.1, line 4: Delete “complete inspection approval stamp on the lower right hand side of the lower receiver, or the forward face of the magazine well.” and substitute “complete inspection approval stamp on the packaging list of each shipping container .“

PAGE 33

* TABLE IV: Delete note 7 in its entirety and substitute:

"[7]When five successive inspection lots meet the requirements, the inspection lot size shall be increased to 5000 rifles or a month’s production, whichever is smaller, and the inspection sample selected. If rejection of the inspection sample occurs at any time, the inspection lot size of 1000 rifles (or smaller) shall be reinstated and the above procedures repeated in returning to the 5000 rifle (or smaller) lot size.”

PAGE 37

4.7.5.3.2, line 5: Delete “occurring on the fourth or fifth trigger pull” and substitute “occurring on the sixth or seventh trigger pull”.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

PAGE 43

Group I, last line: Delete "(9349129)" and substitute "(12597640)".

PAGE 47

4.7.8.1, Delete “Rifles shall be lubricated as specified below at the beginning of the test and after the fifth cycle in every 10 cycle increment. Rifles shall be cleaned and lubricated at the end of every 10 cycles.” and substitute "Rifles shall be cleaned and lubricated at the beginning of the test and at the end of every 10 cycles. Rifles shall be lubricated after the fifth cycle and every 10 cycle increments.”

PAGE 53

6.1, Add as new subparagraph p.:

“P” Bar code marking requirements.”

PAGE 54

* 6.5.1.e, last line: Delete “extracted from the magazine.” and substitute ‘extracted from the chamber.”

The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been entered in the document, insert the amendment as the cover sheet to the last previous amendment.

Replacement page	Page Replaced
55	55
56	56

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

Class II. Clearable by gunner with available equipment. (Basic Issue Items).

Class III. Not clearable by gunner.

6.5.6 Defective rifle. A defective rifle is a unit of product which contains one or more defects (end item assembly or component).

6.6 Quality program. When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208, as appropriate, in the Management Control Systems Summary List, DD Form 1660.

6.7 Inspection equipment. Unless otherwise specified, the contract should specify the application of MIL-I-45207 and MIL-STD-45662 on the Management Control Summary List, DD Form 1660.


6.8 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center may also include drawings prepared by, and identified as Rock Island Arsenal, Frankford Arsenal, Picatinny Arsenal or ARRADCOM drawing. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.9 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any Inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.10 Subject term (key-word) listings.

Gun
Small arms
Weapon

Source: https://assist.dla.mil -- Downloaded: 2026-01-23T03:09Z
Check the source to verify that this is the current version before use.



A – 10 shot group extreme spread
B – Vertical distance from target centerline to point of aim
C – Height of heavy outline
D – Width of heavy line
E – Radius of corners of heavy outline
F – Width of shaded areas
G – Height of upper shaded area
H – Heights of lower shaded areas
– Grid dimensions

Target Diagram For		Dimensions in inches								
		Group	P.O.A.	Heavy Outline			Shaded Areas			Grid
Meters	Yards	A	B	C	D	E	F	G	H	I
* 91.4	100	5.0	3.5	17.6	11.6	2.8	2.0	2.0	1.0	1.0

FIGURE 1. Targeting and accuracy diagram.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1005-A811)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code)	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:09Z
Check the source to verify that this is the current version before use.