MILITARY SPECIFICATION

FUZE, PIBD, XM740, SECOND ENVIRONMENT SENSOR ELECTRONIC MODULE FOR

This amendment forms a part of Military Specification MIL-F-63231 (AR) dated 17 August 1979, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title block: Add "(M740)" to title and wherever it appears in this specification.

2.1, SPECIFICATIONS:

FEDERAL:

* Delete:

"PPP-T-97 - Tape, Pressure Sensitive, Adhesive, Filament Reinforced".

* Add:

"PPP-T-45 - Tape, Gummed, Paper Reinforced and Plain, for Sealing and Securing.

PPP-T-60 - Tape, Packaging, Waterproof"

MILITARY:

* Delete:

"MIL-B-81705 Barrier Materials, Flexible, Electrostatic-Free, Heat Sealable."

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

Add:

"MIL-B-117 - Bag, Sleeve and Tubing-Interior Packaging"

PAGE 2

Other Publications: Delete: "AR700-15 Packaging of Material."

PAGE 3

3.2.1.1: Delete in its entirety and substitute the following:

"3.2.1.1 Output signals. The SESE shall provide a "go" (arm) signal or a "no go" (not arm) signal, depending upon the condition and timing of the input signals. The number 1 input signal shall be a single pulse with a voltage rise from 0 to 16 volts in 80+ 5, -0 microseconds and a decay to less than 10 volts at 100+ 10 microseconds and shall be applied to terminals 1 and 2 with terminal 1 positive and terminal 2 negative. The number 2 input signal shall be a single pulse with a voltage rise from 0 to 16 volts in 40 $\pm$ 5 microseconds and shall be applied to terminals 3 and 4 with terminal 3 positive and 4 negative."

3.2.1.1.1: Delete in its entirety and substitute the following:

"3.2.1.1.1 Go Output signals. The SESE shall produce a "go" signal when input signal number 2 is applied within 180 microseconds or less after the application of input signal number 1, as measured from the beginning of each input signal pulse. A "go" signal shall be a pulse which changes from less than +0.2VDC and maintained at greater than 4.0VDC for 0.7 seconds minimum. This signal shall be measured at terminals 6 and 5 with terminal 6 positive and terminal 5 negative. The "go" signal shall occur within 40 microseconds after the start of input signal pulse number 2."

3.2.1.1.2: Delete in its entirety and substitute the following:

"3.2.1.1.2 No-Go Output signals. The SESE shall produce a "no go" signal when input signal number 2 is applied at 270 microseconds or more after the application of input signal number 1, as measured from the beginning of each input signal pulse. A "no go" signal shall be a voltage of not greater than 0.2VDC. This signal shall be measured at terminals 6 and 5 with terminal 6 positive and terminal 5 negative. The "no go" signal shall be maintained continuously from the application of signal number 1 until the SESE is discharged."

PAGE 4

Figure 1: Delete and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.




Figure 1 - Direction of Applied Acceleration

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

4.5.2.1: Delete in its entirety and substitute the following:

"4.5.2.1 Go Output signal. Apply input signals number 1 and number 2 to proper terminals of the SESE as defined by 3.2.1.1 and with the polarity as specified by 3.2.1.1, and with input signal number delayed 180 + 10, -0 microseconds after input signal number 1, as measured from the beginning of each input signal pulse; the output measured at terminals 5 and 6 with an instrument of 10 ± 2% meg ohm input impedance across a 1.1 ± 1% meg ohm resistor shall be as specified in 3.2.1.1.1."

4.5.2.2: Delete in its entirety and substitute the following:

"4.5.2.2 No Go Output signal. Apply input signals number 1 and number 2 to proper terminals of the SESE as defined by 3.2.1.1 and with the polarity as specified by 3.2.1.1, and with input signal number 2 delayed by 270 + 0, -10 microseconds after input signal number 1, as measured from the beginning of each input signal pulse; the output measured at terminals 5 and 6 with an instrument of 10 ± 2% meg ohm input impedance across a 1.1 ± 1% meg ohm resistor shall be as specified in 3.2.1.1.2."

4.5.7: Delete in its entirety and substitute the following:

"4.5.7 Environmental tests. With the exception of high and low temperature tests the SESE shall be mounted in a carrier or a test fixture which simulates the mounting of the SESE by its normal means in its normal position in the projectile."

4.5.7.1: Delete in its entirety and substitute the following:

"4.5.7.1 High temperature. The SESE shall be conditioned at 145 +5, -0°F for a minimum of one hour. While at the high temperature, the units shall be tested as specified in 4.5.2. The tests may be performed outside the temperature chamber if accomplished within one minute after removal from the chamber."

4.5.7.2: Delete in its entirety and substitute the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

"4.5.7.2 Low temperature. The SESE shall be conditioned at -25 +0, -5°F for a minimum of one hour. While at the low temperature condition, the units shall be tested as specified in 4.5.2. The tests may be performed outside the temperature chamber if accomplished within one minute after removal from the chamber. NOTE: Care must be taken to prevent frost from forming on the device which will affect the testing."

4.5.7.3, lines 1 and 2: Delete the first sentence in its entirety and substitute the following:

"The SESE shall be mounted in a carrier or test fixture as specified in para. 4.5.7."

line 3: Delete "±5°F" and substitute "+5, -0°F".

lines 6, 7, and 8: Delete "Remove the ... in 4.5.2" in its entirety and substitute the following:

"Remove the carrier/SESE assembly from the test projectile. Remove the SESE from the carrier and condition it at +145 +5, -0°F for one hour. While at the high temperature, the units shall be tested as specified in 4.5.2. The tests may be performed outside the temperature chamber if accomplished within one minute after removal from the chamber."

4.5.7.4, lines 1 and 2: Delete the first sentence in its entirety and substitute the following:

"The SESE shall be mounted in a carrier or test fixture as specified in para. 4.5.7."

line 3: Delete "±5°F" and substitute "+0, -5°F".

lines 6, 7, and 8: Delete "Remove the ... in 4.5.2" in its entirety and substitute the following:

"Remove the carrier/SESE assembly from the test projectile. Remove the SESE from the carrier and condition it at -25 +0, -5°F, for one hour. While at the low temperature, the units shall be tested as specified in 4.5.2. The tests may be performed outside the temperature chamber if accomplished within one minute after removal from the chamber.
NOTE: Care must be taken to prevent frost from forming on the device which will effect the testing."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

PAGE 10

* 5.1, Delete in its entirety and substitute the following:

"5.1 Preservation and packaging - Level B. Place each item in a bag in accordance with Type I, Class F, Style 1 of MIL-B-117 and heat seal bag. Place bagged items in a partitioned 275 pound test corrugated fiberboard carton. One bagged item per partition cell. Seal the carton with pressure sensitive case sealing tape in accordance with (PPP-T-60) or water remoistenable reinforced gummed case sealing tape in accordance with (PPP-T-45)."

* 5.2 Delete in its entirety and substitute the folowing:

"5.2 PACKING - Cartons as described in 5.1 shall be labeled and shipped on individual basis. Unitizing of two or more cartons for shipment is not allowed except in overpack cartons, (optional). Overpack, if used, shall consist of 200 pounds test corrugated boxes; voids in overpack to be filled with anti-static cushion dunnage. Overpack cartons shall be sealed with PPP-T-60 or PPP-T-45 case sealing tape. Gross shipping weight shall not exceed 65 pounds per carton."

PAGE 13

Major 101: Delete "Gage" and substitute "Gage/4.5.3".

Majors 102, 103, 104, and 105: Delete in their entirety and substitute the following:

"102 Go signal initiation/output 100% 3.2.1.1.1 4.5.1/4.5.2

103 No go signal initiation/output 100% 3.2.1.1.2 4.5.1/4.5.2"

PAGE 16

Major 101: Delete "Gage" and substitute "Gage/4.5.3".

Majors 102, 103, 104, and 105: Delete in their entirety and substitute the following:

"102 Go signal initiation/output 100% 3.2.1.1.1 4.5.1/4.5.2

"103 No go signal initiation/output 100% 3.2.1.1.2 4.5.1/4.5.2"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

Major 102: Delete in its entirety and substitute the following:

"102 Conformal coating; 100% 3.3.2 4.5.4".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions,modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A430)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.