MILITARY SPECIFICATION

TURRET SUBSYSTEM, UNIVERSAL (UTS) FOR ARMAMENT SUBSYSTEM, HELICOPTER, 20MM: M97E1 and M97E2, ELECTRIC DRIVE MOTOR FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for manufacture and acceptance of the XM97E1 and XM97E2 20mm Armament Subsystem Electric Drive Motor, hereinafter referred to as the motor.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-E-5400	Electronic Equipment, Airborne, General Specification fOr.
MIL-M-8609	Motors, Direct-Current, 28-Volt System, Aircraft, General Specification for.
MIL-W-63150	Weapons and Support Material, Standard Assurance Provisions for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document or by letter.

Source: DLA (assist.dla.mil). Downloaded: 2026-04-25T00:00Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling procedures and Tables for Inspection by Attributes.
MIL-STD-109	-	Quality Assurance Terms and definitions.
MIL-STD-454	-	Standard General Requirements for Electronic Equipment.
MIL-STD-704	-	Aircraft Electric Power Characteristics.
MIL-STD-81O	-	Environmental Test Methods,

2.1.2 other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT

905D490	-	Motor, Electric Drive.

PACtiAGING

P905D490	-	Motor, Electric Drive

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B 117	-	Method of Salt Spray (Fog) Testing.

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:03Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Material shall be in accordance with applicable drawings, specifications and standards.

3.2 Parts and subassemblies. All parts and subassemblies shall comply with applicable drawings, specifications and standards.

3.3 Assembly. The assembly shall comply with all requirements specified on Drawing 905D490, all associated drawings, and with all requirements specified in applicable specifications.

3.4 Interchangeability. All parts having the same part number shall be completely interchangeable with each other and with like parts of other manufacturers with respect to installation and performance. Parts joined together by welding, brazing, or riveting shall be interchangeable as assemblies. Interchangeability shall be in accordance with MIL-STD-454, Requirement 7. Testing shall be in accordance with 4.4.7.

3.5 Design and construction.

3.5.1 Input characteristics. The motor line voltage shall be 28 volts direct current (Vdc) per MIL-STD-704.

3.5.2 output characteristics. The motor output characteristics shall be per torque-speed curve defined on drawing 905D490 unless otherwise specified by the contract.

3.5.3 Duty cycle. The motor duty cycle shall be intermittent consisting 15 seconds on and 45 seconds off repeated 10 times maximum with rated load and terminal voltage of 28 Vdc followed by cooling off period of 15 minutes between runs.

3.5.4 Motor enclosure. The motor shall be totally enclosed.

3.5.5 Connector bracket. The connector bracket assembly shall be able to a withstand force of 500 pounds (lbs) maximum in the directions ath the centerline of the connector without visible distortion as noted on drawing 905D490.

3.6 Performance characteristics. The motor shall be capable of meeting the requirements of MIL-M-8609 except as modified by drawing 905D490.

3.6.1 Horseposer. The motor shall provide 2.85 horsepower as specified on drawing 605D490, Note 1.

3.6.2 Torque. The motor shall provide the torque specified on drawing 905D490, Notes 11 and 12.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

3.6.4 Proof test (first article inspection only). Electric Drive Motors shall operate when assembled to an accepted Universal Turret Subsystem (UTS).

3.6.3 Direction of rotation. The direction of motor output rotation shall be counterclockwise as viewed from the spine end of the motor.

3.7 Environmental requirements. The motor shall perform as specified in 3.5 and 3.6 after exposure to the environments specified herein.

3.7.1 Temperature. The operating temperature of the motor shall be from -65°F to 125°F and the non-operating temperature shall be from -650F to +160°F.

3.7.2 Altitude. The operating altitude of the motor shall be from sea level to 50,000 feet.

3.7.3 Temperature - Altitude combination. The motor shall meet the requirements of MIL-E-5400 paragraph 3.2.24.3.

3.7.4 Humidity. The motor shall withstand the effects of humidity up to 100 percent, including conditions wherein condensation takes place in and on the motor. the motor shall withstand the above conditions during operating and non-operating conditions.

3.7.5 Vibration. The motor shall meet the requirements of MIL-E-5400 paragraph 3.2.24.5.1.3 except as modified by drawing.

3.7.6 Shock. The motor shall meet the equirements of MIL-E-5400 paragraph 3.2.24.6.

3.7.7 Sand and dust. The motor shall withstand, in both an operating and non-operating condition, exposure to sand and dust particles as encountered in areas of the world.

3.7.8 Fungus. The motor shall withstand, in both an operating and non-operating condition, exposure to fungus growth as encountered in tropical climates.

3.7.9 Salt fog. The motor shall withstand in both an operating and non-operating condition, exposure to salt-sea atmospheres.

3.8 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract and 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

3.8.1 Disassembly and inspection. The motor shall show no evidence of excessive wear damage, burning, galling, or moving parts, etc.

3.9 Dimensions. Dimensions and tolerances shall be as specified on drawing 905D490.

3.10 Weight. The maximum weight of the motor shall be 6.8 lbs.

3.11 Color. The color of the motor enclosure shall be black wrinkle.

3.12 Identification plate. The motor shall be marked as specified on drawing 905D490.

3.13 Workmanship. Workmanship and finish shall be in accordance with MIL-STD-454, Requirement 9. Finished items and parts shall not exhibit faulty material and processing such as seams, laps, laminations, cracks, visible steps, sharp edges, nicks, scratches, burrs, foreign matter, deformation, and missing operations which may affect serviceability operation, or safety.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herin or in the contract, the provisions of MIL-W-63150 shall apply and are hereby made a part of this detail specification.

4.1.1 Certification provisions. The certification provisions of MIL-W-63150 shall apply. (See 6.2.1)

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

4.3 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First Article Inspection (SeE 4.4).

b. Quality Conformance Inspection (see 4.5).

4.4 First article inspection.

4.4.1 Submission. The contractor shall submit five sample motors for evaluation in accordance with the provisions of 4.4.2.

4.4.2 Inspection to be performed. See Table I herin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.3 Rejection. If any assembly, component, or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component, or test specimen in the sample that fails to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection
CLASSIFICATION OF DEFECTS & TESTS MIL-

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWIN 905 NEXT H
	Motor, 28 Volts dc				
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRA
	Assembly	5		3.3	4.4
	Interchangeability	3		3.4	4.4
	Design and Construction	5		3.5	4.4
	Performance Tests	5		3.6	4.4
	Environmental Tests	5		3.7	4.4
	Disassembly and Inspection	5		3.8.1	4.4
	Dimensions	5		3.9	4.4
	Weight	5		3.10	4.4
	Color	5		3.11	4.4
	Identification Plate	5		3.12	4.4
	Proof Test	3		3.6.4	4.5

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.4 Disassembly and inspection (First Article Only). conclusion of all first article tests, the motor shall be disassembled and inspected for excessive wear and defects as follows:

Part	Inspect For:
a. Shaft spline	Wear or damage
b. Armature shaft	Wear or damage
c. Bearings	Galling or binding
d. Commutator	Damage, excessive grooving, thrown solder, burned segments
e. Brushes	Excessive wear, broken leads
f. Brush holders	Cracks, breaks, burned areas
g. Brush springs	Damage or cracks
h. Armature	Broken wires, damaged wires, insulation defects
i. Spacers, washers, seals	Damage or cuts
j. Yoke assembly	Broken or bare wires, stripped or damaged screw threads, cracked or broken housing, loose or broken connector pins, damaged connector body, loose or damaged pole shoes, loose, damaged or burned field windings.

This inspection shall be performed using procedures satisfactory to the contracting officer. If any motor fails to comply with the requirements of 4.4.3,it shall be classed defective.

4.4.5 Materials. Verify that materials used are in accordance with the applicable drawings and specifications.

4.4.6 Assembly. Verify that the assembly of the motor is in accordance with the applicable drawings and specifications.

4.4.7 Interchangeability testing. The motor shall be subjected to the interchangeability tests specified herein.

4.4.7.1 Motor assembly. A sample of three motors randomly selected, shall be tested for interchangeability using the test method specified in 4.4.7.3. Motors taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. The three motors shall comply with the applicable specification functioning requirements of 4.4.8 and 4.4.9 before and after the interchange of parts. It shall be the responsibility of the agency responsible for the test to inform the contracting officer by letter or other methods satisfactory to the contracting officer, when selective assembly has become necessary. Statement shall contain, as a minimum, contractor’s name and FSCM, contract number, parts involved in the selective fit, conditions of parts and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

rationale for action taken. No hand refinement of parts shall be permissible without approval by the contracting officer. No malfunctions shall be allowed in the functioning tests. Failure of a motor in the interchangeability test shall cause retest or rejection of the first article.

At the discretion of the Government representative, an interchangeability retest may be allowed. Failure during the retest shall cause rejection of the first article. A sample of six motors from each retest shall be tested using the same procedures described above.

4.4.7.2 Repair parts. At least two parts of concurrent repair parts shall be subjected to the interchangeability test specified in 4.4.7.3. Failure of any part to meet the interchangeability requirements shall be cause for rejection, subject to reconditioning and further test. A sample consisting of double the number of parts used in the original test shall be tested using the test methods specified above.

4.4.7.3 Test method for interchangeability. Motors shall be tested by disassembling and then reassembling the parts. Parts shall be disassembled from the motor and identical parts placed together and mixed. Any commercial part (screws, pins, etc.) rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test.

4.4.7.4 Repair parts. Concurrent repair parts shall be tested by disassembling two motors previously tested in 4.4.7.3 and then reassembling them using the concurrent repair parts. No hand refinement of parts will be allowed, and the assembled motors shall operate and function as intended. This test may be performed independently of the motor interchangeability testing specified in 4.4.7.1 and at more frequent intervals using accepted motors taken from current production.

4.4.8 Design and construction. Any motor which fails to comply with the specified requirements or evidences degradation of its operational performance shall be classed defective. Test equipment and procedures shall be satisfactory, to the contracting officer (see 4.5.5),

4.4.8.1 Input characteristics. Verify by measurement that the motor line voltage is 28 volts direct current.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.8.2 output characteristics. Verify by measurement that the motor output characteristics are as specified by the torque-speed curve defined on drawing 905D490.

4.4.8.3 Duty cycle. Verify by measurement that the motor duty cycle is intermittent consisting of 15 seconds on and 45 seconds off repeated 10 times maximum with rated load and terminal voltage of 28 Vdc followed by a cooling off period of 15 minutes between runs.

4.4.8.4 Motor enclosure. Verify by observation that the motor is totally enclosed.

4.4.8.5 Connector bracket. Verify by measurement that the connector bracket can withstand a force of 500 lbs maximum as noted in drawing 905D490.

4.4.9 Performance tests of motor. Any motor which fails to comply with the specified requirements or evidences degradation of its operational performance shall be classed defective. Test equipment and procedures shall be satisfactory to the contracting officer (see 4.5.5).

4.4.9.1 Performance tests. The motor selected shall be subjected to all the performance tests specified on the applicable drawing. These shall include output, torque, speed and load, current, deceleration, stall torque time, and stall condition. Test equipment and procedures shall be in accordance with the applicable drawing and satisfactory to the contracting officer. If any motor fails to comply with any test requirement, it shall be classed defective, and the lot shall be rejected.

4.4.9.2 Service life. The motor selected shall be subjected to the service life test as specified on the applicable drawing. Provisions shall be made for determining output, torque, speed and load, current deceleration, stall torque time, and stall condition on the first duty and last duty cycle.

Test equipment and procedures shall be in accordance with the applicable drawing and satisfactory to the contracting officer. If any motor fails to comply with the specified requirement, it shall be classed defective, and the lot shall be rejected.

4.4.10 Environmental tests (First article only). Any motor which fails to comply with the specified requirements or evidences degradation of its operational performance shall be classed defective. Test equipment and procedures shall be satisfactory to the contracting officer (see 4.5.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.10.1 Temperature. A high temperature test shall be performed in accordance with MIL-STD-810, Method 501.1, Prodedure I, and a low temperature test shall be performed in accordance with MIL-STD-810, Method 502.1, Procedure I. The minimum temperature during the low temperature test shall be -65°F and the maximum temperature during the high temperature test shall be +160°F.

4.4.10.2 Altitude. A low pressure altitude test shall be performed in accordance with MIL-STD-810, Method 500.1, Prodedure I.

4.4.10.3 Temperature/Altitude combination. A temperature/ altitude test shall be performed in accordance with MIL-STD-810, Method 504.1, Procedure I and equipment category 5.

4.4.10.4 Humidity. A humidity test shall be performed in accordance with MIL-STD-810, Method 507.1, Procedure I.

4.4.10.5 Vibration. A vibration test shall be performed in accordance with MIL-STD-810, Method 514.2, Procedure I equipment category C, except use 0.3 inch double amplitude form 5 to 40 cps or +3 g acceleration whichever is less and use 0.036 inch double amplitude from 40 cps to 73 cps and +10 g from 73 cps to 500 cps.

4.4.10.6 Shock. A shock test shall be performed in accordance with MIL-STD-810, Method 516.2, Procedure I.

4.4.10.7 Sand and dust. A dust test shall be performed in accordance with MIL-STD-810, Method 510.1, Procedure I.

4.4.10.8 Fungus. A fungus test shall be performed in accordance with MIL-STD-810, Method 508.1, Procedure I.

4.4.10.9 Salt fog. Samples shall be selected from each lot and subjected to the salt spray (fog) test in accordance with the procedure specified in ASTM Bl17. Unless otherwise specified on the applicable drawing the minimum exposure time shall be one and onehalf (1-1/2) hours using a 5% sodium chloride solution. Rejection shall be in accordance with the applicable protective finish specification.

4.4.11 Dimensions. Verify by measurement that the dimensions of the motor meet the requirements specified on drawing 905D490.

4.4.12 Weight. Verify by weighing the motor to determine that the motor weight is 6.8 lbs.

4.4.13 Color. Verify by observation that the color of the motor enclosure is black wringle.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.14 Identification plate. Verify by observation that the identification plate meets the requirements of drawing 905D490.

4.4.15 Workmanship. The requirements of 3.13 shall be verified by continuous inspection of all parts and assemblies to assure conformance to high quality workmanship.

4.5 Quality conformance inspection.

4.5.1 Lot formation. The term “inspection lot” is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements. In addition, motors shall be from not more than one lot from one manufacturer.

4.5.1.1 Spare parts lot. A spare part lot shall consist of spare parts as produced concurrently by a manufacturing process common to the lot. Each lot of spare parts shall not include more than one lot of material where parts are subjected to heat treatment.

4.5.1.2 Replacement parts lot. A replacement parts lot shall consist of all spare parts of the same design presented for acceptance at one time, in which the unit of product is a part manufactured separate from the process of assembled feed assemblies.

NOTE: An inspection lot shall not exceed one (1) month’s production.

4.5.2 Examination. The examinations listed in the item detail specification for Classification of Defects shall be performed on inspection lots as defined in 4.5.1 of this specification. Equipment necessary for the performance of the inspections shall be listed in accordance with 4.5.5.

4.5.3 Sampling plans. Unless otherwise specified in the Classification of Defects and Test Table, sampling plans for major and minor defects shall be in accordance with MIL-sTD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING
4.5.3.1	Motor, 28 Volts dc				905
					NEXT HI
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRA
Critical	None defined				
Major					
101.	Performance Tests		100%	3.6	4.4
102.	Weight		0.65%	3.10	4.4
103.	Evidence of Poor Workmanship		0.65%	3.13	4.4
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 20261O-23T03:03Z
Check the source to verify that this is the current version before use.

4.5.4 Testing. Testing is described in the first article and quality conformance inspection tables.

4.5.4.1 Spare Parts. Spare parts furnished with an inspection lot of motors will be accepted, provided motors of the lot are accepted after all inspections and tests. In case of a failure of any motor in any acceptance inspection and tests, associated spare parts from the lot associated with the defective motor shall be accepted only after screening by the contractor for the revealed defect and resubmission for inspection as directed by the Government

4.5.4.2 Replacement Motors. Each lot of replacement motors will ordinarily be accepted on the basis of the inspections and tests of this specification: however, the Government inspector may, if he deems necessary, submit a representative sample of replacement motors for the inspections and tests of this specification.

4.5.5 Inspection Equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in Table 4.5.3.1. The contractor shall submit for approval all inspection equipment designs in accordance with the terms of the contract. See MIL-W-63150 and 6.3 herein.

4.5.6 Proof test (first article inspection only). When specified in the contract (see 6.2) three (3) Electric Drive Motors -shall be forwarded to the site specified by the contracting agency and assembled to an accepted Universal Turret Subsystem (UTS). The Electric Drive Motor shall function in accordance to the intent of the design and with no evidence of malfunction. When approved by the contracting agency, this test may be performed at the aircraft system level.

5. PACKAGING

5.1 Preservation, packaging, packing, and marking. Controls shall be preserved, packaged, packed and marked in accordance with the requirements of the Preservation and Packaging Data for Drawing P 905D490 at the level of production specified in the contract (See 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended Use. The electric drive motor covered bv this specification is intended for use with Gun, automatic, 20mm: M197 on Armament Subsystem, Helicopter, 20mm: M97E1 and M97E2.

6.2 Ordering Data. Procurement documents shall specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Quantity required and delivery schedules.

c. Serialization requirements, if applicable.

d. Quality Conformance Inspection, if other than specified in Section 4 of this specification.

e. First Article Sample requirements, if other than specified in Section 4 of this specification.

f. Packaging requirements, if other than specified in Section 5 of this specification.

g. Certificates of conformance for each lot or shipment of product and as specified in MIL-W-63150.

h. Spare parts required.

i. Replacement parts schedules.

j. Marking requirements for shipment.

6.2.2 Contract data requirements. Contract data requirements for inspection equipment design shall conform to Data It;m Description DI-R-1714, Tailored.

6.3 Submission of inspection equipment design for approval. Equipment designs shall be submitted as required to: Commander, ARRADCOM, ATTN: DRDAR-QAF-1, Dover, NJ 07801. Request letter of submittal shall state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, ARRADCOM, Dover, NJ 07801, ATTN: DRDAR-QAF-S.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1005 A616)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-63535 TURRET SUBSYSTEM, UNIVERSAL (UTS) FOR ARMAMENT SUBSYSTEM, HELICOPTER 20MM

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
ENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US ARMY ARMAMENT RESEARCH & DEVELOPMENT COMMAND
ATTN:: DRDAR-QAF
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.