
MILITARY SPECIFICATION SHEET

BATTERY, DRY, BA-1393A/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the dry battery described herein shall consist of this document and the latest issue of Specification MIL-B-18.



WIRING DIAGRAM

INCHES	MM
1/32	.79
1/16	1.59
1/8	3.18
5/16	7.94
1	25.4
1 1/8	28.58
4 15/16	125.41

NOTES:

1. All dimensions shown on figure are in inches.

Ⓐ denotes changes

Source: https://assist.dla.mil - Downloaded: 2026-10-15T16:59Z
Check the source to verify that this is the current version before use.

NOTES:

2. Metric equivalents specified in table are for general information only and are based upon 1 inch = 25.4 millimeters.

3. Wrap both ends with polyester film tape of 3/4" minimum width.

4. The cells shall be made with a poly-vinyl-chloride barrier material or equal, and with a polyethylene seal or equal.

5. Positive and negative terminals shall be MALCO Co. of Chicago, Ill.

6. Insulating sleeve for negative terminal only shall be Rayclad, Inc., Redwood City, Calif., Part No. RNF-100, Type 2, Part (CLEAR), or equal.

7. Wire leads shall be LW-C24(7) per MIL-W-76 and shall extend 2-3/8 $\pm$ 1/4 from battery to terminal ends.

REQUIREMENTS:

Dimensions and configuration: See figure.

Nominal voltage: 13.0 volts.

Usual number and type of cells: 10 "R-3WA".

Usual cell connection: Series.

Terminals: See figure.

Weight (Maximum): 8.5 ounces.

(A) Capacity tests: When the battery is tested in accordance with the methods of examination and test of this Specification, the minimum capacity-test requirements shall be not less than the minimum time specified for SLD or SLT.

(A) First Article inspection:

Visual and mechanical (External).
Battery voltage.
Vibration test.
Mechanical-shock test per MIL-STD-202, method 213, test condition I.
Insulation resistance test per MIL-STD-202, method 302, test condition Letter B, tolerance $\pm$20 volts.
Capacity, D (without storage).
Jacket integrity test.

(A) Quality conformance inspection:

Visual and mechanical (External).
Battery voltage.
Insulation-resistance test per MIL-STD-202, method 302, test condition Letter B, tolerance $\pm$20 volts.
Vibration test.
Mechanical-shock test per MIL-STD-202, method 213, test condition I.
Jacket integrity test.
Electrode leakage.
Capacity, D & T.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:59Z
Check the source to verify that this is the current version before use.

Methods of examination and test:

Capacity tests: See requirements for capacity specified herein.

Storage -	Test	Period
	D	12 months
	T	90 days

Discharge - The battery shall be discharged through 370 ohms continuously to a test-end voltage of 9.0 volts.

Closed circuit voltage -

Special marking on each unit package:

TO TEST THIS BATTERY WITH TS-183 ( )/U:

USE JACK NO.	MINIMUM PERMISSIBLE VOLTAGE
11	10.0

Unless expressly authorized, this test information shall apply to Army and Air Force applications only.

Custodian:
Army - ER

Preparing activity:
Army - ER

Review activities:

Project Number: (6135-A171-14)

User activities:

Army - ME, AV

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:59Z
Check the source to verify that this is the current version before use.