MIL-C-20/3B
25 May 1973
SUPERSEDING
MIL-C-20/3A
2 June 1961


MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE COMPENSATING) (INSULATED), NON-ESTABLISHED RELIABILITY, STYLE CC22

INACTIVE FOR NEW DESIGN AFTER DATE OF THIS SPECIFICATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-C-20.



INCHES	MM
.025	.64
.030	.76
.060	1.52
.062	1.57
.225	5.72
.250	6.35
.430	10.92

NOTES
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Leads shall be of tinned wire, .025, .032 (.64, .08 mm) diameter and 1.250(31.75 mm) minimum length.

FIGURE 1. Style CC22 capacitors (insulated).

REQUIREMENTS:

Design and construction:
Dimensions and configuration: See figure 1.
Lead type: Radial.
DC rated voltage: 500 volts.
Operating temperature range: -55° to +125°C.
Characteristic: See table I.

Capacitance: Within tolerance specified (see table I).

Quality factor (Q): In accordance with MIL-C-20.

Dielectric withstanding voltage: In accordance with MIL-C-20.
Body insulation - Test I.

Temperature coefficient and capacitance drift: In accordance with MIL-C-20.
For capacitors with values of 20 pF or less, the temperature-coefficient tolerance shall be determined in accordance with the curve shown on figure 2. For points below the curve, characteristics are not considered practicably measurable.

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:02Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Type designation 1/	Capacitance (pF)	Capacitance tolerance	Temperature coefficient shown as column head and tolerance envelope for temperature coefficient shown in column								
			A	C	H	L	P	R	S	T	U
CC22-K0R5C	0.5	C	K	K	K	K	K	K	K	K	K
CC22-KR75-	0.75	CD	K	K	K	K	K	K	K	K	K
CC22-K1R0-	1	CD	K	K	K	K	K	K	K	K	K
CC22-K1R5-	1.5	CD	K	K	K	K	K	K	K	K	K
CC22-K2R0-	2	CD	K	K	K	K	K	K	K	K	K
CC22-K2R2-	2.2	CD	K	K	K	K	K	K	K	K	K
CC22-J3R0-	3	CD	J	J	J	J	J	J	J	J	J
CC22-J3R3-	3.3	CD	J	J	J	J	J	J	J	J	J
CC22—4R0-	4	CD	H	H	H	H	H	H	H	J	J
CC22—4R7-	4.7	CD	H	H	H	H	H	H	H	J	J
CC22—5R0-	5	CDF	H	H	H	H	H	H	H	J	J
CC22—6R0-	6	CDF	H	H	H	H	H	H	H	J	J
CC22—6R8-	6.8	CDF	H	H	H	H	H	H	H	J	J
CC22—7R0-	7	CDF	H	H	H	H	H	H	H	J	J
CC22—8R0-	8	CDF	H	H	H	H	H	H	H	J	J
CC22—9R0-	9	CDF	H	H	H	H	H	H	H	J	J
CC22—100-	10	CDFG	H	H	H	H	H	H	H	J	J
CC22—120-	12	GJK	H	H	H	H	H	H	H	J	J
CC22—150-	15	GJK		H	H	H	H	H	H	J	J
CC22—180-	18	GJK		H	H	H	H	H	H	J	J
CC22—200-	20	GJ		H	H	H	H	H	H	H	J
CC22—220-	22	GJK		H	H	H	H	H	H	H	J
CC22—240-	24	GJ	.....	H	H	H	H	H	H	H	J
CC22—270-	27	FGJK	..			H	H	H	H	H	J
CC22—300-	30	FGJ					H	H	H	H	J
CC22—330-	33	FGJK						H	H	H	J
CC22—360-	36	FGJ						H	H	H	J
CC22—390-	39	FGJK							H	H	J
CC22—430-	43	FGJ								H	J
CC22UJ470-	47	FGJK									J
CC22UJ510-	51	FGJ									J
CC22UJ560-	56	FGJK									J
CC22UJ620-	62	FGJ									J

1/ Complete type designation will include additional letter symbols to indicate, where applicable, temperature coefficient, tolerance envelope for temperature coefficient, and capacitance tolerance.

Life: In accordance with MIL-C-20, operating condition 1.

Marking:

Method I - In accordance with MIL-C-20, except for "JAN" brand. The beginning of the type designation shall be adjacent to the end having the inner-electrode terminal.

Method II - In accordance with MIL-C-20 and as shown on figure 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:02Z
Check the source to verify that this is the current version before use.





FIGURE 2. Limits for characteristic measurement.



1. The characteristic, capacitance, and capacitance tolerance shall be indicated on the capacitor by five spots of color. The characteristic spot shall be adjacent to the inner-electrode terminal; the diameter shall be at least twice that of any other spot, or the space from the characteristic spot to the adjacent end of the capacitor body shall be no larger than one-third the space from the capacitance-tolerance spot to the opposite end of the capacitor body.

2. The MIL identifier (black spot) shall be applied to the capacitor body diametrically opposite the color spots.

FIGURE 3. Color-code marking.

Source: https://assist.dla.mil -- Downloaded: 202610-15T17:02Z
Check the source to verify that this is the current version before use.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army -
Navy - OS
Air Force - 80
DSA - ES

User activities:
Army -
Navy - AS, SH, MC
Air Force -

Preparing activity:
Air Force - 11

Agent:
DSA - ES

(Project 5910-1064-3)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1973-714-546/3816

Source: https://assist.dla.mil -- Downloaded: 202640-15T17:02Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

C 16061

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-15T17:02Z
Check the source to verify that this is the current version before use.

FOLD

4950/TZS
Wright-Patterson AFB, O 45433
OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE
DoD-318



4950/TZS
Wright-Patterson AFB, Ohio 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:02Z
Check the source to verify that this is the current version before use.