
MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, CERAMIC DIELECTRIC (TEMPERATURE COMPENSATING) (UNINSULATED), NON-ESTABLISHED RELIABILITY, STYLE CC25

INACTIVE FOR NEW DESIGN AFTER DATE OF THIS SPECIFICATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-C-20.



INCHES	MM
.020	.51
.040	1.02
.060	1.52
.180	4.57
.375	9.53
.650	16.51

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Leads shall be of tinned wire, .025±.002(.64±.05 mm) diameter and 1.250(31.75 mm) minimum length.

FIGURE 1. Style CC25 capacitors (uninsulated).

REQUIREMENTS:

Design and construction:
Dimensions and configuration: See figure 1.
Lead type: Radial.
DC rated voltage: 500 volts.
Operating temperature range: -55° to +85°C.
Characteristic: See table I.

Capacitance: Within tolerance specified (see table I).

Quality factor (Q): In accordance with MIL-C-20.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:03Z
Check the source to verify that this is the current version before use.

TABLE I. Capacitor characteristics.

Type designation 1/	Capacitance (pF)	Capacitance tolerance	Temperature coefficient shown as column head and tolerance envelope for temperature coefficient shown in column								
			A	C	H	L	P	R	S	T	U
CC25-H150-	15	GJK	H	H							
CC25-H180-	18	GJK	H	H							
CC25-H200-	20	GJ	H	H							
CC25-H220-	22	GJK	H	H							
CC25-H240-	24	GJ	H	H							
CC25-H270-	27	FGJK	H	H	H	H	H				
CC25-H300-	30	FGJ	H	H	H	H	H				
CC25-H330-	33	FGJK	H	H	H	H	H	H	H		
CC25-H360-	36	FGJ	H	H	H	H	H	H	H		
CC25-H390-	39	FGJK	H	H	H	H	H	H	H		
CC25-H430-	43	FGJ	H	H	H	H	H	H	H		
CC25-H470-	47	FGJK	H	H	H	H	H	H	H	H	
CC25-H510-	51	FGJ	H	H	H	H	H	H	H	H	
CC25—560-	56	FGJ	H	H	H	H	H	H	H	H	J
CC25—620-	62	FGJ						H	H	H	J
CC25—680-	68	FGJ						H	H	H	J
CC25—750-	75	FGJ						H	H	H	J
CC25—820-	82	FGJ							H	H	J
CC25—910-	91	FGJ								H	J
CC25—101-	100	FG								H	J
CC25—111-	110	FG								H	J
CC25UJ121-	120	FG									J
CC25UJ131-	130	FG									J
CC25UJ151-	150	FG									J

1/ Complete type designation will include additional letter symbols to indicate, where applicable, temperature coefficient, tolerance envelope for temperature coefficient, and capacitance tolerance.

Temperature coefficient and capacitance drift: In accordance with MIL-C-20.
For capacitors with values of 20 pF or less, the temperature-coefficient tolerance shall be determined in accordance with the curve shown on figure 2. For points below the curve, characteristics are not considered practicably measurable.

Moisture resistance: In accordance with MIL-C-20, except polarization is not applicable.

Life: In accordance with MIL-C-20, operating condition 1.

Marking:
Method I - In accordance with MIL-C-20, except for "JAN" brand. The beginning of the type designation shall be adjacent to the end having the inner-electrode terminal.
Method II - In accordance with MIL-C-20 and as shown on figure 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:03Z
Check the source to verify that this is the current version before use.





FIGURE 2. Limits for characteristic measurement.



1. The characteristic, capacitance, and capacitance tolerance shall be indicated on the capacitor by five spots of color. The characteristic spot shall be adjacent to the inner-electrode terminal; the diameter shall be at least twice that of any other spot, or the space from the characteristic spot to the adjacent end of the capacitor body shall be no larger than one-third the space from the capacitance-tolerance spot to the opposite end of the capacitor body.

2. The MIL identifier (black spot) shall be applied to the capacitor body diametrically opposite the color spots.

FIGURE 3. Color-code marking.

Source: https://assist.dla.mil -- Downloaded: 202610-15T17:03Z
Check the source to verify that this is the currentversion before use.

Custodians:
Army - EL
Navy - EC
Air Force - 11

Review activities:
Army -
Navy - OS
Air Force - 80
DSA - ES

User activities:
Army -
Navy - AS, SH, MC
Air Force -

Preparing activity:
Air Force - 11

Agent:
DSA - ES

(Project 5910-1064-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:03Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

4950/TZS
Wright-Patterson AFB, OH 45433

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T17:03Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER (I... Code) – Optional — An
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 202640-15T17:03Z
Check the source to verify that this is the current version before use.