MIL-P-26958A (USAF)
18 December 1956
Superseding
MIL-P-26958 (USAF)
13 March 1956

MILITARY SPECIFICATION

PUMP, ROTARY, POWER DRIVEN, 60 GPM CAPACITY, MOBILE, TYPE MC-2

1. SCOPE

1.1 This specification covers one type of mobile, 60 gpm capacity, power driven, rotary pump, designated Type MC-2.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Federal

CC-M-641	Motors; Alternating-Current, Integral Horsepower
NN-B-591	Boxes, Fiberboard, Wood-Cleated (For Domestic Shipment)
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed And Lock-Corner

Military

MIL-P-100	Packaging and Packing For Overseas Shipment, General Specification
MIL-P-116	Preservation, Methods of
MIL-B-121	Barrier Material, Greaseproofed, Flexible (Waterproofed)
MIL-B-130	Barrier-Material, Paper, Noncorrosive
MIL-A-148	Aluminum Foil
MIL-P-775	Packaging and Packing for Overseas Shipment and Domestic Shipment Involving Storage of Hose, Rubber or Fabric (Including Tubing); and Fittings, Nozzles, and Strainers
MIL-P-4185	Paper, Tissue, Wrapping
MIL-H-4441	Hose, Rubber, Gasoline, Lightweight
MIL-C-5756	Cable and Wire, Power, Electric, Portable
MIL-H-6615	Hose, Rubber, Gasoline, With Reusable Couplings, Low Temperature
MIL-C-7474	Casters, Industrial
MIL-W-8005	Wheels And Hubs, For Industrial Pneumatic Tires

FSC 1320

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T10:33Z
Check the source to verify that this is the current version before use.

MIL-M-8090	Mobility Requirements, Ground Support Equipment, General Specification For
MIL-B-10377	Box, Wood, Cleated, Veneer, Paper Overlaid

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables For Inspection By Attributes
MIL-STD-129	Marking For Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property

DRAWINGS

Ordnance

B7041347	Lunette Eye
C7073209	Pintle Assembly

Air Force

52C6417	Caster, Truck, Swivel

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 OTHER PUBLICATIONS.- The following document forms a part of this specification. Unless otherwise specified, the issue in effect on date of invitation for bids shall apply.

National Board of Fire Underwriters

Phamphlet 70	National Electrical Code (Electric Wiring and Apparatus)

(Copies of NBFU pamphlets may be obtained upon application to the National Fire Protection Association, 60 Batterymarch Street, Boston 10, Massachusetts.)

3. REQUIREMENTS

3.1 COMPONENTS.- The pump shall consist of the following major components: pump unit, electrical equipment, motor, hose, frame and drawbar, and running gear.

Source: https://assist.dla.mil -- Downloaded: 20260-20T10:33Z
Check the source to verify that this is the current version before use.

3.2 MATERIALS.- Materials shall be as specified herein. Materials not definitely specified shall be of the best quality used in commercial practice and shall be free from all defects and imperfections that might affect the serviceability of the finished product.

3.3 DESIGN AND CONSTRUCTION.- The pump shall be designed and constructed so that no parts will work loose in service. It shall be built to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, and service.

3.3.1 ADJUSTMENT AND REPAIRS.- The pump shall be so constructed that adjustments and repairs can be easily made by personnel with the minimum use of special tools.

3.3.2 SAFETY.- All moving parts and parts subject to high temperatures considered hazardous shall be insulated.

3.3.3 CAPACITY.- The pump shall have a capacity of 50 to 60 gpm at a 20-foot lift. The pump shall be suitable for liquids of any viscosity, from ether to asphalt, up to 700 standard Saybolt units free flow.

3.3.4 MOBILITY.- The pump shall incorporate mobility features in accordance with the applicable requirements of MIL-M-8090, type II mobility, and as specified in 3.10.

3.4 PERFORMANCE.- The pump shall be capable of meeting the performance requirements specified herein.

3.5 PUMP UNIT.- The pump unit shall be of the rotary type and shall be equipped with a suitable petcock, adequately marked for priming purposes. The pump unit shall be belt-driven by the electric motor specified in 3.7.

3.5.1 STRAINER.- A strainer shall be provided on the suction side of the pump unit. It shall be designed to permit easy removal without the use of special tools.

3.6 ELECTRICAL EQUIPMENT.- All applicable electrical equipment shall be explosion-proof and shall meet the requirements of NBFU pamphlet 70 for hazardous locations, class I, division I, group D. Electrical components, both equipment and circuitry, shall meet the requirements of the Underwriters' Laboratories, Inc. (see 6.3).

3.6.1 POWER CABLE AND PLUG.- A power cable conforming to MIL-C-5756 shall be connected to the motor. The cable shall have a ground lead and shall be 50 feet long. The free end of the cable shall be provided with a weathertight, explosion-proof male plug having a 30-amp, 220 to 440V, 3-wire, 4-pole rating.

Source: https://assist.dla.mil -- Downloaded: 20260-20T10:33Z
Check the source to verify that this is the current version before use.

3.7 MOTOR.- The pump shall have a 2-hp, 3-phase, 60-cycle 1,800-rpm induction-type motor conforming to CC-M-641. The motor shall be capable of operating on either 220 or 440V and shall be equipped with a thermal overload relay and across-the-line starter. Prior to shipment, the motor shall be wired for 220V operation.

3.8 HOSE.- The pump shall be provided with a 30-foot length of 2-inch suction hose conforming to MIL-H-4441 and a 50-foot length of 2-inch discharge hose conforming to MIL-H-6615. The free end of each hose shall have a female fitting.

3.8.1 HOSE BRACKETS.- Two adequately braced brackets shall be affixed to the pump to permit coiling of the hose when not in use.

3.9 FRAME AND DRAWBAR.- The pump shall be mounted on a rectangular steel frame, end-swept at one end to form a fixed drawbar. The drawbar shall be equipped with a lunette eye conforming to Drawing B7041347.

3.10 RUNNING GEAR

3.10.1 WHEELS AND HUBS.- Two wheels and hubs conforming to MIL-W-8005, with size 6.00-9 industrial pneumatic tires, shall be provided.

3.10.2 AXLES.- Two cantilever-mounted axles shall be permanently affixed to the frame so that a tread of 46 inches will be provided.

3.10.3 LANDING GEAR.- The landing gear shall be equipped with an 8-inch-diameter rubber-tired swivel caster conforming to MIL-C-7474 and 52C6417-10 casters.

3.10.4 PINTLE HOOK.- A pintle hook conforming to Drawing C7073209 shall be mounted at the rear of the frame for towing in train.

3.11 INTERCHANGEABILITY.- All replaceable parts shall be constructed to definite standards, tolerances, and clearances in order that any such part of a particular type or model may be replaced or adjusted without requiring modification. When practicable, all such parts shall be permanently and legibly marked with the manufacturer's part number.

3.12 IDENTIFICATION OF PRODUCT.- Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.13 WORKMANSHIP.- The pump, including all parts and accessories, shall be fabricated and finished in a workmanlike manner. Particular attention shall be given to the following:

a. Freedom from blemishes, defects, burrs, and sharp edges.

Source: https://assist.dla.mil -- Downloaded: 20260-20T10:33Z
Check the source to verify that this is the current version before use.

b. Thoroughness of soldering, welding, brazing, wiring, and riveting.

c. Alignment of parts and tightness of assembly screws and bolts; et cetera.

4. QUALITY ASSURANCE PROVISIONS

4.1 CLASSIFICATION OF TESTS.- The inspection and testing of the pump shall be classified as acceptance tests.

4.2 ACCEPTANCE TESTS.- Acceptance tests shall consist of the following:

a. Individual test

b. Sampling plan and tests

4.2.1 INDIVIDUAL TEST.- Each pump shall be subjected to the examination of product test as described under 4.3.

4.2.2 SAMPLING PLAN AND TESTS

4.2.2.1 SAMPLING PLAN.- Sampling of the pump shall be in accordance with MIL-STD-105. Acceptance quality levels to be employed shall be as specified by the procuring activity. The samples shall be subjected to the tests listed below and described under 4.3.

a. Hydrostatic test

b. Capacity

c. Mobility

4.2.2.1.1 MIL-STD-105.- When MIL-STD-105 specifies an action by the Government, it shall, at the option of the Government, be performed either by the Government or by the contractor under the supervision of the Government inspector.

4.3 TEST METHODS

4.3.1 EXAMINATION OF PRODUCT.- The pump shall be examined to determine compliance with the requirements specified herein with respect to materials, workmanship, dimensions, and marking.

4.3.2 HYDROSTATIC TEST.- The pump shall be subjected to a hydrostatic pressure equal to 1-1/2 times the maximum working pressure for a period of 5 minutes. Any leakage shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 20260-20T10:33Z
Check the source to verify that this is the current version before use.

4.3.3 CAPACITY.- The pump shall be operated at normal voltage and speed against a vertical lift of 20 feet and a discharge pressure of not less than 10 psi for a period of not less than 12 hours. The pump shall deliver at least 50 gpm of aviation gasoline or jet-engine fuel at atmospheric pressure without overheating the shaft bearing, seal or packing gland, and with no evidence of unsatisfactory operation.

4.3.4 MOBILITY.- The pump shall be subjected to the type II mobility test specified in MIL-M-8090. Upon completion of this test, the test specified in 4.3.3 shall be repeated.

5. PREPARATION FOR DELIVERY

5.1 PRESERVATION AND PACKAGING

5.1.1 LEVEL A.- The pump shall be preserved in accordance with MIL-P-116 and as specified herein.

5.1.1.1 The motor and components shall be preserved in accordance with method II.

5.1.1.2 The pump, frame, and running gear shall be preserved in accordance with method I. The internal parts of the pump shall be flushed with type P-10 oil. All unpainted exterior surfaces shall be coated with type P-1 preservative.

5.1.1.3 The hose, fittings, and strainer shall be preserved and packaged in accordance with MIL-P-775.

5.1.2 LEVEL B.- The pump shall be preserved and packaged in accordance with the manufacturer's commercial practice. Unit quantities shall be as specified by the procuring activity. Packaging material in direct contact with unprotected surfaces susceptible to damage by corrosion shall conform to MIL-B-121, MIL-B-130, MIL-A-148, or MIL-P-4185 (see section 6).

5.1.3 LEVEL C.- The pump shall be preserved and packaged in accordance with the manufacturer's commercial practice.

5.2 PACKING

5.2.1 LEVEL A.- Pumps preserved and packaged as specified in 5.1.1 shall be packed in exterior-type shipping containers conforming to PPP-B-601, PPP-B-621, or MIL-B-10377. Insofar as practicable, exterior containers shall be of uniform shape and size, of minimum cube and tare consistent with the protection required, and shall contain identical quantities. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto.

Source: https://assist.dla.mil -- Downloaded: 20260-20T10:33Z
Check the source to verify that this is the current version before use.

5.2.2 LEVEL B.- Pumps preserved and packaged in accordance with 5.1.1 and 5.1.2 shall be packed in domestic-type exterior containers conforming to NN-B-591, PPP-B-601, PPP-B-621, or MIL-B-10377 respectively. Exterior containers shall be of minimum cube and tare consistent with the protection required. Insofar as practicable, exterior containers shall be of uniform shape and size. The gross weight of each pack shall be limited to approximately 500 pounds. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto.

5.2.3 LEVEL C.- Packages which require overpacking for acceptance by the carrier shall be packed in exterior-type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall conform to the Consolidated Freight Classification Rules or regulations of other common carriers as applicable to the mode of transportation.

5.3 PHYSICAL PROTECTION.- Cushioning, blocking, bracing, and bolting, as required, shall be in accordance with JAN-P-100 except that for domestic shipments, waterproofing requirements for cushioning materials and containers shall be waived. The drop tests of JAN-P-100 shall be waived when preservation, packaging, and packing of the item are for immediate use or when the drop tests of MIL-P-116 are applicable.

5.4 MARKING FOR SHIPMENT.- Interior and exterior containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 INTENDED USE.- The pump covered by this specification is intended for use in removing residue from fuel storage tanks and for pumping liquids of relatively high viscosity.

6.2 ORDERING DATA.- Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Required level of preservation, packaging, and packing (see section 5).

(1) Level B preservation and packaging is intended to provide economical but limited protection, and should be specified only when it is determined to be appropriate. Effective period of protection 180 days from date of initial packaging.

Source: https://assist.dla.mil -- Downloaded: 202610-20T10:33Z
Check the source to verify that this is the current version before use.

6.3 HAZARDS QUARANTEE.- The bidder shall submit proof to the procuring activity that the electrical equipment specified in 3.6. which he proposes to supply under this specification conforms to the standards of the Underwriters' Laboratories, Inc. as regards fire and casualty hazards. The label or listing of the Underwriters' Laboratories, Inc. will be accepted as evidence of conforming to the specification requirements.

6.3.1 In lieu of the label or listing, the bidder may submit independent proof satisfactory to the procuring activity that this equipment conforms to the published standards, including methods of tests, of the Underwriters' Laboratories, Inc. Compliance with the fire and casualty hazards requirements does not absolve the bidder from complete compliance with the other requirements of this specification.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

JWS/PAS/let
WCLE

GPO 809185

Source: https://assist.dla.mil -- Downloaded: 202610-20T10:33Z
Check the source to verify that this is the current version before use.