METRIC
MIL-C-83522/18A
25 June 1992
SUPERSEDING
MIL-C-83522/18
7 May 1991

MILITARY SPECIFICATION

CONNECTOR FIBER OPTIC, SINGLE TERMINUS, ADAPTER.
2.5 MILLIMETER BAYONET COUPLING PC MOUNT.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-83522.




FIGURE 1. Dimensions and configuration.


DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.

Letter	Millimeters		Inches	
	Max	Min	Max	Min
A	2.517	2.502	0.0991	0.0985
B	5.82	5.64	0.229	0.220
C	1.32	1.12	0.065	0.044
D	7.04	6.81	0.277	0.268
E	7.80	7.75	0.307	0.300
F	5.33	5.03	0.226	0.180
J	6.98	6.85	0.275	0.270
K	7.34	7.24	0.290	0.285
L	5.46	5.21	0.215	0.205
M	8.38	8.13	0.340	0.320
P	9.91	9.65	0.390	0.380
Q	20.6	20.37	0.810	0.781
R	2.01	1.91	0.85	0.075
S	5.84	5.74	0.230	0.226
T	9.65	9.40	0.380	0.370
U	5.46	5.21	0.235	0.205
V	9.70	9.45	0.420	0.310
W	12.8	12.6	0.505	0.495
X	0.203	0.152	0.008	0.006
Y	5.33	5.08	0.210	0.200

FIGURE 1. Dimensions and configuration - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.



NOTES:
1. Dimensions are in millimeters.
2. Inches equivalents are given for general information only.
3. Tolerance is 0.38 mm (±.005 inch) unless otherwise specified.
4. This dimension may be held by use of a spacer to be supplied with receptacle.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

Metals: The coupling and bushing housing shall be of corrosion resistant steel in accordance with QQ-S-763, class 303/316L or nickel plated brass in accordance with QQ-B-626.

Dust covers: Shall be thermoplastic.

Hex nut: Shall be nickel plated brass or stainless steel.

Dimensions and configuration: See figure 1.

Optical requirements:

Optical loss (attenuation): Not applicable.

Nuclear radiation resistance: Not applicable.

Weight: 20 grams maximum.

Safety wire holes: Not applicable.

Force to engage and disengage:

Longitudinal force: Not applicable.

Torque: Not applicable.

Coupling proof torque: Not applicable.

Coupling mechanism retention force: Not applicable.

Fiber optical cable: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.

Water Submersion: Not applicable.

Ozone exposure: Not applicable.


Fluid immersion: Not applicable.

Temperature cycling: Applicable except 5 cycles, -55°C to +85°C.

Mating durability: Applicable except 500 cycles.

Residual Magnetism: Not applicable.

Part or Identifying Number (PIN) is a new term encompassing previous terms used in specifications such as part number, type designator, or identification number.



Temperature:
H - High
N - Normal

Fiber size
X (type I) (125 μm, MM)
Y (type II)(125 μm, MM/SM)
Z (type I) (140 μm, MM)

Addition considerations:
S - Qualified to space flight requirements.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Navy - SH
Air Force - 17, 19, 71, 80, 90, 99
DLA - ES
NASA - LRC, MSF

User activities:
Navy - AS, MC, OS
Air Force - 13, 14, 80

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project number 6060-0098-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-83522/18A	92-06-25

3. DOCUMENT TITLE CONNECTOR FIBER OPTIC, SINGLE TERMINUS, ADAPTER, 2.5 MILLIMETER BAYONET COUPLING PC MOUNT

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
2750 LOG/ES GENTILE AFS	(1) Commercial (513) 296-5517	(2) AUTOVON 986-5517
c. ADDRESS (Include Zip Code) 1060 HAMILTON STREET DAYTON, OH 45444-5400	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-29T08:36Z
Check the source to verify that this is the current version before use.