MILITARY SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, 6PDT,
[illegible] AMPERES, PERMANENT MAGNET DRIVE, HERMETICALLY SEALED,
ALL WELDED, AC COIL

This specification is approved for use by all Departments
and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation MIL-R-83536






FIGURE 1 Dimensions and configurations

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.



MOUNTING HOLE LAYOUT



AC SOCKET PIN

TERMINAL LAYOUT FOR SOCKET PIN RELAYS

FIGURE 1 Dimensions and configurations - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.




FIGURE 1 Dimensions and configurations - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm
001	0 03	1 000	25 40
002	0 05	1 010	25 65
005	0 13	1 053	26 75
040	1 02	1 090	27 69
062	1 57	1 410	35 81
150	3 81	1 412	35 86
156	3 96	1 437	36 50
174	4 42	1 462	37 13
200	5 08	1 483	37 67
260	6 60	1 520	38 61
270	6 86	1 708	43 38
310	7 87		

NOTES
1. Dimensions are in inches
2. Metric equivalents are given for general information only
3. Unless otherwise specified, tolerance is ± 010 (0 25 mm)
4. There shall be affixed to the relay a suitable legible circuit diagram that identifies each terminal location specified
5. These relays are polarized monostable
6. This relay shall not operate or be damaged by reverse polarity
7. Permanent magnet drive consists of a permanent magnet with its flux path switched and combined with the electro-magnet flux
8. Applicable to horizontal flange mount only The circuit diagram, manufacturer's PIN, and the military PIN shall be marked on the near side The remaining portion of the nameplate data shall be marked on the far side
9. Applicable to horizontal flange mount only Relays shall be marked with the manufacturer's name or CAGE code and date code Marking shall be with the bottom of the print adjacent to the near side
10. Socket pin terminals shall be gold-plated in accordance with MIL-G-45204, type II, class I The nickel underplating shall be 50 to 150 microinches thick minimum
11. Silicone rubber gasket, AMS 3332, shore hardness 15 to 35, thickness 050 ± 005 (1 27 ±0 13 mm)
12. Indicated terminals shall be identified by contrasting beads
13. Plane of critical motion for vibration and shock is Y-axis

FIGURE 1 Dimensions and configurations - Continued

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Contact data

Load ratings See table I

Low level 10 to 50 µA at 10 to 50 mV dc or peak ac

Intermediate current Applicable

Mixed loads Applicable

TABLE I Rated contact load and cycles (amperes per pole)

Type of load (high level)	Cycles x 10^3	28 V dc	115 V ac 1 phase 400 Hz	115 V ac 1 phase 50/60 Hz 1/	115/200 V ac 3 phase 400 Hz	115/200 V ac 3 phase 50/60 Hz 1/
Resistive	100	10	10	2 5	10	2 5
Inductive	20	8	8	2 5	8	2.5
Motor	100	4	4	2 0	4	2.0
Lamp	100	2	2	1.0	N/A	N/A

1/ For 50/60 Hz rating, rupture and overload are not applicable and life for each load shall be 10,000 cycles

Life 100,000 cycles, unless otherwise specified (see table I).

Contact voltage drop or resistance

High level

Initial. 0 100 ohm maximum

During life 5 percent open circuit voltage maximum

After life 0 125 volt maximum

Intermediate current.

Initial 0 100 ohm maximum

During intermediate current 3 ohms maximum

Low level

Initial 0.050 ohm maximum

During low level. 33 ohms maximum

After low level 0 125 ohm maximum

Contact bounce: 1 0 millisecond maximum

Contact stabilization time 2 5 milliseconds maximum

Overload current 40 amperes dc, 60 amperes ac

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

Rupture current 50 amperes dc, 80 amperes ac

Time current relay characteristics See table II

TABLE II Time current relay characteristics 1/

Successive application	Amperes	Time
1	15	1 hour
2	50	5 0 seconds
3	100	1 2 seconds
4	250	0 2 second
5	350	0 1 second

1/ All relays shall withstand overload and fault currents Relays must be able to sustain five applications (make and carry only) of power concurrently on adjacent poles at each of five different current levels in the sequence listed in table II. Separate relays shall be tested at 28 V dc and 115/200 V ac, 400 Hz 3-phase Cooling time between successive applications shall be 30 minutes Tests shall be performed on both normally open and normally closed contacts There shall be no failures or evidence of welding or sticking and relays shall pass contact voltage drop at the conclusion

Coil data 1/ See table III

Operate time 20 milliseconds maximum with rated coil voltage over the temperature range

Release time 50 milliseconds maximum from rated coil voltage over the temperature range

Duty rating Continuous

Coil transient suppression Not applicable

Neutral screen Not applicable

Electrical data

Insulation resistance

Initial. 100 megohms minimum at 500 V dc.

After life or environmental tests 50 megohms at 500 V dc

1/ CAUTION Due to possible interaction of relay magnetic fields, the following spacing requirements, as a minimum, shall be considered in dense packaging situations.

a Row to row assisting fields 125 (3 18 mm)

b Row to row opposing fields 1875 (4 763 mm)

c Side to side alternating fields 0625 (1 588 mm).

d Side to side like fields 125 (3 18 mm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

TABLE III. Dash numbers and characteristics. 1/

Dash number 2/		Mount	Coil data											
			At 25°C						Over temperature range			Maximum pickup voltage		
Solder hook	Socket pin		Coil voltage (V dc) 3/		Frequency (Hz)	Coil current (amperes) minimum	Specified pickup voltage (V ac) 4/	Specified hold voltage (V ac) 4/	Specified dropout voltage (V ac) 4/	Specified pickup voltage (V ac) 4/	Specified hold voltage (V ac) 4/	Specified dropout voltage (V ac) 4/	High temperature test	Continuous current test
			Rated	Max										
001	002	RVFM	115	122	400	.06	72	22	7.5	90	30	5 0	95 4	105

1/ Each relay possesses high level and low level capabilities. However, relays previously tested or used above 10 mA resistive at 6 V dc maximum or peak ac open circuits are not recommended for subsequent use in low level applications.

2/ The suffix letter L, M, P, or R to designate the applicable failure rate level shall be added to the applicable listed dash number Failure rate level (percent per 10,000 cycles): L, 3.0; M, 1.0; P, 0 1; R, 0 01 Example: 001L, 002R

3/ CAUTION. The use of any coil voltages less than the rated coil voltage will compromise the operation of the relay

4/ Pickup, hold, and dropout voltages as shown are for test purposes only and are not to be used for design criteria

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

Dielectric withstanding voltage 2/

Sea level	Coil to case	All other points
Initial	1,000	1,250
After life	1,000	1,000
Altitude		
At 80,000 feet	350	350
At 300,000 feet	500	500

Environmental characteristics

Temperature range -70°C to +125°C

Maximum altitude rating 300,000 feet

Shock (specified pulse) Applicable, MIL-STD-202, method 213, test condition C, except peak value shall be 50 g's for 6 to 9 ms Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts

Vibration (sinusoidal) Applicable, MIL-STD-202, method 204, 20 g's except frequency range shall be 10 to 2,000 Hz Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts

Vibration (random) Applicable to qualification and group C inspection Test in accordance with MIL-STD-202, method 214, test condition IF (0.3 g^2/Hz, 50 to 2000 Hz), 15 minutes each plane Contact chatter shall not exceed 10 microseconds maximum for closed contacts and 1 microsecond maximum closure for open contacts.

Acceleration. Applicable, except 15 g's

Physical data

Dimensions and configurations See figure 1

Weight 0.26 pound (117.94 g's)

Terminal strength

Solder hook terminals

Pull force 10 pounds ±1.0 pound

Bend Applicable

Twist Not applicable.

Socket pin terminals·

Pull force For .062 diameter terminals 10 pounds ±1.0 pound.

Bend Applicable

Twist Not applicable

2/ Dielectric may be improved by suitable insulation of terminals and wiring after installation

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

Terminal solderability Applicable to solder hook terminals only

Seal Hermetic.

Marking Applicable

Part or Identifying Number (PIN) M83536/27 (dash number from table I and suffix letter designating failure rate level) PIN is a new term encompassing previous terms used in specifications such as part number, type designator, and identification number.

Qualification inspection:

Qualification inspection and sample size See table IV.

TABLE IV Qualification inspection and sample size

Single submission	Group submission	
18 units plus 1 open unit for level L at C = 0 1/ 33 units plus 1 open unit for level M at C = 0 1/ Qualification inspection as applicable	M83536/27-001 " " M83536/27-002	18 units plus 1 open unit for level L at C = 0 1/ 33 units plus 1 open unit for level M at C = 0 1/ Qualification inspection as applicable 2 units, qualification inspection table, group II, shock, vibration, acceleration, terminal strength, and seal 2 units, qualification inspection table, group II

1/ The number of units required for qualification testing shall be increased as required in group V, table II of MIL-R-83536, if the contractor elects to test the number of units permitting one or more failures Prior to performance of qualification testing, the relay manufacturer shall preselect the sampling plan.

Supersession data: See table V

TABLE V Supersession data

Superseded PIN M6106/8-	Replacement PIN M83536/27-
003	001
004	002
007	001
008	002

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Air Force - 99
DLA - ES

Preparing activity
Air Force - 85

Agent
DLA - ES

(Project 5945-0824-25)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:08Z
Check the source to verify that this is the current version before use.