MIL-S-85064(AS)
8 June 1977

SUPERSEDING
XWS-4669(RU)
14 November 1963

MILITARY SPECIFICATION

SIGNAL, UNDERWATER SOUND, MARK 82 MOD 0 and MARK 128 MOD 1

This specification is approved for use by the Naval Air Systems Command Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification establishes the requirements for the manufacture and acceptance of both the Signal, Underwater Sound (SUS), Mark 82 Mod 0 and Mark 128 Mod 1, referred to herein as the signal(s).

1.2 Classification. - The signals specified herein are of identical construction and vary only in explosive loading and are identified by different Mark and Mod.

1.2.1 Signal, Underwater Sound, Mk 82 Mod 0. - This signal contains a nominal explosive load of 1.1 ounces of tetryl and 1.8 pounds of TNT.

1.2.2 Signal, Underwater Sound, Mk 128 Mod 1. - This signal contains a nominal explosive load of 1.1 ounces of tetryl.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. - The following documents of the issue in effect on the date of invitation for bids, or request for proposal, form a part of this document to the extent specified herein.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

COMMENTS OR RECOMMENDATIONS WHICH MAY BE OF USE IN IMPROVING THIS DOCUMENT MAY BE SENT TO THE PREPARING ACTIVITY WHEN A SELF-ADDRESSED STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL (DD FORM 1426) APPEARS AT THE END OF THIS DOCUMENT, OR BY LETTER ADDRESSED TO THE COGNIZANT ACTIVITY.

FSC 1361

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND
(Code Ident 30003)

DL 695493	Signal, Underwater Sound, Mk 82 Mod 0, Assembly, Loaded
DL 695494	Arming and Firing Mechanism, Mk 39 Mod 0, Loaded
DL 1332255	Pack, Shipping and Storage (For Six or Eight Signals, Underwater Sound)
DL 2116941	Explosive Section, Underwater Sound Signal, Mk 4 Mod 0, Loaded
DL 2116973	Explosive Section, Underwater Sound Signal, Mk 8 Mod 0, Loaded
DL 2127915	Pack, Shipping and Storage (For Six Signals, Underwater Sound)
DL 3261252	Signal, Underwater Sound, Mk 128 Mod 1, Assembly, Loaded
696819	Arming Wire Assembly

OTHER PUBLICATIONS

NAVAL SEA SYSTEMS COMMAND
(Code Ident 53711)

WR 54/131	Weapons Requirement, Palletizing, Fleet Issue Unit Load, Signals, Underwater Sound
WR 54/167	Weapons Requirement, Palletizing, Fleet Issue Unit Load, Signals, Underwater Sound

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Item identification. - The signals specified herein are hydrostatically operated explosive loaded ordnance items designed to detonate at nominal water depths of 60 or 300 feet, selectable prior to launch, for the purpose of providing a high energy underwater sound source. The SUS Mk 82 Mod 0, DL 695493, is composed of an arming and firing mechanism (A&F), Mk 39 Mod 0, DL 695494; an explosive section, Mk 4 Mod 0, DL 2116941; and an arming wire assembly, Dwg. 696819. The SUS Mk 128 Mod 1, DL 3261252, is composed of an A&F, Mk 39 Mod 0, DL 695494; an explosive section, Mk 8 Mod 0, DL 2116973; and an arming wire assembly, Dwg. 696819.

3.2 Government furnished property list. - The shipping containers and explosive components may be Government furnished when so specified in the contract or order.

3.3 Performance.

3.3.1 Time from water entry to detonation. - The signal, when launched from an aircraft, shall enter the water, sink to the preset depth and detonate. When detonation occurs, the time from water entry to detonation shall be as follows (see 4.5.1).

(a) Shallow depth setting: 4 ± 2 seconds (Cl).

(b) Deep depth setting: 17 ± 3 seconds (C2).

3.3.2 Detonation quality. - The signal shall detonate high order as determined by the first bubble periods of Table I (see 4.5.2).

TABLE I. FIRST BUBBLE PERIODS

Depth setting	Mk 82		Mk 128	
	Period (msec)	Characteristic	Period (msec)	Characteristic
Shallow	121 ± 13	M101	42 ± 4	M103
Deep	42.2 ± 4.0	M102	14.5 ± 1.2	M104

3.4 Design and construction. - The signal shall be fabricated and assembled in accordance with the drawings, parts lists and other documents listed on DL 695493 or DL 3261252, as specified in the contract or order.

3.5 First article. - When specified (see 6.2), the contractor shall furnish sample units for first article inspection and approval (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. In addition, the Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. - The inspection requirements specified herein are classified as follows.

(a) First article inspection (see 4.3).

(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. - Unless otherwise specified in the contract or order, a first article sample of 80 signals shall be submitted for evaluation. The sample will be subjected by the Government to any or all of the examinations and tests specified in 4.5.1 and 4.5.2 of this specification and any or all requirements of the applicable drawings. The first article sample shall be manufactured using the same methods and materials prepared for production. Any production prior to acceptance of the first article sample shall be at the risk of the supplier.

4.3.1 First article performance test sampling. - Of the sample submitted, 20 each shall be tested under each Condition of Table II. Two defective units in any one of the samples of 20 shall reject the total first article sample for MAJOR characteristics. One CRITICAL defect shall reject the first article sample.

4.4 Quality conformance inspection. - The quality conformance inspection shall verify that all characteristics of Section 3, Requirements, and Section 5, Packaging, have been met.

4.4.1 Inspection lot. - The inspection lot shall be as defined in MIL-STD-105, shall not exceed 3200 signals, and shall not be less than 1201 except in start-up and in final lots. Lot sizes shall be in multiples of pallet loads plus samples for destructive tests.

4.4.2 Inspection lot sample. - The inspection lot sample shall be selected and examined to the data package in accordance with MIL-STD-105, Inspection Level II, with an Acceptable Quality Level (AQL) of 1.0 defects per hundred units for MAJOR characteristics and 2.5 defects per hundred units for MINOR characteristics, except as specified in 4.4.3. One CRITICAL defect shall reject the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

4.4.3 Sampling for performance tests. - After acceptance of the inspection lot sample, the performance lot sample shall be selected and tested in accordance with 4.5.1 and 4.5.2 under the conditions listed in Table II, In accordance with MIL-STD-105, inspection level S-3 for each test Condition with an AQL of 4.0 percent defective. for MAJOR characteristics. One CRITICAL defect shall reject the lot.

TABLE II. PERFORMANCE TEST CONDITIONS

Test condition No.	SUS depth setting	Aircraft launch	
		Altitude ± 10% (ft)	Velocity ± 10% (knots, true air speed)
1	Shallow	300	300
2	Deep	300	300
3	Shallow	10,000	190
4	Deep	10,000	190

4.4.3.1 Performance lot sample inspection. - Prior to conducting the performance tests, 100 percent of the sample shall be visually examined to verify the following, with an AQL of 1.0 defects per hundred units for MAJOR characteristics and 2.5 defects per hundred units for MINOR characteristics (not annotated). One CRITICAL defect shall reject the lot.

(a) The container marking is legible and correct.

(b) The container is not deformed in a manner that would adversely affect sealing or removal of the contents.

(c) The lid gasket shall not be damaged or exhibit deterioration or permanent deformation.

(d)The presence of eight desiccant units, and one each humdiity indicator, instruction sheet and ammunition data card.

(e) The styrofoam trays are anti-static treated (C3).

(f) There is no evidence of TNT exudate from the tail and the plastic closure plug is securely in place (C4). (Note: This applies to the SUS Mk 82 only.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

(g) The arming wire assembly is properly assembled and not free to fall out by gravity (C5).

(h) The explosive section is not damaged (C6).

(i) The signal marking and color coding are legible and correct (C7).

(j) The depth setting wire is properly installed (M105).

(k) The four screws holding the A&F mechanism to the explosive section are tightened to flatten the lockwashers (M106).

(l) There is no evidence of corrosion of the metal parts.

(m) The tail shroud is not loose (M107).

4.5 Test and inspection methods.

4.5.1 Time from water entry to detonation. - The signal shall be launched from a suitable aircraft and the time from water entry to detonation measured to an accuracy of 1.0 percent of the mean specified times.

4.5.2 Detonation. - The detonation first bubble period shall be measured to an accuracy of 2.5 percent of the mean specified times.

4.5.3 Packaging. - Prior to shipment, the pallet loading shall be inspected to ensure the assemblage is complete, that markings for identity and shipping are in accordance with the applicable drawings and Section 5.

5. PACKAGING

5.1 Packing. - The signal shall be packed in ammunition boxes in accordance with the drawings and specifications listed on either DL 2127915 or DL 1332255.

5.2 Palletizing. - The packaged signals shall be palletized in accordance with the requirements specified on either WR 54/131 or WR 54/167.

5.3 Marking. - In addition to any special marking required by the contract or order, each exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. - The signal is an expendable item intended for launching from aircraft or surface vessels to provide a powerful source of undewater acoustic energy. It may be used for echo ranging, position fixing, conmnication, bottom mapping, sound transmission studies, etc.

Source: https://assist.dla.mil -- Downloaded: 202640-23T10:18Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. - Procurement documents shall specify the following:

(a) Title, number, revision and date of this specification.

(b) Mark and Mod of signal and the applicable data list number required (see 1.2, 3.1 and 3.4). The packaging data list number and the palletizing WR number (see 5.1 and 5.2).

(c) Provisions for submission of first article samples (see 3.5 and 4.3).

(d) Provisions for submission of quality conformance samples for performance (destructive) testing and test activity address (see 4.4.3).

(e) The maximum time allowed for the Government tests for the first article and the quality conformance test samples.

(f) The material, quantity, schedule of delivery and providing activity for the Government furnished property (see 3.2).

(g) Identification of the cognizant activities (including codes) that represent the Government.

(h) Invoke the provisions of 7-104.79(a) of the Armed Services Procurement Regulations, Safety Precautions for Ammunition and Explosives, when not performed by a Government activity. Specify the specific sections to be complied with in DOD 4145.26M (see 6.3).

6.3 Safety precautions. - The safety precaution requirements of the "DOD Contractors' Safety Manual for Ammunition, Explosives, and Related Dangerous Material," DOD 4145.26M, are applicable. Note: When this specification is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of Ammunition and Explosives Ashore," OP 5, should be made applicable.

6.4 Specific safety precautions. - This is an explosive loaded item and therefore potentially very destructive. For specific safety precautions see Description, Operation and Handling Instructions - Signals, Underwater Sound (SUS), NAVAIR 11-1-107.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

6.5 Precedence - When the requirements of the contract, this specification, or applicable subsidiary specifications are in conflict, the following precedence shall apply:

(a) Contract - The contract shall have precedence over any specifications.

(b) This Specification - This specification shall have precedence over all applicable subsidiary specifications.

(c) Referenced Specification, Standards, and Requirements - Any referenced specification shall have precedence over all applicable subsidiary specifications referenced therein. All referenced specifications shall apply to the extent specified.

(d) Drawings - Drawings or lists of drawings referenced herein shall have precedence over all subsidiary drawings. All referenced drawings shall apply to the extent specified thereon.

6.6 Changes from previous issue - Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.7 This specification is under the cognizance of AIR-53301G.

Custodian:
Navy (AS)

Preparing Activity:
Navy (AS)

(Project No. 1361-N012)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-S-85064(AS) Signal, Underwater Sound, Mark 82 Mod 0 and Mark 128 Mod 1

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 202610-23T10:18Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Naval Air Systems Command
Washington, D. C. 20360

NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20361

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

INCH-POUND

NOTICE
OF VALIDATION

MIL-S-85064(AS)
NOTICE 1
17 October 1991

MILITARY SPECIFICATION

SIGNAL, UNDERWATER SOUND, MARK 82 MOD 0 AND MARK 128 MOD 1

MIL-S-85064(AS), dated 8 June 1977, has been reviewed and determined to be valid for use in acquisition.

Preparing activity:
Navy-AS

AMSC N/A FSC 1361

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:18Z
Check the source to verify that this is the current version before use.