INCH-POUND

MIL-C-82865(OS)
8 August 1989
SUPERSEDING
WS 13689B (IN PART)
7 September 1978
(See 6.6)

MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, MARK 152 MOD 0, MARK 153 MOD 0, MARK 154 MOD 0, AND MARK 155 MOD 0

This specification is approved for the use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 **Scope.** This specification covers the requirements for the manufacture and acceptance of the Mark 152 Mod 0, Mark 153 Mod 0, Mark 154 Mod 0, and Mark 155 Mod 0 Impulse Cartridges.

2. APPLICABLE DOCUMENTS

2.1 **Government documents.**

2.1.1 **Specifications, standards and handbooks.** The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

UU-P-268 Paper, Kraft, Untreated, Wrapping

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (3730), Indian Head, MD 20640-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:42Z
Check the source to verify that this is the current version before use.

PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-676	Box, Setup
PPP-F-320	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes
PPP-T-45	Tape, Gummed, Paper, Reinforced and Plain, For Sealing and Securing

MILITARY

MIL-B-131	Barrier Materials, Watervaporproof, Greaseproof, Flexible, Heat-Sealable
MIL-P-20306	Powder, Ignition Cartridge, (M9), 60 MM and 81 MM Mortar

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-331	Fuze and Fuze Components, Environmental and Performance Tests for
MIL-STD-453	Inspection, Radiographic
MIL-STD-1168	Ammunition Lot Numbering

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

NAVAL SEA SYSTEMS COMMAND (CAGE Code 53711)

DL2128146	Cartridge, Impulse, Mark 152 Mod 0

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

DL2128147	Cartridge, Impulse, Mark 153 Mod 0
DL2128148	Cartridge, Impulse, Mark 154 Mod 0
DL2128149	Cartridge, Impulse, Mark 155 Mod 0
DL6261402	4.5 Cubic Inch Closed Bomb Test Fixture Assembly

(Application for copies of NAVSEA drawings should be addressed to: Commanding Officer, Naval Ordnance Station, Attn: Code 802, Louisville, KY 40214-5001.)

PUBLICATIONS

NAVAL SEA SYSTEMS COMMAND (CAGE Code 53711)

OP 5	Ammunition and Explosives Ashore
WR-43	Classification of Characteristics

(Application for copies of OPs and WRs should be addressed to: Commanding Officer, Naval Publications and Forms Center, Attn: NPODS, 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

CODE OF FEDERAL REGULATIONS (CFR)

49 CFR 100-199	Transportation

(Application for copies of CFRs should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402-0001.)

2.2 **Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2), a first article sample (see 6.3) shall be subjected to first article inspection in accordance with 4.4.

3.2 Design and construction. The cartridges covered by this specification shall be manufactured, examined, tested, and packed in accordance with the contract documents and all documents listed on DLs 2128146, 2128147, 2128148, and 2128149.

3.3 Materials. All materials used in the manufacture of the cartridges shall conform to the specifications referenced on the respective drawing unless specific approval in writing covering a departure therefrom has been obtained

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the current version before use.

from the contracting activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 **Primary Components.** For the purpose of this specification the propellant (MIL-P-20306 and Drawings 2113841 and 2113856) and 120M-257W percussion primer (Drawing 7645332) are defined as primary components (see 4.5.1).

3.5 **Percussion primer.** The percussion primers in each cartridge lot shall be from a single lot which has been manufactured within the past 24 months or recertified within 12 months prior to cartridge lot completion.

3.6 **Propellant charge.**

3.6.1 **Quantity.** All propellant charges in each cartridge lot shall be from a single lot and shall conform to cartridge drawings. Charge amounts shall be determined by weight rather than by volume measurement.

3.6.2 **Propellant condition.** The propellant used shall exhibit no evidence of decomposition(see 4.6.1).

3.7 **Cartridge requirements.**

3.7.1 **X-ray.** Cartridge assemblies shall be free of imperfections when examined in accordance with 4.6.3.

3.7.2 **Hydrostatic pressure.** Cartridges shall withstand the hydrostatic pressure conditioning specified in Table I then meet the ballistic requirements cited in 3.9 when tested (see 4.4.2, 4.5 and 4.6.4).

TABLE I. Hydrostatic conditioning.

Item	Hydrostatic pressure (psig[1]/water)	Duration of conditioning (Hours)
MK152	300 ± 25	12 minimum
MK153 MK154 MK155	10 ± 2	1 minimum

[1] Pounds per square inch (lb/in^2) gage.

3.8 **Environmental.** Cartridge assemblies shall not fire, dud, or be adversely affected and shall meet the requirements of 3.9 after being subjected to the environmental tests of 4.6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.9 **Ballistic requirements.** Cartridges shall meet the ballistic requirements specified in 3.9.1 through 3.9.3 when subjected to the test prescribed in 4.6.6.

3.9.1 **Chamber pressure.** The upper (U) and lower (L) limits of maximum pressure in pounds per square inch shall be as follows:

MK152: (U)=2100, (L)= 1550
MK153: (U)=1700, (L)= 1275
MK154: (U)=2800, (L)= 2200
MK155: (U)=3800, (L)= 3250

3.9.2 **Delay time.** The time from actuation of the firing mechanism to start of pressure rise shall not exceed 50 milliseconds.

3.9.3 **Misfire.** There shall be no misfires (see 4.6.6.2).

3.10 **Workmanship.** The cartridges, in all stages of production, shall be processed under such inspection control as to assure uniformity in quality. Cartridges shall be free of burrs, dents, scratches or other defects which may prevent entry of the cartridge into the firing chamber. All components shall be free of chips, dirt, grit or other foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements(examinations and tests) as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 **Responsibility for compliance.** All items shall meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 **Classification of inspections.** The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed as specified in the applicable test method of 4.6.

4.4 First article inspection. First article inspection shall be performed after award of contract and prior to production by a facility designated in the contract or order (see 6.2). A first article sample acceptable for environmental and function testing shall be considered as a sample which meets the requirements of 3.2 through 3.7.1 and 3.10 of this specification. First article inspection shall be performed on sample units which have been produced using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be from the intended sources of supply.

4.4.1 Sample size. The first article sample shall consist of 125 cartridges.

4.4.2 Inspection routine. One hundred and fifteen cartridges shall be divided into three groups and expended in the tests listed in table II and ten shall be inspected and retained for investigative purposes. Failure of any cartridge to meet the specified requirements of 3.9 shall be cause for rejection of the first article sample. Firing shall be conducted in the test fixture specified in 4.6.6.

TABLE II. First Article inspection routine for the cartridge assembly.

Sequence No.	Test/Inspection	Req'ts	Test	No. of Cartridges Tested/ Inspected Per Group			
1	Visual	3.10	4.6.2	25	25	65	10
2	Radiographic	3.7.1	4.6.3	25	25	65	10
3	Vibration	3.8	4.6.5.1	25			
4	T & H	3.8	4.6.5.2		25		
5	Radiographic	3.7.1	4.6.3	25	25		
6	Hydrostat. Pres	3.7.2	4.6.4	25	25	65	
7	Bal. Test @ -65°F	3.9	4.6.6			22	
8	@ 70°F			25	25	21	
9	@ 200°F					22	

4.4.3 Failure. Failure of any cartridge to meet the requirements of 3.1 through 3.10 shall be cause for rejection of the first article sample.

4.5 Quality conformance inspection. Quality conformance inspection shall consist of the tests specified in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

TABLE III. Quality conformance tests and examinations.

Item	Nature of test	Requirement	Test Para.	Classification (WR-43)
Primary component	Single lot verification	3.5 & 3.6.1	4.5.1	M101
Propellant charge	Type and weight	3.6.1	4.6.2	C1
Propellant charge	Condition	3.6.2	4.6.1	C2
Cartridge	Visual inspection	3.10	4.6.2	M102
Cartridge	Radiographic inspection	3.7.1	4.6.3	C3
Cartridge	Hydrostatic	3.7.2	4.6.4	C4
Cartridge	Ballistics	3.9	4.6.6	C5
Cartridge	Preservation-packaging, packing and marking	Section 5	4.6.2	M103

4.5.1 Lot size (M101). Unless otherwise specified (see 6.2), the production lot size shall not be less than 151 and not greater than 3200. Only primary components from a single lot shall be used in a production lot of cartridges; however, one primary component production lot may be used in more than one cartridge production lot.

4.5.2 Sampling. Unless otherwise specified (see 6.2), sampling shall be in accordance with Table IV of this specification or MIL-STD-105, table I, inspection level II. An additional sample of 10 cartridges shall be randomly selected from each lot and retained for the tests required by 4.7.1.

TABLE IV. Quality conformance sample size.

Lot size	Test sample	Retained sample	Total sample size
151-280	32	10	42
281-500	50	10	50
501-1200	80	10	90
1201-3200	125	10	135

4.5.3 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as critical, major, or minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol(C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of the test or examination. Tests and examinations which are not annotated with a classification code are classified as minor.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:42Z
Check the source to verify that this is the current version before use.

4.6 Tests.

4.6.1 Propellant condition (C2). The propellant shall be inspected in accordance with the applicable paragraphs of OP 5. Evidence of decomposition shall be cause for rejection.

4.6.2 Visual inspection (Safety, C1; Others, M102 and M103). All cartridges shall be visually examined for defects. Cartridges having any of the defects cited in 3.5, 3.6.1 and 3.10 shall be rejected. The preservation-packaging, packing, and marking of the cartridges shall be examined for conformance to section 5.

4.6.3 Radiographic examination (C3). All cartridges, in the production test sample, shall be radiographically examined in accordance with MIL-STD-453. Failure of any cartridge to meet the requirements of 3.7.1 shall be cause for rejection of the cartridge. The cartridges shall be positioned on their sides for the most revealing exposure. All cartridges shall be identified with serial numbers prior to examination. The cartridge serial numbers shall be in consecutive order beginning with the number 001 in each production lot. The cartridges shall be arranged on trays or boards in consecutive numerical order, and each radiograph shall carry a permanent identification of the cartridges displayed thereon. The radiograph identification shall include the complete lot number, as stamped on the cartridges, contract number and the span of serial numbers displayed. If any assembly or loading defects are noted in the production lot samples, the contractor shall X-ray 100 percent of the represented lot and make the X-rays available to the contracting activity for review. Discontinuities in serial numbers shall be identified on the X-ray. Defective cartridges found by the vendor shall be clearly identified on the X-ray and those defectives removed from the production lot. The serial numbers shall be pen or ink stamped permanently on the cartridges with approximately 1/8-inch-high characters. The serial numbers shall be located apart from the other cartridge markings.

4.6.4 Hydrostatic inspection (C4). Acceptance test samples which are designated for ballistic test shall be subjected to a hydrostatic pressure in accordance with the conditions specified in 3.7.2. The test shall be conducted in a suitable chamber. Any cartridge which fails to meet the requirements of 3.7.2 and 3.9 shall be cause for rejection of the lot.

4.6.5 Environmental tests.

4.6.5.1 Vibration. Twenty-five cartridge assemblies in the first article test shall be subjected to the transportation vibration test in accordance with Test 119, Procedure 2, of MIL-STD-331. The test shall be conducted on cartridges packed in accordance with 5.1.1.

4.6.5.2 Temperature and humidity. Twenty-five cartridge assemblies in the first article test shall be subjected to the temperature and humidity test in accordance with Test 105 of MIL-STD-331 (except that 14 days shall be used in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

lieu of 28 days). The test shall be conducted on cartridges packaged in accordance with 5.1.1.

4.6.6 **Ballistic tests** (C5). The number of cartridges randomly selected from each production lot for the ballistic test shall be in accordance with table IV. The samples shall be randomly divided into three equal groups with group one conditioned at -65 ± 5°F, group 2 conditioned at 200 ± 5°F and group 3 conditioned at 70 ± 5°F for not less than 6 hours nor more than 24 hours. If the lot sample is not divisible by three, the additional cartridges shall be placed in the second group. Cartridges shall be removed from the conditioning chamber and fired within 5 minutes in test fixture, Drawing 6261402. If any cartridge is exposed or not fired within 5 minutes after removal, it shall be returned to 70 ± 10°F environment for at least 4 hours and then reexposed to the original environment for not less than 6 and not more than 24 hours before test firing.

4.6.6.1 **Criteria of acceptability.** The failure of any cartridge to meet the requirements of 3.9.1 through 3.9.3 shall be cause for rejection of the lot represented.

4.6.6.2 **Misfire.** The failure of any cartridge to fire shall be cause for rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure (see 4.7.1).

4.7 **Retest.** There shall be no retests.

4.7.1 **Test failure.** If test failure is attributable to an assignable cause, excluding the test cartridge, original test results should be discarded and that portion of the test reconducted.

5. PACKAGING

5.1 **Preservation and packaging.** Preservation and packaging shall be level A (see 6.4).

5.1.1 **Level A.** Level A packaging of all production lots for service use for each type cartridge is described below.

MK152

Twenty(20) cartridges shall be packaged in a box conforming to PPP-B-676, Type 1, Variety 1, Class C, Style 4, with separator for individual cartridges. The separator shall consist of a corrugated fiberboard conforming to PPP-F-320, Type CF, Class Domestic, Variety SW, Grade 275, B Flute. Inside dimensions (in inches) of the box shall be approximately 2 11/16 in length X 2 3/16 in width X 1 3/16 in depth. Adequate support and cushioning shall be provided for the packaged item. A tight pack is mandatory. The box shall be wrapped with 40 pound Kraft paper conforming to UU-P-268 Grade B. The wrapping paper shall be secured with tape conforming with PPP-T-45. Each box shall be sealed in a heat

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the currentversion before use.

sealable bag conforming to MIL-B-131, Class 1. All air shall be evacuated from bag prior to sealing.

MK153, MK154 and Mk155

Twenty-five cartridges shall be packaged in a box conforming to PPP-B-676, Type 1, Variety 1, Class C, Style 4, with separator for individual cartridges. The separator shall consist of a corrugated fiberboard conforming to PPP-F-320, Type CF, Class Domestic, Variety SW, Grade 275, B Flute. Inside dimensions (in inches) of the box shall be approximately 2 3/4 in length X 2 3/4 in width X 1 5/16 in depth. Adequate support and cushioning shall be provided for the packaged item. A tight pack is mandatory. The box shall be wrapped with 40 pound Kraft paper conforming to UU-P-268 Grade B. The wrapping paper shall be secured with tape conforming with PPP-T-45. Each box shall be sealed in a heat sealable bag conforming to MIL-B-131, Class 1. Air shall be evacuated from bag prior to sealing.

5.2 Packing. Packing shall be level A or C as specified in the contract or purchase order (see 6.2).

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Twenty (20) inner containers as described in 5.1.1 shall be packed in a box in accordance with PPP-B-621, Class 2, Style 2. Adequate support and cushioning shall be provided for the inner containers to maintain a tight pack. A tight pack is mandatory.

5.2.2 Level C. When directed by the contracting activity (see 6.2), cartridges intended for expenditure in first article testing and for production lot acceptance tests and are packaged in accordance with 5.1.1 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with 49 CFR 171-178.

5.3 Marking.

5.3.1 Special marking. Marking of exterior containers shall be in accordance with 49 CFR 171-178.

5.3.2 Normal marking. Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be as specified below:

Inner container marking

a. NSN/DODIC
b. Item nomenclature
c. Drawing number
d. Quantity
e. Lot number in accordance with MIL-STD-1168
f. DOT explosive Class

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

Outer container marking

a. NSN/DODIC
b. Item nomenclature
c. Drawing number
d. Quantity
e. Gross weight and cube
f. Lot number in accordance with MIL-STD-1168
g. Contract or purchase order number
h. Warning--Explosive Device--Class C Explosive--Handle Carefully--Keep Fire Away

Additionally, the above specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The cartridge is intended for use to activate the cutting punch of mine sweeping cutters in severing mine mooring cables or chains.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, number and date of this specification

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1)

c. Whether first article inspection is required, and if so, specify the test activity (see 3.1 and 4.4)

d. Inspection conditions, if any other than specified (see 4.3)

e. Lot size if other than specified (see 4.5.1)

f. Sampling, if other than specified (see 4.5.2)

g. Marking if other than as specified (see 5.3.2)

h. That the safety precaution requirements of the "Contractor's Safety Manual for Ammunition, Explosives, and related Dangerous Material" DoD 4145.26M are applicable (see 6.5).

6.3 First Article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample, a first

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the current version before use.

production item, a sample selected from the first production items, a standard production item from the contractor's current inventory (see 3.1) and the number of items to be tested as specified in 4.4. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 **Definitions.** For the purpose of this specification, the following definitions apply.

6.4.1 **Level A packaging.** The degree of preservation-packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.2 **Level A packing.** The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.3 **Level C packing.** The degree of packing which will afford protection against damage during direct shipment from the source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirements of this level.

6.5 **Safety precautions.** The safety precaution requirements of the "Contractors Safety Manual for Ammunition, Explosives and Related Dangerous Material" (DoD 4145.26M) are applicable and should be specified in the contract as required by the Federal Acquisition Regulation (FAR) 23.3.

NOTE: When this document is used as part of the description of work to be accomplished by a Government activity, the safety precaution requirements of "Ammunition and Explosives Ashore" (OP5) should be made applicable.

6.5.1 **Explosive hazard classification information.**

Hazard Classification Division: 1.4
Storage Compatibility Group: S
DOT Class: C
DOT Marking - Explosive Power Device - Class C - Handle Carefully - Keep Fire Away

6.5.2 **Hazard notice.** The cartridges described herein and certain of their components are flammable or explosive and present hazards in manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

handling, storage, and shipment. The contractor should recognize these properties and take appropriate measures to guard against fire, explosion, adverse environment, corrosive atmosphere, rough handling, and electrically induced incidents.

6.6 **Supersession data.** This specification supersedes the functional test requirements of WS 13689B.

6.7 **Subject term (key word) listing.**

Fuze
Mine sweeping
Percussion primer
Propellant

Preparing activity:
Navy - OS
(Project 1377-N967)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-82865(OS)	Cartridge, Impulse, Mark 152 Mod 0, Mark 153 Mod 0, Mark 154 Mod 0, and Mark 155 Mod 0

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commanding Officer
Naval Ordnance Station
Standardization/Documentation Div. (3730)
Indian Head, Maryland 20640-5000

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding Officer
Naval Ordnance Station
Standardization Branch (3730)
Indian Head, MD 20640-5000

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the current version before use.