INCH-POUND

MIL-G-82932(OS)
23 June 1994

MILITARY SPECIFICATION

GAS GENERATOR, M17, REMANUFACTURED ASSEMBLY

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 **Scope.** This specification covers the requirements for the remanufacture and acceptance of the M17 Gas Generator, referred to herein as "gas generator."

2. APPLICABLE DOCUMENTS

2.1 **Government documents.**

2.1.1 **Specifications and standards.** The following specifications and standards form part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (6.2).

SPECIFICATIONS

MILITARY

MIL-V-173	Varnish, Moisture and Fungus Resistant
MIL-C-5501	Caps and Plugs, Protective, Dust and Moisture Seal
MIL-C-5604	Compass; Magnetic, Pilot's Standby
MIL-C-16555	Coating Compound, Strippable, Sprayable
MIL-G-60624	Generator, Gas Pressure, Propellant Actuated, XM17, Assembly

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5035 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage- Ammunition and Explosives
MIL-STD-171	Finishing of Metal and Wood Surfaces
MIL-STD-413	Visual Inspection Guide for Elastomeric O-rings
MIL-STD-453	Inspection, Radiographic
MIL-STD-1168	Ammunition Lot Numbering
MS29513	Packing, Preformed, Hydrocarbon Fuel Resistant, O-ring
MS51965	Setscrew-Hexagon Socket, Flat Point, Alloy Steel, Cadmium Plated, UNC-3A, Plain and Self-Locking
MS51966	Setscrew-Hexagon Socket, Flat Point, Alloy Steel, Cadmium Plated, UNF-3A, Plain and Self-Locking

(Unless otherwise indicated, copies of Federal and Military specifications and standards are available from: Standardization Documents Order desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 **Other Government documents, drawings, and publications.** The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

NAVAL SURFACE WARFARE CENTER, INDIAN HEAD DIVISION (CAGE CODE 19200)

8593297	Cap, Shipping
8593745	Cartridge, Impulse, M37, Assembly
8864324	Box, Packing, Ammunition, for Generator, Gas Pressure, Propellant Actuated: M17, In Fiber Container M510
8864325	Container, Ammunition, Fiber, M510 for Generator, Gas Pressure, Propellant Actuated: M17, In Fiber Container M510

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the currentversion before use.

9242372	Carton, Alternative Packing, Ammunition, for Generator, Gas Pressure, Propellant Actuated: M17, In Fiber Container M510
10520494	Lubricant
10521864	Label, Identification
10522490	Generator, Gas Pressure, Propellant Actuated, M17 Assembly
10522491	Label, Warning
10522492	Generator, Gas Pressure, Propellant Actuated, M17, Metal Parts Assembly
10522493	Cap, Initiator
10522494	Pin, Firing
10522495	Pin, Shear
10522496	Body, Chamber
10522497	Cap, Shipping

CODE OF FEDERAL REGULATIONS (CFR)

49 CFR 100-199	Transportation

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 **Order of precedence.** In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 **General.** Materials, components, and assemblies shall comply with the requirements of Drawing 10522492 and all referenced specifications and procedures unless otherwise specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the current version before use.

3.1.1 **New components or materials.** During gas generator remanufacture, the following previous installed components or materials shall be discarded following disassembly and replaced with new components or materials which conform to cited documents:

Component or material	Document	Quantity
a. Coating, Compound	MIL-C-16555, TYPE II	A/R
b. Cartridge, M37, Impulse	8593745	1 Each
c. Cap, Shipping	8593297	1 Each
d. Cap, Shipping	10522497	1 Each
e. Compound, Thread	10522490, Note 10	A/R
f. DC-33 Lubricant	10520494	A/R
g. Label, Identification	10521864	1 Each
h. Label, Warning	10522491	1 Each
i. O-ring	MS29513-12	1 Each
j. O-ring	MS29513-20	1 Each
k. Pellet, Nylon	10522496, Note 9	2 Each
l. Pin, Shear	10522495	1 Each
m. Setscrew	MS51965-133	1 Each
n. Setscrew	MS51966-110	2 Each
o. Varnish	MIL-V-173	A/R

3.1.2 **Reusable items**. The following previous assembled components may be suitable for reuse, when components meet cited documents and inspection requirements:

Components	Document	Quantity
a. Body, Chamber	10522496	1 Each
b. Cap, Initiator	10522493	1 Each
c. Pin, Firing	10522494	1 Each

3.2 **Primary components.** For the purpose of this specification, the M37 Impulse Cartridge (Drawing 8593745) is defined as a primary component. Only one lot of primary components shall be used in each lot of gas generators, although, a primary component lot may be used in more than one gas generator lot. The gas generator lot shall contain only one M37 Impulse Cartridge lot manufactured and accepted within 12 months of completed gas generator lot assemblies.

3.3 **Gas generator production.** The gas generators shall be remanufactured in accordance with this specification, the documents listed herein and as described in specification MIL-G-60624. Each production gas generator or component, as applicable, shall meet the requirements of 3.3.1 through 3.3.2.4, respectively. Failure of any component or gas generator to meet the applicable requirements of 3.3 shall result in rejection of that unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.3.1 **Gas generator caps and chambers (Drawings 10522493 and 10522496).**

3.3.1.1 **Protective finish.** For any gas generator cap or chamber having a nonconforming exterior protective finish, the existing finish shall be stripped from the part. Following the stripping operation, a finish meeting 1.1.2.2 of MIL-STD-171 shall be applied to the exterior of the gas generator caps and chambers. (Note: The Nylon pellets (see Drawing 10522496) shall be removed from the chamber body prior to the stripping operation and discarded.)

3.3.1.2 **Hydrostatic pressure.** Each gas generator cap and chamber, after application of protective finish per 3.3.1.1, shall be tested to withstand a pressure of 9250 ± 250 psig for a duration of 15 seconds without deformation or mechanical failure (For definition see 6.4.1).

3.3.2 **Gas generator inspection.**

3.3.2.1 **Visual inspection.** All gas generators and components remanufactured under contract shall be visually inspected and screened for defects as outlined in 4.5.1.

3.3.2.2 **Breakaway torque.** There shall be no indication of movement or deformation when a breakaway torque is applied in accordance with 4.5.2.

3.3.2.3 **Residual magnetism.** Gas generators shall not deflect an approved pilot's standby compass more than 5 degrees in either direction when passed in front of the compass at a distance of 6 inches. The gas generators shall be tested in accordance with 4.5.3.

3.3.2.4 **Radiographic inspection.** Gas generators shall show proper assembly, presence of parts, and sealing when examined radiographically in accordance with 4.5.4.

3.4. **Ballistic requirements.** Gas generators shall meet the requirements of 3.4.1. through 3.4.4 when tested in accordance with 4.5.5.

3.4.1 **Shear delay time.** The upper (U) limit for shear delay shall be U= 150 milliseconds when tested in accordance with 4.5.5.1.

3.4.2 **Velocity.** The lower (L) limit for velocity shall be 120 feet per second when tested in accordance with 4.5.5.2.

3.4.3 **Misfire. There shall be no misfires.**

3.4.4 **Mechanical failure.** Gas generators shall function without mechanical failure.

4. QUALITY ASSURANCE PROVISIONS.

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements(examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:42Z
Check the source to verify that this is the currentversion before use.

specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 **Responsibility for compliance.** All items shall meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contractor. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 **Inspection conditions.** Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: 68° to 77°F
b. Altitude: Sea Level
c. Humidity: 50 percent relative, maximum.

4.3 **Classification of inspections.** The inspection requirements specified herein are classified as follows:

a. Quality Conformance Inspection (see 4.3.1)
b. Production inspection (see 4.3.2)
c. Lot acceptance inspection (see 4.3.3)

4.3.1 **Quality conformance inspection.**

4.3.1.1 **Component lot(s).** Formation, identification and submission of gas generator component lots shall be in accordance with MIL-STD-105.

4.3.1.2 **Metal part component lot size.** The maximum lot size for metal part components shall be 2500 maximum, provided the homogeneity requirements of inspection lots have been retained.

4.3.1.3 **Examination.** Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for rubber o-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability.

4.3.1.3.1 **Reusable item examination.** Of the reusable items (see 3.1.2), 100 percent examination shall be performed for all critical characteristics. Examination for major and minor defects shall be performed in accordance with MIL-STD-105, General Inspection Level I. All nonconforming material shall be considered reject.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.3.1.3.1.1 **Cap, Initiator (Drawing 10522493).**

Characteristic	Inspect for	Method of Inspection
Critical		
C1	Metal defects (e.g.—cracks, splits)	Visual
Major		
101	Damage such as gouges, dents, or corrosion to surface of .4375-20UNF-3B thread	Visual
102	Condition of 1.5625-18UNEF-2B thread (proper thread form and damage)	Visual
103	Proper pitch diameter of .4375-20UNF-3B thread	Gage (go/no go)
104	Proper pitch diameter of .75-16UNF-3A thread	Gage (go/no go)
105	Proper pitch diameter of 1.5625-18UNEF-2B thread	Gage (go/no go)
106	Proper pitch diameter of .164-32UNC-3B thread	Gage (go/no go)
107	Proper pitch diameter of .190-32UNF-3B thread	Gage (go/no go)
108	Inadequate or defective protective finish (plating)	Visual
109	Surface damage such as gouges on firing pin bore	Visual
Minor		
None defined		

4.3.1.3.1.2 **Body, Chamber (Drawing 10522496).**

Critical		
C1	Metal defects (e.g.—cracks, splits)	Visual
Major		
101	Damage such as gouges, dents, or corrosion to surface of 1.1875-16UN-3A thread	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

102	Condition of 1.5625-18NEF-2A thread (proper thread form and damage)	Visual
103	Proper pitch diameter of 1.1875-16UN-3A thread	Gage (go/no go)
104	Proper pitch diameter of 1.5625-18NEF-2A thread	Gage (go/no go)
105	Inadequate or defective protective finish (plating)	Visual

Minor
None defined

4.3.1.3.1.3 **Pin, Firing (Drawing 10522494).**

Critical		
C1	Tip Length of 0.150 + .01 inches	Gage
Major		
101	Metal defects or surface finish damage within the o-ring groove area	Visual
102	Burrs or sharp corners	Visual

Minor
None defined

4.3.2 **Production inspection.** All production gas generators remanufactured under contract shall be inspected and screened to requirements specified in 3.2 through 3.3.2.4. Any unit failing to meet the requirements listed in 3.2 through 3.3.2.4 shall be rejected and removed from the lot.

4.3.3 **Lot acceptance inspection.** Lot acceptance inspection shall consist of the examinations and tests specified in table I. Failure of any sample gas generator to comply with the requirements listed in table I shall be cause for rejection of the lot represented.

4.3.3.1 **Sample size.** A random sample from each production lot, including the retained sample for investigative purposes, shall be selected in accordance with table II for lot acceptance inspection. Test sample gas generators and gas generators retained for investigative purposes shall not be applied as part of the quantity specified for delivery by the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

TABLE I. Lot acceptance inspections and tests.

Inspection or Test	Test Paragraph	Quantity
1. Visual	4.5.1	Test and retain sample
2. Radiographic	4.5.4	Test and retain sample
3. Ballistic: -65 ± 5°F 70 ± 5°F 160 ± 5°F	4.5.5	 1/3 sample 1/3 sample 1/3 sample

TABLE II. Lot acceptance sampling.

Lot Size	Test Sample Size	Retained Sample Size
up to 50	9	2
51 to 200	15	3
201 to 500	21	3

4.4 **Assembly.**

4.4.1 **Gas generator cap assembly.**

a. Assure firing pin (Drawing 10522494), without assembled o-ring, moves freely in firing pin bore of initiator cap (Drawing 10522493).

b. Apply DC-33 Lubricant (Drawing 10520494) to the o-ring (MS29513-12) and install on firing pin.

c. Insert firing pin assembly into initiator cap (Note: Use care when inserting firing pin assembly to avoid damaging o-ring).

d. While inserting firing pin assembly, align the firing pin shear hole with initiator cap hole and install shear pin (Drawing 10522495).

e. Install and torque shear pin setscrew (MS51965-133) to 7-9 in-lbs.

f. Verify correct installation of shear pin by applying a torque of 10-15 inch ounces with a torque screwdriver to the firing pin slot. (Note: The firing pin will not rotate when shear pin is properly installed.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

g. After successful verification of installed shear pin, apply coating compound (MIL-C-16555, Type II) over the shear pin setscrew, filling the cavity approximately flush with the initiator cap outer surface. The coating compound shall not be allowed to contaminate any other area on gas generator.

4.4.2 **Chamber assembly.** Install nylon pellets on the chamber body in accordance with Drawing 10522496. (Note: Nylon pellets shall be installed following chamber body refinishing.)

4.4.3 **Gas generator final assembly.**

a. Insert M37 Impulse Cartridge (see 3.2) into chamber assembly.

b. Apply thread compound (Drawing 10522490, Note 10) or equivalent to 1.5625-18NEF-2A thread of chamber. No thread compound is permitted beyond depth of thread engagement.

c. Assemble cap assembly to chamber assembly and torque to 300-350 inch-pounds.

d. Measure overall length of the gas generator assembly to verify conformance with Drawing 10522490.

e. Install and torque two setscrews (MS51966-110) to 9-11 in-lbs.

f. After thread compound has been allowed to dry, conduct a breakaway torque inspection in accordance with 4.5.2.

g. Install the protective shipping caps (Drawing 8593297 and 10522497 or equivalent protective caps in accordance with MIL-C-5501) to the ends of the gas generator.

h. Install the warning label (Drawing 10522491) on the gas generator body (see Drawing 10522490, Note 4).

i. Install the identification label (Drawing 10521864) on the gas generator body (see Drawing 10522490, Note 3).

j. Check gas generator for residual magnetism (see 4.5.3). Any gas generator which fails to meet the requirement of 3.3.2.3 shall be demagnetized and retested.

k. X-ray all gas generators (see 4.5.4).

4.5 **Inspections and tests.**

4.5.1 **Visual inspections.** Each assembled gas generator shall be visually examined. Reject those with inadequate or illegible descriptive markings or serial numbers, dents, deep scratches, or other defects which may prevent proper installation or function.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.5.2 **Breakaway torque.** Each gas generator shall be subjected to a breakaway torque of 400 + 8 inch-pounds (approximately 34 foot-pounds), to the wrench flats of gas generator cap. The gas generator shall be acceptable if the requirement of 3.3.2.2 is met.

4.5.3 **Residual magnetism.** Each gas generator shall be moved past a pilot's standby compass face (in accordance with MIL-C-5604) by placing the gas generator 6 inches from the compass set in an east-west heading. The gas generator and the compass shall be placed at the same height from the floor. The gas generator shall be moved past the compass face in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis, and moved back past the compass face. This procedure shall be repeated for each 90 degrees rotation of the gas generator. The gas generator shall be acceptable if the requirement of 3.3.2.3 is met.

4.5.4 **Gas generator radiographic examination.** Radiographic examination of gas generators shall include x-ray in accordance with MIL-STD-453. All gas generators shall be identified with serial numbers beginning with 001 prior to examination. The gas generators shall be arranged on trays or boards in consecutive numerical order with any missing serial numbers identified on the radiographic plate. The initiators shall be positioned for the most revealing exposure with the long axis perpendicular to the radiographic beam. Each radiograph shall carry a permanent identification of the items displayed thereon in a 4 x 6 inch region maximum. The radiographic identification shall include the Drawing number, the complete lot number in accordance with MIL-STD-1168, the contract number, and the span of serial numbers displayed. Radiographs of the entire production lot shall accompany the ballistic sample to the activity conducting the tests (see 6.2). In addition, a marriage log indicating which M37 Impulse Cartridge serial number is installed in which gas generator serial number shall be provided with radiographs. Any observable imperfections as outlined in 3.3.2.4 shall be cause for rejection of the gas generator. Defective gas generators found during radiographic review are to be marked on the radiographic plate and removed from the production lot.

4.5.5 **Ballistic test.** Sample gas generators shall be conditioned for a period not less than 4 hours nor more than 24 hours at the specified temperatures. The gas generators shall be removed from the conditioning chamber and test fired within 5 minutes. If any gas generator is not fired within 5 minutes after removal, it shall be reconditioned at the specified temperature for an additional 4 hours and then tested. The gas generators shall meet the requirements specified in 3.4.

4.5.5.1 **Shear delay time.** The shear delay time shall be measured from the initiation of the M37 impulse cartridge to the shear of the 7200 (reference) pound shear joint. Each gas generator shall meet the requirements of 3.4.1.

4.5.5.2 **Velocity.** The velocity of an 80 pound weight transversing in a horizontal to a 10° below horizontal direction shall be measured within a maximum distance of 42 inches from the origin. Each gas generator shall meet the requirements of 3.4.2.

4.5.5.3 **Misfire.** An gas generator that does not fire under the conditions specified in 4.5.4 shall be considered defective, and the lot shall be considered unacceptable, unless the misfire is clearly attributable to faulty test equipment or procedure. Each gas generator shall meet the requirements of 3.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.5.5.4 **Test failure.** If test failure is attributable to an assignable cause, excluding the test gas generator, the original test results shall be discarded and that test reconducted.

5. PACKAGING

5.1 **Preservation, packaging, packing and marking.** Preservation, packaging, packing and marking shall be in accordance with 49 CFR 100-199. The contractor shall also comply with all applicable transportation regulations. The markings shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

5.1.1 **Level A.** Level A preservation, packing (see 6.4.2), and marking shall be in accordance with Drawings 8864324 and 8864325.

5.1.2 **Level C.** Level C preservation, packing (see 6.4.3), and marking shall be in accordance with Drawings 8864325 and 92423372.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 **Intended use.** The M17 gas generator provides the necessary energy to forcibly eject the parachute in the bomb dummy unit (BDU-20).

6.2 **Acquisition requirements.** Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1 and 2.2).

c. Production test activity and lot size (see 4.1).

d. Directions for shipping radiographs of entire production lot and marriage log (report indicating cartridge serial number to initiator serial number), along with the ballistic sample to the activity conducting the production lot acceptance tests (see 4.5.2).

.g. That the safety requirements of the "Contractor's Safety Manual for Ammunition, Explosives and Related Dangerous Material" (DOD 4145.26M) are applicable (see 6.3).

6.3 **Safety precautions.** The safety precaution requirements of the contractor's Safety Manual for Ammunition and Explosives" (DOD 4145.26M), are applicable and should be specified in the contract as required by the Federal Acquisition Regulation (FAR) 23.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

6.4 **Definitions.**

6.4.1 **Mechanical failure.** A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.4.2 **Level A packaging.** The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration, and physical damage during shipment, handling, indeterminate storage, and world-wide redistribution.

6.4.3 **Level C packaging.** Packaging for immediate use.

6.5 **Subject term (keyword) listing.**

Coating compound
Impulse cartridge
Lubricant

Preparing Activity
Navy - OS
(Project 1377-NE66)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2. 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-G-82932	2. DOCUMENT DATE (YYMMDD) 940623

3. DOCUMENT TITLE
GAS GENERATOR, M17, REMANUFACTURED ASSEMBLY

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)
	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDER INDIAN HEAD DIVISION, NSWC IDE 8420	b. TELEPHONE (Include Area Code) (1) Commercial 301-743-4510/4358
c. ADDRESS (Include Zip Code) 101 STRAUSS AVE INDIAN HEAD, MD 20640-5035	(2) AUTOVON DSN 354-4510/4358
	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:42Z
Check the source to verify that this is the current version before use.