NOT MEASUREMENT SENSITIVE

MIL-I-83034B
25 May 1990
SUPERSEDING
MIL-I-83034A
25 April 1972

MILITARY SPECIFICATION

INDICATOR, HORIZONTAL SITUATION AQU-6A/A

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for one type of horizontal situation indicator, designated AQU-6A/A.

2. APPLICABLE

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards, form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation. (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air logistics Center/MMEOR, Tinker AFB OK 73145-5990 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6605

DISTRIBUTION STATEMENT X. Distribution authorized to U.S. Government agencies and private individuals or enterprises eligible to obtain export-controlled technical data in accordance with regulations implementing 10 U.S.C. 140c. 11 Apr 88. Controlling DoD Office is OC-ALC/MMEOR, Tinker AFB OK 73145-5990.

WARNING. This document contains technical data, whose export is restricted by the Arms Export Control Act (Title 22, U.S.C., Sec. 2751 et seq.) or Executive Order 12470. Violations of these export laws are subject to severe criminal penalties.

DESTRUCTION NOTICE. For classified documents, follow the procedures in DoD 5200.22-M Industrial Security Manual, Section II-19 or DoD 5200.1-R, Information Security Program Regulation, Chapter IX. For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

Federal

PPP-B-601	Boxes, Wood, Cleated Plywood
PPP-B-636	Box, Shipping, Fiberboard

Military

MIL-P-116	Preservation, Method Of
MIL-E-5400	Electronic Equipment, Airborne, General Specification For
MIL-C-5541	Chemical Conversion Coating On Aluminum Alloys
MIL-S-7742	Screw Threads, Standards, Optimum Selected Series: General Specification For
MIL-M-7793/6	Meter, Time Totalizing, Miniature, Digital, 115 Volts, 400 Hz
MIL-A-8625	Anodic Coatings, For Aluminum And Aluminum Alloys
MIL-C-14806	Coatings, Reflection Reducing, For Instrument Cover Glass And Lighting Wedges
MIL-L-27160	Lighting, Instrument, Integral, White, General Specification For
MIL-B-27497	Bearings, Jewel, Sapphire or Ruby Synthetic

STANDARDS

Federal

FED-STD-595	Color

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-129	Marking For Shipment And Storage
MIL-STD-130	Identification Marking Of U.S. Military Property
MIL-STD-454	Standard General Requirements For Electronic Equipment
MIL-STD-461	Electromagnetic Emission And Susceptibility Requirements For The Control Of Electromagnetic Interference
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement Of
MIL-STD-471	Maintainability Demonstration
MIL-STD-704	Aircraft Electric Power Characteristic
MIL-STD-781	Reliability Tests Exponential Distribution
MIL-STD-810	Environmental Test Methods
MIL-STD-838	Lubrication Of Military Equipment
MIL-STD-889	Dissimilar Metals
MIL-STD-970	Standard and Specification, Order Of Preference For The Selction Of
MIL-STD-2073-1	DOD Material Procedure For Development And Application
MS33558	Numerals And Letters, Aircraft Instrument Dial, Standard Form Of

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications and standards, are available from the Naval Publications and Forms Center, Standardization Documents Order Desk, Building 4D, 700 Robbins Ave, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document (s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the documents not listed in the DODISS are the issues of the documents cited in the solicitation.

American Society For Testing And Materials (ASTM)

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Non-Government standards and other publications are normally available from the ogranization that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this document take precedence. Nothing in this document however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. The indicators furnished under this specification shall be products which are authorized by the qualifying activity for listing on the applicable qualified products list at the time of award of contract (see 4.4 and 6.4).

3.2 Materials.. Materials shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.2.1 Fungus-proof materials. Materials that are nutrients for fungi shall not be used where it is practical to avoid them. Where used and not hermetically sealed, they shall be treated with a fungicidal agent acceptable to the contracting activity. However, if they will be used in a hermetically sealed enclosure, fungicidal treatment will not be necessary.

3.2.2 Nonmagnetic materials. Nonmagnetic materials shall be used for all parts except where magnetic materials are essential.

3.2.3 Nonferrous materials. Nonferrous materials shall be used for all parts except where ferrous materials are essential.

3.2.4 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt fog, or atmospheric conditions likely to be met in storage or normal service.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.2.5 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.2.6 Corrosive fumes. The materials as installed in the indicator and under the service conditions specified herein shall not liberate deleterious fumes.

3.2.7 Hermetic seal. Nonferrous materials contained within hermetically sealed enclosures (see 6.3.1) shall be considered suitably protected from corrosion. Requirements specified for fungicidal and corrosion protective treatment and anodizing of aluminum-alloy parts shall not be applicable for parts within hermetically sealed enclosures. Cadmium plating shall not be used.

3.2.8 Protective treatment. When materials are used in the construction of the indicator that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.

3.2.9 Recycled and reclaimed materials. Recycled and reclaimed materials shall be used to the maximum extent possible without jeopardizing the end use of the item.

3.3 Selection of standards and specifications. Standards and specifications for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-970.

3.4 Design and construction

3.4.1 Design. The indicator shall be designed to present the following information:

a. Stabilized magnetic compass (within 0.50°) provided from the master directional reference.

b. Command heading information (within 0.50°) provided from a remote source or desired heading, set in manually.

c. Command course (within 0.50°) provided from a remote source or desired course set in manually and displayed by a pointer and a numerical indication.

d. Displacement of the aircraft from a manually or automatically selected track as indicated by a course bar.

e. Invalidity of course deviation data as indicated by a course-deviation alarm flag.

f. Numerical indication of distance to a transmitting radio source or target.

g. To-from indication for a selected radio facility.

h. Two independent pointers displaying bearing to selected stations or targets (within 0.50°).

i. Reciprocal bearing pointers for item h.

Source: https://assist.dla.mil - Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

j. Power failure.

3.4.1.1 Reliability. The indicator shall have a minimum acceptable mean-time-between-failures (MTBF) of 1,000 hours at a confidence level of 100 percent.

3.4.1.2 Longevity. Equipment longevity, as defined in MIL-STD-781, shall be 5,000 hours before wearout failures occur or the equipment consitently fails to meet the specified MTBF requirements.

3.4.1.3 Maintainability. Maintainability shall be in accordance with MIL-STD-471 and as specified in 3.4.1.3.1 and 3.4.1.3.2.

3.4.1.3.1. Qualitative requirements. The following qualitative requirements shall be considered in the design of the indicator.

a. Minimization of complexity of maintenance tasks (for example: calibration, adjustments, inspecton, et cetera) by maximum use of simple design which includes optimum interchangeability and use of standardized equipment or commercial items.

b. Rapid and positive recognition of equipment malfunction or marginal performance.

c. Rapid and positive identification of the replaceable defective part, assembly, or component.

d. Maximum number and types of tools and test equipment (special and standard) needed to perform maintenance.

e. Optimum accessibility in all components requiring maintenance, inspections, removal, or replacement.

3.4.1.3.2 The mean corrective maintenance downtime (M_{ct}) shall be 100 minutes less the time required to unseal and then hermetically seal the instrument after repair. The maximum corrective maintenance downtime (M_{maxct}) shall be no greater than 300 minutes less the time required to unseal and hermetically seal the case.

3.4.2 Construction. The indicator shall be so constructed that no parts will work loose in service. It shall be built to withstand the strains, jars, vibrations, and other conditions incident to shipping, storage, installation, and service.

a. The indicator shall be so constructed that overhaul, including replacement of worn parts, adjustment balance, and calibration, may be accomplished by instrument and electronic repairmen provided with simplified tools and equipment and trained in the repair of electronic equipment.

3.4.3 Compatibility. The HSI must be designed and built to be compatible with all of the aircraft interfacing equipment in use at the time of contract award. This equipment includes, but is not limited to, the AN/ARN-118 TACAN set, the AN/ARN-108 ILS set and the CPU-80A and CPU-132A Flight Director Computers. The HSI must operate with the above equipment in both single and dual HSI installation. In the dual installation the HSI must operate properly as the master or as the slave.

3.5 Performance. The indicator shall meet all requirements specified herein after exposure to the following conditions:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

a. Operating temperatures ranging from -54° to +71°C and storage temperatures ranging from -62° to +85°C.

b. Altitudes from sea level to 70,000 feet.

c. Relative humidity up to 95 percent.

d. Rainfall of 4 ±1 inches each hour.

e. Fungus growth as encountered in tropical climates.

f. Exposure to salt-laden atmosphere.

g. Dust (fine sand) particles as ecnountered in desert areas.

h. Thermal shock forces as encountered during rapid changes of extreme temperature.

i. Vibration incident to service use.

j. Acceleration force of 20g nonoperating and 5g operating.

k. Application of 250V dc for 10 seconds.

l. Alternate immersions in water at 85° ±5° and 5° ±4°C for 8 cycles with not more than 5 seconds between immersions.

3.5.1 Electromagnetic Interference (EMI). The indicator shall be designed to meet the EMI requirements of MIL-STD-461.

3.5.2 Attitude. The indicator shall be capable of operating satisfactorily while in any attitude.

3.5.3 Friction error. Not more than 0.25° of error shall be introduced into the readings as a result of friction between moving parts.

3.5.4 Magnetic effect. When the indicator is held in various positions magnetically east or west of and not more than 12 inches from the center of a free magnet in a magnetic field having a horizontal intensity of 0.18 ±0.01 oersted, deflection of the magnet shall not exceed 5°.

3.5.5 Fogging. There shall be no evidence of moisture or oil fogging of the coverglass, wedge, or display when the indicator is subjected to 71° +2°C for 1 hour and the coverglass then rubbed with ice for 1 to 2 minutes.

3.6 Part numbering of interchangeable parts. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of MIL-STD-100 shall govern the manufacturer's part numbers and changes thereto.

3.7 Electronic requirements. Electronic requirements shall be in accordance with MIL-E-5400 except as specified herein.

3.8 Miniaturization. Modern techniques of miniaturization, potting, and hermetic sealing shall be exploited to the greatest extent practicable without sacrificing ruggedness, reliability, and service life.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.





FIGURE 1. Case dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.



A. DIGITAL DISTANCE READOUT
B BEARING POINTER NO 1
C. COMPASS CARD SCALE
D COURSE POINTER
E BEARING POINTER NO. 2
F. HEADING MARKER
G. DIGITAL COURSE READ OUT
H. COURSE DEVIATION BAR
J. POWER OFF FLAG
K. FIXED MARKER
L. ELAPSED TIME INDICATOR
M COURSE SET KNOB
N. RECIPROCAL BEARING POINTER NO 1
O. RECIPROCAL BEARING POINTER NO 2
P RECIPROCAL COURSE POINTER
Q. AIRCRAFT SYMBOL
R. HEADING SET KNOB
S. COURSE DEVIATION DOTS
T. COURSE DEVIATION WARNING FLAG
U LUBBER LINE
V. TO ARROW
W FROM ARROW

FIGURE 2. Dial.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.8.1 Amplifiers. Five d-c amplifiers shall be provided and shall be integral with the indicator mechanism within the case. The amplifiers shall feature module plug-in capability, if possible. Each amplifiers module shall be designed with partial redundant circuits so that the servos will continue to operate, with reduced performance, should partial failure of the amplifier occur.

3.9 Case. The indicator case shall be in accordance with figure 1. It shall be metal, uniform in texture, shall have a smooth surface, and shall be entirely covered with a durable finish. The inside of the case around the electrical connector shall be of sufficient strength to prevent damage to the case when the electrical connector is tightened during installation.

3.9.1 Control knobs. Control knobs as shown on figure 2 shall be provided. A minimum of 2 ounce-inches and a maximum of 10 ounce-inches shall be required to turn the knobs. The knobs shall be medium gray, color No. 36231 of FED-STD-595, except the ends shall be black with white lettering. Block-type lettering shall be used.

3.9.2 Hermetic sealing. The case shall be hermetically sealed and so designed that the internal mechanism may be removed, replaced, and the case resealed without the use of special tools and fixtures unless they are approved by the contracting activity. Hermetic sealing shall be such that the sealing will not be affected by the action of any atmosphere to which the component may be subjected. The case shall meet the necessary pressure requirements when tested for leaks by means of a mass-spectrometer-type helium leak detector. (see 6.3.1).

3.9.2.1 Filling medium. The filling medium shall be of least 98 percent purity, free of dust particles, and shall contain not more than 0.006 milligram of water vapor per liter (dewpoint -65°C) at the filling pressure. The filling medium shall be a mixture of 88 to 92 percent nitrogen and the remainder helium. The absolute pressure of the filling medium in the case shall be 12 to 14.7 psi.

3.9.2.2 Leakage. The indicator shall be so sealed that the leak rate at a pressure differential of 12 to 14.7 psi will not exceed 0.1 micron cubic foot per hour.

3.10 Reflective surfaces. All reflective glass surfaces shall be provided with a reflection reducing coating which shall meet the requirements of MIL-C-14806 in addition to withstanding the environmental conditions specified herein.

3.11 Indicator display. The indicator display shall conform to figures 2 and 3. All sizes of the pointers, azimuth card, deviation bar, numerals, and letters shall conform to the size and width listed on figures 2 and 3. The azimuth card, center section of the display, and main mask of the display shall lie in one plane, designated plane A, and shall be 0.7 ±0.5 inch from the forward edge of the coverglass. The forward edge of the heading marker shall be 0.01 inch forward of plane A; the forward face of bearing pointer No. 2 shall be 0.03 to 0.04 inch forward of plane A; the forward face of bearing pointer No. 1 shall be 0.04 to 0.05 inch forward of plane A; the lubber line shall be 0.07 inch forward of plane A; the forward face of the course arrow and deviation bar shall be 0.18 inch forward of plane A; and the fixed airplane reference shall be 0.25 inch forward of plane A. The first set of deviation dots shall be .07 inch forward of plane A and the second set shall be 0.03 inch forward of plane A. The forward face of the TO-FROM pointer and deviation alarm flags shall be not more than 0.025 inch behind plane A. The dimensions given are design center values.

3.11.1 Visibility. All markings, course counter, distance readout, compass card graduations, heading marker, and bearing pointers shall be clearly visible and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

readable when viewed at a distance of 2 feet from the front of the indicator at an elevation angle of 30° from the top of the coverglass and 4 inches to the right or left of the instrument centerline. The units digit of the course counter and the hundreds digit of the distance readout shall be visible when viewed at a distance of 2 feet in front of the indicator at an angle of 20° to the right or left of the sides of the coverglass and 4 inches above or below the instrument centerline.

3.12 Standard synchro test transmitter. A standard calibrated synchro with minimum and known errors shall be provided and shall be an Eclipse-Pioneer type AY201-1, or equal, high-precision transmitting synchro. A 0° to 360° dial clamped to the rotor of the synchro shall be settable, rotatable, and readable through 360° of rotation to 6 minutes of arc. The following procedure shall be used to calibrate the test synchro:

3.12.1 The rotor leads shall be designated as H and C and one stator lead designated as Z and connected to C. When 26V is applied to H and C (C being ground) the dial shall be positioned. on 0° and clamped to the rotor when:

a. The voltage across H and Y is maximum

b. The voltage across the remaining two stator leads (X and Y) is minimum

c. The voltage across X and Z increases before it decreases for increasing heading indication of the dial. The voltage X to Z and Y to Z shall be in phase with the excitation voltage C to H when the dial reading is zero. For increasing heading indication of the dial, the voltage X to Y shall increase and be in phase with the excitation voltage C to H. The test transmitter will be set at an index reference of zero to a positive rotation reference XYZ.

3.13 Presentation. The presentation shall be in accordance with figure 2.


3.14 Aircraft heading. The aircraft heading shall be displayed on the azimuth ring and shall be read under the fixed lubber line located at the top of the indicator face as shown on figure 2.

3.14.1 Azimuth ring signal input. The input synchro control transformer (CT) shall be a high impedance type EP AY500-5, or equal, which shall receive an input from a synchro device similar to the test transmitter described in 3.12. Any CT with the same general impedance of the stator windings as a type EP AY500-5 may be utilized.

3.14.2 Azimuth ring servo system. The servo followup system, consisting of a CT, d-c torquer motor, and amplifier, shall drive the azimuth card and rotor or the input CT to a null. It shall be capable of receiving a change of heading at any rate between 0° and 60° per second without hunting. There shall be no appreciable hunting or oscillating in the servo system while the input compass signal is changing or stationary. The servo system shall position the heading indication under the lubber line to within ±0.500° of the position of a calibrated synchro. The design of the azimuth card loop shall result in operation such as would be achieved in the system shown on figure 4. The functional design shall be as shown in the block diagram on figure 4, except that d-c torquers and position feedback shall be used.

3.14.3 Azimuth card control transformer zero. The azimuth card CT shall be zeroed with a positive rotation reference at an index reference of 270°. With the XYZ leads of the azimuth card CT as specified on figure 4 and the excitation voltage of the test transmitter C to H in phase with the power input pin AA to pin BB:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.



LETTERS: I 100 R TO BOTTOM EDGE; .250 HIGH OVERALL; .040 LINE WIDTH.
NUMERALS: I.100 R TO BOTTOM EDGE; .188 HIGH OVERALL; .030 LINE WIDTH.
10° LINES: .031 LINE WIDTH, LENGTH .125.
2° AND 8° LINES: .010 LINE WIDTH, LENGTH .062.
4° AND 6° LINES: .010 LINE WIDTH, LENGTH .100.
NUMERALS AND LETTERS SHALL CONFORM TO MS 33558.
DIMENSIONS IN INCHES: TOLERANCES: DECIMALS ± .010, FRACTIONS: ± 1/16, ANGLES ± 2°.
LUBBER LINE TOUCHING COMPASS CARD EDGE, NOT OVER.
COURSE POINTER TOUCHING MINOR INDICES.
NUMBER 1 AND 2 ON BEARING POINTERS TO BE 3/32 HIGH, SAME STYLE AS ON CARD.
INDICES ON BEARING POINTERS TO BE .070 LONG AND .031 WIDE; COLOR. BLACK.

FIGURE 3. Display component dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

a. The azimuth ring shall position at 0° (north) when the rotor of the test transmitter dial is at 0°

b. If the dial on the rotor of the test transmitter is continuously rotated so that its heading indication increases, the azimuth ring heading shall increase (counterclockwise (ccw) rotation) accordingly and the voltage C' to H' of the CT shall be in phase with the excitation voltage C to H. (see 6.3.2)

3.15 Command heading. A means of selecting a desired heading both automatically and manually shall be provided. A heading marker as shown on figure 2, which can rotate around the azimuth ring shall be dirven by a d-c torquer servo system when excited by a remote device similar to the standard test transmitter specified in 3.12 and manually by a knob at the lower left corner of the instrument. There shall be no visible interaction between the knob and the servo motor so that when the remote sycnhro device is driving the servo system, turning the knob will have no lasting effect on the heading marker position. The heading marker shall rotate in synchronism with the azimuth ring after it is set. The heading selection knob shall be connected with the heading marker in such manner that clockwise (cw) rotation of the knob produces cw rotation of the knob produces cw rotation of the heading marker and vice versa. The turning ratio between the knob and the heading marker shall be 7 to 1. The azimuth scale reading indicated under the heading marker shall be the desired heading. The heading set knob shall be as shown on figure 1. The maximum backlash between the command heading marker and the azimuth card shall be 0.250°.

3.15.1 Heading marker servo system. A d-c torquer servo system similar to that described in 3.14.2 for driving the azimuth ring shall be employed for positioning the heading marker in response to a remote input signal. The servo shall receive a change of command heading at any rate between 0° and 60° per second without hunting. There shall be no appreciable hunt or oscillation in the servo system and it shall position the heading marker around the azimuth ring to within 0.50^{o} of the position of the test synchro, the function design of the heading marker loop shall be as shown on figure 4. The heading marker servo shall conform to the electrical connector and pin wiring shown on figure 4.

3.15.2 Heading marker signal input. The heading synchro device shall be a Clifton precision transolver CDSH-10-AS-4, or electrical equivalent.

3.15.3 Heading datum control transformer. The heading datum CT shall be a Clifton Precision CTC-8-A-4 CT, or equal, and shall operate as shown on figure 4. Electronic circuitry may be utilized to obtain the datum CT function when approved by the contracting activity.

3.15.4 Heading command and heading datum control transformer zero. Both the heading command and heading datum CT's shall be zeroed with positive rotation referenced at an index reference of 270°. Both synchros shall be zeroed in the following manner:

a. The standard test transmitter shall be positioned to zero indication on its dial and locked, connected to the heading command and heading datum CT's in accordance with the XYZ notation indicated on figure 4, and excited with 26V, 400 Hz.

b. The heading marker shall be positioned to 0° (north) on the azimuth card and the voltage C' to H' of the heading command CT rotor and heading datum CT rotor shown on figure 4 shall be null.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.




FIGURE 4. Functional schematic diagram.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

c. When the heading marker is rotated cw around the azimuth ring, voltage C' to H' of the heading command CT rotor and heading CT rotor shall be in the opposite phase sense as the voltage C to H of the standard test transmitter from 0° (north) to 180°, null at 180° (south) and shall be in the same phase sense as voltage C to H of the standard test transmitters from 180° (south) to 0° (north).

d. When the heading marker is set on 0° (north) on the azimuth dial and the rotor of the standard test transmitters rotated to indicate an increasing heading (dial ccw), the voltage C' to H' of the heading command CT and the heading datum CT shall be null at 0° in the same phase as the excitation voltage C to H from 0° to 180°, null at 180°, and opposite to the phase sense of C to H from 180° to 0°.

e. When the transmitter winding of the heading command CT is excited with 26V ac so that the voltage C to H is in phase with power excitation ground to phase and the heading marker is set on 0° (north), then voltage X to Z and Y to Z will be in phase with C to H and voltage X to Y null. When the heading marker is rotated cw to east, the voltage X to Z will increase before decreasing.

3.15.5 Heading marker servo zero. The heading command control transformer shall be connected to its servo system. The standard test transmitter shall be connected to the heading command CT in accordance with XYZ notation on figure 4. The excitation voltage of the test transmitter C to H shall be in phase with the servo power excitation voltage, pin AA to pin CC. The following conditions shall be satisfied:

a. The heading marker shall position to 0° (north) on the azimuth ring when the dial of the standard test transmitter is at 0°.

b. The heading marker shall rotate in an increasing heading indication on the azimuth ring (cw) when the dial of the test transmitter synchro is rotated in an increasing heading indication (dial ccw).

c. When the dial of the standard test transmitter is rotated in the increasing heading indication, the voltage C' to H' of the heading command CT shall be in the same phase sense with the voltage C to H of the standard test transmitter.

3.16 Command course. A means of selecting a desired course both automatically and manually shall be provided. A course arrow, as shown on figure 2, that can rotate around the inside edge of the azimuth ring shall be driven by a servo system when excited by a remote device similar to the standard test transmitter specified in 3.12, and shall be manually turned by a knob at the lower right corner of the instrument. As in the heading marker servo system, turning of the course knob shall have no lasting effect on the course arrow when the servo is being driven by a remote device. The course marker shall rotate in synchronism with the azimuth ring after it is set. The scale reading on the azimuth ring at the tip of the course arrow shall be the selected course or track. The course selection knob shall be connected with the course arrow in such manner that cw rotation of the knob produce cw rotation of the course arrow, and vice versa. The turning ratio between the knob and the course marker shall be 7 to 1. The course set knob shall be as shown on figure 2. A digital-type counter shall present the selected course in a window on the right side of the indicator.

3.16.1 Course marker servo system. A d-c torquer servo system, similar to that described in 3.14.2 for driving the azimuth ring, shall be employed for positioning course marker in response to a remote input signal. The servo shall be capable of receiving a change of command course at any rate between 0° and 60° per second without hunting. There shall be no appreciable hunt or oscillation in the servo

Source: https://assist.dla.mil Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

system during steady-state dynamic operation and it shall position the course around the inside-edge of the azimuth ring to within 0.50° of the position of the test synchro. The design of the differential gearing shall be such as to result in operation of the course marker with respect to the azimuth ring, remote synchro command input, and knob command input as shown on figure 4. The course marker servo shall conform to the electrical connector and pin wiring shown on figure 4.

3.16.2 Course marker signal input. The course marker servo system shall receive its input signal from a transmitting synchro device similar to the test transmitter described in 3.12. The synchro device shall be a Clifton Precision transolver CDSH-10-AS-4, or equivalent, which shall be capable of operating as a CT and a transmitter as shown on figure 4.

3.16.3 Course datum control transformer. The course datum CT shall be Clifton Precision CTC-8-A-4, or equivalent, and shall operate as shown on figure 4. Electronic circuitry may be utilized to obtain the course datum function when approved by the contracting activity.

3.16.4 Course command and course datum control transformer zero. Both the course command and course datum CT's shall be zeroed as a standard test transmitter at an index reference of 270°. Both synchros can be zeroed in the same manner as the heading command CT and heading datum CT specified in 3.15.4 through 3.15.4.4 with course marker substituted for heading marker and with all references made to the course servo system (the course servo system shall not be excited with power).

3.16.5 Course marker servo zero. The course command CT shall be connected to the standard test transmitter in accordance with the XYZ notation given on figure 4. The excitation voltage of the test transmitter C to H shall be in phase with the servo power excitation voltage pin AA to pin DD. The following conditions shall be satisfied.

a. The course marker shall position to 0° (north) on the azimuth ring when the dial of the standard test transmitter is at 0°.

b. The course marker shall rotate in an increasing heading indication on the azimuth ring (cw) when the dial of the test transmitter synchro is rotated in an increasing heading indication (ccw).

c. When the dial of the test transmitter synchro is rotated in an increasing heading indication (ccw), the voltage C' to H' of the course command CT shall be in phase with the voltage from C to H of the standard test transmitter.

d. When the transmitter winding of the course command CT is excited with 26V ac so that the voltage C to H is in phase with power excitation ground to phase and the course pointer is set on 0° (north), then voltage X to Z and Y to Z will be in phase with C to H and voltage X to Y null. If the course pointer is rotated cw to east, voltage X to Z shall increase before decreasing.

e. A resolver of any size with electrical characteristics of the type EP AY221-5-B, or equal, shall be connected to the course gear train to function as shown on figure 4 and zeroed at a scale reference of 0° and an index reference of 300°.

3.16.6 Rotor windings

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.16.6.1 Rotor winding number 1 (RW-1) is the leading winding which mechanically leads rotor winding number 2 (RW-2) by 90° in the direction of higher dial numbers with respect to the azimuth card. At the index reference point 300°, when properly zeroed, stator winding 1 (SW-1) and RW-1 are directly coupled and stator winding 2 (SW-2) and RW-2 are directly coupled. The following steps shall be used to designate rotor and stator leads:

a. The common pin of the rotor windings is designated as pin C. The two leads of a stator winding are arbitrarily labeled D and E and this stator winding is called SW-1.

b. When the course marker is rotated 300° against the azimuth card, a rotor lead shall be chosen and labeled A. This rotor winding shall be excited (C being the common ground with 10V, 400-Hz ac and the resolver rotator shaft adjusted (with scale locked at 300°), respectively. The resolver rotor shaft shall be locked to scale and the scale rotated 90° in a positive direction to 10° against the azimuth card. Voltage A to C of RW-1 shall be removed and applied to B to C of RW-2. The voltage as read across D to E of SW-1 should be maximum and in phase with applied voltage B to C of RW-2. If the voltage is out of phase, labeling A and B of the rotor leads shall be reversed and the above zeroing procedure repeated.

c. The scale reading shall be set at 300° against the azimuth card and leads B and C of RW-2 excited. Letters F and G shall be assigned to stator winding SW-2 so that the voltage measured from F to G is in phase with voltage B to C of RW-2.

d. Fine zeroing can be accomplished by exciting leads B to C of RW-2 and nulling the voltage D to E of SW-1 by rotating resolver rotor shaft when the scale readin is 300° against the azimuth card.

e. The course selector resolver shall have proper characteristics or additional provisions as required to permit use with VOR system requiring 30-Hz Omni Range Zero (ORZ). Proper ORZ at 30 Hz shall be obtained when the resolver is electrically zeroed with 400-Hz excitation at 300°. The ORZ leads shall be designated as H and C. The leads designated as A to G shall be connected to the pins specified on figure 4 on connector PTIH-24-61P, or equal (see 3.25). The VOR phase shifting component shall be connected to pin A, as shown on figure 4, on connector PTIH-24-61P, or equal.

3.17 Course bar. An indication of the displacement of the aircraft to the right or left of the selected course shall be provided by means of a course bar and dots in accordance with figure 2.

3.17.1 Course bar mechanism. Direct-current deflection signals shall cause the course bar to move across the face of the instrument. The total movement of the course bar shall be 0.687 ±0.031 inch in both directions measured from the center of the instrument. A movement of 0.625 inch from center shall require 150 microampere (ua) nominal. A d-c polarity of "+" and "-" indicated as pins on figure shall cause a deflection on the right when course arrow is on top. The course bar sensitivity shall be 75 ua per dot and range of displacement shall be ±2 dots. The course bar mechanism shall have a resistance of 1,000 ohms ±3 percent. The test limits at standard conditions for the course bar mechanism shall be as follows:

±1 dots deflection ±6 ua
±2 dots defelection ±150 ua ±12 ua.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.17.1.1 Dynamic response. The course bar mechanism shall have a damping ratio of not less than 1. The frequency response shall be such that the amplitude ratio of output to input will not decrease by more than 3 decibels (db) at 0.2 Hz.

3.17.2 Deviation bar alarm flag. A deviation bar alarm flag shall be incorporated as shown on figure 2. The flag shall be operated by a suppressed zero-type mechanism which, in the absence of current or when the current is below 180 ua, shall hold the flag against a stop in the position shown on figure 2. Upon application of 180 ua, with the polarity as shown on figure 4, the flag shall leave its stop and shall disappear completely (black background showing) with the application of 245 ua. A consecutive application of 500 ua as a step function shall not damage the mechanism. The meter movement resistance shall be 1,000 ohms ±3 percent.

3.18 TO-FROM arrow. A TO-FROM arrow shall be incorporated as shown on figure 2 and shall operate from a meter movement having a resistance of 200 ohms ±15 percent. The sensing shall be such that with no signal applied, the arrow will not be visible. A signal with polarity as shown on figure 3 shall cause the TO-FROM arrow to appear on the same side as the course arrow; a signal with opposite polarity shall cause the TO-FROM arrow to appear on the tail side of the course arrow; and a signal not greater than 225 ua shall cause the TO-FROM arrow to reach full displacement.

3.19 Display movement. The central portion of the display, including the course arrow, course bar, deviation bar alarm flag, TO-FROM arrow, and course deviation dots, shall rotate as a unit turning with the azimuth ring as the airplance's heading changes, in addition to the individual motions listed.

3.20 Meter movement bearing and pilots. Meter movements shall turn on hardened ground and highly polished pivot bearings, highly polished first quality sapphire bearings, or other materials that meet the performance requirements of this specification.

3.21 Balancing. The meter movements shall be balanced by an approved means (threaded nut or splice nuts, or a wire helix moving along a crown arm and counterweight arm) with easily accessible means for rebalancing. The use of solder, shellac, or similar means of holding balance weights will not be acceptable.

3.22 Bearing markers. Bearing marker d-c torquer servo systems shall be incorporated for positioning the bearing pointers shown on figure 2 from remote sources similar to a standard test transmitters synchro. The servo systems shall be similar to the d-c torquer servo that drives the azimuth ring. The servos shall receive changes in bearing between 0° and 60° per second without hunting. There shall be no appreciable hunting or oscillating in the servo systems and they shall position the bearing pointers around the azimuth ring to within $\pm 0.50^{\circ}$ of the test synchro position. The servo systems shall be connected as specified on figure 3.

3.22.1 Bearing pointer signal input. Each bearing pointer servo system shall receive its input signal from a transmitting synchro device similar to the test transmitter described in 3.12. The bearing pointer CT shall be a type EP AY500-5, or equal. Any CT with the same general impedance of the stator windings as a type EP AY500-5, or equal, may be used.

3.22.2 Bearing pointer control transformer zero. Each bearing pointer CT shall be zeroed at a scale reference of 180° (under the lubber line at the bottom of the display) and at an index reference of 90°.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

3.22.2.1 Conditions with a zero transmitter output. With the standard test transmitter connected in accordance with the XYZ notation on figure 3 and excited with voltage from C to H in phase with the servo excitation pins AA to BB, the transmitter dial shall be positioned to zero. The following conditions shall apply:

a. The bearing pointer shall position under the lubber line at the bottom of the display

b. Rotation of the card on the test transmitting synchro to an increasing heading indication shall cause the bearing pointer to rotate cw

c. If the rotor of the test transmitter synchro is rotated to an increasing heading indication voltage C to H of the bearing, CT shall be in the same phase sense as voltage C to H of the standard test transmitter.

3.23 Distance display. A digital-type distance display shall be provided at the upper left of the instrument as specified on figure 2. The range of the display shall be 000 to 1,999 miles. The hundreds, tens, and units numerals shall be individually driven by receiver synchros with a 1:1 ratio. The units display shall have 1-mile and 0.50-mile index lines. The numerals shall be centered each 36° of synchro shaft rotation. The receiver synchro shall be Clifton CRC-8-A-1, or equal. The thousand digit shall be driven by a shutter showing black when normally unexcited and 1 excited with 27V dc.

3.23.1 Distance synchro electrical zero. With a standard test transmitter connected in accordance with the XYZ common with C notation, and C to H of both the receiver synchros and transmitter synchro excited, the three synchros shall be zeroed as follows:

a. With test transmitters rotor position set on 0°, the 0 shall be in position on the distance dial of each receiver synchro.

b. Rotation of the test transmitter synchro to 36° shall result in 1 being positioned on the distance dial.

c. Increasing numerical dial readings on the receiver synchros shall be indicated for each 36° of the transmitter synchro rotation.

3.23.2 Distance shutter mechanism. A red and white (diagonally striped) masked shutter shall be provided for obscuring the distance display. The shutter mechanism shall be excited by 28V dc. Voltage excitation shall cause the shutter to disappear from view. The units digit shall be only partially masked by the shutter.

3.24 Power. The indicator shall be capable of operating on power supplied from an aircraft infinite bus source at 115V, 400-Hz single phase in accordance with MIL-STD-704. The indicator shall also comply with the requirements of MIL-STD-704 for utilization equipment, except when a 28V d-c source, infinite or limited, is connected to any indicator coil, disconnecting the circuit by any normally utilized aircraft switch shall not produce positive or negative transients in the system exceeding 40V maximum. Each of the five servo systems shall be excited with 115V, 400 Hz on the specific connector and pins shown on figure 4. In addition, for operation of the integral lighting, 5V a-c power shall be supplied to the proper connector end pins shown on figure 4.

3.24.1 Voltage and frequency variation. The indicator shall operate properly and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

continuously when the voltage and frequency are varied from 103 to 127V and 320 and 480 Hz, respectively, or any combination thereof.

3.24.2 Power-off flag. A power-off flag as shown on figure 2 shall be incorporated. It shall be red with black letters and so mechanized that it will appear when 115V power to the bearing and azimuth circuit is interrupted or when there is a failure of the bearing and azimuth B+ voltage. The flag shall disappear (black background showing) when both voltages are present and pin GG is externally grounded. If pin GG is not grounded, the flag shall not disappear even though both voltages are present.

3.24.3 Time totalizing meter. A time totalizing meter conforming to MIL-M-7793/6 shall be provided to record the running time of the indicator when power is applied to the azimuth and bearing servo. It shall be located in the lower right-hand corner of the indicator face behind the coverglass and just above the course set knob and shall be visible only when viewed from above and slightly in front of the coverglass. When viewed as specified the numerals shall be easily distinguishable.

3.25 Connector. An electrical connector shall be supplied on the indicator as shown on figure 1. The connector shall be Bendix part No. PTIH-24-61P, or equal. All electrical connections shall be in accordance with figure 4. The connector shall be protected during shipment and storage by a moisture-proof cap and gasket.

3.26 Integral lighting. The indicator shall be integrally lighted as shown on figure 4. The lighting system shall be in accordance with MIL-L-27160. Lighting shall be subjected to the approval of the contracting activity.

3.26.1 The integral lighting shall be comparable to and shall balance in brightness with a prime standard. The prime standard shall be an indicator conforming to this specification or a lighted mockup. The prime standard shall have applied to its lighting circuit the specific voltage which the contracting activity has established as being necessary to assure equality or presentation (from a lighting standpoint) with adjacent but dissimilar instruments. The contractor shall submit to the contracting activity for approval the test procedure for determining compliance with this requirement.

3.27 Weight. The weight of the indicator shall not exceed 8 pounds.

3.28 Screw threads. Unless otherwise specified, the threads of all machine screws shall conform to MIL-S-7742.

3.29 Lubrication. The indicator shall be lubricated in accordance with MIL-STD-838.

3.30 Jewel bearings. Jewel bearings shall be in accordance with MIL-B-27497.

3.31 Finishes and protective coatings

3.31.1 Aluminum-alloy parts. Aluminum parts shall be covered with an anodic film conforming to MIL-A-8625, except as follows:

a. Dials, small holes, and case inserts need not be anodized.

b. Aluminum alloys which do not anodize satisfactorily shall be coated with a chemical film in accordance with MIL-C-5541.

c. Where the primary purpose of the treatment is to afford a suitable paint base,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

chemical treatments in accordance with MIL-C-5541 may be used in lieu of anodizing.

d. Castings containing nonaluminum-alloy integral inserts may be treated with a chemical film in accordance with MIL-C-5541 in lieu of anodizing.

e. When abrasion resistance is a factor, chemical film in accordance with MIL-C-5541 shall not be used in lieu of anodizing.

3.32 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.33 Installation

3.33.1 Mounting screws. The contractor shall furnish sufficient mounting screws for installing the indicator. They shall be round-head, brass machine screws and shall have a durable dull-black finish. Length shall be sufficient to permit mounting on a panel 0.187 inch thick. Screw threads shall be size .190-32 UNF-2A.

3.33.2 Envelope. An envelope containing the mounting screws shall be furnished with each indicator. The following information shall be printed on the face of the envelope:

IMPORTANT
THIS ENVELOPE CONTAINS
MOUNTING SCREWS

3.34 Workmanship. The indicator, including all parts and accessories, shall be so fabricated and finished as to assure freedom from blemishes, defects, burrs, and sharp edges, accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of soldering, welding, brazing, painting, wiring and riveting; alignment of parts and tightness of assembly screws and bolts.

3.34.1 Riveting. riveting operations shall be carefully performed to insure that the rivets are tight and satisfactorily headed.

3.34.2 Cleaning. The indicator shall be thoroughly cleaned and loose, spattered, or excess solder, metal chips, and other foreign materials removed during and after final assembly.

3.34.3 Dimensions and tolerances. Dimensions and tolerances not specified shall be as close as is consistent with the best shop practices. Where dimensions and tolerances may affect the interchangeability, operation, or performances of the indicator, they shall be held or limited accordingly.

3.34.4 Soldering. Soldering shall be accomplished in accordance with MIL-STD-454, requirement 5.

3.34.5 Screw assemblies. Assembly screws and bolts shall be tight. The word tight means that the screw or bolt cannot be appreciably tightened further without damage or injury to the screw, bolt, or threads.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in this specification where such inspections are deemed necessary to ensure supplies and service conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be peformed in accordance with the test conditions specified in 4.3.1 of this specification.

4.3.1 Standard atmospheric conditions. Whenever the pressure and temperature existing at the time of the test are not specified definitely, it is understood that the test is to be made at atmospheric pressure (approximately 29.92 inches Hg) and at room temperature (approximately 25°C).

4.3.2 Voltage input. Unless otherwise specified, the indicator shall be tested with 115V 400-Hz (nominal) single-phase power connected to the specific pins of the indicator connector.

4.3.3 Proper connection. When the indicator is referred to as being properly connected, it shall be understood that it is connected to a test fixture that provides a lighting circuit voltage variable from 5 to approximately 1V and that it provides:

a. Synchro signals for remote inputs to the servo systems

b. Variable current d-c signals with reversible polarity to meter movements

c. 27V dc for shutter excitation

d. A-C power as required for operation of the servo system.

4.3.3.1 Servo operation inspections. The test specified in 4.6.3 may be performed, at the contractor's option, prior to final sealing of the indicator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.3.4 Visual observation. Unless otherwise specified, all visual observations of indicator performance shall be made at a distance of 2 feet.

4.4 Qualification inspection

4.4.1 Test samples. The test samples shall consist of six indicators representative of the production equipment. The samples shall be identified with the manufacturer's own part number and such other information as required by the qualifying activity.

4.4.3 Qualification inspections. The qualification inspections shall consist of all the tests specified under 4.6, except 4.6.29.4.

4.5 Quality conformance inspections. Quality conformance inspections shall consist of:

a. Individual tests

b. Sampling tests.

4.5.1 Individual tests. Each indicator shall be subjected to the following tests as described under 4.6:

a. Examination of product

b. Synchro and receiver zero

c. Servo operation

d. Power-off flag

e. Course bar mechanism

f. TO-FROM arrow

g. Deviation alarm flag

h. Distance display

i. Shutter

j. Leakage

k. Lighting

l. Fogging

m. Control knobs

n. Early failure detection

4.5.2 Sampling tests

4.5.2.1 Sampling plan A. Indicators shall be selected in accordance with the following and subjected to the tests specified as described under 4.6:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

Number of items	Quantity of items to be tested
*First 10	1
Next 90	2
Each additional 100	2

a. Individual tests

b. Power consumption

c. Voltage and frequency variation

d. Magnetic effect

e. Acceleration

f. Dielectric

g. Vibration error

h. Oscillation and variation

i. Servo null position shift

j. Low-temperature operation

k. High-temperature operation.

4.5.2.2 Sampling plan B. Unless otherwise specified (see 6.2), three indicators shall be selected at random from the first 15 on the contract or order and subjected to the following tests as described under 4.6:

a. Sampling plan A tests

b. Radio noise interference

c. High-temperature exposure

d. Low-temperature exposure

e. Temperature-altitude cycling

f. Temperature shock

g. Humidity

h. Fungus

i. Salt fog

j. Dust (fine sand)

k. Vibration failure

l. Acceleration

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

m. Sealing thermal shock

n. Production reliability

4.5.2.2.1 Individual tests after completing. At the option of the contractor, the tests may be divided into three groups as shown in table I to be performed on three sets of three indicators if a need exists to expediate tests. Each indicator shall meet the individual tests after completing the group of specific tests to which it is subjected.

4.5.2.3 Sampling plan C. When specified (see 6.2) MIL-STD-105 sampling and inspection procedures shall be applied for Government Acceptance of all lots of production indicators on contract. Special inspection level S-1 and Acceptable Quality Level (AQL) 6.5 shall be used throughout the acceptance program. Each sample selected shall be subjected to and meet all tests listed under 4.5.2.1 prior to acceptance of the lot by the Government.

4.5.2.4 Rejection and retest. When one indicator selected from a production run fails to meet the specification, no indicators still on hand or later produced shall be accepted until the extent and cause of failure are determined. After corrections have been made, all necessary tests shall be repeated.

4.5.2.4.1 Individual tests may continue. For operational and production reasons, individual tests may be continued pending the investigation of a sampling test failure. But final acceptance of items on hand or later produced shall not be made until it is determined that the indicators meet all the requirements of the specification.

TABLE I. Groups and tests.

Group	Test	Paragraph
I	Electromagnetic interference	4.6.25
	High-temperature exposure	4.6.26.1
	Low-temperature operation	4.6.22
	Temperature shock	4.6.26.4
II	Humidity	4.6.26.5
	Fungus	4.6.26.6
	Salt fog	4.6.26.7
	Dust (fine sand)	4.6.26.8
	Sealing thermal shock	4.6.28
III	Vibration failure	4.6.26.9
	Acceleration	4.6.27
	Production reliability	4.6.29.4

4.5.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in indicators already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.6 Test methods

4.6.1 Examination of product. The indicator shall be examined to determine compliance with the requirements specified herein with respect to materials, workmanship, marking, and visibility of the display components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.6.2 Synchro and resolver zero. The CT receiver synchro and resolver shall be checked for zero in accordance with the method specified in section 3.

4.6.3 Servo operation. The indicator shall be properly connected and the rotor of the calibrated synchro rotated at constant speed of 1.5° and 60° per second. All five servos shall be tested. The indicated azimuth, heading, bearings, and course indications shall not differ from the calibrated synchro indication more than $\pm 1^{\circ}$ at 1.5° per second nor more than $\pm 5^{\circ}$ at 60° per second. This test shall be conducted in both cw and ccw directions.

4.6.3.1 Hunting and jumping. There shall be no noticeable hunting and jumping when the standard calibrated synchro shaft is not rotated. Under dynamic conditions, the peak-to-peak amplitude of hunting and jumping shall not exceed 0.250°. The error signal shall be measured and shall not vary more than 0.1V peak-to-peak for any 0.5 second time frame for either of the rate tests specified in 4.6.3. This test shall be performed while the indicator is still uncased or provisions shall be made to measure the error signals on the spare pins of the connector.

4.6.3.2 Servo sensitivity and friction error. The indicator shall be properly connected. The rotor of the calibrated synchro shall be rotated 1° and there shall be a perceptible movement in each of the pointers and dial as their respective CT's are excited. Friction error shall not exceed 0.250°.

4.6.3.3 Scale error. The indicator shall be properly connected, the standard calibrated synchro set to zero, and the heading indication read and recorded. The calibrated synchro connected to the azimuth card shall be turned successively to heading of 30°, 60°, 90°, 120°, 150°, 180°, 210°, 240°, 270°, 300°, 330°, and 360°C and the readings under the lubber line recorded. No one reading shall differ from the corresponding synchro heading by more than 0.50°. An identical procedure shall be followed for the heading and course marker except that the reading shall be with respect to the azimuth card. An identical procedure shall also be followed for the bearing pointer, except that the test transmitter shall be set at 180° (bearing pointer will position at the top lubber line) and readings taken relative to this zero.

4.6.3.3.1 Heading marker datum output (error output). With the azimuth signal input at electrical zero, the heading marker shall be set to each azimuth card position listed in table II. The voltage output shall be as specified therein.

4.6.3.3.2 Course marker datum output (error output). With the azimuth signal input at electrical zero, the course arrow shall be set to each azimuth card position listed in table II. The voltage output shall be as listed therein.

4.6.3.4 Servo followup rate and damping. The indicator shall be properly connected. The calibrated synchro connected to the azimuth card shall be de-energized and its rotor rotated 90° and re-energized. The time required for the azimuth ring to rotate between 5° and 85° of its original displacement from the calibrated synchro shall not exceed 1.5 seconds and the total time before the azimuth ring comes to rest shall not exceed 2 seconds. An identical test shall be performed on each of the other servo systems.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

TABLE II. Azimuth card position and voltage output.

Azimuth Card Position (Degrees)		Error Voltage	
5	185	2.0	±0.4
10	190	3.9	±0.4
15	195	5.8	±0.4
30	210	11.2	±0.35
45	225	15.9	±0.3
135	315	15.9	±0.3
150	330	11.2	±0.35
165	345	5.8	±0.4
170	350	3.9	±0.4
175	355	2.0	±0.4

4.6.4 Power-off flag. With the indicator properly connected but with no power applied, the flag shall be in full view. Power shall be applied and the flag shall immediately disappear. The connection between pin GG and ground shall be broken and the flag shall appear. Pin GG shall then be grounded and the flag shall disappear. Power shall be removed and the flag shall immediately reappear.

4.6.5 Course bar mechanism. The course bar mechanism shall operate with the polarity and sensitivity specified in 3.17.1.

4.6.5.1 Balance. A static balance test with the normal 1g force of gravity acting successively along each mutually perpendicular axis of the case shall not cause the bar to deviate from its center position more than one-half bar width.

4.6.5.2 Accuracy. An accuracy test with ±d-c polarity applied to the proper terminals shall result in the following:

a. ±1 dot deflection ±75 ±6 ua

b. ±2 dots deflection ±150 ±12 ua

4.6.5.2.1 Tolerances applicable to the tests specified in 4.6.22, 4.6.23, 4.6.26.1, 4.6.26.3, and 4.6.29 shall be as follows:

±1 dot deflection ±75 ±10 ua.

±2 dots deflection ±150 ±17 ua.

4.6.5.3 Stop. Twice normal current shall be applied in each direction and slowly reduced. The pointer shall not stick.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.6.6 TO-FROM arrow. The sensitivity of the TO-FROM arrow shall be checked by applying current in each direction as specified in 3.18. Double voltage shall be applied in both directions and slowly reduced. There shall be no sticking.

4.6.7 Deviation alarm flag. The sensitivity of the deviation alarm flag shall be checked by applying voltage in the proper polarity as specified in 3.18. Double voltage shall be applied and slowly reduced there shall be no sticking.

4.6.8 Distance display. Standard test transmitter synchros shall be applied to each receiver synchro. A scale error test shall be conducted for each numeral of the units, tens, and hundreds counter. Each numeral shall center on consecutive 36° ±4.0 increments of the test transmitter as specified in 3.23.1. A voltage of 27V dc shall be applied to the thousand shutter and the thousand digit shall appear. Counter motion shall be smooth with no sticking.

4.6.9 Shutter. Proper polarity of 28V dc shall be applied to the shutter mechanism. The shutter shall disapper from view.

4.6.10 Leakage. The indicator shall be tested for leakage by means of a mass-spectrometer-type helium leak detector. The detected leak rate at a pressure differential of 12 to 14.7 psi shall not exceed 0.1 micron cubic foot per hour.

4.6.11 Lighting. The lighting circuits shall be properly connected individually and tested to show compliance with 3.26.

4.6.12 Fogging. The indicator shall be properly connected with power applied and placed in a 71° ±2°C controlled ambient for a minimum period of 1 hour. Upon completion of this period and while still at the specified temperature, an ice cube shall be rubbed on the indicator coverglass for a period of from 1 to 2 minutes. The glass shall be carefully wiped dry (compressed air shall not be used) and the indicator inspected for evidence of moisture or oil fog on the coverglass, wedge, or display. Evidence of fogging shall be cause for rejection.

4.6.13 Control knobs. The torque required to rotate the course and heading set knobs shall be measured throughout one revolution of the course arrow and the heading marker in both cw and ccw directions and shall be within 2 to 10 ounce-inches.

4.6.14 Early failure detection. Following final assembly and at the completion of the preceding individual tests, the indicator shall be properly connected with power applied to each of the five servo systems and the lighting circuits .

The five servos and three distance counters shall be operated at 10° per second for approximately 720° and then alternated in the opposite direction. The course bar, TO-FROM arrow, and deviation alarm flag shall be driven through their full range one time per minute. The heading and course knobs shall be rotated for five revolutions in each direction every hour with the remote transmitting synchro source unexcited. The test shall be conducted for a minimum of 10 hours. No failure shall occur during this test.

4.6.15 Power consumption. The power consumption of the indicator shall be measured with suitable meters. The a-c consumption shall not exceed 15 va with all five servo loops driving at 60° per second.

4.6.15.1 Voltage and frequency variation. The indicator shall be properly connected and the voltage and frequency reduced to 103V/320 Hz. The indicator shall then meet

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

all individual tests, except the scale error accuracy may be increased from 1° to 2° and servo operation may be decreased from 10 to 20 percent in the 320- to 380-Hz range.

4.6.15.2 Voltage transient test. The indicator shall be connected to an aircraft-type power supply and all indicator coil circuits tested for compliance with 3.24. A switch shall be used in the test circuit which has essentially point contacts and no built-in arc suppression capabilities. Adequate recording equipment, subject to the approval of the procuring activity, shall be used to read and record the resulting voltage transients.

4.6.16 Magnetic effect. This test shall be made first with no power applied to the indicator and then repeated with the indicator operating on rated power. The indicator shall be held in various positions magnetically east or west of and 12 inches from the center of a free magnet approximately 1.50 inches long in a magnetic field with a horizontal intensity of 0.18 ±0.01 oersted. The maximum deflection of the magnet shall not exceed 5°. An aircraft compass with the compensating magnets removed may be used as the free magnet for this test.

4.6.17 Acceleration (operating). The indicator shall be properly connected power applied to the servos and meter movements, and the indicator accelerated with a force of 5g along each axis. The servoed pointers and azimuth card shall not vary more than 1° from the initial indication and the deviation bar shall not vary more than one bar width from its initial position. The TO-FROM arrow with no power applied shall not appear.

4.6.18 Dielectric. A potential of 250V dc shall be applied between isolated pins and between pins and the case for a period of 10 seconds. There shall be no breakdown of insulation.

4.6.19 Vibration error. The indicator shall be properly connected and mounted and subjected to a vibration error test in accordance with MIL-STD-810C, method 514.2, equipment category (b), procedure I, part 2, curve AR. During this test, the indicator shall be subjected to the tests specified in 4.6.3.3 and 4.6.5.2.

4.6.20 Oscillation and variation. Oscillation and variation tests may be conducted at any indication. The maximum total amplitude of pointers, azimuth card, and course bar oscillation shall not exceed 0.50° for the pointers and azimuth card nor one-half bar width for the course bar. During vibration, the maximum variation of the pointers, azimuth card, and course bar from the original indication before vibration, throughout the frequency range, shall be noted and shall not exceed 0.50° for the pointers and azimuth card nor one-half bar width for the course bar.

4.6.21 Servo null position shift. The five servos shall be properly connected to standard test transmitters set at the zero indication. The input voltage and frequency shall be varied within the following limits and combinations thereof:

Frequency	320 to 480 Hz
A-C voltage	103 to 127V

The zero indication of the servoed pointers and azimuth card shall not shift more than 1° from the normal null position.

4.6.22 Low-temperature operation. The indicator shall be properly connected, with no power applied, and subjected to a temperature of -54° ±2°C for a period of 4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

hours. At the end of this period and while still at the low temperature, power shall be applied. There shall be no sticking of moveable component parts, and pointers shall move throughout their range of travel without sticking. No failure shall result from this test. There shall be a 5-minute warmup period after the application of power before data are taken. The HSI shall pass the tests specified in 4.6.3 through 4.6.10, except that an additional 15 percent will be permitted on all tolerances except those specified in 4.6.5.2 and 4.6.5.2.1.

4.6.23 High-temperature operation. With power applied, the indicator shall be properly connected, place in a chamber, and maintained at a temperature of $71^{\circ} \pm 2^{\circ}C$ for a period of 4 hours. There shall be no sticking of moveable component parts, pointers shall move throughout their range of travel without sticking, and there shall be no failure as a result of this test. The indicator shall pass the tests specified in 4.6.3 through 4.6.10, except that an additional 15 percent shall be permitted on all tolerances except those specified in 4.6.5.2 and 4.6.5.2.1.

4.6.24 Course bar mechanism. The course bar mechanism shall conform to the dynamic response characteristics specified in 3.17.1.

4.6.25 Electromagnetic Interference. The EMI test shall meet the requirements of MIL-STD-461 when subjected to the applicable test method of MIL-STD-462.

4.6.26 Environmental tests. The indicator shall be subjected to the following environemental tests, performed in accordance with the applicable procedures of MIL-STD-810C and as specified herein.

4.6.26.1 High-temperature exposure. The indicator shall be properly connected and subjected to a high-temperature exposure test in accordance with method 501.1, except the temperature shall be $85^{\circ}C$. No power shall be applied. At the end of the 48-hour exposure period and while still at the high temperature, the indicator shall pass the tests specified in 4.6.3 through 4.6.10, except an additional 15 percent tolerance shall be permited on all tolerances except those specified in 4.6.5.2 and 4.6.5.2.1.

4.6.26.2 Low-temperature exposure. The indicator shall be properly connected and subjected to a low-temperature exposure test in accordance with method 502.1 at $-62^{\circ}C$ with no power applied. At the end of a 48-hour exposure period and while still at the low temperature, the indicator shall pass the tests specified in 4.6.3 through 4.6.10, except an additional 15 percent tolerance shall be permitted on all tolerances except those specified in 4.6.5.2 and 4.6.5.2.1.

4.6.26.3 Temperature-altitude (cycling). The indicator shall be subjected to a temperature-altitude cycling test in accordance with method 504.1 class 2 equipment, except that step 7 shall be conducted at $71^{\circ}C$ and step 10 shall not be conducted. There shall be no binding or sticking at any time. After the indicator has returned to room temperature, it shall pass the individual tests. After the application of power and before data are taken, there shall be a 5-minute warmup period.

4.6.26.4 Temperature shock. The indicator shall be subjected to a temperature shock test in accordance with method 503.1. At the conclusion of this test, the indicator shall pass the individual tests.

4.6.26.5 Humidity. The indicator shall be subjected to a humidity test in accordance with method 507.1, procedure I, after which it shall pass the tests specified in 4.6.3.4 through 4.6.10. There shall be no deterioration that would affect subsequent operation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.6.26.6 Fungus. The fungus test shall be conducted in accordance with method 508.1. At the conclusion of this test, the indicator shall pass the tests specified in 4.6.3.4 through 4.6.10.

4.6.26.7 Salt fog. The indicator shall be subjected to a salt fog test in accordance with method 509.1 after which it shall pass the tests specified in 4.6.3.4 through 4.6.10. There shall be no damage to the indicator that would affect its operation as a result of this test.

4.6.26.8 Dust. The indicator shall be subjected to a dust test in accordance with method 510.1 after which it shall pass the tests specified in 4.6.3.4 through 4.6.10.

4.6.26.9 Vibration failure. With no power applied, the indicator shall be subjected to a vibration failure test in accordance with method 514.2, equipment category (b), sinusoidal cycling only, curve J. At the conclusion of this test, the indicator shall pass all individual tests.

4.6.26.10 Rain. The indicator shall be subjected to a rain test in accordance with method 506.1. At the conclusion of this test, the indicator shall pass the tests specified in 4.6.3.4 through 4.6.10.

4.6.27 Acceleration. The indicator, nonoperating, shall be mounted in its normal operating position and accelerated first along its vertical axis and then along each of two axes that are perpendicular to the vertical axis and to each other. The indicator shall be subjected to an acceleration of 20g in each axis for a period of 1 minute. At the end of this acceleration, the indicator shall pass the individual tests. No damage to the indicator shall result from this test.

4.6.28 Sealing thermal shock. The indicator shall be immersed alternately in tap water maintained at $85^{\circ} \pm 5^{\circ}C$ and $5^{\circ} \pm 4^{\circ}C$ for a total of 8 cycles. The length of time for each bath immersion shall be 30 minutes; not more than 5 seconds shall elapse between bath immersions. No damage to the hermetic seal shall result due to this test. Following the immersions, the indicator shall be tested for leaks by means of a mass-spectrometer-type helium leak detector. The initial maximum detected leak rate at a pressure differential of 12 to 14.7 psi shall not exceed 0.1 micron cubic foot per hour.

4.6.29 Reliability

4.6.29.1 Qualification. The six indicators shall be subjected to a reliability test in accordance with MIL-STD-781, test level F. During the ON cycle, each servo loop and each distance counter shall be operated at 10° per second cycle, for 720° then operated the same in the opposite direction. The course bar TO-FROM pointer, and deviation alarm flag shall be driven through their ranges five times per minute. The distance shutter shall be operated for 30 minutes of every 1-hour period. The heading and course knobs shall be rotated 20 revolutions in each direction every 15 minutes during the ON period with the remote transmitting synchro source unexcited. The individual tests shall be conducted every 200 hours of ON time.

4.6.29.2 Accept-reject criteria. Accept-reject criteria shall be in accordance with MIL-STD-781, test plan I except as follows:

a. Upon accumulation of 6 failures, the indicators shall be rejected

b. The test time shall be no more than 8,500 hours nor less than 4,400 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

4.6.29.3 Longevity. Unless otherwise specified, two of the indicators specified in 4.6.29.1 shall continue to be tested for a total of 10,000 hours (5,000 hours each). Evaluation of this test shall be in accordance with MIL-STD-781, test plan XXVIII.

4.6.29.4 Production. The three samples specified in 4.5.2.2 shall be subjected to a reliability test in accordance with the ON-cycle conditions specified in 4.6.29.1. Each of the three samples shall be tested for 1,500 hours. At the conclusion of this test, the MTBF shall be calculated using the Chi squared distribution and shall be 1,000 hours. Each out-of-tolerance condition shall be considered a failure.

4.6.30 Maintainability demonstration. The indicator shall be subjected to a maintainability test in accordance with MIL-STD-471, appendix B, test method 1, test plan $^{A}1$ plus $^{B}1$. The indicator shall have M of 100 minutes less the time required to unseal and hermetically seal the instrument after repair. The M_{max} shall be no greater than 300 minutes less the time to unseal and hermetically seal the case.^{C}

4.6.31 Compatibility demonstration. The test indicators shall be tested for compatibility with the using aircraft. The HSI shall be properly connected with the appropriate input/output signals from/to the interfacing equipment listed in Paragraph 3.4.3. In the dual installation one HSI shall be connected as the master and one as the slave. The HSI shall be operated in accordance with functional tests as approved by the procuring agency and shall meet the requirements of this specification. Successful completion of the aircraft compatibility test shall be a determinant in the approval of qualification.

4.7 Examination of packaging. A random sample of complete packages shall be selected from each quantity submitted under contract and examined to insure compliance with section 5 of this specification. Samples shall be selected in accordance with MIL-STD-105, inspection level I, AQL 4.0 defective.

5. PACKAGING

5.1 Preservation. Preservation shall be level A, C, or Industrial, IAW MIL-STD-2073-1, as specified (see 6.2)

5.1.1 Level A.

5.1.1.1 Cleaning. Indicators shall be cleaned in accordance with process C-1 or MIL-P-116.

5.1.1.2 Drying. Indicators shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Preservative shall not be used.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packed in MIL-P-116. Each indicator shall be placed in a PPP-B-636 Fiberboard container weather resistant, with sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in g's established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Each indicator shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

5.1.3 Industrial. The Industrial preservation of indicators shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 appply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged indicator shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance :with MIL-STD-129."

6. NOTES

6.1 Intended use. The AOU-6A/A indicator covered by this specification is intended for use in high performance aircraft with an integrated panel. The display will be controlled by reference and remote command sources providing transmitter synchro output signals and d-c master movement signals.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.

b. When sampling plan B tests will not be conducted (see 4.5.2.2).

c. When specified, sampling plan C shall be used in lieu of sampling plan A.

d. Levels of packaging and packing required.

e. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

6.3 Definitions

6.3.1 Hermetic seal. A hermetic seal is a perfectly closed and airtight seal made between vitric, metallic, elastomeric and resinous materials. To meet the specified leak rate requirements, combinations of these materials may be used in areas approved by the procuring activity. A hermetic seal is not intended to include seal accomplished by gaskets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

6.3.2 Index reference position. The index reference position of a synchro is that position specified in terms of dial reading where the voltage XY is zero and the stator voltage XZ and YZ is 180° out-of-phase with the rotor voltage HC. When the synchro is in this position, the voltage between H and X will be the sum of the rotor and stator voltages. The index reference position of the standard test transmitter and the distance counter receiver synchros is 0°, the CT's in course and heading is 270° and the bearing pointer CT is 90°.

6.4 Qualification. With respect to products requiring qualification, awards will be made only for such products which are at the time of contract award, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is the Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 and information pertaining to qualification of products may be obtained from that activity.

6.5 Subject term (key word) listing.
Aircraft
Instrument
Navigation

6.6 International standardization agreement. Certain provisions to this specification are the subject of international standardization agreements ASCC Air Std 10/45 and STANG 3741(AI). When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardizational offices to change the agreement or make other appropriate accommodations."

6.7 Change from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the change.

Custodians:
AIR FORCE -99
ARMY -AV

Preparing activity:
AIR FORCE -71

Reviewer:
DepSo -01

Project No:
6610-0276

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-I-83034 A	2. DOCUMENT DATE (YYMMDD)

3. DOCUMENT TITLE

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5 REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If applicable)*	7. DATE SUBMITTED (YYMMDD)

8 PREPARING ACTIVITY

a NAME	b TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON
c ADDRESS *(Include Zip Code)*	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT. Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:42Z
Check the source to verify that this is the current version before use.