MIL-T-83303B(USAF)
28 January 1975
SUPERSEDING
MIL-T-83303A(USAF)
21 July 1972

MILITARY SPECIFICATION

TRUCK, FIRE FIGHTING, AIRFIELD RAMP, A/S32P-13A; 4 BY 4, PICKUP

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a four-wheel, four-wheel drive, airfield ramp fire fighting truck, designated A/S32P-13A.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-P-514	Plate, Identification, Instruction and Marking, Blank
MIL-A-8421	Air Transportability Requirements, General Specification for
MIL-T-12171	Truck; Commercial, 5,000 to 10,000 Pounds GVW, 4 x 4
MIL-E-83304	Extinguisher Unit, Fire, Bromochlorodifluoromethane FEU-4/S32P; 500-Pound Capacity, Truck Mounting
MIL-E-83381	Extinguisher Unit, Fire, Dry Chemical FEU-6/S32P; 350-Pound Capacity, Truck Mounting

STANDARDS

Federal

FED-STD-595	Colors

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-281	Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies; Preservation and Packaging of
MIL-STD-461	Electromagentic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-808	Finishes, Protective, and Codes, for Finishing Schemes for Ground and Ground Support Equipment
MIL-STD-831	Test Reports, Preparation of
MIL-STD-889	Dissimilar Metals
MIL-STD-1223	Administrative Wheeled Vehicles Treatment, Painting, Undercoating, Identification Marking, Data Plates and Warranty Notice Standards
MS51317	Light, Warning, Vehicular, Rotating, D.C.

DRAWING

The Ansul Company

26251	Air Force Truck, A/S32P-13A

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

Society of Automotive Engineers, Incorporated
SAE Standards and Recommended Practices

J683	Tire Chain Clearance
J833	Male Physical Dimensions for Construction and Industrial Equipment Design

(Application for copies should be addressed to the Society of Automotive Engineers, Two Pennsylvania Plaza; New York, New York 10001.)

American National Standards Institute

S1.4	General Purpose Sound Level Meters

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, New York 10018.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

3.2 Components. The truck shall consist of the following major components:

Item or System Name	See Requirement
Chassis	3.7
Agent system	3.8.

3.3 Selection of standards and specifications. Standards and specifications for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.4 Materials. Materials shall be as specified herein. Materials not specifically covered by this or applicable specifications shall be suitable in every respect and of good quality for this type of equipment.

3.4.1 Metals. Where practicable, the metals used for the framework construction (see 3.8) shall be of a high strength-weight ratio to effect a saving in weight of the equipment. All metal piping and associated fittings which come into direct contact with bromochlorodifluoromethane shall be made of copper, brass, or bronze.

3.4.1.1 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.4.2 Protective treatment. When materials are used that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the performance requirements of this specification. Protective coatings that will chip, crack, or scale with age or extremes of climatic condition shall not be used.

3.5 Design and construction. Truck-mounted components shall not work loose in service, and shall withstand the strains, shocks, vibrations, and other conditions incident to operation, shipping, and storage. All assemblies, controls, and installed equipments shall be so located that there will be no adverse interference with each other, and shall be readily accessible for operation, maintenance, removal, and replacement.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

3.5.1 Functional design. The truck shall be designed to operate efficiently at military installations worldwide for the purpose of providing quick response for fire protection at flight line and other airfield facilities. The truck shall be designed and constructed to operate on paved surfaces and unimproved roads as required to accomplish the fire-fighting mission at such installations.

3.5.2 Reliability. The reliability of the truck to satisfy its intended use shall be demonstrated by successful completion of the tests specified herein.

3.5.3 Maintainability. The truck shall be designed and constructed to provide:

a. Ease of servicing, adjusting, and removing and replacing parts and components

b. Use of readily available standard tools and equipment for maintenance

c. Maintenance with a minimum number of tools.

3.5.3.1 Major assemblies. It shall be possible to remove major assemblies in any sequence, after disconnecting interconnected piping and floor mounting attachments, without the necessity for discharging fire-fighting agents or dismantling other assemblies. Major assemblies shall be equipped with lifting eyes or other suitable provisions for ready attachment of lifting equipments.

3.5.3.2 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with an adequate means for preventing loss of proper tightness and adjustment. When subject to removal, replacement, or adjustment, attaching hardware for any component shall be easily removable and shall not be swaged, peened, staked, or otherwise permanently deformed.

3.5.4 Component protection. Metal protective looms or grommets shall be furnished at points where piping passes through panel or structural members.

3.5.5 Air transportability. The truck, with the agent system in both empty and filled conditions, shall be designed for air transportability to the extent that agent system attachments (see 3.8) to the pickup body floor will withstand the flight and taxiing load requirements of MIL-A-8421.

3.6 Performance. Performance requirements shall be based on operation at sea level.

3.6.1 Roadability. With the installed agent system filled to capacity, the truck shall be capable of traversing paved and unimproved roads as follows without adversely effecting installed equipments:

a. Paved roads at an average speed of 45 mph

b. Graded gravel roads at an average speed of 25 mph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

3.6.2 Agent discharge. The truck shall be capable of selectively discharging fire-fighting agents from their respective hose reel mounted handlines as follows:

a. Bromochlorodifluoromethane (Halon 1211), at a rate of between 5-to-5-1/2-pps (pounds per second) for an effective range of not less than 20 feet without assist from downwind conditions

b. Potassium bicarbonate base dry chemical at a rate of between 6-1/2-to 8-pps (pounds per second) for an effective range of not less than 40 feet without assist from downwind conditions.

3.7 Chassis. The chassis shall be the manufacturer's standard except as modified to comply with requirements specified herein. The chassis shall be a 4 by 4 conforming to MIL-T-12171, Type II, Class C, except the cab to axle dimension shall be not less than 55 inches. If drive hubse are provided, they may be of either the automatic or manual operated type. Unless otherwise specified (see 6.2), tow hooks and brush guard shall not be provided.

3.7.1 Engine. The truck engine shall be the chassis manufacturer's current standard or optional that delivers the required performance.

3.7.1.1 Power plant heaters. Truck coolant, engine oil, and battery heaters shall be provided when specified (see 6.2).

3.7.1.2 Exhaust system. The exhaust system shall discharge downward and away from other components of the truck.

3.7.2 Lighting system. In addition to lights furnished as standard equipment on the truck chassis, the following lights shall be provided:

3.7.2.1 Spotlight. An automotive-type sealed beam spotlight, lamp No. 4435, shall be mounted on the left front door post. The spotlight universal control shall be operable from inside the cab. The control shall not obscure the driver's vision, nor interfere with normal driving functions and entering and exiting the cab.

3.7.2.2 Warning light. A rotating red warning light conforming to MS51317-2 shall be mounted on the cab roof similar to the installation shown in Drawing 26251. The warning light shall be controlled by an identified switch on the cab instrument panel.

3.7.3 Siren. A 12-V, electronic-type siren shall be provided with the siren speaker mounted on the cab roof similar to the installation shown in Drawing 26251. The siren shall transmit an automatic-controlled, slow-wail sound level. The steady-state magnitude of the A-weighted sound level produced by the siren shall be not less than 115 dBA (reference 0.00002 Newtons/square meter) at a

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

distance of 6 feet from the speaker. The siren system shall include all necessary wiring and connections so that it is adaptable to Air Force two-way radios which utilize either carbon or magnetic-type microphones, and can be used for a public address system and for transmitting incoming radio messages through the siren speaker. Reset-type circuit breakers shall be provided in the system. The siren controls shall be readily accessible from both the driver and passenger seats.

3.7.4 Transmission. An automatic transmission shall be provided.

3.7.5 Wheels and tires. Tires shall be 7.50-16 LT, 8-ply rating. Adequate clearance for tire chains shall be provided in accordance with SAE Standard J683. A spare wheel and tire assembly is not required. Tools for changing wheel and tire assemblies are not required.

3.7.6 Steering. Power assist steering shall be provided.

3.7.7 Body. The pickup body shall be of the flush-side (internal wheelwells) type with steel floor. The load space width, excluding wheelwells, shall provide a clearance of not less than 65 inches for loading from the top and through the tailgate opening. The load space width between wheelwells shall be not less than 49 inches.

3.8 Agent system. The truck mounted agent system shall consist of a FEU-4/S32P bromochlorodifluoromethane fire extinguisher unit conforming to MIL-E-83504, and when specified (see 6.2), a FEU-6/S32P dry chemical fire extinguisher unit conforming to MIL-E-83381. The units shall be installed in the pickup body similar to the installation shown in Drawing 26251 using bolted attachments. The pickup body floor shall be reinforced in areas where bolted attachments are made. The units shall be positioned such that, when filled to capacity with their respective agents, they can be individually lifted in any sequence by means of a crane hoist with hooks after disconnecting floor attachments and interconnected piping and without interference or danger of damage to piping, gages, and controls. All agent system operating controls shall be readily accessible to personnel standing on the ground and having physical dimensions in the range of small to large as defined in SAE Standard J833. Controls which charge the handlines (see 3.8.2) shall be operable from both the right and left sides of the truck and shall be positioned higher than the body sides for ease of accessibility.

3.8.1 Bromochlorodifluoromethane unit installation. If the dry chemical unit is not to be installed, the bromochlorodifluoromethane unit shall be installed adjacent to the cab.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

3.8.2 Hose reel assemblies. The hose reel assemblies shall be so positioned that the rewind crank mechanism and handline are readily accessible for operation by personnel standing at the rear of the truck with the body tailgate closed. The hose reels shall be so installed that the handlines can be individually and simultaneously withdrawn from the rear of the truck without interference from other components. The adjustable friction device, to prevent overtravel during handline withdrawal operations, shall be located on the outboard side of each reel. Hose guides or rollers shall be provided to assist in withdrawing the handlines to the rear and each side of the truck, and to prevent the handlines from coming into contact with the body tailgate and other mounted equipments that may interfere with operations. The handline nozzles shall be securely mounted in quick-release devices. Piping interconnects between the hose reels and agent supply units shall be equipped with union ends for ease in disconnecting. The dry chemical and bromochlorodifluoromethane agent systems shall interconnect with the left and right side mounted hose reels respectively.

3.9 Part numbering of interchangeable parts. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of MIL-STD-100 shall govern the manufacturer's part numbers and changes thereto.

3.10 Electromagnetic interference. The truck shall comply with the requirements of MIL-STD-461, Class D, Method RE05. This requirement shall apply to the truck, including any and all equipment used in or on the truck, during operation under all conditions specified herein.

3.11 Weight. The total gross weight of the complete truck shall not exceed the chassis manufacturer's GVW and axle ratings when fully equipped as specified herein, including all fire fighting equipment; a full complement of fuel, lubricants, and coolant; filled to capacity with fire-fighting agents; and carrying three men weighing not less than 175 pounds each.

3.12 Finishes and protective coatings. The truck chassis, including the cab and pickup body, shall be cleaned, treated, and painted in accordance with best commercial practice. Mounted equipment not covered above shall be cleaned and treated in accordance with MIL-STD-808. The cab exterior, pickup body, and mounted equipment shall be painted gloss red, color 11136 of FED-STD-595. The cab interior shall be green conforming to the manufacturer's standard practice.

3.12.1 Rustproofing. The truck shall be rustproofed in accordance with MIL-STD-1223.

3.13 Markings

3.13.1 Identification and marking. The truck shall be identified and marked in accordance with MIL-STD-1223, except the legend on the third line shall read (A/S32P-13A) instead of (For Official Use Only). All lettering and numbering shall be reflectorized tape as specified in MIL-STD-808 and by the procuring activity (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

3.13.2 Data plates. Instruction and identification data shall be permanently and legibly etched upon nonferrous metal plates in accordance with MIL-P-514. All plates shall be of a size and shape consistent with information required thereon.

3.13.2.1 Identification of product. A plate, containing nameplate information in accordance with MIL-STD-130, shall be mounted in the cab. Except for the serial number and date of delivery which may be stamped, all data shall be inscribed. The following nomenclature shall be included on the nameplate:

TRUCK, FIRE FIGHTING A/S32P-13A, 4 BY 4.

3.13.2.2 Identification of controls. All valves, gages, controls, and indicators, other than standard vehicle instrumentation, used in operation of the truck shall be identified by securely attached nameplates of such composition that exposure to oil, dirt, light, et cetera, will not cause them to fade or become eradicated. Tags and decals shall not be used.

3.13.2.3 Caution plate. The following caution plate shall be installed at a conspicuous location on the cab dash panel.

CAUTION

THIS TRUCK IS EQUIPPED WITH RADIO INTERFERENCE SUPPRESSION DEVICES. CARE SHOULD BE EXERCISED DURING TRUCK MAINTENANCE TO RETAIN AND REINSTALL THESE DEVICES PRIOR TO REUSE OF THE TRUCK.

3.13.2.4 Transportation data plate. A transportation data plate shall be provided and shall contain at least the following:

a. Side and rear silhouette views of the truck

b. Horizontal and vertical location of the truck center of gravity marked on the silhouette views

c. Shipping weight

d. Loading cubage

e. Overall length, width, and height.

3.13.3 Operational markings. The operational markings and stenciling shall be applied in accordance with the marking requirements of MIL-STD-808.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:43Z
Check the source to verify that this is the currentversion before use.

3.13.3.1 Tire pressure. The recommended maximum tire inflation pressure shall be stenciled as follows in 1/2 inch letters and numerals of non-reflective paint on the truck as near to each wheel as practical:

M.T.P _____ P.S.I.

3.14 Workmanship. The truck, including all parts and accessories, shall be fabricated and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs and sharp edges; marking of parts and assemblies; thoroughness of soldering, welding, brazing, riveting, painting, and wiring; alignment of parts; and tightness of assembly screws, bolts; et cetera.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of tests. The inspection and testing of the truck shall be classified as follows:

a. Preproduction testing . . . . . See 4.4

b. Quality conformance tests . . . . . See 4.5.

4.3 Test conditions

4.3.1 Preparation for test. All trucks submitted for test shall contain all specified components and shall be completely assembled and properly prepared for operation. The truck, including all components, shall be correctly adjusted, lubricated, and serviced; and all equipment which has been ordered shall be mounted for immediate operation. Unless otherwise specified for a particular test, fuel and agent tanks shall be full.

4.3.2 Data. During the tests specified herein, at least the following data shall be recorded. Additional data may be required as dictated by test objectives:

a. Time started and completed

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

b. Pressure and quantity of agent in the bromochlorodifluoromethane tank

c. Pressure and quantity of agent in the dry chemical tank

d. Ambient temperature and wind conditions

e. Type of road surface traversed

f. Average road speed.

4.3.3 Test observations. Throughout all tests specified herein, the truck shall be closely observed for the following conditions which shall be considered cause for rejection:

a. Failure to conform to design and performance requirements specified herein

b. Spillage or leakage of fire-fighting agents

c. Structural failure of mounting provisions, including permanent distortion or evidence of impending failure

d. Interference of components

e. Misalignment of parts and components

f. Evidence of undesirable roadability features, including instability in handling during braking the turning.

4.4 Preproduction testing (see 6.2)

4.4.1 Test sample. One truck complete with a FEU-4/S32P bromochlorodifluoromethane unit, and a FEU-6/S32P dry chemical unit if applicable, shall be subjected to the tests specified in 4.4.3.

4.4.2 Test report. After completion of the preproduction tests, a test report shall be prepared in accordance with MIL-STD-831. The report shall cover each test required under a separate section or paragraph which in turn shall list individual test purposes or objectives; describe procedures followed in each individual test; and compare by means of a checklist and table (as applicable) test results with the respective performance or design requirement for which the test is intended to demonstrate compliance.

4.4.3 Preproduction tests. The preproduction tests shall consist of all tests specified under 4.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance tests. The quality conformance tests shall consist of the following:

a. Individual tests . . . . . See 4.5.1

b. Sampling plan and tests . . . . . See 4.5.2.

4.5.1 Individual tests. Each truck shall be subjected to the following tests as described under 4.6:

a. Examination of product . . . . . See 4.6.1

b. Mechanical inspection . . . . . See 4.6.2.

4.5.2 Sampling plan and tests. One truck shall be selected at random from each fifty, or fraction thereof produced, and subjected to the following tests as described under 4.6:

a. Roadability . . . . . See 4.6.6

b. Agent discharge . . . . . See 4.6.7.

4.5.2.1 Rejection and retest. When an item selected from a production run fails to meet the specification, no items still on hand or later produced shall be accepted until the extent and cause of failure have been determined and appropriately corrected. The contractor shall explain to the Government representative the cause of failure and the action taken to preclude recurrence. After correction, all tests shall be repeated.

4.5.2.2 Individual tests may continue. For production reasons, individual tests may be continued pending the investigation of a test failure. Final acceptance of the items on hand or produced later shall not be made until it is determined that all items meet all the requirements of the specification.

4.5.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.6 Test methods

4.6.1 Examination of product. The truck shall be inspected to determine compliance with requirements of this specification with respect to materials, finishes, markings, workmanship, and installation of components.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

4.6.2 Mechanical inspection. A critical inspection shall be made of all truck and fire-fighting system components, and data recorded as to the condition, defects and manufacture, damage in transit, and damage through use prior to test.

4.6.3 Component removal. With the agent system properly installed on the truck and filled to capacity with agent, it shall be demonstrated that major components consisting of the bromochlorodifluoromethane unit, the dry chemical unit if applicable, and the hose reels can be readily and individually removed from the truck in any sequence, and without interference between the units, by means of their lifting attachments without disconnecting other than piping interconnects between the units and bolted attachments to the pickup body floor.

4.6.4 Operation and servicing. It shall be demonstrated that all agent tank discharge valve controls are readily accessible for operation by personnel standing on the ground at each side of the truck. It shall also be demonstrated that the bromochlorodifluoromethane agent tank fill provisions are readily accessible for connection of resupply hose by personnel standing beside the truck.

4.6.5 Hose reel operation. With the agent system properly installed on the truck, and with the tailgate closed, it shall be demonstrated that the hose reel handlines are readily accessible to personnel standing on the ground at the rear of the truck. It shall be demonstrated that the handlines can be individually and simultaneously withdrawn directly toward any away from the rear and each side of the truck without interference with the truck body or mounted equipments that may snag, chaff, cut, or otherwise interfere with operation. It shall also be demonstrated that the operator can readily rewind the handlines with the tailgate closed.

4.6.6 Roadability. The fully equipped truck, with the extinguisher unit(s) filled to rated capacity, shall be selectively operated in both two-wheel drive and four-wheel drive over improved and unimproved roads as follows. Upon completion of each run, the extinguisher unit(s) shall be thoroughly inspected for looseness and damage to components, agent leakage, and loss of pressure as a result of vibrations, jarring, and other conditions incident to the road test.

a. Paved roads for a distance of 100 miles at an average speed of 45 mph

b. Graded gravel roads for a distance of 100 miles at an average speed of 25 mph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

4.6.7 Agent discharge. Upon successful completion of the roadability test, agent shall be dischraged from the truck installed ageng system handlines to determine that there has been no agent system damage that prevents proper discharge:

a. Bromochlorodifluoromethane at a rate of between 5-to 5-1/2-pps for an effective range of not less than 20 feet without assist from downwind conditions.

b. Dry chemical, if applicable, at a rate of between 6-1/2-to 8-pps for an effective range of not less than 40 feet without assist from downwind conditions.

4.6.8 Transportability. The A/S32P-13A truck shall be capable of being transported by rail, drive-away (mobile), haul away, and air in accordance with MIL-A-8421. The loading demonstration and engineering evaluation conducted to determine compliance with MIL-A-8421 shall include body attachment for all applicalbe major components (dry chemical unit, bromochlorodifluoromethane unit, and hose reels) of the agent system when empty and when filled to capacity. Ocean transportation by vessel shall not be considered a normal mode for overseas deployment.

4.6.9 Siren test. The steady-state sound level produced by the siren shall be measured. The sound level meter used in performing this test shall meet the requirements of ANSI S1.4. Siren manufacturer test data which verify compliance with the performance requirements will be accepted in lieu of this test.

4.6.10 Electromagnetic interference. The truck shall be subjected to the radio interference suppression tests in accordance with MIL-STD-462, Method RE05, to show compliance with the requirements of MIL-STD-461A, Notice 3, Class D when any or all equipment used in or on the truck is operating.

4.6.11 Determination of weight. The curb and gross weights, and corresponding load distributions on each wheel, of the completely equipped truck shall be determined. Curb weight includes the truck with all equipments specified herein and a full compliment of fuel, lubricants, and coolants. Curb weight does not include agents and personnel.

4.7 Inspection of preparation for delivery. Preservation, packaging, packing and marking for shipment and storage shall be inspected to determine conformance to the requirements of section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. Preservation, packaging, and packing shall be in accordance with MIL-STD-281 at level A, B, or C as specified (see 6.2.1). Unless otherwise specified the truck shall be prepared for mobile requirements (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

5.1.1 Components of the extinguisher units shall be adequately secured to prevent movement and damage. Exposed gauges, controls and similar items shall be cushioned, covered with a waterproof barrier and taped with waterproof tape. All openings shall be closed with caps, plugs or waterproof barrier and tape.

5.1.2 For mobile shipments, accessory items that are subject to pilferage shall be secured in place by locking or strapping or removed and packaged in separate overseas type wooden container(s) to prevent loss. If items are packed in separate container(s), container(s) shall be secured to vehicle by strapping.

5.2 Marking. Marking for shipment and storage shall be in accordance with MIL-STD-129. Additional markings shall be as specified (see 6.2.1).

6. NOTES

6.1 Intended use. The A/S32P-13A truck is intended for use at military installations worldwide for fire protection during flight line and other airfield operations.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. When tow hooks are required (see 3.7)

c. When brush guard is required (see 3.7)

d. When power plant heaters are required (see 3.7.1.1)

e. When a dry chemical fire extinguisher unit is required (see 3.8)

f. Lettering and numbering required on the truck (see 3.13.1)

g. Location and conditions for preproduction testing (see 4.4)

h. Level of preservation and packaging and packing required (see 5.1)

i. Specify if other than mobile requirements are required (see 5.1)

j. Additional markings if required (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

6.3 Identification of changes. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Air Force - 11

Reviewer:
Air Force - 84

Preparing activity:
Air Force - 11

Project No. 4210-F114

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

C16061

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.

FOLD

ASD/ENYESS
Wright-Patterson AFB, O 45433

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE
DoD-318

ASD/ENYESS
Wright-Patterson AFB, Ohio 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:43Z
Check the source to verify that this is the current version before use.