MIL-P-35003E
30 June 1987
SUPERSEDING
MIL-P-35003D
18 November 1976

MILITARY SPECIFICATION

PEPPERS, GREEN AND RED, DEHYDRATED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers dehydrated red and green sweet bell peppers for use by the Department of Defense as an item of general issue.

1.2 Classification. The product shall be of the following types, as specified (see 6.1):

Types

I - Green
II - Red
III - Mixed red and green

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8915

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

TT-C-495	- Coatings, Exterior, for Tinned Food Cans
PPP-C-29	- Canned, Subsistence Items, Packaging Of
PPP-B-636	- Boxes, Shipping, Fiberboard

MILITARY

MIL-L-1497	- Labeling of Metal Cans for Subsistence Items
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-D-43266	- Desiccants and Desiccation, Method of: For Packaging Subsistence

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

NATIONAL ACADEMY OF SCIENCE

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 111 North 19th Street, Suite 210, Arlington, VA 22209.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

AMERICAN DAIRY PRODUCTS INSTITUTE

Standards for Grades of Dry Milk, Including Methods of Analysis, Bulletin 916

(Application for copies should be addressed to the American Dairy Products Institute, 130 North Franklin St., Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, 222 South Riverside Plaza, Suite 1120, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.1.1 Sweet bell peppers. The peppers shall be properly matured, either green or red, sweet bell peppers of similar variety and dehydration characteristics. Peppers of the hot pungent variety shall not be used. The peppers shall be firm and free from defects caused by hail, scars, sunburn, disease, insects, or mechanical or other means, except for small fresh holes or splits due to proper handling procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

3.1.1.1 Type I. Peppers for type I shall be a generally uniform green color with some variation from bright green to olive green.

3.1.1.2 Type II. Peppers for type II shall be a generally uniform red color with some variation from bright red to orange red after being properly trimmed and washed.

3.1.1.3 Type III. Mixed green and red peppers for type III shall consist of, by weight, not less than 35 percent generally uniform typical green pieces and not less than 35 percent generally uniform typical red pieces. Sweet bell peppers which are in the process of turning from green to red, including shades of brown, are permitted provided the minimum percentages of strictly green and red pieces are present.

3.1.2 Sodium sulfite or sodium acid sulfite. The sulfite(s) used shall comply with the Food Chemicals Codex.

3.1.3 Water. Water used for washing and rehydration shall conform to the National Primary Drinking Water Regulations.

3.2 Preparation and processing.

3.2.1 Preparation. The peppers shall be properly washed to remove soil, spray residue, and foreign material. Any diseased and seriously damaged units shall be discarded. The peppers shall be cored and trimmed to remove seeds, seed cells, and rotted areas, then cut, with a minimum of tearing and rough cutting, into pieces approximately 1/4 inch by 1/4 inch square.

3.2.2 Sulfiting. The peppers, either prior to or after dehydration, shall receive a sulfite treatment by such method as will ensure distribution of the sulfite throughout the product and a residual sulfur dioxide content in the dehydrated product within the limitations specified in 3.3.1. Contact of the wet peppers with iron subsequent to the sulfiting operation shall be strictly avoided.

3.2.3 Dehydration. Dehydration shall be by such method that the finished product complies with 3.3. The moisture content of the dehydrated sweet bell peppers by weight, prior to packaging, shall not exceed 5.0 percent for type I, 7.5 percent for type II, and 5.5 percent for type III. The dehydration conditions shall be such that the product will not be scorched or otherwise damaged by heat or drying.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

3.3 Finished product requirements.

3.3.1 Dehydrated product. The product shall comply with the following requirements:

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, paper, paint, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, musty, or moldy.

c. There shall be not color foreign to the product.

d. The sulfite level (calculated as sulfur dioxide) shall be not less than 1,000 nor more than 2,500 parts per million (ppm) by weight.

e. Not more than 10 percent, by weight, of the product shall pass through a U.S. Standard No. 8 sieve, when examined as specified in 4.4.1.

f. There shall be not more than 25 seeds per 100 grams of dehydrated sweet bell peppers.

g. The average net weight, on a dry solids basis, shall be not less than 4.25 ounces for type I, 7.5 ounces for type II, or 5.4 ounces for type III product.

h. No individual can shall contain less than the dry solids weight of 4.03 ounces for type I, 7.12 ounces for type II or 5.13 ounces for type III product.

3.3.2 Rehydrated product. The rehydrated product shall possess the color, odor, flavor, and appearance typical of normal sweet bell peppers and a texture that is tender, firm, full fleshed, but not mushy. The sweet bell peppers shall rehydrate to approximately their original physical form when 1.0 ounce of the dehydrated product (on a dry solids basis) is added to 16.0 ounces of 35° to 55°F water, by weight, and allowed to soak for 2 hours at ordinary refrigerated temperature (approximately 40°F). The rehydrated product shall contain not more than 2 percent by weight of defective pieces such as those affected by scorch, hail, sunburn, disease, rot, insect or mechanical damage, stem, core, or placenta tissue.

3.3.2.1 Color.

3.3.2.1.1 Type I. Not less than 95 percent, by weight, of the green sweet bell peppers shall possess a generally uniform typical green color with some variation from bright green to olive green.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

3.3.2.1.2 Type II. Not less than 95 percent, be weight, of the red sweet bell peppers shall possess a generally uniform typical red color with some variation from bright red to orange red.

3.3.2.1.3 Type III. The mixed red and green sweet bell peppers shall consist of not less than 35 percent generally uniform typical green pieces and not less than 35 percent generally uniform typical red pieces, by weight. The balance of the pieces may be in the process of turning from green to red and may include pieces of varying shades of brown provided the color is natural and is not due to scorching.

3.4 Plant qualification. The product shall be prepared, processed, and packaged in establishments meeting the requirements of Title 21, Code of Federal Regulations, Part 110: "Current Good Manufacturing Practice in Manufacturing, Processing or Holding of Human Foods," and the plant sanitation requirements of the appropriate Government inspection agency.

3.5 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of supervision necessary to assure compliance with the requirements of this document.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.1 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:48Z
Check the source to verify that this is the currentversion before use.

acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the condition requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.3.1.2 Unfilled can inspection. Conformance of unfilled cans to the requirements specified in 5.1.1 shall be determined by examination of certificates of conformance or of other valid documents. Any nonconformance shall be cause for rejection of the can lot or of any involved product.

4.3.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.3.3 Net weight examination. The cans of product shall be examined for net weight. Dry solids weight is determined by subtracting the weight of the moisture, as determined by the moisture test specified in 4.4.2, from the actual net weight. The lot size shall be expressed in units of cans. The sample unit shall be one can of product. The inspection level shall be S-3. The results shall be reported to the nearest 1.0 gram. If the average net weight, on a dry solids basis, is less than specified, or if the net weight, on a dry solids basis, of any individual can is less than specified, the lot shall be rejected.

4.3.4 Product examination. The finished product shall be examined for the defects listed in table I. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

TABLE I. Product defects 1/

Category	Defect
Major	
	Desiccant
101	Desiccant bag(s) missing
102	Desiccant bag has tear, hole, or open seam
	Dehydrated product
103	More than 25 seeds per 100 grams
104	More than 10 percent, by weight, passes through a U.S. Standard No. 8 sieve (see 4.4.1)
	Rehydrated product 2/ 3/
105	Sweet bell peppers do not rehydrate to a form similar to their original physical form
106	More than 5 percent, by weight, of type I sweet bell peppers do not possess a generally uniform typical green color with some variation from bright green to olive green
107	More than 5 percent, by weight, of type II sweet bell peppers do not possess a generally uniform typical red color with some variation from bright red to orange red
108	Type III sweet bell peppers possess less than 35 percent, by weight, of generally uniform typical red pieces, or less than 35 percent, by weight, of generally uniform typical green pieces
109	Sweet bell pepper pieces not firm, fully fleshed, and tender, but mushy

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

TABLE I. Product defects 1/ - Continued

Category	Defect
Major	
110	More than 2 percent, by weight, of defective pieces
111	Rehydrated product does not possess the color, odor, flavor, and appearance typical of normal sweet bell peppers

1/ The presence of foreign material (e.g. dirt, insect parts, hair, wood, paper, paint, glass, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, musty, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Rehydration of product shall be in accordance with 3.3.2.

3/ Determine once per sample unit.

4.3.5 Product testing.

4.3.5.1 Moisture and sulfur dioxide content testing. The finished product shall be tested as specified in 4.4.2 and 4.4.3 for conformance to the moisture and sulfur dioxide requirements in 3.3.1. The sample for testing shall be an 8-ounce composite, derived from the number of cans indicated by inspection level S-2. The lot size shall be expressed in cans. Each sample can shall be selected during the packaging operation just prior to closure. The desiccant shall be removed from each sample can. Each sample can shall be appropriately marked for identification and then closed immediately. The composite shall be formed at the laboratory just prior to testing. Results for moisture shall be reported to the nearest 0.1 percent, and for sulfur dioxide to the nearest 10 ppm. A test failure for either moisture or sulfur dioxide content shall be cause for rejection of the lot.

4.3.5.2 Oxygen in headspace testing (types II and III). Cans with type II or III product shall be tested as specified in 4.4.4 for conformance to the oxygen in headspace requirement in 5.1.1. The lot size shall be expressed in

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:48Z
Check the source to verify that this is the current version before use.

cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.3.6 Can condition examination. Examination of filled and sealed cans shall be in accordance with U.S. Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.3.7 Leakage and vacuum (when applicable) examination. Examination for leakage and vacuum shall be in accordance with PPP-C-29 (see 5.1.1).

4.3.8 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect, or illegible.
Arrangement or number of cans not as specified.
Container not snug-fitting.

Level C shipping containers shall be examined only for the marking, arrangement, and number of can defects specified above and for the closure method specified in 5.2.3.

4.3.9 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

4.4 Methods of inspection.

4.4.1 Screening. Weigh entire contents of can. Place approximately 2 ounces of dehydrated material on an 8 inch diameter, or 4 1/2 ounces on a 12 inch diameter U.S. Standard No. 8 sieve. Tip back and forth through a 90-degree arc 25 times. Empty material remaining on sieve into an appropriate container and repeat this procedure until entire contents of can have been screened. Weigh total material passing through sieve and calculate percentage.

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:48Z
Check the source to verify that this is the currenversion before use.

4.4.2 Moisture content test. Grind approximately 100 grams of a well mixed sample in a clean, dry Waring blender or similar mill for 1 minute. Weigh two samples, approximately 3.0 grams each of the sieved material, into tared, dry, aluminum weighing dishes (approximately 2 or 2 1/2 inches in diameter and 3/4 inch in depth) with tight-fitting covers. Place the dishes with cocked lids in a vacuum oven and dry for 6 hours at 70°C under a pressure of not more than 100 mm mercury. During drying, admit to the oven a slow current of air (approximately two bubbles per second) dried by passing through concentrated sulfuric acid. Remove the dishes and allow them to cool in a desiccator before weighing. Calculate the percent of moisture in the original samples.

4.4.3 Sulfur dioxide content test. Sulfur dioxide of the ground sample shall be determined in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Food Additives: Direct, Section: Chemical Preservatives, Method: Total Sulfurous Acid, Modified Monier-Williams.

4.4.4 Oxygen content test. Oxygen content of headspace gas shall be determined in accordance with American Dairy Products Institute publication, Bulletin 916, Standards for Grades of Dry Milk; Including Methods of Analysis: Determination of Oxygen. The result of each determination shall be reported to the nearest 0.1 percent for each can. Alternatively, the headspace oxygen content may be determined by an Instrumentation Laboratories Oxygen Analyzer or equivalent instrument. Test results shall be reported to the nearest 0.1 percent for each can. The lot shall be rejected if any of the cans exceeds 2.0 percent oxygen. When referee testing is necessary, the American Dairy Products Institute method shall be followed.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C, as specified (see 6.1).

5.1.1 Level A. A net weight, on a dry solids basis, of 4.25 ounces of the type I, 7.5 ounces of the type II, or 5.4 ounces of type III product, in accordance with 3.3, as applicable, shall be unit packed into an open-top style, round metal can, size 401 by 411 with a soldered or welded side seam and compound-lined double-seamed ends. The can shall be made throughout from not less than 0.25 pound per base box electrolytic tin plate. The base plate of the can shall be of sufficient temper to protect the product during shipment and storage. The entire inside area of the can shall be coated. The interior can coating shall not peel or blister when in contact with the product. The can shall be coated on the outside with a coating conforming to type I or when specified (see 6.1) type III of TT-C-495. Desiccant in accordance with MIL-D-43266 and in quantities capable of lowering the moisture

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:48Z
Check the source to verify that this is the current version before use.

content of the type I or type III product to 1.5 percent and of the type II product to 2.5 percent shall be included in each can. The type II and type III product cans shall be sealed under an atmosphere of nitrogen so that the oxygen content of the gases in the filled and sealed container shall not exceed 2.0 percent when tested in accordance with 4.3.5.2. The cans shall be hermetically sealed and shall not show leakage when examined in accordance with 4.3.7. Alternatively, the type II and type III product cans may be hermetically sealed under a vacuum of not less than 27 inches of mercury when examined in accordance with procedures in PPP-C-29. When cans are closed under vacuum, the oxygen requirement is not applicable.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with or without exterior commercial coating will be acceptable. Alternatively, cans may be made from 0.20 pound per base box electrolytic tin plate provided the cans have an exterior commercial coating.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed in a fiberboard box, constructed and closed in accordance with style RSC, grade V2s of PPP-B-636. The cans shall be packed on end four in length, three in width, and two in depth within a snug-fitting shipping container. The tiered cans shall be separated with a full length and width fiberboard pad made of the same material as the box. Each shipping container shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of unit load specified (see 6.1). When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1 except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Twenty-four cans of product, preserved as specified in 5.1, shall be packed in a fiberboard box on end four in length, three in width, and two in depth within a snug-fitting shipping container in accordance with the Uniform Freight Classification or National Motor Freight Classification, as applicable, except the closure of the fiberboard boxes shall be in accordance with Method II as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:48Z
Check the source to verify that this is the current version before use.

5.3 Unit loading. When specified (see 6.1), the product packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling and marking.

5.4.1 Cans. Cans shall be labeled in accordance with MIL-L-1497 and shall include the following information:

Peppers, Dehydrated
Type I - Green
Type II - Red
Type III - Mixed Red and Green
Net Weight oz. (dry solids basis)
Name and address of contractor
Date packaged
Preserved and Sulfur Dioxide
GAS PACKAGED (when applicable to types II and III)
Remove and discard dessicant bag

Directions for Use

Peppers, sweet, dehydrated	1.0 oz.
Water,(35° to 55°F)	16.0 oz.

1. Add dehydrated product to water.

2. Allow to soak for 30 minutes if sweet peppers are to be used for cooking purposes.

or

Allow to soak for 60 minutes or more if sweet peppers are to be used for salad preparation.

3. Dehydrated sweet bell peppers may be added to soups and stews without a presoaking.

NOTE: One ounce of dehydrated sweet bell peppers equals 8 ounces of fresh sweet bell peppers, as purchased; 6 1/2 ounces cut green sweet bell peppers; 5 ounces cut red sweet bell peppers, or 5 3/4 ounces cut mixed green and red sweet bell peppers, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

5.4.2 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Type of product required (see 1.2).
c. Level of preservation and packing required (see 5.1 and 5.2).
d. When type III exterior coating of cans is required (see 5.1.1).
e. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specified item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 Subject term (key word) listing.

Dehydrated foods
Peppers
Vegetables

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8915-0812

Review activities:

Army - MD, TS
Navy - MC, MS
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-35003E	Peppers, Green and Red, Dehydrated

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 20240-21107:48Z
Check the source to verify that this is the current version before use.