MIL-V-35017F
10 December 1984
SUPERSEDING
MIL-V-35017E
16 March 1977

MILITARY SPECIFICATION

VINEGAR, DRY, SYNTHETIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers synthetic dry vinegar for use by the Department of Defense as an item of general issue.

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8950

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:49Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-566 - Boxes, Folding, Paperboard
PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078 - Loads, Unit; Preparation of Nonperishable Subsistence Items; General Specification for
MIL-D-43266 - Desiccants and Desiccation, Method of; For Packaging Subsistence

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

OTHER GOVERNMENT DOCUMENTS

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder (21, CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:49Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 No. 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS.

3.1 Bid sample approval. A bid sample consisting of six filled and sealed bags including sufficient desiccant and representative of the product which the bidder proposes to furnish shall be submitted to the contracting officer prior to the bid opening date. Part of the bid sample will be evaluated for acceptability by a consumer panel at the U.S. Army Natick Research and Development Center (see 6.3). The remainder of an approved bid sample will

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:49Z
Check the source to verify that this is the currentversion before use.

be retained for use as a reference standard for product palatability during production in the event that the contract is subsequently awarded to the bidder. The approval of any bid sample will not constitute approval of the sample as meeting the other requirements of this document.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 dl-malic acid and other organic acids. Malic acid shall conform to the requirements specified in Food Chemicals Codex. When other organic acids are used, they shall be suitable substitutes for malic acid. They shall be listed in Food Chemicals Codex and shall conform to the requirements specified therein.

3.2.2 Sodium salts of acetic acid. Sodium salts of acetic acid shall conform to the requirements specified in Food Chemicals Codex.

3.2.3 Caramel coloring. Caramel color shall be powdered acid proof derivatives of burnt sugar.

3.2.4 Apple flavor. Apple flavor shall be free flowing, spray-dried powder.

3.2.5 Tricalcium phosphate. Tricalcium phosphate shall be anhydrous conforming to Food Chemicals Codex.

3.3 Preparation.

3.3.1 Vinegar preparation. Synthetic dry vinegar shall be prepared according to the following formula:

Ingredients	Percent by weight
dl-Malic acid	1/
Sodium diacetate	36.0 minimum
Sodium acetate, anhydrous	optional 1/
Caramel color, dry	0.1
Apple flavor	0.1
Tricalcium phosphate	optional 1/

1/ Any combination of dl-malic acid, or other organic acids as specified in 3.2.1, with not less than 36.0 percent by weight of sodium diacetate, 0.1 percent by weight of dry caramel color, 0.1 percent by weight apple flavor

Source: https://assist.dla.mil -- Downloaded: 202610-21T07:49Z
Check the source to verify that this is the current version before use.

and with or without the addition of anhydrous sodium acetate and/or trecalcium phosphate in amounts necessary to meet the finished product requirements.

3.4 Finished product requirements.

3.4.1 Dry product. Synthetic dry vinegar shall be a free flowing homogenous mixture and shall be packed with desiccant in a quantity sufficient to meet moisture removal requirements specified in 5.1.1.1.

3.4.2 Prepared product. Synthetic dry vinegar, when prepared in accordance with the directions in 5.4.1, (q.s. one quart) shall comply with the following requirements:

Solubility	The product shall completely dissolve in not more than 2 minutes when reconstituted with specified amount of water at 25° to 30°C
Taste	Sweet, tart taste of vinegar
Sediment	None
Aroma	apple
Titratable acidity (as acetic acid)	5.5 to 6.5 percent
pH	3.4 ± 0.4
Color	Color shall be light to medium amber comparable to commercially available cider vinegar.
Cloudiness	None

3.4.3 Palatability. The product rehydrated in accordance with 5.4.1 shall be equal in palatability to the prepared bid sample.

3.5 Plant qualification. The product shall be prepared, processed, and packaged under sanitary conditions in accordance with good manufacturing practice. The product shall be processed in establishments meeting the sanitary requirements of the applicable Government inspection agency.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

3.6 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and acceptance service. Product acceptability shall be determined by the USDA. The USDA will determine the degree of acceptance service necessary to assure compliance with the requirements of this document. The cost of grading and acceptance services performed by the USDA involving inspection, official documentation, and related services shall be borne by the contractor.

4.3 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of reference documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.3.1.1 Ingredient examination. Conformance of ingredients to identity requirements shall be determined by examination of pertinent labels, markings, U.S. Grade certificates, invoices, certificates of analysis or other documents. Conformance of ingredients to condition requirements as specified in 3.2 shall be determined by examination. Any nonconformance to identity, condition or other requirements shall be cause for rejection of the ingredient lot or of any involved product.

4.3.1.2 Material certification. Material listed shall be accepted on the basis of a contractor's certification of conformance to the indicated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

Material	Requirement	Requirement paragraph
Flexible bag material	Material identification	5.1.1.1
	Films and foil thickness	5.1.1.1
	Construction	5.1.1.1
	Color	5.1.1.1

4.3.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, desiccant addition, and unit packing requirements. Any nonconformance revealed by actual examination or by review of records of formulation and calculation of desiccant amounts or by review of other valid documents shall be cause for rejection of the involved product.

4.3.3 Net weight examination. The filled and sealed bags of product shall be examined for net weight. Any individual bag having a net weight of more than 5.0 percent under labeled net weight shall be scored as a minor defect. The lot size shall be expressed in bags. The sample unit shall be one bag of product. The inspection level shall be S-3 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than the labeled net weight.

4.3.4 Filled and sealed bag examination. The filled and sealed bags shall be examined for the defects listed in table I. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed bag. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.25 for major A defects, 1.5 for major B defects, and 6.5 for minor defects.

TABLE I. Filled and sealed bag defects

Category			Defect
Major A	Major B	Minor	
101			Sifter, tear, hole, or open seal
	151		Not type specified
	152		Objectionable odor
		201	Color not as specified
	153		Item description, directions for use, or caution note, missing, incorrect, or illegible
	154		Not clean

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:49Z
Check the source to verify that this is the current version before use.

TABLE I. Filled and sealed bag defects (cont'd)

Category			Defect
Major A	Major B	Minor	
		202	Labeling information other than item description, directions for use, or caution note, missing, incorrect or illegible

4.3.5 Product examination. The finished product shall be examined for the defects listed in table II. The lot size shall be expressed in bags. The sample unit shall be the contents of one filled and sealed bag. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

TABLE II. Product defects 1/

Category		Defect
Major	Minor	Desiccant bag
151		Desiccant bag missing.
152		Tear, hole, or open seam in desiccant bag.
153		Desiccant bag folded over itself.
		Finished dry product
154		Not free flowing.
155		Not a well blended homogeneous mixture.
		Finished prepared product 2/ 3/
156		Not completely dissolved within 2 minutes after preparation.
157		Presence of sediment.
	201	Cloudy.
158		Does not have sweet tart taste of vinegar.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

TABLE II. Product defects 1/ (cont'd)

Category		Defect
Major	Minor	Finished prepared product 2/ 3/ (cont'd)
159		Does not have an apple aroma.
160		Color not as specified.

1/ The presence of any foreign material (e.g., glass, dirt, insect parts, hair, wood, metal, etc.), foreign odor or flavor (e.g., burnt, scorched, moldy, rancid, sour, stale, etc.), or foreign color shall be cause for rejection of the lot.

2/ Add sufficient amount of water (25° to 30°C) to the finished product to make one quart of prepared product.

3/ Product not equal to or better than the bid sample in palatability shall be cause for rejection of the lot (This comparison shall be performed only when deemed necessary by an AMS agent).

4.3.6 Leakage testing. The filled and sealed bags shall be placed in a dry desiccator, or similar apparatus, and subjected to a vacuum of 26 inches of mercury for 30 seconds. Any bag which does not swell and become tightly distended with at least one distorted edge shall be recorded as a leaker. Any leaker or any bag with delamination or with seal separation to within 1/16 inch of the product edge shall be classified as a major defect. The lot size shall be expressed in bags. The sample unit shall be one filled and sealed bag. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

4.3.7 Product testing. A composite sample of the dry product shall be tested for titratable acidity as specified in 4.4.1 and for pH as specified in 4.4.2. The lot size shall be expressed in bags. The sample shall be an 8-ounce composite derived from the number of filled and sealed bags indicated by inspection level S-2. A sufficient amount of the composite to make 1 quart of vinegar in accordance with bag label instructions shall be reconstituted and used for the titratable acidity and pH tests. Any test failure shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

4.3.8 Intermediate pack examination. The filled paperboard boxes shall be examined for the defects in table III. The lot size shall be expressed in boxes. The sample unit shall be one filled and closed intermediate box. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

TABLE III. Intermediate pack defects

Category		Defect
Major B	Minor	
151		Box damaged impairing serviceability.
	201	Cover not securely closed in manner specified.
	202	Not a snug-fitting box.
	203	Less than 12 bags in box.
	204	Bags not stacked flat.
	205	Label missing, incorrect, or illegible.

4.3.9 Shipping container examination. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in construction, closure, and reinforcement shall be in accordance with the appendix of PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number, or date of pack markings missing, incorrect, or illegible.

Minor: Other required markings missing, incorrect, or illegible.
Reinforcement with nonmetallic strapping or tape is not used.
Arrangement or number of intermediate cartons not as specified.
Not snug fitting.

Level C shipping containers shall be examined for the marking, arrangement, and number of intermediate cartons defects specified above and for the closure method specified in 5.2.3.

4.3.10 Unit load inspection. Inspection of unit loads shall be in accordance with Quality Assurance Provisions of MIL-L-35078 for the type and class of load specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

4.4 Methods of inspection.

4.4.1 Titratable acidity test. Titratable acidity shall be determined by the Total Acids method described in the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Spices and Other Condiments; Section: Vinegars.

4.4.2 pH test. pH shall be determined by the Electrometric method described in the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Cereal Foods; Section: Wheat flour.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A.

5.1.1.1 Unit pack. A quantity of synthetic dry vinegar sufficient to make one quart of vinegar shall be filled into a heat sealable laminated bag. A minus 5.0 percent tolerance under labeled net weight will be allowed in any individual bag, provided the average net weight of the bags, inspected in accordance with 4.3.3, is not less than the labeled net weight. The bag material shall be a 3-ply laminate consisting of, from inside to outside, 0.003-inch thick polypropylene laminated to 0.00035-inch thick aluminum foil laminated to 0.0005-inch thick polyester. The laminating adhesive shall be an odorless and permanently plastic water-resistant material other than wax. The bag shall be made by heat sealing the top, sides, and bottom. The complete exterior of the bag shall be the color of natural kraft or a similar dull brown color. When applicable, electric eye markings for automatic bag making and filling machinery may be white. The filled and sealed bag shall not leak or delaminate when tested in accordance with 4.3.6. Each bag shall be provided with sufficient desiccant complying with MIL-D-43266 to remove all moisture in the product. The amount of desiccant required to remove all moisture in the product shall be calculated from the formula specified in MIL-D-43266, except that the value for percent water in the formula shall be the actual moisture content of the product, at the time of unit packing as determined by the Karl Fisher method described in the Official Methods of Analysis of the Association of Official Analytical Chemists; Chapter: Vegetable Products, Processed; Section: Dried Vegetables except that anhydrous methanol shall be used instead of N, N- dimethylformamide in titrating both the sample and the blank. A record of the calculations shall be maintained.

Source: https://assist.dla.mil -- Downloaded: 202640-21T07:49Z
Check the source to verify that this is the current version before use.

5.1.1.2 Intermediate pack. Twelve bags of product shall be stacked flat in a snug-fitting intermediate paperboard box, constructed in accordance with variety 1, style X, XI or XIA for a semi-supporting load of PPP-B-566. The tuck end shall be provided with tuck locks which shall be engaged when the box is completely closed.

5.2 Packing. Twelve intermediate packs of synthetic dry vinegar shall be packed in a shipping container in accordance with level A, B, or C. as specified (see 6.1 and 6.2).

5.2.1 Level A packing. The shipping container shall be a snug-fitting fiberboard box constructed and closed in accordance with style RSC-L, V2s of PPP-B-636. Each shipping container shall be reinforced with non-metallic strapping or pressure sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to non-metallic strapping, except for type II, class F loads.

5.2.2 Level B packing. The shipping container shall be a snug-fitting fiberboard box constructed and closed in accordance with style RSC-L, V3c, V3s or V4s of PPP-B-636. Each shipping container shall be reinforced with non-metallic strapping or pressure sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing. The shipping container shall be in accordance with the National Motor Freight Classification or Uniform Freight Classification, as applicable, except the closure of the fiberboard boxes shall be in accordance with method II as specified in the appendix of PPP-B-636.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to non-metallic strapping.

5.4 Marking and labeling.

5.4.1 Unit pack. The following information shall be legibly printed in black on one side of the bag:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

VINEGAR, DRY, SYNTHETIC
Net Weight
Name and address of supplier
REMOVE AND DISCARD DESICCANT BAG

Directions: Mix the contents of this envelope in sufficient water (approx. 3 3/4 cups) to make up one quart of the prepared product.

CAUTION: This instant vinegar in dry form has eight times the strength of 50-grain vinegar. DO NOT INHALE DRY POWDER.

5.4.2 Intermediate pack. Intermediate pack shall be labeled in black ink with the following information:

12 UNIT PACKS
VINEGAR, DRY, SYNTHETIC
EACH UNIT PACK MAKES ONE QUART
NAME AND ADDRESS OF MANUFACTURER

5.4.3 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129. In addition, the following precautionary markings shall appear in letters not less than 1 inch high on top of each container.

STORE IN COOL, DRY AREA

5.4.4 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. Level of packing required (see 5.2).
c. Type and class of unit load, when unit load is specified (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling, and storage of the specific item being procured, the contracting officer should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

6.3 Bid sample evaluation. Bid samples will be evaluated by the U.S. Army Natick Research and Development Center in accordance with the following procedure. The bid sample will be used to prepare a vinegar and oil dressing as follows:

Vinegar, rehydrated	10 fl oz.
water	2 fl oz.
salad oil	20 fl oz.
salt	1-1/2 TBSP (1 avoir oz.)
pepper, black	3/4 tsp.

NOTE: Rehydrate vinegar in accordance with 5.4.1; Combine and blend pepper, salt and water; Add oil and vinegar and mix well; Cover and refrigerate until ready for use. Shake or beat well before use.

Individual servings of the above dressing will be prepared by adding one tablespoon of the dressing to a 1-inch cube of lettuce. The servings will be rated by consumer panel members on a 9-point Hedonic scale graduated in successive degrees of "like extremely" to "dislike extremely". For further details of this taste panel evaluation procedure see:

"Food Technology Vol. XI, No. 9 (1957) - Hedonic Scale Method of Measuring Food Preference." (Copies may be obtained from the U.S. Army Natick Research and Development Center, ATTN: STRNC-WBF, Natick, MA 01760-5014)

6.4 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

Project No. 8950-0277

Review activities:

Army - MD, TS
Navy - MS, MC
DP - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-V-35017F	Vinegar, Dry, Synthetic

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP. 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:49Z
Check the source to verify that this is the current version before use.