MILITARY SPECIFICATION SHEET

CONNECTOR, COMPONENT PARTS,
ELECTRICAL BACKPLANE, PRINTED WIRING, HOUSING

This amendment forms a part of Military Specification Sheet MIL-C-28859/2C(EC), dated 4 December 1984, and is approved for use by the Space and Naval Warfare Systems Command, and is available for use by all Departments and Agencies of the Department of Defense.

Page 5

TABLE I: Delete and substitute:

"TABLE I. Dash numbers and dimensions.

| DASH NO | MODULAR PARTS | A ±.005 | B BSC | J EQUAL SPACES AT .100 BSC | K ±.005 | L EQUAL SPACES AT .100 BSC | NO. OF CONTACT LOCATIONS (EACH PIECE) | TOTAL NO. OF CONTACTS |
|---|---|---|---|---|---|---|---|---|
| -1 | 1 | 2.440 | 2.200 | 19 | .200(.215 MAX AFTER ASSY) | | 40 (2 ROWS OF 20) | 40 |
| | 2 EA DETAIL W 1/ | 2.440 | 2.200 | 9 | | | 20 (2 ROWS OF 10) | 40 |
| -4 | 2 EA DETAIL W | 5.440 | 5.200 | 24 | .200(.215 MAX AFTER ASSY) | | 50 (2 ROWS OF 25) | 100 |
| | 2 EA DETAIL W<br>1 EA DETAIL Z } 1/ | 5.440<br>5.440 | 5.200<br>5.200 | 19<br>9 | | | 40 (2 ROWS OF 20)<br>20 (2 ROWS OF 10) | 100 |
| -5 | 1 EA DETAIL R&S | 5.440 | 5.200 | 24 | .300(.315 MAX AFTER ASSY) | 2 | 75 (3 ROWS OF 25) | 150 |
| | 1 EA DETAIL R&S<br>1 EA DETAIL V } 1/ | 5.440 | 5.200 | 19<br>9 | | 2<br>2 | 60 (3 ROWS OF 20)<br>30 (3 ROWS OF 10) | 150 |
| -6 | 1 EA DETAIL R&S | 5.440 | 5.200 | 24 | .400(.415 MAX AFTER ASSY) | 3 | 100 (4 ROWS OF 25) | 200 |
| | 1 EA DETAIL R&S<br>1 EA DETAIL V } 1/ | 5.440 | 5.200 | 19<br>9 | | 3<br>3 | 80 (4 ROWS OF 20)<br>40 (4 ROWS OF 10) | 200 |
| | 2 EA DETAIL W<br>2 EA DETAIL Z } 1/ | | | 24 | | | 50 (2 ROWS OF 25)<br>50 (2 ROWS OF 25) | 200 |
| | 2 EA DETAIL W<br>1 EA DETAIL Z<br>2 EA DETAIL Z<br>1 EA DETAIL Z } 1/ | 5.440 | 5.200 | 19<br>9<br>19<br>9 | | -<br>-<br>-<br>- | 40 (2 ROWS OF 20)<br>20 (2 ROWS OF 10)<br>40 (2 ROWS OF 20)<br>20 (2 ROWS OF 10) | 200 |
| -7 | 1 EA DETAIL R&S | 5.440 | 5.200 | 24 | .500(.515 MAX AFTER ASSY) | 4 | 125 (5 ROWS OF 25) | 250 |
| | 1 EA DETAIL R&S<br>1 EA DETAIL V } 1/ | 5.440 | 5.200 | 19<br>9 | | 4<br>4 | 100 (5 ROWS OF 20)<br>50 (5 ROWS OF 10) | 250 |
| | 2 EA DETAIL W<br>2 EA DETAIL V } 1/ | | | 24<br>24 | | -<br>2 | 50 (2 ROWS OF 25)<br>75 (3 ROWS OF 25) | 250 |
| | 2 EA DETAIL W<br>1 EA DETAIL Z<br>2 EA DETAIL V } 1/ | 5.440 | 5.200 | 19<br>9<br>24 | | -<br>-<br>2 | 40 (2 ROWS OF 20)<br>20 (2 ROWS of 10)<br>75 (3 ROWS OF 25) | 250 |

".

1/ Alternate construction.

PAGE 6

Under REQUIREMENTS: Delete and substitute: "Housing retention force: 6 oz. minimum and 30 oz. maximum per compliant pin. Retention only on outside rows of individual housing.".

Preparing activity:
NAVY-EC

(Project No. 5935-N273)

FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:56Z
Check the source to verify that this is the current version before use.