INCH-POUND


MIL-F-28861/2A
2 November 1988
SUPERSEDING
MIL-F-28861/2
17 December 1981

MILITARY SPECIFICATION SHEET

FILTERS, RADIO FREQUENCY/ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY SEALED, STYLE FS20

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-F-28861.



MOUNTING HARDWARE


FIGURE 1. Case and hardware dimensions and circuit diagrams.

(A) Denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:05Z
Check the source to verify that this is the current version before use.

Dash number	A dimension (±.010)
001 thru 012	.187
013 thru 024	.312



CIRCUIT DIAGRAMS

Inches	mm	Inches	mm
.003	0.08	.115	2.92
.005	0.13	.145	3.68
.007	0.18	.187	4.75
.010	0.25	.200	5.08
.015	0.38	.250	6.35
.022	0.56	.312	7.92
.045	1.14	.395	10.03
.070	1.78	.408	10.36
.093	2.36	.410	10.41
		.793	20.14

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Circuit diagrams are for information only.
4. All filters shall be supplied with mounting hardware (hex nut and lockwasher). Mounting hardware shall be furnished with the same finish as the filter case.
5. Terminal identification (non-symmetrical filters): The case shall be marked at the threaded end of the filter with the symbol "C" or the symbol "L", as follows, or the circuit diagram shall be marked on the case.

Circuit	Symbol
L_1	C
L_2	L

6. Optional slot may be supplied, .050 ±.010 inches (1.27 ±0.25 mm) x .070 ±.010 inches (1.78 ±0.25 mm).
7. Imperfect thread or undercut optional .050 inch (1.27 mm) maximum.
8. One imperfect thread allowed .035 inch (0.89 mm) maximum.
9. Recommended mounting torque: 44 oz-in ±4 oz-in.

FIGURE 1. Case and hardware dimensions and circuit diagrams - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:05Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Weight: 10 grams maximum.

Case finish:

Class B filters, T only (tin plated or tin-lead plated).

(A) Classes A and S filters, T or G only (tin plated, tin-lead plated, or gold plated). In accordance with MIL-F-28861.

Terminals: Solderable.

Operating temperature range: -55°C to +125°C.

Rated voltage: 100 V dc.

Rated current: See table I.

Capacitance: See table I for minimum capacitance value.

Dissipation factor: 3 percent maximum.

Voltage and temperature limits of capacitance: +15 percent, -40 percent.

Insulation resistance:

At +25°C: 1,000 megohms minimum or 1,000 megohm-microfarads minimum, whichever is less.

At +125°C: 100 megohms minimum or 100 megohm-microfarads minimum, whichever is less.

Insertion loss: See table I.

Voltage drop: See table I.

DC resistance: See table I.

(A) Seal: In accordance with MIL-F-28861. Leakage rate for classes A and S filters shall not exceed 1 x 10^{-7} atm cm^3/s.

Temperature rise: +25°C maximum.

Solderability of terminals: In accordance with MIL-F-28861.

(A) Quality assurance provisions:

Class B and class S filters: In accordance with MIL-F-28861.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:05Z
Check the source to verify that this is the current version before use.

Ⓐ TABLE I. Electrical characteristics.

Dash number	Product assurance level (Class)			Circuit	Maximum current (amps)	Minimum capacitance (µF)	Maximum voltage drop (volts)	Maximum DC resistance (ohms)	Minimum insertion loss (dB) in accordance 1/ 2/ with MIL-STD-220														
									At +25°C							At -55°C and +125°C							
	A	B	S						100 kHz	150 kHz	300 kHz	1 MHz	10 MHz	100 MHz	1 GHz	100 kHz	150 kHz	300 kHz	1 MHz	10 MHz	100 MHz	1 GHz
001, 013	X	X	X	L1	0.25	0.45	0.375	1.5	30	38	50	60	60	60	70	28	36	48	58	60	60	70
002, 014	X	X	X	L2	0.25	0.45	0.375	1.5	30	38	50	60	60	60	70	28	36	48	58	60	60	70
003, 015	X	X	X	π	0.25	0.90	0.375	1.5	54	64	80	80	80	80	80	52	62	78	78	80	80	80
004, 016	X	X	X	L1	1.0	0.45	0.250	0.25	15	23	34	55	60	60	70	13	21	32	53	60	60	70
005, 017	X	X	X	L2	1.0	0.45	0.250	0.25	15	23	34	55	60	60	70	13	21	32	53	60	60	70
006, 018	X	X	X	π	1.0	0.90	0.250	0.25	40	52	70	80	80	80	80	38	50	68	78	80	80	80
007, 019	X	X	X	L1	3.0	0.45	0.150	0.05	14	18	27	45	60	60	70	12	16	25	43	60	60	70
008, 020	X	X	X	L2	3.0	0.45	0.150	0.05	14	18	27	45	60	60	70	12	16	25	43	60	60	70
009, 021	X	X	X	π	3.0	0.90	0.150	0.05	---	25	51	80	80	80	80	---	23	49	78	80	80	80
010, 022	X	X	X	L1	5.0	0.45	0.075	0.015	14	17	24	36	60	60	70	12	15	22	34	60	60	70
011, 023	X	X	X	L2	5.0	0.45	0.075	0.015	14	17	24	36	60	60	70	12	15	22	34	60	60	70
012, 024	X	X	X	π	5.0	0.90	0.075	0.015	---	---	38	75	80	80	80	---	---	36	73	80	80	80

1/ Insertion loss measurements shall be made under full load over the frequency range of 100 kHz to 10 MHz. Insertion loss measurements above this frequency range shall be made under no load.

2/ The insertion loss requirements between any two adjacent specified frequencies shall be that of the lower of the two frequencies in order to accommodate resonant dips.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:05Z
Check the source to verify that this is the current version before use.

Class A filters:

Qualification inspection: Initial qualification may be granted based on qualification to class B. Baseline documentation in accordance with MIL-F-28861 is required and shall be submitted to the qualifying activity prior to completion of quality conformance inspection on the initial lot. Retention of qualification shall be in accordance with class S requirements.

In-process inspection: In accordance with class S requirements, except that the requirements of MIL-C-123 shall not apply.

Quality conformance inspection: The inspection lot definition and inspection of product for delivery shall be in accordance with the class S requirements.

Product assurance level: In accordance with table I.

Part or identifying number: The part or identifying number shall be as follows:

M28861/02 - XXX X X

- XXX: Dash no. per figure 1 and table I
- X: Case finish
- X: Product assurance level per MIL-F-28861 and table I

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - SH
Air Force - 11, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5915-0337-01)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:05Z
Check the source to verify that this is the current version before use.