MILITARY SPECIFICATION SHEET

FILTERS, RADIO FREQUENCY/ELECTROMAGNETIC INTERFERENCE SUPPRESSION, HERMETICALLY SEALED, STYLE FS30

This amendment forms a part of MIL-F-28861/3, dated 17 December 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Following "Capacitance", add the following: "Dissipation factor: 3 percent maximum."

* Insulation resistance, delete in its entirety and substitute:

"Insulation resistance:

At +25°C: 1,000 megohms minimum or, 1,000 megohm microfarads minimum, whichever is less.

At +125°C: 100 megohms minimum or, 100 megohm microfarads minimum, whichever is less."

The margin of this amendment is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Army - AR, MI
Navy - SH
Air Force - 11, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - AS, MC, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5915-0314-2)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil - Downloaded: 2026-10-20 20:06:02
Check the source to verify that this is the current version before use.