MILITARY SPECIFICATION

PUMPING UNIT, FRAME MOUNTED, 1-1/2 INCH,

ELECTRIC MOTOR DRIVEN, 35 GPM AT

25 FEET TOTAL HEAD

This amendment forms a part of MIL-P-53065 (ME), dated 8 October 1986, and is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2, under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM), delete the following:

"B 26 - Aluminum Alloy Sand Castings, Spec for.
B 210 - Aluminum-Alloy Drawn seamless Tubes.
B 221 - Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Shaped, and Tubes.
B 584 - Copper Alloy Sand Castings for General Application, Spec for."

PAGE 5

3.4.1, add at the end of paragraph: "It shall also operate under adverse weather conditions such as rain, dust, high humidity, salt fog and solar radiation.

3.5, add at the end of paragraph: "The pump shall comply with applicable safety and health requirements and shall not present any Uncontrolled hazards to user personnel throughout its life cycle."

3.6, add at the end of paragraph: "The pump shall be operable in reduced visibility without protection, with a minimum of illumination, by the 5th through 95th percentile soldier, and by two vehicle crewmen in MOPP IV protective ensemble."

AMSC N/A FSC 4320

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:57Z
Check the source to verify that this is the current version before use.

* 3.7, line 2, after "category E requirements" add "[75 dB(A)]".

Lines 3 thru 7, delete third sentence in its entirety and substitute: "Category E requirements may not be exceeded."

3.8, line 2, delete "with minimum flow of 35 GPM at 25 feet of total head" and substitute: "capable of transferring from 25 to 50 GPM of diesel fuel viscosity range of 1.3 cs to 5.0 cs at 20 “C at 20 feet of head."

3.8.4.1, lines 1 and 2, delete first sentence and substitute: "The pump case and volute shall be a one piece casting of a nonsparking material compatible with diesel fuel."

3.8.4.2, line 2, delete "constructed from 356-T6 aluminum."

3.8.4.3, delete in its entirety and substitute:

"3.8.4.3 Impeller. The impeller shall be of a nonsparking material compatible with diesel fuel."

After 3.8.4.5, add:

"3.8.4.6 Physical characteristics. A maximum size of 28 inches long, 18 inches wide and 18 inches high, with a maximum weight of 80 pounds is permissible."

"3.8.5 Nuclear biological chemical (NBC) contamination. The pump and assembly shall be NBC contamination survivable."

3.9, last sentence, delete "Groups C and D" and substitute "Group D"

3.10, line 1, delete "tubular aluminum".

Lines 2 and 3, delete second sentence in its entirety.

3.13, add at the end of paragraph: "The pump and hose fittings shall be standard cam-lock, 1-1/2 inches in diameter."

* 3.13.2, after the first sentence, add: "Unless otherwise specified (see 6.2), the nozzle shall be type 1, size 2, class A, style 2.

* 3.16, lines 3 and 4, delete "for other than engine-driven equipment." and substitute: "class C1, group II."

* 3.17, lines 3 thru 5, delete the second sentence in its entirety and substitute: "The top coat shall be camouflage green 383 or tan 363 as specified (see 6.2) conforming to MIL-C-46168."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:57Z
Check the source to verify that this is the current version before use.

After 3.19.5, add:

"3.20 Government-loaned property. The following property in the quantity indicated will be loaned by the Government (see 6.7).

Item	Description	Quantity
1	Army MOPP IV protective mask and cold weather clothing	As required"

* 4.4, delete in its entirety and substitute:

"4.4 Quaity conformance inspection. Quality conformance inspection shall be performed on each pumping unit and include the examinations of 4.5 and test of 4.6.1."

* 4.6, after "Tests", add: "The hydrostatic test (see 4.6.1) and the performance test (see 4.6.3) shall be conducted on three complete pump and fitting setup and the evaluation of each shall be in accordance with the stated requirements."

* 4.6.2, line 2, delete "3.11" and substitute "3.10"

4.6.3.4, line 6, after sentence ending "of any component", add "Operator performing functional operational test shall be dressed in Army MOPP IV protective mask and cold weather clothing."

* 4.6.3.6.1, line 2, delete "method 501.1, procedure I." and substitute "method 501.2, procudures I and II."

Line 4, delete "procedure I" and substitute: "procedure II".

* 4.6.3.6.2, line 2, delete "method 502.1, procedure I." and substitute: "method 502.2, procedure I and II."

4.6.5, add at the end of paragraph: "Operation will be verified by personnel representing the 5th through 95th percentile soldier. This will address compatibility with NBC protective clothing and equipment and ease of use under conditions of reduced visibility."

After 4.6.7, add:

"4.6.8 Physical characteristics. The pumping unit's weight and dimensions shall be determined. Nonconformance to 3.8.4.6 shall constitute failure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:57Z
Check the source to verify that this is the current version before use.

"4.6.9 NBC contamination. The pumping unit must be capable of withstanding five cycles of contamination/decontamination with degradation. It must be functional after these cycle."

PAGE 13

* 4.8.2.1, lines 3 and 4, delete the last sentence in its entirety and substitute: "Presence of one or more defects shall be cause for rejection."

PAGE 14

* After 6.2, h., add:

"i. Type, size, class, and style of nozzle required (see 3.13.2)."

PAGE 15

After 6.6, add:

"6.7 Government-loaned property. The contracting officer should arrange to lend the property listed in 3.20."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were rode. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in the notations. Bidders and contractors are cautioned to evaluate the the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4320-A331

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:57Z
Check the source to verify that this is the current version before use.