MIL-L-48066B(AR)
1 April 1977
Superseding
MIL-L-48066A (PA)
21 April 1975

MILITARY SPECIFICATION

LEAD, EXPLOSIVE, PA 510 (See 6.8)
PARTS FOR, AND LOADING, ASSEMBLING AND PACKING

"This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense".

1. SCOPE

*1.1 This specification covers the inspection of the parts and the loading, assembling and packing of one type of lead designated as Lead, Explosive, PA 510.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

MILITARY

MIL-P-116	- Preservation, Method of
MIL-R-398	- RDX
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-P-48395	- Pellets, Explosive Compositions (For Use in Ammunition)

STANDARDS

MILITARY

FSC: 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

MIL-STD-650 - Explosives; Sampling, Inspection and Testing
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

*U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKING DRAWINGS

7548099 - Box, Packing, Ammunition
7548103 - Box, Set-up, Packing, Ammunition, Outer
7548104 - Box, Set-up, Packing, Ammunition, Inner
9236504 - Lead, Explosive, PA 510

INSPECTION EQUIPMENT DRAWINGS

8868629 - Adapter, ball
9202853 - Firing Pin
9202854 - Holder
9247125 - Firing assembly
9247126 - Bushing
9247127 - Body, set-up
9247128 - Block, witness

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications. - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for the proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM Designation E300 - Industrial Chemicals, Recommended Practice for Sampling

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:11Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

*3.2 Lead, Explosive, PA 510.- The lead, explosive, PA 510 shall comply with all requirements specified on Drawing 9236504 and with all requirements specified in the applicable specifications.

3.3 Moisture content. - The moisture content of the RDX pellets or composition at the time and site of loading shall not exceed 0.20 percent.

3.4 Functioning. - The lead shall be capable of high order initiation by an M94 detonator across a minimum air gap of 0.145 inches when tested as specified. High order detonation will be evidenced by a depression of a minimum depth of .0253 inches in the witness block of Rockwell Hardness B81-B85.

*3.5 First Article Inspection. - This specification contains technical provision for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly no shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. (Required packing shall be dry).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:11Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. - The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

*4.3 First Article Inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Cup, Lead	9236505	25
Disc, Retainer	9236506	25
Lead, Explosive, PA510	9236504	700

4.3.2 Inspections to be Performed. - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-49078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

MIL-L-48066B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Lead, Explosive, PA 510 and Components				See below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup, Lead (Dwg 9236505)				
	Examination for Defects	25	-	3.2	4.4.2.1
	Disc, Retainer (Dwg 9236506)				
	Examination for Defects	25	-	3.2	4.4.2.2
	Lead, Explosive, PA 510 (Dwg 9236504)				
	Density of Explosive within the cup (a)	315	-	3.2	4.4.2.4
	Functioning	315	-	3.4	4.4.2.4
	Examination for Defects	25	-	3.2	4.4.2.4

NOTES:

(a) See Note 1 of 4.4.2.4

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. - Inspection lost shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of leads shall contain RDX from not more than one batch or a blend of batches which results in homogenity of all RDX used in loading a lot.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-L-48066B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.4.2.1	Cup, Lead		9236505
			NEXT HIGHER ASSEMBLY 9236504

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Outside Diameter, max		0.40%	3.2	Gage
103	Wall thickness		0.40%	3.2	Gage
104	Concentricity of hole with outside diameter				
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-L-48066B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.2	Disc, retainer				9236506
					NEXT HIGHER ASSEMBLY
					9236504
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Diameter, min.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74 4810

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-L-48066B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9236504
*4.4.2.3	Explosive RDX Prior to Pelleting				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Moisture Content	See Notes 1&2		3.3	4.5.2
102	Composition	See Notes 1&2		3.2	4.5.3
Minor	None Defined				

NOTE 1: A representative sample shall be chosen as outlined in MIL-P-48395.

NOTE 2: These tests shall be performed if 120 or more days have passed between the date that the pellets were accepted per MIL-P-48395 and the loading of the PA 510 Explosive Lead or if alternative loading per Note 10 of drawing 9236504 is used.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 19:17:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-L-48066B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.4	Lead, Explosive, PA 510				9236504
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cracks or splits		100%	3.2	Visual
Major					
101	Total length		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Lacquer seal missing or color incorrect		0.40%	3.2	Visual
104	Assembly distorted or damaged to extent that function may be impaired		0.40%	3.2	Visual
105	Incorrect density of explosive within the cup. (Note 1)		0.40%	3.2	4.5.5
106	Functioning	315		3.4	4.5.4
Minor					
201	Crimp not full 360 degrees		0.65%	3.2	Visual
202	Disc folded or wrinkled		0.65%	3.2	Visual
203	Evidence of poor workmanship other than critical above		0.65%	3.5	Visual

NOTES: 1. This inspection to be performed only if alternative loading per note 10 of drawing 9236504 is utilized.

Source: https://assist.dla.mil -- Downloaded: 2026-02-27T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548104
*4.4.2.5	Box, Set-Up, Packing Ammunition, Inner				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined.				
Major					
101	Box damaged exposing contents		0.40%	3.2	Visual
102	Label missing, incomplete, illegible, or incorrect		0.40%	3.2	Visual
103	Leads not positioned securely in spacer		0.40%	3.2	Visual
104	Component missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-L-48066B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548103
*4.4.2.6	Box, Set-Up, Packing, Ammunition, Outer				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to extent that inner box will not fit properly		0.40%	3.2	Visual
102	Filler missing		0.40%	3.2	Visual
103	Sealing strip insecure or improperly applied		0.40%	3.2	Visual
104	Box corners not blunted prior to insertion of box into barrier bag		0.40%	3.2	Visual
105	Label not securely applied to box		0.40%	3.2	Visual
106	Marking illegible, incorrect or missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2024-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-L-48066B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.7	Bag, Barrier, Material				7548103
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Heat seal test of sealed bag	(a)	(a)	3.2	(a)
102	Sealed bag will not permit 2 additional seals		0.40%	3.2	Visual
103	All excess air not exhausted from bag prior to sealing		0.40%	3.2	Visual
104	Evidence of hole or holes in bag		0.40%	3.2	Visual
105	Marking missing, illegible or incorrect		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: (a) In accordance with MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2020-10-22T19:11Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-L-48066B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.4.2.8	Box, Packing, ammunition				7548099
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged		0.40%	3.2	Visual
102	Nailing inadequate		0.40%	3.2	Visual
103	Strapping missing or loose		0.40%	3.2	Visual
104	Marking incomplete, misleading or unidentifiable		0.40%	3.2	Visual
105	Cushioning missing or improper thickness		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2022-10-22T19:11Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the section 6.2 herein.

*4.5 Test Method and Procedures

*4.5.1 Materials, Components and Processes. - Compliance with all requirements of section or paragraph 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

*4.5.1.1 Visual and Mechanical Inspections. - The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of section or paragraphs 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Moisture content. - The moisture content of the RDX shall be determined in accordance with MIL-P-48395.

4.5.3 Composition.-The composition of the RDX pellets shall be determined in accordance with MIL-P-48395.

4.5.4 Functioning. The lead shall be assembled in the test fixture. A steel ball .750 inches in diameter and weighing 1.00 ounces, maximum, shall be dropped on the firing pin to function an M94 detonator, from a height of (3) inches, maximum. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A lead that fails to fire or fails to create a depression in the steel block of the required depth shall be classed defective. Test method shall be in accordance with 8868629, 9202853, 9202854, 9247125, 9247126, 9247127, and 9247128. The lot shall be rejected if more than one lead fails to function as required.

*4.5.5 Determination of Density of Explosive within the Cup. - The explosive lead shall be weighed on a balance and the weight recorded as dry weight. The lead shall then be weighed while

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

completely submerged in water and the weight recorded as weight under water. After both these operations have been completed, the explosive shall be dissolved from the assembly using warm cyclohexanone. The the lead cup shall be weighed on a balance and the weight recorded as dry weight. Then the lead cup shall be weighed while completely submerged in water and the weight recorded as weight under water. The temperature of the water shall be 68 degrees F plus or minus 5 degrees F. Specific gravity of the Comp A5 shall be calculated as follows:

$$\text{Specific Gravity} = \frac{A - C}{(A-C) - (B-D)}$$

where:
A = Dry weight of assembly
B = Weight under water of assembly
C = Dry weight of cup only
D = Weight under water of cup only

5. PACKAGING

5.1 Preservation Packaging.-Preservation-packaging shall be Level B as specified (See 6.7).

*5.1.1 Level B

*5.1.2 Unit Packaging.-The leads shall be preserved and packaged in accordance with dwg. 7548103 and 7548104.

5.1.3 Unit Packaging.- Metal parts shall be packaged in accordance with MIL-STD-1169 Level C requirements.

5.2 Packing

5.2.1 Level B. - Not applicable.

5.2.2 Leads.- The containers shall be packed in accordance with 7548099.

5.2.3 Metal Parts.- Metal parts shall be packed in accordance with MIL-STD-1169 Level C requirements.

5.3 Marking. - Marking shall be in accordance with dwgs. 7548103, 7548104, and 7548099. Unit and exterior containers for metal part shall be marked in accordance with MIL-STD-1169 requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:11Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and data of this specification.

b. Provisions of MIL-A-48078.

*6.2 Submission of Inspection Equipment Designs for Approval (See MIL-A-48078). Submit equipment designs as required, to Commander, ARRADCOM, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

*6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, ARRADCOM, ATTN: DRDAR-QAR-R, Dover, New Jersey 07801.

6.4 Check test for possible deterioration. - The following test is designed to prevent leads that have deteriorated from being assembled into major ammunition items. The test shall be performed on leads from each lot which have been stored under normal conditions for more than two years or under adverse conditions for any period of time. If the specification for the ammunition item into which the leads are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration. Lead, Explosive PA 510's shall be selected from each lot for this test.

6.4.1 Functioning. - The sample size and acceptance or rejection criteria shall be in accordance with Table II-A, Code Letter H, of MIL-STD 105, using and AQL of 0.40. Test shall be performed as specified in 4.5.4, using equipment in accordance with 4.4.4.

*6.5 Drawings. - Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

6.6 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as anconvenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

6.7 The requirements herein for Level B are equivalent to requirements for full Level B use in accordance with AR 700-15, 20 June 1975. They are intended to provide for limited storage life necessary to meet on-going loading, assembly and packing operations and to provide uniform packing from all producers of an item to all using facilities.

6.8 This specification reflects a change in nomenclature. The Lead, Explosive, PA 510 was formerly identified as Lead, Multipurpose.

Custodian:
Army-R

Preparing Activity:
Army-AR

Project Number: 1375-A201

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Armament R&D Command
ATTN: DRDAR-QAR
Dover, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:11Z
Check the source to verify that this is the current version before use.