MILITARY SPECIFICATION

REELING MACHINE, CABLE, ENGINE DRIVEN

This specification is approved for use by the USA Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a reeling machine for use in the field and aboard vessels for reeling wire rope onto or off standard military steel cable reels.

2 APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-P-664	- Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
UU-T-81	- Tags, Shipping and Stock.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-C-650	- Crates, Wood, Open and Covered.

FSC 3895

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-E-10062	- Engines: Preparation for Shipment and Storage of.
MIL-T-22085	- Tapes, Adhesive, Preservation and Sealing.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

DRAWINGS

ME

TA13213E8110	- Reeling Machine Assembly.

(Copies of specifications, standards, and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN WELDING SOCIETY, INC.

D1.1 - Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. 7th Street, Miami, FL 33125.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 1616 P Street NW, Washington, DC 20036.)

DEPARTMENT OF LABOR

Occupational Safety and Health Adminstration (OSHA Regulations).

(Application for copies should be addressed to the Bureau of National Affairs, Inc., 1231 25th Street, NW, Washington, DC 20037.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The reeling machine shall be in accordance with Top Assembly TA13213E8110 and as specified herein. The reeling machine shall be powered by a Government-furnished, 20 hp, military design engine (see 3.7). The reeling machine shall operate with a 56 inch reel, in place, without binding or permanent deformation of any part. The reel (NSN 8130-00-53-0102) will be loaned by the Government (see 4.5.2 and 6.5). The lift roller shall rotate freely by hand in each of its mounting positions.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

3.2 First article (preproduction model). The contractor shall furnish a reeling machine for examination and testing within the time frame specified (see 6.2), to prove prior to starting production that his production methods will produce reeling machines that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4, and shall be subject to surveillance and approval by the Government (see 6.3). When specified, the Government will conduct any or all of the preproduction examinations and tests as specified (see 6.2).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.4 Lubrication. All surfaces requiring lubrication shall be provided with a means for lubricating.

3.4.1 Lubricants. The reeling machine shall operate as specified herein when lubricated with military lubricants (see 6.6).

3.4.2 Filling, draining, and checking provisions. Enclosures such as gear cases and transmission housings that contain a reservoir of lubricants for the lubrication of the parts enclosed shall be equipped with dipsticks, check plugs not less than 1/2-inch pipe size, or sight gages to determine the level of the lubricant. Each enclosure shall be equipped for filling the enclosure with a lubricant and for draining. The drain outlet shall be located so that removal of the plug will result in complete drainage of the lubricant from the enclosure. Drainage shall be by gravity to a container, to preclude the drainage of lubricants to the deck of a vessel.

3.5 Identification marking. The reeling machine shall be identified in accordance with MIL-STD-130. The marking shall be applied to the reeling machine on plates conforming to MIL-P-514, Type I, Style 1, Composition C, Grade A, Class 1.

3.6 Technical publications. Such technical publications as are specified shall be furnished (see 6.2).

3.7 Government-furnished property. The following property in the quantities indicated will be furnished by the Government (see 6.4):

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

Item No.	Description	NSN Identification	Qty. for each reeling machine
1.	Engine, gasoline, air cooled, 20 BHP, Model 4A084-3	2805-00-872-5972	1
2.	Air inlet housing assembly	2805-00-B00-0461	1
3.	Can, gasoline, 5 gal	7240-00-222-3088	1
4.	Adapter assembly, fuel	2910-00-066-1235	1
5.	Toolbox, portable	5140-00-587-5558	1
6.	Battery, storage, 4 HN	6140-00-059-3528	1

3.8 Workmanship. All parts, components, and assemblies of the reeling machine, including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful extraneous material. All edges shall be rounded or chamfered.

3.8.1 Metal fabrication. Metal used in the fabrication of the reeling machine shall be free from kinks, splitting, buckling, wrinkling, and sharp bends. The straightening of material shall be accomplished by methods that will not cause injury to the metal. Shearing and chipping shall be done neatly and accurately. All burrs and rough edges shall be smooth. All bends of a major character shall be made with metal dies or fixtures to insure uniformity of size and shape.

3.8.2 Bolted connections. Boltholes for connecting members or attaching other parts shall be accurately punched or drilled and shall have burrs removed.

3.8.3 Rollers. Rollers and roller shafts shall aline with each other. Final machining of the rollers and roller shafts shall be done after fabrication to insure correct alinement.

3.8.4 Welders and welding.

3.8.4.1 Welders. Before assigning any welder to manual welding work covered by this specification and applicable drawings, the contractor shall provide the contracting officer with certification that the welder has passed qualification tests in accordance with the Standard Qualification Procedure of the American Welding Society, AWS D1.1, Structural Welding Code, Section 5, Qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

3.8.4.2 Welding. The surfaces of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loading. Welds involving corrosion-resistant steel shall be passivated and annealed.

3.8.4.3 Steel welding. Steel welding shall be done by the shield-electric-arc method in accordance with Standard Qualification Procedures of the American Welding Society or by any other method providing equivalent mechanical properties of the filler metal to base metal. Where embrittlement of the joined metal may result, preheating or annealing or both shall be employed. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part. Work shall be positioned for flat welding whenever practicable.

3.8.4.4 Rewelding defects. Portions of steel weld joints that have been rejected on inspection because of defects may be repaired only by rewelding. The defective area shall be removed by chipping or machining. Flame cutting shall be permitted. Before rewelding, the joint shall be inspected to assure that all of the defective weld has been removed and that the joint is accessible so that the welding operator can obtain full penetration through the joint.

3.9 Safety. All belts, gears, shafts, pulleys, chains and other reciprocating, rotating, or moving parts of equipment shall be graded per current OSHA general machine guarding requirements when such parts are exposed to contact by personnel or otherwise create a hazard. All points requiring lubrication during operation shall have fittings located or guarded so as to be accessible without hazardous exposure to personnel performing these operations. Nonfunctional sharp edges, projecting points, and excessive length of fastening devices shall be avoided.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined and tested in accordance with referenced specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

4.1.2 Disassembly inspection. Reeling machines failing the performance test shall be disassembled in the presence of a Government representative. Each disassembled part shall be inspected in detail for compliance of materials, dimensions and tolerances with the specification and referenced drawings. Parts not complying with such requirements shall be rejected.

4.1.3 Parts and components. Parts and components shall be inspected in accordance with the Supplementary Quality Assurance Provisions (SQAP) shown on the drawings.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of packaging (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The reeling machine shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The reeling machine shall be tested as specified in 4.5.2. Failure of the test shall be cause for performing the inspection specified in 4.1.2.

4.4 Quality conformance inspection.

4.4.1 Examination. Each reeling machine shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests. Each reeling machine shall be tested as specified in 4.5.2. Failure of test shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The reeling machine shall be examined for the following defects:

101. Materials not as specified.
102. Nonconformance to dimensions shown on the drawings.
103. Components missing or not as specified.
104. Identification marking improper, illegible, or missing.
105. Workmanship not as specified.
106. Improper assembly defects such as misalinement of bearings, gears, pulleys, chains, and belts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

4.5.2 Test. Operate the reeling machine without a reel in place. Determine whether all moving parts function properly. Mount the lift roller in each of its several mounting positions and rotate several turns by hand. Determine whether the lift roller rotates freely in each position. Then operate the reeling machine with a 56 inch reel (see 6.5) in place. Moving parts not functioning properly, inability of the lift roller to rotate by hand, or binding or permanent deformation of any part of the reeling machine when operating with a reel shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Preproduction pack inspection.

4.6.1.1 Examination. Examine the preproduction pack for the defects specified in 4.6.2.3. Presence of one or more defects shall be cause for rejection.

4.6.1.2 Test. The preproduction pack of the crated reeling machine for Level A or B shall be subjected to the railroad-car test as specified for guided-impact tests in accordance with MIL-STD-1186, Appendix A. The car shall strike a string of five empty cars with draft gear extended and the brakes set, at a speed of not less than 10 miles or more than 11 miles per hour. At the conclusion of the preproduction pack test, the pack shall be examined. Any shifting of contents, loosening or breaking of holddowns, ties, stays, blocking or bracing, or any visual damage to the components shall constitute failure of the preproduction pack and shall be cause for rejection.

4.6.2 Quality conformance inspection of pack.

4.6.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.2.3 Examination. Samples selected in accordance with 4.6.2.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

107.	Materials, methods, and containers not as specified for Level A or B.	Each incorrect material, method, or container shall constitute one defect.
108.	Unprotected surfaces not preserved as specified for Level A or B.	
109.	Engine and engine accessories not preserved in accordance with the referenced document for Level A or B.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

110. Hydraulic system not preserved as specified for Level A or B.
111. Hydraulic supply tank not filled as specified for Level A or Commercial.
112. Drive belts not removed or released from tension as specified for Level A or B.
113. Unpainted pulley grooves not coated with primer as specified for Level A or B.
114. Gear housings not preserved and tagged as specified for Level A or B or Commercial.
115. Exposed drive chains not preserved as specified for Level A or B.
116. Gasoline can not preserved as specified for Level A or B.
117. Consolidation not as specified for Level A or B.
118. Packing not as specified for Level A or B.
119. Marking missing, illegible, incorrect, or incomplete for Level A or B or Commercial.

5. PACKAGING

5.1 Preproduction pack. The contractor shall furnish a preproduction pack for examination and test within the time frame specified (see 6.2), to prove prior to starting production packaging that the applied preservation, packing, and marking comply with the preparation for delivery requirements of this specification. Examination and test shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.7). The preproduction pack may be accomplished utilizing either the preproduction reeling machine or a production reeling machine. If the preproduction model reeling machine is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government when requested by the Government to facilitate comparison between the preproduction model reeling machine and the production reeling machine.

5.2 Preservation. Preservation shall be Level A, Level B, or Commercial as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in MIL-P-116 and shall be applied in accordance with MIL-P-116.

5.2.1.2 Unprotected surfaces. Unpainted exterior metal surfaces of components such as frame, base, shafts, bolts, nuts, cable guides, pulleys, or any other unpainted exterior metal surfaces not specifically specified herein shall be coated with Type P-1 preservative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

5.2.1.3 Engine. The engine and engine accessories shall be preserved in accordance with the Level A requirements of MIL-E-10062, as specified for Type II, Method 1.

5.2.1.4 Hydraulic system. The hydraulic fluid supply tank shall be filled with the hydraulic fluid recommended for operation. The piston shall be fully retracted into the cylinder and secured. Any exposed portions of the piston rod (ramshaft) shall be coated with Type P-6 or P-11 preservative and wrapped or covered with barrier material conforming to MIL-B-121, Type I, Grade A, Class 2, extending the wrap approximately 2 inches on the ram cylinder. The wrap shall be secured in place with tape conforming to MIL-T-22085, Type I or II. The hydraulic control valve shall be secured in the neutral position. Hose shall not be disconnected. Any unpainted exterior metal surfaces of the system requiring the application of a contact preservative in accordance with MIL-P-116, shall be coated with Type P-1 preservative. A tag shall be attached indicating: "The hydraulic supply tank is filled with the fluid required for operation." The tag and the printing thereon shall be waterproofed.

5.2.1.5 Drive belts and pulleys. Drive belts shall be removed or released from tension. Unpainted surfaces of pulley grooves shall be coated with a thin film of primer conforming to TT-P-664. Belts removed shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3.

5.2.1.6 Enclosed gears. Gear housings shall be filled to the operating level with the operational lubricant and the gears actuated to assure coating of all interior parts and surfaces with the lubricant. A tag conforming to UU-T-81, Type A, shall be attached in a conspicuous location. Information on the tag shall be applied with a waterproof ink and shall indicate: "The gear housing is filled with the approved lubicant. Do not drain."

5.2.1.7 Exposed drive chains. Exposed drive chains shall be coated with enough Type P-9 preservative to insure penetration of the preservative to the inner surfaces of the rollers, pins, and bushings. After the excess preservative has drained, the entire chain shall be coated with Type P-1 preservative.

5.2.1.8 Gasoline can. The interior surfaces of the gasoline can shall be fogged with Type P-10, Grade 2, and the excess preservative drained. The can shall be placed and secured as provided for.

5.2.1.9 Technical publications. Technical publications shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3.

5.2.1.10 Consolidation. Components not attached to the reeling machine shall be consolidated together in the toolbox as space permits. When sufficient space is not available in the toolbox the additional components

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

shall be consolidated together in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional. The contents shall be blocked and braced to prevent movement or damage. Strapping of the box shall not be required.

5.2.2 Level B. Preservation shall be as specified in 5.2.1 for Level A.

5.2.3 Commercial. Each complete reeling machine and all items issued with the reeling machine shall be preserved to afford adequate protection against mechanical and physical damage. Items with critical surfaces required for fit or function shall be provided protection by the use of preservative coatings. Items with critical surfaces required for fit or function shall be provided protection by the use of preservative coatings. Items requiring protection from physical damage shall be protected by wrapping or cartonizing of the individual item. All lubrication reservoirs, sumps, etc., shall be filled to the operating level with the grade of military lubricant designated for use in the temperature range at the shipping destination. A tag shall be attached in a conspicuous location to indicate which military lubricant has been used, the temperature range of lubricant used and grade of lubricant used. A deprocessing guide shall be furnished indicating in detail the preservation materials to be removed and any other servicing required prior to placing the reeling machine in operation.

5.3 Packing. Packing shall be Level A, Level B, or Commercial as specified (see 6.2).

5.3.1 Level A. Each complete reeling machine, preserved as specified in 5.2, shall be packed in an open crate conforming to PPP-C-650, Type V, Style B. The loose or boxed components shall be secured to the reeling machine or to the crate base to prevent movement. The reeling machine shall be blocked, braced, anchored, and protected with a full shroud in accordance with the appendix to the crate specification.

5.3.2 Level B. Each complete reeling machine, preserved as specified in 5.2, shall be packed as specified in 5.3.1 except a shroud shall not be required.

5.3.3 Commercial. Each complete reeling machine, preserved as specified in 5.2, shall be packed in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.4 Marking.

5.4.1 Military. Marking for military levels of protection shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

5.4.2 Commercial. Marking for commercial packaging shall reflect as a minimum, the item name, National Stock Number, quantity, contract number, and appropriate address markings. The marking shall be applied with a waterproof material, be legible, and shall provide a definite contrast.

6. NOTES

6.1 Intended use. The reeling machine shall be used for reeling wire rope onto or from 50, 56, 78 or 84 inch diameter standard military cable reels conforming to MIL-R-10409.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model (see 3.2).
(c) When the Government will conduct any or all preproduction model examinations and tests. When the Government will conduct some but not all preproduction examinations and tests, the contracting officer should specify which examinations and tests will be conducted by the Government and which examinations and tests shall be conducted by the contractor (see 3.2).
(d) Technical publications required (see 3.7).
(e) Time frame required for submission of the preproduction pack (see 5.1).
(f) Degree of preservation and packing required (see 5.2 and 5.3).

6.3 Preproduction model. Any changes or deviations of production reeling machine from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the contractor of his obligation to furnish reeling machines conforming to this specification.

6.4 Government-furnished property. The contracting officer should arrange to furnish the property specified in 3.7.

6.5 Government-loaned property. The contracting officer should arrange to loan the property specified in 3.1 and 4.5.2.

6.6 Lubricants. The contracting officer should furnish a list of military lubricants applicable to the reeling machine covered by this specification as contained in the Federal Supply Catalog, Department of Defense Section, Identification List C9100-IL, for FSC Group 91.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

6.7 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the contractor of his obligation to preserve, pack, and mark the reeling machine in accordance with this specification.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 3895-A171

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-R-52562A(ME) Reeling Machine, Cable, Engine Driven

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:25Z
Check the source to verify that this is the current version before use.