INCH-POUND

MIL-M-13081F
AMENDMENT 3
25 October 1989
SUPERSEDING
INT. AMENDMENT 2(ME)
10 August 1988

MILITARY SPECIFICATION

MIXER, ROTARY TILLER, SOIL STABILIZATION,

SELF-PROPELLED

This amendment forms a part of MIL-M-13081F, dated 20 July 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.1, under SPECIFICATIONS, MILITARY, delete "MIL-A-8421" in its entirety and add:

"MIL-C-1283 - Can, Gasoline, Military, 5 Gallon.
MIL-T-83133 - Turbine Fuel, Aviation, Kerosene Type, Grade JP-8."

* Under STANDARDS, MILITARY, add:

"MIL-STD-1791 - Air Transportability Requirements, General Specification for.
MS53052 - Bracket Assembly, Liquid Container, 5 Gallon."

PAGE 3

* 2.2, delete AMERICAN NATIONAL STANDARD INSTITUTE/AMERICAN WELDING SOCIETY (ANSI/AWS) in its entirety and substitute:

"AMERICAN WELDING SOCIETY (AWS)

D1.1 - Structural Welding Code - Steel.

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJune Road, P. O. B ox 351040, Miami, FL 33135.)"

AMSC N/A FSC 3895
DISTRIBUTION STATEMENT A. Approved for public release,distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-18T00:02Z
Check the source to verify that this is the currenversion before use.

PAGE 7

* 3.9, line 5, after "(189.27 litre).", add "The tank shall be marked "FILL WITH DIESEL OR JP-8 FUEL ONLY.'

Line 17, after "(48.9 ^{O}C)", add: "on fuel conforming to both VV-F-800, grade DF-2 and MIL-T-83133, grade JP-8."

PAGE 10

* 3.13.6, line 2, after "diesel", add "operating on fuel conforming to both VV-F-800, grade DF-2 and MIL-T-83133, grade JP-8".

PAGE 14

* 3.29.2, line 3, delete "MIL-A-8421" and substitute "MIL-STD-1791".

*
After 3.32, add the following:

"3.33 Decontamination unit. A bracket assembly conforming to MS53052 shall be mounted by the contractor. The location of the bracket shall be such that it is accessible to personnel and provides clearance to remove and emplace a 5 gallon container conforming to MIL-C-1283. Location of the bracket assembly shall be away from heat producing sources."

PAGE 15

* 4.3.2, line 2, delete "4.5.2.19" and substitute "4.5.2.18".

* 4.4.2, line 1, delete "4.5.2" and substitute "4.5.3".

PAGE 16

* 4.5.1, after 145, add "146. Decontamination bracket not as specified."

* 4.5.2.1, lines 6 and 7, delete "diesel fuel conforming to VV-F-800 and shall be lubricated with oil conforming to MIL-L-2104" and substitute "MIL-T-83133, grade JP-8 for first article tests and either MIL-T-83133, grade JP-8 or VV-F-800, grade DF-2 for the quality conformance tests. The engine shall be lubricated with oil conforming to MIL-L-2104."

PAGE 21

After 4.5.2.18.1, add:

"4.5.3 Run in testing. Start engine and turn on all lights. Lights shall remain on for the duration of the preliminary operation. Operate the vehicle in each gear for not less than five minutes. Horn, backup alarm, and all controls shall be operated sufficiently to verify proper function. The vehicle shall be stopped from maximum speed three times in succession using service brakes. All tiller controls shall be operated sufficiently to determine proper function but not less than 10 times each.

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the current version before use.

The margins of the amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletion) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME
Navy - YD
Air Force - 99

Review activities:
Army - AT
Air Force - 84

Preparing activity:
Army - ME

Project 3895-A274

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the current version before use.