INCH-POUND

MIL-M-13081F
INT. AMENDMENT 4(ME)
14 September 1990
USED IN LIEU OF
AMENDMENT 3
25 October 1989

MILITARY SPECIFICATION

MIXER, ROTARY TILLER, SOIL STABILIZATION,

SELF-PROPELLED,

This amendment forms apart of MIL-M-13081F, dated 20 July 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.1, under SPECIFICATIONS, MILITARY, delete "MIL-A-8421" in its entirety and add:

"MIL-C-1283 - can, Gasoline, Military, 5 Gallon.
* MIL-T-62314 - Test Equipment (Simplified) for Inernal Combustion Engines Reprogramable (STE.ICE-R) Test Set.
MIL-T-83133 - Turbine Fuel, Aviation, Kerosene Type, Grade JP-8."

Under STANDARDS, MILITARY, add:

"MIL_STD-1791. - Air Transportability Requirements, General Specification for.
MS53052 -Bracket Assembly, Liquid Container, 5 Gallon."

* After 2.1.1, add:

"2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the soliciatation.

DRAWINGS

TAOOM

22250955 -Vehcile Test Card.
1 2 2 5 8 9 4 1 STE/ICE-R Diagnostic Connection.

AMSC N/A FSC 3895
DISTRIBUTION STATEMENT A. Approved for public release,distributim is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the currentversion before use.

TAOOM REPORT

CR-82-588-003 - STE/ICE Design Guide for Vehicle Diagnostic Connector."

(Copies of the drawings and the TACOM report required by contractors in connection with specific acquisition functions should be obtained from the USA Tank Automotive Command, ATTN: AMSTA-MD, Warren, MI 48397-5000.)....

PAGE 3

2.2, delete AMERICAN NATIONAL STANDARD INSTITUTE/AMERICAN WELDING SOCIETY (ANSI/AWS) in its entirety and substitute:

"AMERICAN WELDING SOCIETY (AWS)

D1.1 -Structural Welding Code-Steel.

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJeune Road, P.O. Box 351040, Miami, FL 33135.)"

PAGE 7

3.9, line 5, after "(189.27 litre).", add "The tank shall be marked "FILL WITH DIESEL OR JP-8 FUEL ONLY. "

Line 17, after "(48.9 °C)", add: "on fuel conforming to both VV-F-800, grade DF-2 and MIL-T-83133, grade JP-8."

PAGE 8

* After 3.10.4, add: , .

"3.10.5 Diagnostic connector assembly (DCA). Unless otherwise specified (see 6.2), the mixer shall incorporste an esily accessible DCA in the operator's compartment for interface with the Government's Simplified Test Equipment/Internal Combustion Enginess Reprogrammable (STE/ICE-R) specified in MIL-T-62314.All requirements for the DCA shall be in accordance with STE/ICE-R design guide far Vehicle Diagnostic Connector Assemblies, Report No. CR-82-588-003, revision 1. The DCA shall be in accordance with Drawing 12298941 and shall be labeled "Diagnostic Connector Assembly". Aa a minimum, the DCA shall be capable of monitoring the functions defined in Report No. CR-82-588-003, revision 1, table 2-2. Additional test "partameters" to be monitored in either the DCA or transducer kit (TK) mode shall be as follows: fuel return pressure, starter solenoid voltage, and transmission oil pressure. Test points identified to monitor functions in the TK mode shall be accessible with the removal of other components and installed attachments. Those additional test parametes which are inacessible for monitoring in the TK mode shall be monitored in the DCA mode. Fittings\adapters required for interface with the STE/ICE-R test set when monitring in the TK mode, shall be permanently istalled on the mixer to assure that adapters in the STE/ICE-R test set readily mate with TK mode test point locatians. A separate wiring harness shall be provided for the DCA and shall include all wiring and neccessary hardware to perform required capabilities. A fuel shut-off method shall be provided for conducting compression unbalance

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the current version before use.

checks. The contractor shall also provide STE/ICE-R vehicle test cards in the format identified in Drawing 12258955 addressing DCA and TK mode measurements and shall incorporate the test cards into the mixer technical manuals."

PAGE 10

3.13.6, line 3, after the first sentence, add "The engine shall operate on fuel conforming to both VV-F-800, grade DF-2 and MIL-T-83133, grade JP-8".

PAGE 14

3.29.2, line 3, delete "MIL-A-8421" and substitute "MIL-STD-1791".

* After 3.32, add the following:

"3.33 Decontamination unit. A bracket assembly conforming to MS53052 shall be mounted by the contractor. The location of the bracket shall be such that it is accessible to personnel and provides clearance to remove and emplace a 5 gallon container conforming to MIL-C-1283. Location of the bracket assembly shall be away from heat producing sources. The bracket assembly shall be mounted such that a soldier will not lift the container more than 3 feet to mount the container in the bracket. If necessary, a series of lifts may be used so long as no single lift requires the soldier to lift the container more than 3 feet (i.e., lift the container to the fender, climb on the fender, lift the container to the bracket). Lift height shall be measured from the bottom of the soldier's feet to the bottom of the container."

PAGE 15

4.3.2, line 2, delete "4.5.2.19" and substitute "4.5.2.18".

4.4.2, line delete "4.5.2" and substitute '4.5.3".

PAGE 16

4.5.1, after 145, add:

"146. Decontamination bracket not as specified.
147. Diagnostic connector assembly not as specified."

4.5.2.1, lines 6 and 7, delete "diesel fuel conforming to VV-F-800 and shall be lubricated with oil conforming to MIL-L-2104" and Substitute "fuel conforming to MIL-T-83133, grade JP-8 for first article tests and either MIL-T-83133, grade JP-8 or VV-F-800, grade DF-2 for the quality conformance tests. The engine shall be lubricated with oil conforming to MIL-L-2104."

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the current version before use.

* After 4.5.2.11.1, add:

"4.5.2.11.2 DCA - STE/ICE testing. The contractor shall perform a 100 percent visual inspection of all DCA wiring harnesses prior to installation on the mixer to ensure wires and connections are free of error. After installation on the mixer, test the DCA harness (reference chapter 5 of design guide for DCA) on each vehicle with a DCA tester prior to interfacing with STE/ICE. Nonconformance to 3.10.5 shall constitute failure of the DCA.

"4.5.2.11.3 DCA - STE/ICE interfaces. Upon completion of inspection and tests specified in 4.5.2.11.2, test the DCA for all measurements specified in 3.10.5 using STE/ICE. After completion of all first article testing, the test shall be repeated and the results compared to the first test performed as specified in 4.5.2. Nonconformance to 3.10.5 or failure of any component or wiring in the DCA harness, which results in inability to obtain the measurements previously recorded with the STE/ICE, shall constitute failure of this test."

After 4.5.2.18.1, add:

"4.5.3 Run in testing. Start engine and turn on all lights. Lights shall remain on for the duration of the preliminary operation. Operate the vehicle in each gear for not less than five minutes. Horn, backup alarm, and all controls shall be operated sufficiently to verify proper function. The vehicle shall be stopped from maximum speed three times in succession using service brakes. All tiller controls shall be operated sufficiently to determine proper function but not less than 10 times each. Each mixer shall be tested as specified in 4.5.2.11.2.

* "4.5.3.1 DCA - STE/ICE interface. Upon completion of inspection and tests specified in 4.5.2.11.1, test the DCA for all measurements specified in 3.10.5 using STE/ICE. Nonconformance to 3.10.5 or failure of any component of wiring in the DCA hardness which result in inability to obtain the measurementmente previously recorded with the STE/ICE shall. constitue failure of the test."

* 6.2.1, add:

"t. When DCA is not required (see 3.10.5)."

* Figure, delete figure number and title and substitute "Figure 1. Gabarit International De Chargement (GIC) clearance diagram.

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the current version before use.

a The margins of the amendment are marked with an asterik to indicate where changes (additions, modifications, corrections, deletion) from the previous amendment were made. This was done as a convenience only and the Government assures no liability whatsoever for any inaccuracies in these rotations l Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ME
Air Forcet - 99

Preparing activity:
Army - ME

Project 3895-A311

Review activities:
Army - AT
Air Force - 84

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:02Z
Check the source to verify that this is the current version before use.