MIL-T-13013E
12 July 1985
SUPERSEDING
MIL-T-13013D
29 March 1974

MILITARY SPECIFICATION

TESTER, INTERNAL COMBUSTION ENGINE

(VACUUM AND PRESSURE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope This specification covers one type of tester used for testing various vacuums and pressures of internal combustion gasoline engines in vehicles and other types of gasoline engine driven equipment.

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-C-843	- Cushioning Material, Cellulosic.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-H-13444	- Hose and Hose Assemblies, Rubber: Fuel and Oil.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, ATTN: SMCAR-ETS (R), Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards for Federal Services.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-889 - Dissimilar Metals.
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods.

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

US DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B40.1 - Gauges-Pressure Indicating Dial Type-Elastic Element.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951-82 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE).

SAE J512 - Automotive Tube Fittings.
SAE J530 - Automotive Pipe Fittings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale PA 15096-0001.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2.1), the contractor shall furnish one or more testers for first article inspection. The first article may be either a preproduction model or an initial production item which conforms to the requirements of this specification. In either case, the approved first article and the production items shall be identical and in accordance with the terms of the contract. Approval of the first article shall not relieve the contractor of the responsibility to furnish equipment in accordance with the requirements of this specification.

* 3.2 Design. The vacuum and pressure tester shall be new and of the manufacturer's latest design meeting the performance requirements specified herein. The tester shall be a portable unit consisting of a combination pressure and vacuum gage, hose, adapter set, and carrying case. The unit shall be designed for vacuum and pressure measurement testing of gasoline engines. Those parts of the tester subject to wear, breakage, or distortion shall be accessible for adjustment, repair, and replacement without modification, distortion, or damage to the tester or any tester component.

* 3.2.1 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with commercial practice within the producing industry, shall be suitable for the intended purpose in the design of the end item, and shall meet all requirements specified herein. Materials shall be free from defects which would adversely affect the performance or maintainability of the individual components or the overall assembly. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

* 3.2.2 Safety and health requirements. The tester shall comply with the general safety and health requirements promulgated under OSHA 2206 that are applicable to the tester itself. The gage case shall be a solid front, with a pressure relief back type, or an open front, with pressure relief plug or opening type, in accordance with ANSI B40.1. Exceptions and additional requirements for safety and health shall be as specified in the contract (see 6.2.1 and 6.4).

* 3.2.3 Interchangeability. All parts shall be manufactured to definite standards, clearances, and tolerances in order that any such parts of a particular type or model may be replaced, interchanged, and adjusted without modification of the replacement parts or any other parts of the unit. When practical, all parts shall be permanently and legibly marked in accordance with MIL-STD-130.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

* 3.2.4 Threads. Threads shall conform to FED-STD-H28 and the applicable Detailed Standard section referenced therein.

3.2.5 Corrosion resistance. All components shall be designed to be inherently corrosion resistant or shall be finished or treated to resist corrosion.

* 3.3 Construction. The tester shall be furnished complete so it can be used for the operations specified herein. Parts used in fabricating the tester shall be new and free of defects. All part surfaces shall be clean and free of extraneous materials. External surfaces shall be smooth and free of sharp edges. Functional surfaces shall be free from burrs and defects affecting performance.

* 3.3.1 Fastening devices. All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness and adjustment. The methods for preventing loss of tightness or adjustment shall be in accordance with accepted engineering standards and practice. All such parts when subject to removal or adjustment shall not be swaged, peened, staked, or otherwise deformed.

* 3.3.2 Welding, brazing, and soldering. Welding, brazing, and soldering shall be of a quality which shall sustain all requirements of the welded, brazed, or soldered parts. These operations shall not be employed as repair measures for defective parts.

3.4 Performance and product characteristics.

3.4.1 Accuracy. The accuracy of the pressure and vacuum indications of the tester shall be as specified in 3.4.1.1 and 3.4.1.2.

3.4.1.1 Pressure indication. The error in pressure indication of the assembled tester at +80° Fahrenheit (F) ±10°F shall not exceed 0.5 pound-force per square inch gage (psig) at any point on the scale.

3.4.1.2 Vacuum indication. The error in vacuum indication of the assembled tester at +80° ±10°F at any vacuum from 10 to 22 inches of mercury shall not exceed 1.0 inch of mercury. For the remainder of the scale, the error shall not exceed 1.5 inches of mercury.

3.4.2 Vibration. The tester and all components, when enclosed in the carrying case, shall be capable of withstanding without damage or change in accuracy (see 3.4.1) a vibration of simple harmonic motion at a frequency range of 5 to 55 hertz with a maximum amplitude of 0.031 inch (0.062 inch maximum total excursion) through each of its three major axes for a period of one hour in each axis.

3.4.3 Shock. The tester and all components, when enclosed in the carrying case, shall withstand without damage or change in accuracy (see 3.4.1) the shock resulting from being dropped on the bottom surface of the carrying case three times a vertical distance of eight inches to a concrete surface.

3.4.4 Endurance. The tester shall exhibit no failure when subjected to test runs of 2,000 operating cycles at each of the following: three and five psig and 10 and 20 inches of mercury. The error in pressure and vacuum indications at the finish of these operations shall not exceed the accuracy requirements of 3.4.1.1 and 3.4.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

* 3.4.5 Operating temperature. The tester and its components shall be capable of operation within a temperature range of -25 ±2°F to +150° ±2°F while meeting the accuracy requirements of 3.4.1.1 and 3.4.1.2.

3.5 Components. The tester shall consist of, but not be limited to, those principal components covered in 3.5.1 thru 3.5.4.

3.5.1 Gage. The gage shall be a combination vacuum and pressure, dial indicating, Bourdon tube type, with the characteristics specified in 3.5.1.1 thru 3.5.1.6.

3.5.1.1 Operating mechanism. The Bourdon tube shall be of phosphor bronze, beryllium copper, or stainless steel. The tube shall be secured in its socket by solder or shall be threaded and soldered. The Bourdon tube end opposite the socket end shall be sealed by a plug that is soldered or threaded and soldered. Only cut-tooth gears and gear segments shall be used. Means of compensation for backlash in gear tooth engagement shall be incorporated.

* 3.5.1.2 Inlet connection. The tube and other operating mechanisms of the gage shall be supported by the inlet connection which shall be securely connected to the housing in such a manner that working or twisting the housing will not cause movement of the pointer. The inlet connection shall form a pressure-vacuum tight connection with the hose.

3.5.1.3 Dial. The dial scale shall not be less than 2.5 inches in diameter, with a scale arc of not less than 270 degrees. Graduations and figures shall be black on a dull white background or white on a black background. Mechanical stops shall prevent movement beyond the ends of the scale. Unless otherwise specified (see 6.2.1), the pressure scale shall be calibrated from 0 to 8 psig, minimum, in graduations of not more than one psig. The vacuum scale shall be calibrated from at least 0 to 27 inches of mercury in minor graduations of not more than one inch of mercury, and major graduations of not more than five inches of mercury. A zero adjustment of five degrees in each direction from the zero setting shall be incorporated by either rotary adjustment of the dial or by adjustment of the pointer.

3.5.1.4 Pointer. The pointer shall be black for a dial with white background and white for a dial with black background. The pointer shall not contact the dial at any point. The clearance between the dial and pointer index shall not exceed 0.15 inch. The pointer shall be securely attached to the stem.

* 3.5.1.5 Housing. The gage housing shall be of all metal construction and shall have either a threaded or screw retained bezel to retain the crystal window. Provision shall be incorporated on the housing for hanging the gage. The housing shall be vented to the outside atmosphere.

* 3.5.1.6 Crystal. The crystal (window) shall be constructed of clear, transparent material that is impact and oil resistant.

3.5.2 Hose. The overall length of hose shall be not less than 50 inches with a nominal inside diameter of 0.25 inch. The hose shall be designed to insure a pressure-vacuum tight connection with the gage and adapters. The hose shall conform to type I of MIL-H-13444 except that the vacuum collapse test shall be performed with an internal vacuum of 27 inches of mercury with the decrease in outside diameter of the hose not exceeding 30 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

* 3.5.3 Adapter set. Unless otherwise specified (see 6.2.1), the adapter set shall consist of eight threaded adapters fabricated of free cutting brass. The mating end of the adapters shall conform to the applicable SAE standard specified below. The other end of each adapter shall be provided with an extension of sufficient length to assure a pressure type connection to a hose with an inside diameter of 0.25 inch. The adapters shall provide a pressure type seat with the mating connection on the engine. The adapters are identified in (a) and (b) below:

(a) Five adapters conforming to SAE J512 as follows:
3/8 - 24 NF-2 Inverted flared internal type
7/16 - 24 NF-2 Inverted flared internal type
1/2 - 20 NF-2 Inverted flared internal type
5/16 - 24 NF-2 Flared external type
1/2 - 20 NF-2 Flared external type

(b) Three adapters conforming to SAE J530 as follows:
1/8 - 27 NPTF (Dryseal) External type (Test of manifold)
1/4 - 18 NPTF (Dryseal) External type (Test of manifold)
3/8 - 18 NPTF (Dryseal) External type (Test of manifold)

Each adapter and each set of eight adapters shall be marked (identified) with the manufacturer's adapter part number and adapter set part number.

3.5.4 Carrying case. The carrying case shall incorporate means for holding all components of the tester in a positive, secure position within the case. The case shall be fabricated of sheet metal, not less than Manufacturer's Standard Gage No. 22 (.030 inch). The carrying case shall incorporate a carrying handle. The case lid shall provide for storage of a handbook and shall use a piano type hinge(s) and tension type fasteners. The maximum overall size of the carrying case shall not exceed nine inches in length, seven inches in width, and four inches in height.

* 3.6 Painting. Unless otherwise specified (see 6.2.1), painting and finishing shall be in accordance with the best commercial practice in the industry. Before painting, all surfaces shall be clean and be free of all foreign matter detrimental to painting. At least one coat of primer (or a phosphate or chromate base) and one coat of enamel, or equivalent (i.e., epoxy enamel), shall be applied.

3.7 Product identification. The tester shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2.1), shall include the National Stock Number.

* 3.8 Workmanship. Standards of workmanship shall assure that the tester shall have the stability, strength, safety, and efficient operating characteristics found in the best commercial units and as specified in Section 3.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract,

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 First article inspection. First article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.6 and all tests under 4.7. Failure of the first article to pass the examination or any of the tests shall be cause for rejection.

* 4.4 Quality conformance inspection. Unless otherwise specified (see 6.2.1), quality conformance inspection shall be applied to production items offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of (a) through (c) below. Failure of any item to pass an examination or test shall be cause for rejection of the item.

(a) Product examination (see 4.6).
(b) Accuracy test (see 4.7.2).
(c) Packaging inspection (see 4.8 and 4.8.1).

* 4.5 Sampling. Sampling for quality conformance inspection shall be as specified in MIL-STD-105. For product examination (see 4.6) and accuracy test (see 4.7.2), use General Inspection Level II and an Acceptable Quality Level (AQL) of 1.0 percent. For packaging inspection (see 4.8), use Special Inspection Level S-4 and an AQL of 4.0 percent.

* 4.6 Examination. Visually and manually examine the tester to determine conformance with the requirements of 3.2 through 3.2.1 and 3.2.2 through 3.8. Visual examination shall include verification of completeness of manufacture and assembly, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from defects. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the tester and its components have passed the examinations prescribed for them by the contractor's inspection system shall be cause for rejection.

4.7 Tests.

4.7.1 Operating temperature test.

* 4.7.1.1 Low ambient temperature test. The complete tester, after being in an ambient air temperature of -23° to -27°F until stabilized, and while at that temperature, shall be tested for accuracy in accordance with 4.7.2 (see 3.4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

* 4.7.1.2 High ambient temperature test. The complete tester, after being in an ambient air temperature of +148° to +152°F until stabilized, and while at that temperature, shall be tested for accuracy in accordance with 4.7.2 (see 3.4.5).

* 4.7.2 Accuracy test. The gage, hose, and an adapter shall be assembled and tested for accuracy at all graduations throughout the entire scale range by comparison with a standard air pressure measuring device having an accuracy of 0.25 percent of one percent. Accuracy of gages shall be within the range specified in 3.4.1.1 and 3.4.1.2, as applicable.

4.7.3 Vibration test. The tester and all components enclosed in the carrying case shall be rigidly mounted on a vibration machine and subjected to the vibration conditions of 3.4.2. At the conclusion of the test, the tester shall be examined for evidence of damage and tested for accuracy in accordance with 4.7.2.

4.7.4 Shock test. The tester and all components enclosed in the carrying case shall be dropped three times on the bottom surface of the carrying case to a concrete surface from a vertical height of eight inches. On conclusion of the test, the tester shall be examined for evidence of damage and tested for accuracy in accordance with 4.7.2 to determine compliance with 3.4.3.

* 4.7.5 Endurance test. The tester shall be subjected to a positive pressure of 85 percent of full scale range of the gage for three seconds and the pressure then rapidly vented to atmospheric pressure for three seconds. The tester shall then be immediately subjected to a vacuum equal to 85 percent of full scale range of the gage for three seconds and then rapidly returned to atmospheric pressure for three seconds. This shall be considered one full cycle and shall be repeated 8,000 times. Upon completion of the 8,000 cycles, the tester shall be tested for accuracy as specified in 4.7.2 (see 3.4.4).

4.8 Packaging inspection. Packaging inspection shall be conducted before and after packaging to determine compliance with the requirements of Section 5.

* 4.8.1 Packaging inspection for adapters and adapter sets. Each adapter shall be examined to determine that the manufacturer's part number is on the part. Each adapter set, consisting of the eight adapters of 3.5.3, shall be examined to determine that the manufacturer's adapter set part number has been displayed on the adapter container (see 3.5.3).

5. PACKAGING

* 5.1 Preservation. Preservation shall be Level A or Industrial. Unless otherwise specified (see 6.2.1), Industrial preservation shall be provided. When military (Level A) preservation is required, it shall be so specified in the contract.

5.1.1. Level A.

5.1.1.1 Cleaning and drying. Each component part of the tester shall be cleaned by process C-1 and dried by the most applicable procedure of MIL-P-116.

5.1.1.2 Unit packaging. All components comprising one complete tester, including technical data, shall be placed within the carrying case. Cushioning material conforming to PPP-C-843, type II, class A or B, shall be applied to control movement or damage. The carrying case lid shall be secured and the case

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

placed in a fiberboard box conforming to PPP-B-636, grade W5c. Prior to placing the carrying case in the fiberboard box, the handle, hinge(s), and fasteners of the case shall be cushioned to control movement and damage to the fiberboard box. Closure of the box shall be in accordance with the appendix to PPP-B-636.

* 5.1.2 Industrial. Industrial preservation shall be as specified in ASTM D3951-82.

* 5.2 Packing. Packing shall be Level A, Level B, or Industrial. Unless otherwise specified (see 6.2.1), Industrial packing shall be provided. When military (Levels A and B) packing is required, it shall be so specified in the contract.

5.2.1 Level A. A quantity of unit packaged testers (see 5.1.1.2) shall be packed in an exterior shipping container conforming to PPP-B-601, overseas type, or PPP-B-621, class 2. The quantity of testers and the gross weight of the container shall be governed by the limitations of the container specification. Closure and strapping of the container shall be in accordance with the applicable box specification. Blocking, bracing, and cushioning shall be in accordance with MIL-STD-1186.

* 5.2.2 Level B. Testers shall be packed as specified in 5.2.1 except the shipping containers shall conform to PPP-B-601, domestic type, PPP-B-621, class 1, or PPP-B-640, class 2.

* 5.2.3 Industrial. Industrial packing shall be as specified in ASTM D3951-82.

* 5.3 Marking. Marking shall be Level A, Level B, or Industrial. Unless otherwise specified (see 6.2.1), Industrial marking shall be provided. When military (Levels A and B) marking is required, it shall be so specified in the contract.

* 5.3.1 Level A and B marking. Level A and B marking shall be as specified in MIL-STD-129.

* 5.3.2 Industrial marking. Industrial marking shall be as specified in ASTM D3951-82. Where practicable, center of balance marking and arrow marking indicating "THIS SIDE UP" shall be applied to each shipping container.

6. NOTES.

6.1 Intended use. The testers covered by this specification are intended to be used as measurement and diagnostic devices for various pressures and vacuums generated by, or within, gasoline powered engines.

6.2 Ordering data.

* 6.2.1 Acquisition requirements. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) First article when required (see 3.1).
(c) Exceptions and additional safety/health requirements when required (see 3.2.2 and 6.4).
(d) Pressure scale calibration if different (see 3.5.1.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

(e) Adapter material if other than brass (see 3.5.3).
(f) Painting and finishing if different (see 3.6).
(g) Product identification if different (see 3.7).
(h) First article inspection if different (see 4.3).
(i) Quality conformance inspection if different (see 4.4).
(j) Level of preservation, packing, and marking if different (see 5.1, 5.2, and 5.3).

6.3 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operation and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract (see 6.3.1).

* 6.3.1 Repair part manuals. Repair part identification, in repair part manuals, shall include the prime contractor's name, nomenclature, part number, and price. Repair part identification shall also include the name of the original equipment/part manufacturer (OEM - actual part manufacturer), Federal Supply Code for Manufacturers (FSCM), nomenclature, part number, and price of the part immediately after the prime contractor's part identification. High mortality rate items shall be so identified as shown in MIL-M-7298.

* 6.4 Safety and health requirements. In order that equipment integrated into the user's operational environment will comply with OSHA limitations and control of noise levels, radiation, electromagnetic emission, noxious vapors, heat, etc., as applicable, specific requirements concerning such points of operation, and other health and safety requirements, should be specified by the user.

6.5 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - AL
Navy - YD
Air Force - 99

Review activities:

Army - ME
Air Force - 82
DLA - CS

User activities:

Army - AT
Navy - MC, OS

Preparing activity:

Army - AL

Project No. 4910-0541

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Research
and Development Center
ATTN: SMCAR-ETS (R)
Rock Island, IL 61299-7300

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-13013 E	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T23:58Z
Check the source to verify that this is the current version before use.