MILITARY SPECIFICATION

TENT, HATCH TYPE,

FIRE, WATER, WEATHER AND MILDEW RESISTANT, OLIVE DRAB

This amendment forms a part of Military Specification MIL-T-13056E(GL) dated 3 September 1970.

PAGE 3

3.2 After "Materials and components" add "(see 6.6)".

PAGE 6

Add title to 3.3.1.5 "Lubrication of thread"

Add new paragraph "3.3.1.6 Stitching margin. Unless otherwise specified, all stitching margins shall be 1/8 inch ± 1/16 inch."

PAGE 13

Table II. Delete "Stitching margin" and substitute:

Stitching margin	Larger than specified by more than 3/16 inches:	
	- for more than 2 inches but not more than 4 inches in length	Minor B
	- for more than 4 inches in length	Minor A
	Less than specified:	
	- for more than 2 inches but not more than 4 inches in length	Minor B
	- for more than 4 inches in length	Minor A

FSC 8340

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:00Z
Check the source to verify that this is the current version before use.

Add "6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification. (see 3.2)

Custodian:

Army - GL

Review activity:

Army - ME

Preparing activity:

Army - GL

Project No. 8340-A279

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:00Z
Check the source to verify that this is the current version before use.