MILITARY SPECIFICATION

CALCIUM RESINATE

This amendment forms a part of Military Specification MIL-C-20470A, 22 December 1961, and is mandatory for use by all Departments and Agencies of the Department of Defense

Page 1, section 2: Delete and substitute:

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

L-P-378—Polyethylene Film, Thin Gauge.
RR-S-366—Sieves; Standard, Testing.

MILITARY

MIL-D-3463—Desiccants, Activated, Bagged, Packaging Use and Static Dehumidification.
MIL-D-6054—Drums, Metal—Shipping and Storage.

STANDARDS

MILITARY

MIL-STD-129—Marking for Shipment and Storage.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 **Other publications.** The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issued in effect on date of invitation for bids or request for proposal shall apply.

INTERSTATE COMMERCE COMMISSION

49 CFR 71-78—Interstate Commerce Commission Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Interstate Commerce Commission regulations are now a part of the Code of Federal Regulations (1949 Edition—Revised 1950) available from the Superintendent of Documents, Government Printing Office, Washington 25, D.C. Orders for the above publication should cite "49 CFR 71-78".)

Page 5, paragraph 5.1. Delete and substitute:

5.1 **Packing.** Packing shall be level A or C, as specified (see 6.2).

5.1.1 *Level A.* Calcium resinate fused shall be packed in 16 gallon (100 lbs.) steel drums conforming to MIL-D-6054. Calcium resinate precipitated shall be packed in 55 gallon (95 lbs.) steel drums conforming to MIL-D-6054. Steel drums shall be with a full open head provided with a twist lock closure or bolted ring closure. The lid shall have a tubular rubber gasket. The drums shall be provided with a bag liner fabricated from nominal 6 ml. thick polyethylene. Polyethylene bags shall be made from plastic film conforming to Specification L-P-378, type I, finish 1. All bag seams and closure shall be heat sealed. Three units of desiccant con-

FSC 6810

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:53Z
Check the source to verify that this is the current version before use.

forming to MIL–D–3646 shall then put on top of the sealed polyethylene bag (to absorb any moisture which may be entrapped). A printed card identified with marking in accordance with MIL–STD–129 shall be inserted just before the drum is closed.

5.1.2 *Level C.* Calcium resinate fused and precipitated shall be packed in accordance with manufacturer's commercial practice to assure acceptance by common carrier for safe delivery at first destination for immediate use. Container shall comply with Interstate Commerce Commission Regulations (see Code Federal Regulations CFR 71–78) and regulations of carriers as applicable to the mode of transportation.

Custodian:
Army—MU
Navy—WP

Preparing activity:
Army—MU
Project No. 6810–0226

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:53Z
Check the source to verify that this is the current version before use.