INCH-POUND

MIL-F-20420J(AR)
AMENDMENT 1
15 JUNE 1989

MILITARY SPECIFICATION

FLARE, SURFACE, TRIP M49A1, PARTS,
AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-20420J(AR) dated 25 March 1983 and is approved for use within the U.S. Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Add new paragraph 2.2 as follows:

"Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM - B117 "STANDARD METHOD OF SALT SPRAY (FOG) TESTING"

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)"

PAGE 20, 21 and 23

Delete in its entirety and substitute new page 20, 21 and 23 attached.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:46Z
Check the source to verify that this is the current version before use.

4.4.3.7: Delete paragraph in its entirety and substitute the following:

"4.4.3.7 Protective coating (salt-spray) test of clip, safety assembly (dwg. 8836958), lever (dwg. 8836961), cover (dwg. 8836965), striker assembly (dwg. 8836971), pivot, trigger (dwg. 8836974), spring, trigger (dwg. 8836975), washer, trigger (dwg. 8836977), spring striker (dwg. 8864755), and spool retainer - major defects. Testing shall be performed after application of all specified protective finishes. The Salt Spray Test shall be conducted in accordance with ASTM B117, "Standard Method of Salt Spray (Fog) Testing," for a period of 96 hours. To secure uniformity of test results, all test samples shall be aged at room temperature for 24 hours before being subjected to the Salt Spray. A quantity of four parts from each production lot shall be used as the test samples in lieu of specimens. The salt spray tested samples shall show no evidence of white corrosion products (if cadium or zinc is present) or base metal corrosion products at the end of the 96 hour test. The appearance of corrosion products (visible to the unaided eye at normal reading distance) on one or more the test samples shall be cause for rejection, except that corrosion products at the edge of an unprotected area shall not be cause for rejection."

Source: https://assist.dla.mil -- Downloaded: 202640-19T07:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Spring, Striker	1 OF 1	8864755
			NEXT HIGHER ASSEMBLY: 8836957, 9288866 or ~~9313553~~

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Embrittlement of spring	10	0-1	3.3	4.5.1
102	Torque test	50	0-1	3.2	4.5.8
103	Protective coating test	4.4.3.7	4.4.3.7	3.2	4.4.3.7
Minor					
201	Outside diameter	1/	0.65%	3.2	Gage
202	Length over long leg	1/	0.65%	3.2	Gage
203	Length of long leg hook		0.65%	3.2	Gage
204	Diameter of wire (before forming and plating)		0.65%	3.2	Gage
205	Length over short leg	1/	0.65%	3.2	Gage
206	Length from long leg to short leg		0.65%	3.2	Gage
207	Length over bend of short leg	1/	0.65%	3.2	Gage
208	Length of short leg hook		0.65%	3.2	Gage
209	Overall length	1/	0.65%	3.2	Gage
210	Poor workmanship		1.00%	3.8	Visual

NOTES: 1/ See paragraph 4.5.13 for alternate method of dimensional control.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:46Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Safety Clip Assembly		8836958
			NEXT HIGHER ASSEMBLY
			8836957, 9288866 or 9313553

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of wire (prior to forming and plating)		0.40%	3.2	Gage
102	Crack		0.40%	3.2	Visual
103	(Deleted)				
104	Irregular plating of pull pin		0.40%	3.2	Visual
105	Safety clip assembly spring test	4.4.3.5	4.4.3.5	3.2	4.5.7
106	Protective coating test	4.4.3.7	4.4.3.7	3.2	4.4.3.7
Minor					
201	Length from bend to end, min.		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Pull pin incorrectly assembled		0.65%	3.2	Visual
204	Width at closed end improper		0.65%	3.2	Gage
205	Spring clip safety missing or mislocated		0.65%	3.2	Visual
206	Poor workmanship		1.00%	3.8	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-19T07:46Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Spring, Trigger				8836975
					NEXT HIGHER ASSEMBLY 8836973
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Embrittlement of spring	10	0-1	3.3	4.5.1
102	Spring wound improperly		0.40%	3.2	Visual
103	Protective coating test	4.4.3.7	4.4.3.7	3.2	4.4.3.7
Minor					
201	Inside diameter of spring	1/	0.65%	3.2	Gage
202	Inside diameter of loop, max		0.65%	3.2	Gage
203	Distance from loop centerline to tangent of free end (free state)		0.65%	3.2	Gage
204	Width of spring center to loop center		0.65%	3.2	Gage
205	Length of free leg to spring center	1/	0.65%	3.2	Gage
206	Width of free end	1/	0.65%	3.2	Gage
207	Entire loop not flat		0.65%	3.2	Gage
208	Diameter of wire		0.65%	3.2	Gage
209	Poor workmanship		0.65%	3.8	Visual

NOTES:
1/ See paragraph 4.5.13 for alternate method of dimensional control.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:46Z
Check the source to verify that this is the current version before use.

PAGE 47

4.5.4.2: Add new last sentence: "Pull pin force shall be recorded for information only."

PAGE 50

Add the following paragraph:

"4.5.13 Dimensional control of formed parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts shall be dimensionally inspected to qualify the tool used in the forming process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each day's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project: 1370-A 287)

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:46Z
Check the source to verify that this is the current version before use.