MILITARY SPECIFICATION

Fuze, Base Detonating, M91A2

Loading, Assembling & Packing

This amendment forms a part of Military Specification MIL-F-20423D(PA) dated 11 March 1976.

Page 3

Paragraph 3.9, Delete in its entirety and substitute:

"3.9 Static Functioning: The fuze shall function high order as evidenced by a minimum depth depression of 0.115 inches in a steel plate where tested as specified in 4.4.6.1."

Page 10

Paragraph 4.3.3.7.1, Delete the first sentence and substitute the following:

"A sample of fifteen (15) fuzes shall be randomly selected from each lot for this test subsequent to completion of the slider non-arming test."

Page 14

Paragraph 4.4.6.1, Delete in its entirety and substitute the following:

"4.4.6.1 Static - The slider shall be armed and fully aligned by inserting a plug into the slider cavity in the fuze body and reassembling the slider, slider spring and retaining screw. The retaining screw is to be seated and staked into place. The fuze samples are then to be assembled as per dwg. 8837308 except for the percussion plunger assembly and head. A centrally located ½" hole is to be drilled through the head. The percussion plunger assembly is to be armed. These two components together with the restraining spring are to be assembled to the armed body assembly.

A shear wire and plug assembly is to be used to detonate the explosive train. The plug, approsimately 3/8" diameter, is to be mounted so that the shear wire on top of the tracer cavity supports the plug above the percussion plunger assembly.

This modified fuze assembly shall be placed booster end down upon a steel plate (approx. 14" x 18" x 2" in accordance with ASTM836. Rockwell B60-80). A weight shall then be dropped on the plug in such a manner as to shear the wire and detonate the fuze. If the fuze fails to function all personnel will wait behind the barricade for a period of 30 minutes minimum prior to returning to the test sample. The fuze shall then be destroyed in



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:47Z
Check the source to verify that this is the current version before use.

place (in accordance with local safety regulations) by means of a demolition charge, taking extreme care when placing the charge not to disturb the fuze in any way. Any fuze which fails to function high order as evidenced by an improper dent depth shall be cause for rejection of the lot."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1390-A210



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:47Z
Check the source to verify that this is the current version before use.