MILITARY SPECIFICATION

GRENADE, RIFLE, SMOKE, COLORED, M22A2
LOADING, ASSEMBLING, MARKING AND PACKING

This amendment forms a part of Military Specification MIL-G-20473B (MU), dated 7 August 1966 and is approved for use by the US Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following Preamble underneath the title:

"This specification is approved by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

2.1, Standards, Military: Add "MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For."

PAGE 2

2.2: Add the following new paragraph:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

TECP 700-700, Interim Pamphlet 70-73 - US Army Test and Evaluation Command Material Test Procedure.

(Application for copies should be addressed to Headquarters, US army Test and Evaluation Command, Aberdeen Proving Ground, Maryland 21005.)"

o U.S. GOVERNMENT PRINTING OFFICE: 1981—505-022/8229

FSC: 1330

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:53Z
Check the source to verify that this is the current version before use.

Add the following new paragraphs, 3.7, 3.7.1, 3.7.2, 3.7.3, 3.4.7, 3.7.5, and 3.7.6 as follows:

"3.7 Initial production tests. The following tests shall be performed at a Government Proving Ground on samples selected by the Government inspector from the first production lot.

3.7.1 Jumble. The assembly shall comply with the requirements of MIL-STD-331 when tested as specified in 4.4.4.1.

3.7.2 Forty (40) foot drop. The assembly shall comply with the requirements of MIL-STD-331 when tested as specified in 4.4.4.2.

3.7.3 Five (5) foot drop. The assembly shall comply with the requirements of MIL-STD-331 when tested as specified in 4.4.4.3.

3.7.4 Transportation vibration. The assembly shall not function during the test, and shall be safe to handle and operable after the test specified in 4.4.4.4.

3.7.5 Temperature humidity. The assembly shall be safe to handle and operable after the test specified in 4.4.4.5.

3.7.6 Packaged rough handling. The assembly shall comply with the requirements of MIL-STD-331 when tested as specified in 4.4.4.6."

PAGE 4

4.2.3: Delete in its entirety and substitute the following:

"4.2.3 Rejection. The first article sample shall be rejected if a critical or special defect occurs (see 6.5), or if two (2) or more samples exhibit any major defect".

PAGE 6

4.3.3.1, Table I, Stabilizer tube failure: Delete "Critical" classification and substitute "Special" classification.

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:53Z
Check the source to verify that this is the current version before use.

4.3.3.1.1, second sentence: Delete in its entirety and substitute the following:

"The lot shall be rejected if, during the test, a critical or special defect occurs, or if four (4) or more assemblies exhibit any of the major defects listed in Table 1".

4.3.3.1.2, second sentence: Delete in its entirety and substitute the following:

"The lot shall be rejected if, during the test, a critical or special defect occurs, or if the number of major defects exceeds the limits of the sampling plan."

4.3.3.4: Add the following new paragraph:

"4.3.3.4 Initial production tests. These tests (see Table III) shall be performed on samples selected from the first production lot. All results shall be recorded for information and subsequent determination. In the event a Critical defect occurs, the production lot shall be rejected. The test shall be performed as specified in the applicable paragraph in 4.4.4.

TABLE III

Defect	No. of Samples	Classification	Code No.
Jumble safety failure (see 3.7.1)	13	Critical	08001
Forty foot drop safety failure (see 3.7.2)	13	Critical	09001
Five foot drop safety failure (see 3.7.3)	13	Critical	10001
Failure to function after test (see 3.7.3)		Major	10002

Source: https://assist.dla.mil -- Downloaded: 202610-19T07:53Z
Check the source to verify that this is the current version before use.

Defect	No. of Samples	Classification	Code No.
Transportation vibration safety failure (see 3.7.4)	30	Critical	11001
Failure to function after test (see 3.7.4)		Major	11002
Temparature humidity safety failure (see 3.7.5)	32	Critical	12001
Failure to function after test (see 3.7.5)		Major	12002
Packaged rough handling safety failure (see 3.7.6)	30	Critical	14001
Failure to function after test (see 3.7.6)."		Major	14002

PAGE 7

Add new paragraphs, 4.4.4, 4.4.4.1, 4.4.4.2, 4.4.4.3, 4.4.4.4, 4.4.4.5, and 4.4.4.6 as follows:

"4.4.4 Initial production tests. The following tests shall be performed at a Government Proving Ground in accordance with the methods and procedures indicated. All results shall be documented for subsequent evaluation.

4.4.4.1 Jumble. The test shall be performed as specified in Method 102 of MIL-STD-331. The assembly shall be examined after the test to determine compliance with the requirements.

4.4.4.2 Forty foot drop. The test shall be performed as specified in Method 103 of MIL-STD-331, except that the rifle grenade in the ammunition container shall be dropped. The assembly shall be examined after the test to determine compliance with the requirements.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T07:53Z
Check the source to verify that this is the currentversion before use.

4.4.4.3 Five foot drop. The test shall be performed as specified in Method 111 of MIL-STD-331. The assembly, after test, shall be examined visually and any damage recorded. If no damage affecting safety or operability is apparent, the assembly shall be functioned as specified in 4.4.1 and observed for compliance with the requirements.

4.4.4.4 Transportation vibration. The assemblies completely packed in container and box shall be subjected to the fifteen (15) minute simulated two wheel ground vehicle vibration environment and the three (3) hour aircraft vibration test specified in TECP 700-700, Interim Pamphlet 70-73, dated 5 August 1966. After test, the assemblies shall be unpacked, visually examined and any damage recorded. If no deterioration affecting safety or operability is apparent, the assembly shall be functioned as specified in 4.4.1 and observed for compliance with the reqirements.

4.4.4.5 Temperature humidity. The test shall be performed as specified in Method 105 of MIL-STD-331, except that the rifle grenade shall be packed in the ammunition container during the test and a temperature of minus forty-five (45) degrees Fahrenheit (F.) shall be used in lieu of minus sixty-five (65) degrees F. After test the assembly shall be unpacked, visually examined, and any deterioration recorded. If no deterioration affecting safety or operability is apparent, the assembly shall be functioned as specified in 4.4.1 and observed for compliance with the requirements.

4.4.4.6 Packaged rough handling. The test shall be performed as specified in Method 114 of MIL-STD-331. After test, the assemblies shall be unpacked, visually examined, and any damage recorded. If no damage affecting safety or operability is apparent, the assemblies shall be functioned as specified in 4.4.1 and observed for compliance with the requirements."

PAGE 9

6.5: Add the following new paragraph:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:53Z
Check the source to verify that this is the current version before use.

"6.5 Special defect. A special defect is defined as a defect that judgement and experience indicate could, depending on the degree of variance from the design requirement, result in hazardous or unsafe conditions for individuals using, maintaining or depending upon the product."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1330-A166

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:53Z
Check the source to verify that this is the current version before use.