INCH-POUND

MIL-A-27330B(USAF)
AMENDMENT 1
30 MARCH 1994

MILITARY SPECIFICATION

ACCELEROMETER, ELECTRICAL, LINEAR TRU-3/A

This amendment forms part of MIL-A-27330B(USAF), dated 25 March 1987, and is approved for use by the Department of the Air Force and is available for the use by all Departments and Agencies of the Department of Defense.

PAGE 1

Under SPECIFICATIONS, Federal, delete "PPP-B-601", "PPP-B-636" and add: "PPP-B-1762 Boxes, Shipping Reuasble With Cushioning".

Under SPECIFICATIONS, Military, add: "MIL-B-121 Barrier Material Greasedproofed, Flexible".

Under STANDARDS add: "Federal" and under Federal add: "FED-STD-101, Preservation, Pakaging And Packing Materials: Test Procedures".

Under benefical comments block line delete: "MMEDO'; " 5990" and add: "TICLA" and "3037".

PAGE 2

DISTRIBUTION STATEMENT. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:36Z
Check the source to verify that this is the current version before use.

Under STANDARDS, Military, delete "MIL-STD-794" entirely and change "MIL-STD-143" to "MIL-STD-970". Add: "MIL-STD-2073-1 DOD Material Procedures For the Department And Application of Packaging Requiremnts".

2.2 Delete entirely.

3.2 Line 3 delete "MIL-STD-143" and add: "MIL-STD-970".

PAGE 15

Delete "section 5" entirely and new:

" 5. PACKAGING
5.1 Preservation. Preservation shall be level "A" or "C" as specified (see 6.2).

5.1.1 Preservation-packaging. Unless otherwise specified by the contracting activity, item shall be packaged in Quantity Unit Pack(QUP) of one each. Each item will be provided a preservation method IIc In Accordance With(IAW)

5.1.2 Cleaning. Item shall be cleaned IAW MIL-P-116 C-1 process.

5.1.3 Drying. Immediately after cleaning, the item shall be dried following any one or combination of the drying procedures listed in MIL-P-116. The drying procedures employed shall not be injurious to the item.

5.1.4 Level A. Item shall be preserved IAW MIL-P-116 and MIL-STD-2073-1 to provide a method IIc.

5.1.5 Level C. Item shall be individually preserved in a manner that will afford adequate protection against corrision, deterioration, and physical damage during shipment from the supply source to the first receiving activity as specified in MIL-P-116 and MIL-STD-2073-1.

5.2 Packing. Packing shall be level "A', "B", or "C", as specified(see 6.2)

PAGE 16

5.2.1 Container-cushioning. Unit container requirements shall conform to MIL-B-131, barrier material, unless otherwise specified by the contracting activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:36Z
Check the source to verify that this is the current version before use.

Unit container shall be large enough to allow for the apllication of cushioning/warp material, of sufficient density and thickness, to protect from puctures. Intermediate/shipping containers shall be large enough to allow for the application of sufficient cushioning material, between the unit container and immediate/shipping container. Cushioning between the unit container material shall be of sufffiecient density and thickness to insure shock transmission does not exceed peak value in G's established for the item.

5.2.2 Level A. Fiberbooard containers do not meet Level "A" container criteria.

5.2.3 Level B. Item will be preserved as specified in 5.1 and shall be packed in exterior containers conforming to PPP-B-1672, weather-resistant unless otherwise specified by the contracting activity. Exterior container shall be uniform shape, size and minmum tare and cube, consistent with the protection required. Closure shall be in accordance with appropriate PPP-B-1672 procedure, as specified by Special Packaging Instructions(SPI) and contracting activity.

5.2.4 Level C. Item will be packed in such a manner that will afford adequate protection against physical damage during domestic shipment from the supply source to the first receiving activity. These packs conform to MIL-STD-2073-1.

5.3 Marking. Unit, intermediate, and exterior containers shall be marked IAW special markings required by the contracting activity, SPI and MIL-STD-129.

5.4 Inspection and Test. Test of methods of preservation shall be accomplished IAWsection 4 of MIL-P-116 to insure compliance with section 5 of this specification. Packaging test shall be conducted IAW rough handling as specified in FED-STD-101.

Under 6. NOTES add:"(This section contains information of general or explanatory nature thst may be helpful, but is not mandatory.)"

6.2 Delete Line 1 entirely and add: "Acquistion requirements. Acquistions documents must specify the following:".

Add: 6.2e Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced(see 2.1)."

Custodian:
Air Force-99

Preparing Activity:
Air Force-71

Project Number:
6610-F382

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:36Z
Check the source to verify that this is the current version before use.