The documentation and process conversion measures necessary to comply with this document shall be completed by 30 October 2023.

INCH-POUND

MIL-PRF-19500/368N
w/AMENDMENT 3
28 July 2023
SUPERSEDING
MIL-PRF-19500/368N
w/AMENDMENT 2
19 July 2021

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW-POWER
TYPES: 2N3439, 2N3439L, 2N3439UA, 2N3439U4, 2N3439UB, 2N3440, 2N3440L, 2N3440UA, AND 2N3440U4, 2N3440UB, JAN, JANTX, JANTXV, JANS, JANHC, JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN, silicon, low-power, high voltage transistors. Four levels of product assurance are provided for each encapsulated device types as specified in MIL-PRF-19500, and two levels of product assurance for each unencapsulated device type die. RHA level designators “M”, “D”, “P“, “L”, “R”, “F”, “G”, and “H” are appended to the device prefix to identify devices, which have passed RHA requirements.

* 1.2 Physical dimensions. The device package for the encapsulated device type are as follows: Three terminal round metal can modified TO-205AA (formerly similar to TO-5) and modified TO-205-AD (formerly similar to TO-39) in accordance with figure 1, surface mount version (UA) in accordance with figure 2, surface mount version (U4) in accordance with figure 3 and surface mount version (UB, UBC) in accordance with figure 4. The dimensions and topography for JANHC and JANKC unencapsulated die are as follows: The B version die in accordance with figure 5, C version die in accordance with figure 6, and D version die in accordance with figure 7.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C.

Types	P_T (1) T_A = +25°C	P_T (2) T_C = +25°C	P_T (2) T_{SP} = +25°C	$R_{\theta JA}$ (3)	$R_{\theta JC}$ (3)	$R_{\theta JSP}$ (3)	V_{CBO}	V_{EBO}	V_{CEO}	I_C	T_{STG} and T_J
	W	W	W	°C/W	°C/W	°C/W	V dc	V dc	V dc	A dc	°C
2N3439	0.8	5.0	N/A	175	30	N/A	450	7	350	1.0	-65 to +200
2N3439L	0.8	5.0	N/A	175	30	N/A	450	7	350	1.0	
2N3439UA	0.8	N/A	2.0	175	N/A	70	450	7	350	1.0	
2N3439U4	0.8	5	N/A	175	8	N/A	450	7	350	1.0	
2N3439UB, UBC	0.5	N/A	1.5	175	N/A	90	450	7	350	1.0	
2N3440	0.8	5.0	N/A	175	30	N/A	300	7	250	1.0	
2N3440L	0.8	5.0	N/A	175	30	N/A	300	7	250	1.0	
2N3440UA	0.8	N/A	2.0	175	N/A	70	300	7	250	1.0	
2N3440U4	0.8	5	N/A	175	8	N/A	300	7	250	1.0	
2N3440UB, UBC	0.5	N/A	1.5	175	N/A	90	300	7	250	1.0	

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil . Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

1.3 Maximum ratings. Unless otherwise specified, T_A = +25°C. Continued.
(1) For derating, see figure 8.
(2) For derating, see figure 9, figure 10, figure 11, and figure 12.
(3) For thermal impedance curves see, figure 12, figure 13, figure 14, figure 15, and figure 16.

1.4 Primary electrical characteristics. Unless otherwise specified T_A = +25°C.

	h_{FE2} (1) V_{CE} = 10 V dc I_C = 2 mA dc	h_{FE1} (1) V_{CE} = 10 V dc I_C = 20 mA dc	$\|h_{fe}\|$ V_{CE} = 10 V dc I_C = 10 mA dc f = 5 MHz	C_{obo} V_{CB} = 10 V dc I_E = 0 100 kHz ≤ f ≤ 1 MHz	$V_{BE(sat)}$ (1) I_C = 50 mA dc I_B = 4 mA dc	$V_{CE(sat)}$ I_C = 50 mA dc I_B = 4 mA dc
				pF	V dc	V dc
Min	30	40	3			
Max		160	15	10	1.3	0.5

(1) Pulsed, (see 4.5.1).

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.5 for PIN construction example and 6.6 for a list of available PINs.

1.5.1 JAN certification mark and quality level designators.

1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", “JANTXV”, and "JANS".

1.5.1.2 Quality level designators for unencapsulated devices (die). The quality level designators for unencapsulated devices (die) that are applicable for this specification sheet from the lowest to the highest level are as follows: "JANHC" and "JANKC".

1.5.2 Radiation hardness assurance (RHA) designator. The RHA levels that are applicable for this specification sheet from lowest to highest for JANS quality levels are as follows: "M", "D", "P", "L", “R”, “F’, “G”, and “H”.

1.5.3 Device type. The designation system for the device types covered by this specification sheet are as follows.

1.5.3.1 First number and first letter symbols. The semiconductors of this specification sheet use the first number and letter symbols "2N".

1.5.3.2 Second number symbols. The second number symbols for the semiconductors covered by this specification sheet are as follows: "3439" and “3440”.

1.5.4 Suffix symbols. The following suffix letters are incorporated in the PIN for this specification sheet for encapsulated devices.

	A blank first suffix symbol indicates a TO-205AD package. (See figure 1, TO-205AD).
L	An L first suffix symbol indicates a TO-205AA package. (See figure 1, TO205AA)
UA	Indicates a 4 pad surface mount package, (see figure 2)
U4	Indicates a 3 pad surface mount package, (see figure 3)
UB	Indicates a 3 pad surface mount package, (see figure 4)
UBC	Indicates a 3 pad surface mount package with a ceramic lid, (see figure 4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

1.5.5 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

* 1.5.6 Die identifiers for unencapsulated devices (manufacturers and critical interface identifiers). The manufacturer die identifiers that are applicable for this specification sheet is “B”, “C”, and “D”.

* 1.6 Radiation features. The following radiation features are applicable for RHA devices supplied to this specification sheet.

* 1.6.1 Maximum total ionizing dose (TID). The maximum TID that RHA devices were tested to in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of MIL-STD-750 are as follows:

For device type 2N3439, 2N3439L, 2N3439UA, 2N3439U4, 2N3439UB, 2N3439UB: .....100 krads(Si) 1/

For device type 2N3440, 2N3440L, 2N3440UA, 2N3440U4, 2N3440UB, 2N3440UB: .....100 krads(Si) 1/

* 1/ The manufacturers supplying these device types have performed characterization testing in accordance with condition A (dose rate = 50 to 300 rad(Si)/s) of method 1019 of MIL-STD-750. The radiation end point limits are guaranteed only to a maximum TID level of 100 krads(Si).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS


MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Note
	In	In	mm	mm	
	Min	Max	Min	Max	
CD	.305	.335	7.75	8.51	6
CH	.240	.260	6.10	6.60	
HD	.335	.370	8.51	9.40	
LC	.200	TP	5.08	TP	7
LD	.016	.019	0.41	0.48	8,9
LL		See	note	13	
LU	.016	.019	0.41	0.48	8,9
L_1		.050		1.27	8,9
L_2	.250		6.35		8,9
P	.100		2.54		7
Q		.030		0.76	5
TL	.029	.045	0.74	1.14	3,4
TW	.028	.034	0.71	0.86	3
r		.010		0.25	10
α	45°	TP	45°	TP	7




* NOTES:

1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Beyond r (radius) maximum, TW shall be held for a minimum length of .011 (0.28 mm).
4. Dimension TL measured from maximum HD.
5. Body contour optional within zone defined by HD, CD, and Q.
6. CD shall not vary more than .010 inch (0.25 mm) in zone P. This zone is controlled for automatic handling.
7. Leads at gauge plane .054 +.001 -.000 inch (1.37 +0.03 -0.00 mm) below seating plane shall be within .007 inch (0.18 mm) radius of true position (TP) at maximum material condition (MMC) relative to tab at MMC. The device may be measured by direct methods or by gauging procedure.
8. Dimension LU applies between L_1 and L_2. Dimension LD applies between L_2 and LL minimum. Diameter is uncontrolled in L_1 and beyond LL minimum.
9. All three leads.
10. The collector shall be internally connected to the case.
11. Dimension r (radius) applies to both inside corners of tab.
12. Lead 1 = emitter, lead 2 = base, lead 3 = collector.
13. For transistor types 2N3439L and 2N3440L (TO-205AA), dimension LL = 1.5 inches (38.10 mm) min. and 1.75 inches (44.45 mm) max. For transistor types 2N3439 and 2N3440 (TO-205AD), dimension LL = .5 inch (12.70 mm) min. and .750 inch (19.05 mm) max.

FIGURE 1. Physical dimensions modified TO-205AA and TO-205AD (formerly similar to TO-5 and TO-39).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Note
	In	In	mm	mm	
	Min	Max	Min	Max	
BL	.215	.225	5.46	5.71	
BL2		.225		5.71	
BW	.145	.155	3.68	3.93	
BW2		.155		3.93	
CH	.061	.075	1.55	1.90	3
L3	.003		0.08		5
LH	.029	.042	0.74	1.07	
LL1	.032	.048	0.81	1.22	
LL2	.072	.088	1.83	2.23	
LS	.045	.055	1.14	1.39	
LW	.022	.028	0.56	0.71	
LW2	.006	.022	0.15	0.56	5

Pin no.	1	2	3	4
Transistor	Collector	Emitter	Base	N/C

* NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Dimension "CH" controls the overall package thickness. When a window lid is used, dimension "CH" must increase by a minimum of .010 inch (0.254 mm) and a maximum of .040 inch (1.020 mm).
4. The corner shape (square, notch, radius, etc.) may vary at the manufacturer's option, from that shown on the drawing.
5. Dimensions "LW2" minimum and "L3" minimum and the appropriate castellation length define an unobstructed three-dimensional space traversing all of the ceramic layers in which a castellation was designed. (Castellations are required on bottom two layers, optional on top ceramic layer.) Dimension "LW2" maximum define the maximum width and depth of the castellation at any point on its surface. Measurement of these dimensions may be made prior to solder dipping.
6. The coplanarity deviation of all terminal contact points, as defined by the device seating plane, shall not exceed .006 inch (0.15mm) for solder dipped leadless chip carriers.

FIGURE 2. Physical dimensions, surface mount (2N3439UA, 2N3440UA) version.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions			
	In	In	mm	mm
	Min	Max	Min	Max
BL	.215	.225	5.46	5.72
BW	.145	.155	3.68	3.94
CH	.049	.075	1.24	1.91
LH		.020		0.51
LW1	.135	.145	3.43	3.68
LW2	.047	.057	1.19	1.45
LL1	.085	.125	2.16	3.17
LL2	.045	.075	1.14	1.90
LS1	.070	.095	1.78	2.41
LS2	.035	.048	0.89	1.21
Q1	.030	.070	0.76	1.78
Q2	.020	.035	0.51	0.89
1	Collector			
2	Base			
3	Emitter			

* NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Terminal 1 is collector.
4. Terminal 2 is base.
5. Terminal 3 is emitter.

FIGURE 3. Physical dimensions, surface mount (2N3439U4, 2N3440U4) version (U4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Notes	Symbol	Dimensions				Note
	In	In	mm	mm			In	In	mm	mm	
	Min	Max	Min	Max			Min	Max	Min	Max	
BL	.115	.128	2.92	3.25		LL2	.009	.036	0.23	0.89	6
BW	.085	.108	2.16	2.74		LS_1	.035	.040	0.89	1.02	
BH	.040	.056	1.02	1.42	4	LS_2	.071	.079	1.80	2.01	
BH	.055	.069	1.40	1.75	5	LW	.016	.024	0.41	0.61	6
CL		.128		3.25		r		.008		0.20	
CW		.108		2.74		r1		.012		0.30	7
LL1	.022	.038	0.56	0.97	6	r2		.022		0.56	

* NOTES:
1. Dimension are in inches. Millimeters are given for general information only.
2. Hatched areas on package denote metallized areas.
3. Pad 1 = Gate, 2 = Source, 3 = Drain, 4 = shielding connected to the lid (UB only) or lid braze (UBC only)
4. Dimension BH for UB packages with metal lid.
5. Dimension BH for UBC packages with ceramic lid.
6. Three places
7. For design reference only.

FIGURE 4. Physical dimensions for UB and UBC style surface mount package.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




1.	Chip size.....	.049 x .057 inch ±.002 inch (1.24 mm x 1.45 mm ±0.05 mm).
2.	Chip thickness.....	.010 ± .0015 inch nominal (0.254 mm ±0.038 mm).
3.	Top metal.....	Aluminum 15,000Å minimum, 18,000Å nominal
4.	Back metal.....	A. Al/Ti/Ni/Ag 12kÅ/3kÅ/7kÅ/7kÅminimum,15kÅ/ 5kÅ/10kÅ/10kÅ nominal. B. Gold 3,500Å minimum, 5,000Å nominal.
5.	Backside.....	Collector.
6.	Bonding pad.....	B = .005 x .008 inch (0.127 mm x 0.203 mm). E = .010 x .007 inch (0.254 mm x 0.178 mm).

* NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.

FIGURE 5. Physical dimensions JANHCB and JANKCB (die) B versions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




Chip size.....0.045 x 0.045 inch ±0.002 inch (1.143 x 1.143 mm ±0.051mm)
Chip thickness.....0.008 ±0.0005 inch (0.203 ±0.0127mm)
Top metal .....Aluminum 17,500 Å minimum; 20,000 Å nominal
Back metal .....Gold 5,000 Å minimum; 6,500 Å nominal
Backside.....Collector
Bonding pads .....B = 0.008 x 0.005 inch (0.203 x 0.127mm)
E = 0.011 x 0.005 inch (0.279 x 0.127mm)

* NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.

FIGURE 6. Physical dimensions JANHCC and JANKCC (die) C versions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.



Chip size.....0.042 x 0.042 inch ±0.002 inch (1.067 x 1.067 mm ±0.051mm)
Chip thickness.....0.008 ±0.002 inch (0.203 ±0.051mm)
Top metal .....Aluminum 36,000 Å minimum; 40,000 Å nominal
Back metal .....Gold 10,000 Å minimum; 12,500 Å nominal
Backside.....Collector
Bonding pads .....B = 0.006 x 0.006 inch (0.152 x 0.152mm)
E = 0.009 x 0.0055 inch (0.229 x 0.139mm)

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.

* FIGURE 7. Physical dimensions JANHCD and JANKCD (die) D versions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML-19500) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

$R_{\theta JA}$	Thermal resistance junction to ambient.
$R_{\theta JC}$	Thermal resistance junction to case.
$R_{\theta JSP}$	Thermal resistance junction to solder pads.
UA	Surface mount case outlines (see figure 2).
TRB	Technical review board.
T_{SP}	Temperature of solder pads.

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 modified TO-205AA and TO-205AD (formerly similar to TO- 5 and TO-39), figure 2 (UA) surface mount, figure 3 (U4), and figure 4 (UB, UBC) surface mount, figure 5 (JANHCB and JANKCB (B versions)) figure 6 (JANHCC and JANKCC (C versions)), and figure 7 (JANHCD and JANKCD (D versions)).

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.5 Radiation hardness assurance (RHA). Radiation hardness assurance requirements, PIN designators, and test levels shall be as defined in MIL-PRF-19500.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I herein.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

3.8 Marking. Marking shall be in accordance with MIL-PRF-19500, except for the UB, and UBC suffix packages. Marking on the UB, and UBC packages shall consist of an abbreviated part number, the date code, and the manufacturer's symbol or logo. At the option of the manufacturer, marking may be omitted from the body, but shall be retained on the initial container. The radiation hardened designator M, D, P, L, R, F, G, or H shall immediately precede (or replace) the device "2N" identifier (depending upon degree of abbreviation required).

3.9 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I, table II, and table III).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and table III herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table III tests, the tests specified in table III herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

4.3 Screening (JANS, JANTXV, and JANTX levels only). Screening shall be in accordance with MIL-PRF-19500 and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANS level	Measurements for JANTX and JANTXV levels
(1) 3c	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.3)	Thermal impedance, method 3131 of MIL-STD-750 (see 4.3.3)
9	I_{CBO1} and h_{FE1}	Not applicable
11	I_{CBO1}; h_{FE1}; ΔI_{CB01} = 100 percent of initial value or 0.5 μA dc, whichever is greater; Δh_{FE1} = ±15 percent of initial value.	I_{CBO1} and h_{FE1}
12	See 4.3.2	See 4.3.2
13	Subgroups 2 and 3 of table I herein; ΔI_{CB01} = 100 percent of initial value or 200 nA dc, whichever is greater; Δh_{FE1} = ±15 percent of initial value.	Subgroup 2 of table I herein; ΔI_{CB01} = 100 percent of initial value or 200 nA dc, whichever is greater; Δh_{FE1} = ±15 percent of initial value.

* (1) Thermal impedance, see 4.3.3. Shall be performed anytime after temperature cycling, screen 3a; TX and TXV levels do not need to be repeated in screening requirements.

4.3.1 Screening (JANHC and JANKC). Screening of JANHC and JANKC die shall be in accordance with MIL-PRF-19500. As a minimum, die shall be 100 percent probed to ensure the assembled chips will meet the requirements of table I, subgroup 2.

4.3.2 Power burn-in conditions. Power burn-in conditions are as follows: V_{CB} = 10 - 30 V dc. Power shall be applied to achieve T_J = +135°C minimum using a minimum P_D = 75 percent of P_T maximum rated as defined in 1.3. With approval of the qualifying activity and preparing activity, alternate burn-in criteria (hours, bias conditions, T_J, and mounting conditions) may be used for JANTX and JANTXV quality levels. A justification demonstrating equivalence is required. In addition, the manufacturing site's burn-in data and performance history will be essential criteria for burn-in modification approval.

4.3.3 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3131 of MIL-PRF-19500 using the guidelines in that method for determining I_M, I_H, t_H, t_{MD} (and V_C where appropriate). See table III, subgroup 4 and figure 12, figure 13, figure 14, figure 15, and figure 16 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500 and as specified herein. If alternate screening is being performed in accordance with MIL-PRF-19500, a sample of screened devices shall be submitted to and pass the requirements of group A1 and A2 inspection only (table E-VIB, group B, subgroup 1 is not required to be performed again if group B has already been satisfied in accordance with 4.4.2).

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-PRF-19500 and table I herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in E-VIA (JANS) of 4.4.2.1 herein. See 4.4.2.2 for JAN, JANTX, and JANTXV group B testing.

4.4.2.1 Group B inspection, table E-VIA (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
B4	1037	V_{CB} = 10 V dc, 2,000 cycles.
B5	1027	V_{CB} = 10 V dc; $P_D \geq$ 100 percent of maximum rated P_T (see 1.3). (NOTE: If a failure occurs, resubmission shall be at the test conditions of the original sample.) Option 1: 96 hrs minimum, sample size in accordance with table VIA of MIL-PRF-19500, adjust T_A or P_D to achieve T_J = +275°C minimum. Option 2: 216 hrs minimum, sample size = 45, c = 0; adjust T_A or P_D to achieve T_J = +225°C minimum.
B6	3131	$R_{\theta JA}$ for TO-5 and TO-39, $R_{\theta JC}$ for U4 only (see 1.3 and 4.3.3).

4.4.2.2 Group B inspection, (JAN, JANTX, and JANTXV). Separate samples may be used for each step. In the event of a group B failure, the resubmission requirements of MIL-PRF-19500 shall apply. In addition, all catastrophic failures during CI shall be analyzed to the extent possible to identify root cause and corrective action. Whenever a failure is identified as wafer lot or wafer processing related, the entire wafer lot and related devices assembled from the wafer lot shall be rejected unless an appropriate determined corrective action to eliminate the failure mode has been implemented and the devices from the wafer lot are screened to eliminate the failure mode.

Step	Method	Condition
1	1026	Steady-state life: 1,000 hours, V_{CB} = 10 dc, power shall be applied to achieve T_J = +150°C minimum using a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45 devices, c = 0. The sample size may be increased and the test time decreased as long as the devices are stressed for a total of 45,000 device hours minimum, and the actual time of test is at least 340 hours.
2	1048	Blocking life, T_A = +150°C, V_{CB} = 80 percent of rated voltage, 48 hours minimum. n = 45 devices, c = 0.
3	1032	High-temperature life (non-operating), t = 340 hours, T_A = +200°C. n = 22, c = 0.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

4.4.2.3 Group B sample selection. Samples selected from group B inspection shall meet all of the following requirements:

a. Samples shall be selected from an inspection lot that has been submitted to and passed table I, subgroup 2, conformance inspection.

b. When the final lead finish is solder, or any plating prone to oxidation at high temperature, the samples for life test (Step 1) may be tested prior to the application of final lead finish.

c. Separate samples may be used for each step.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and in 4.4.3.1 (JANS) and 4.4.3.2 (JAN, JANTX, and JANTXV) herein for group C testing.

4.4.3.1 Group C inspection, table E-VII (JANS) of MIL-PRF-19500.

Subgroup	Method	Condition
C2	2036	Test condition E, except the UA, U4, UB, and UBC packages.
C5	3131	$R_{\theta JA}$ for TO-5 and TO-39, $R_{\theta JC}$ for U4 only, as applicable (see 1.3 and see 4.3.3) and in accordance with thermal impedance curves.
C6	1026	1,000 hours at V_{CB} = 10 V dc; power shall be applied to achieve T_J = +150°C minimum and a minimum of P_D = 75 percent of maximum rated P_T as defined in 1.3. n = 45 devices, c = 0. The sample size may be increased and the test time decreased as long as the devices are stressed for a total of 45,000 device hours minimum, and the actual time of test is at least 340 hours.

4.4.3.2 Group C inspection, table E-VII (JAN, JANTX, and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Condition
C2	2036	Except the UA U4, UB, and UBC packages.
C5	3131	$R_{\theta JA}$ and $R_{\theta JC}$ only, as applicable (see 1.3 and 4.3.3) and in accordance with thermal impedance curves.
C6		Not applicable.

4.4.3.3 Group C sample selection. Samples for subgroups in group C shall be chosen at random from any lot containing the intended package type and lead finish procured to the same specification which is submitted to and passes table I tests for conformance inspection. Testing of a subgroup using a single device type enclosed in the intended package type shall be considered as complying with the requirements for that subgroup.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

4.4.4 Group D inspection. Conformance inspection for hardness assured JANS, JANTX, and JANTXV types shall include the group D tests specified in table II herein. These tests shall be performed as required in accordance with MIL-PRF-19500 and method 1019 of MIL-STD-750, for total ionizing dose or method 1017 of MIL-STD-750 for neutron fluence as applicable (see 6.2 herein), except group D, subgroup 2 may be performed separate from other subgroups. Group D inspection may also be performed ahead of the screening lot using die selected in accordance with MIL-PRF-19500 and related documents. Alternate package options may also be substituted for the testing provided there is no adverse effect to the fluence profile.

4.4.5 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in appendix E, table E-IX of MIL-PRF-19500 and as specified in table III herein. Electrical measurements (end-points) shall be in accordance with table I, group A, subgroup 2 herein

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.6 Element evaluation of unencapsulated die (quality levels JANHC and JANKC). The element evaluation of unencapsulated die shall be in accordance with appendix G of MIL-PRF-19500. For subgroup 4, the burn-in duration for the JANKC level shall follow the JANS requirements and the JANHC level shall follow the JANTX requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 1 2/						
Visual and mechanical 3/ examination	2071					
Solderability 3/ 4/	2026	n = 15 leads, c = 0				
Resistance to 3/ 4/ 5/ solvent	1022	n = 15 devices, c = 0				
Salt atmosphere (corrosion)	1041	n = 6 devices, c = 0, (For laser marked devices only)				
Temp cycling 3/ 4/	1051	Test condition C, 25 cycles. n = 22 devices, c = 0				
Hermetic seal 4/	1071	n = 22 devices, c = 0				
Fine leak Gross leak						
Electrical measurements 4/		Table I, subgroup 2				
Bond strength 3/ 4/	2037	Precondition T_A = +250°C at t = 24 hrs or T_A = +300°C at t = 2 hrs, n = 11 wires, c = 0				
Decap internal visual (design verification) 4/	2075	n = 4 devices, c = 0				
Subgroup 2						
Thermal impedance 6/	3131	See 4.3.3	$Z_{\theta JX}$			°C/W
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 7 V dc	I_{EBO1}		10	µA dc
* Breakdown voltage, collector to emitter	3011	Bias condition D, I_C = 10 mA, pulsed	$V_{BR(CEO)}$			V dc
2N3439, 2N3439L, 2N3439UA, 2N3439UB, 2N3439UBC				350		
2N3440, 2N3440L, 2N3440UA, 2N3440UB, 2N3440UBC				250		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 2 - Continued						
Collector to emitter cutoff	3041	Bias condition D	I_{CEO}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		VCE = 300 V dc			2	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		VCE = 200 V dc			2	µA dc
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = -1.5 V dc	I_{CEX}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CE} = 450 V dc			5	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CE} = 300 V dc			5	µA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO1}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 360 V dc			2	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 250 V dc			2	µA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 450 V dc			5	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 300 V dc			5	µA dc
Base emitter voltage (saturated)	3066	Test condition A, pulsed (see 4.5.1), I_C = 50 mA dc, I_B = 4 mA dc	$V_{BE(sat)}$		1.3	V dc
Collector to emitter voltage (saturated)	3071	Pulsed (see 4.5.1), I_C = 50 mA dc, I_B = 4 mA dc	$V_{CE(sat)}$		0.5	V dc
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 20 mA	h_{FE1}	40	160	
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 2 mA	h_{FE2}	30		
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 0.2 mA	h_{FE3}	10		

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to emitter cutoff current	3036	Bias condition D	I_{CB03}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 360 V dc			6	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 250 V dc			6	µA dc
Low temperature operation:		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 10 V dc, I_C = 20 mA dc, pulsed (see 4.5.1)	h_{FE4}	15		
Subgroup 4						
Pulse response:	3251	Test condition A				
Turn-on time		V_{CC} = 200 V dc, I_C = 20 mA dc, I_{B1} = 2 mA dc, see figure 18	t_{on}		1	µs
Turn-off time		V_{CC} = 200 V dc, I_C = 20 mA dc, I_{B1} = -I_{B2} = 2 mA dc, see figure 18	t_{off}		10	µs
Magnitude of common- emitter small-signal short-circuit forward-current transfer ratio	3306	V_{CE} = 10 V dc, I_C = 10 mA dc, f = 5 MHz	$\|h_{fe}\|$	3	15	
Open capacitance input open circuited	3236	V_{CB} = 10 V dc, I_E = 0, 100 kHz ≤ f ≤ 1 MHz	C_{obo}		10	pF
Small-signal short- circuit forward-current transfer ratio	3206	V_{CE} = 10 V dc, I_C = 5 mA, f = 1 kHz	h_{fe}	25		
Input capacitance (output open circuited)	3240	V_{CB} = 5 V dc, I_E = 0, 100 kHz ≤ f ≤ 1 MHz	C_{ibo}		75	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 5						
Safe operating area (continuous dc)	3051	(See figure 19) T_C = +25°C, 1 cycle, t = 1.0 s. 1 cycle, t = 0.4 s (UA, UB)				
Test 1		V_{CE} = 5 V dc, I_C = 1 A dc				
Test 2						
Only 2N3439, 2N3439L, 2N3439UA, 2N3439UB, 2N3439UBC		V_{CE} = 350 V dc, I_C = 14 mA dc				
Test 3						
Only 2N3440, 2N3440L, 2N3440UA, 2N3440UB, 2N3440UBC		V_{CE} = 250 V dc, I_C = 20 mA dc				
Electrical measurements		See table I, subgroup 2 herein.				

1/ For sampling plan, see MIL-PRF-19500.
2/ For resubmission of failed test in subgroup 1 of table I, double the sample size of the failed test or sequence of tests. A failure in table I, subgroup 1 shall not require retest of the entire subgroup. Only the failed test shall be rerun upon submission.
3/ Separate samples may be used.
4/ Not required for JANS.
5/ Not required for laser marked devices.
6/ This test required for the following end-point measurements only: See 4.3.3 and figure 13, figure 14, figure 15, figure 16, and figure 17.
Group B, subgroups 3, 4, and 5.
Group B, step 1.
Group C, subgroups 2 and 6.
Group E, subgroups 1 and 2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 1 4/						
Neutron irradiation	1017	Neutron exposure V_{CES} = 0 V				
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 7 V dc	I_{EBO1}		20	µA dc
Collector to emitter cutoff	3041	Bias condition D	I_{CEO}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CE} = 300 V dc			4	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CE} = 200 V dc			4	µA dc
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = -1.5 V dc	I_{CEX}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CE} = 450 V dc			10	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CE} = 300 V dc			10	µA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO1}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 360 V dc			4	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 250 V dc			4	µA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 450 V dc			10	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 300 V dc			10	µA dc
Base emitter voltage (saturated)	3066	Test condition A, pulsed (see 4.5.1), I_C = 50 mA dc, I_B = 4 mA dc	$V_{BE(sat)}$		1.5	V dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 1 4/ Continued						
Collector to emitter voltage (saturated)	3071	Pulsed (see 4.5.1), I_C = 50 mA dc, I_B = 4 mA dc	$V_{CE(sat)}$		0.56	V dc
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 20 mA	h_{FE1} 5/	[20]	160	
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 2 mA	h_{FE2} 5/	[15]		
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 0.2 mA	h_{FE3} 5/	[5]		
Subgroup 2						
Total dose irradiation	1019	Condition A, Gamma exposure				
2N3439		V_{CES} = 280 V				
2N3440		V_{CES} = 200 V				
Emitter to base cutoff current	3061	Bias condition D, V_{EB} = 7 V dc	I_{EBO1}		20	µA dc
Collector to emitter cutoff	3041	Bias condition D	I_{CEO}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CE} = 300 V dc			4	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CE} = 200 V dc			4	µA dc
Collector to emitter cutoff current	3041	Bias condition A, V_{BE} = -1.5 V dc	I_{CEX}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CE} = 450 V dc			10	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CE} = 300 V dc			10	µA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE II. Group D inspection -Continued.

Inspection 1/ 2/ 3/	MIL-STD-750		Symbol	Limit	Limit	Unit
	Method	Conditions		Min	Max	
Subgroup 2/ Continued						
Collector to base cutoff current	3036	Bias condition D	I_{CBO1}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 360 V dc			4	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 250 V dc			4	µA dc
Collector to base cutoff current	3036	Bias condition D	I_{CBO2}			
2N3439, 2N3439L, 2N3439UA, 2N3439U4 2N3439UB, 2N3439UBC		V_{CB} = 450 V dc			10	µA dc
2N3440, 2N3440L, 2N3440UA, 2N3440U4 2N3440UB, 2N3440UBC		V_{CB} = 300 V dc			10	µA dc
Base emitter voltage (saturated)	3066	Test condition A, pulsed (see 4.5.1), I_C = 50 mA dc, I_B = 4 mA dc	$V_{BE(sat)}$		1.5	V dc
Collector to emitter voltage (saturated)	3071	Pulsed (see 4.5.1), I_C = 50 mA dc, I_B = 4 mA dc	$V_{CE(sat)}$		0.56	V dc
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 20 mA	[h_{FE1}] 5/	[20]	160	
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 2 mA	[h_{FE2}] 5/	[15]		
Forward-current transfer ratio	3076	Pulsed (see 4.5.1), V_{CE} = 10 V dc, I_C = 0.2 mA	[h_{FE3}] 5/	[5]		


1/ Tests to be performed on all devices receiving radiation exposure.
2/ For sampling plan, see MIL-PRF-19500.
3/ Electrical characteristics apply to device types unless otherwise noted.
4/ Subgroup 1 is an optional test and must be specified on the contract when required.
5/ See method 1019 of MIL-STD-750 for how to determine [h_{FE}] by first calculating the delta (1/h_{FE}) from the pre- and post-radiation h_{FE}. Notice the [h_{FE}] is not the same as h_{FE} and cannot be measured directly. The [h_{FE}] value can never exceed the pre-radiation minimum h_{FE} that it is based upon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

TABLE III. Group E inspection (all quality levels) - for qualification only or re-qualification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition C, 500 cycles.	
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, subgroup 2.	
Subgroup 2			45 devices c = 0
Intermittent life	1037	Intermittent operation life: $V_{CB} \geq 10$ V dc, 6,000 cycles.	
Electrical measurements		See table I, subgroup 2.	
Subgroup 4			
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 5			15 devices, c = 0
Barometric pressure (reduced)	1001	Normal mounting pressure = 8 mm Hg, ±2 mm Hg for 60 s (minimum).	
Electrical measurements		See table I, subgroup 2.	
Subgroups 6			
ESD (electrostatic discharge)	1020		
Subgroup 8			45 devices c = 0
Reverse stability	1033	Condition A for devices ≥ 400 V, condition B for devices < 400 V.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at $T_J \leq$, 125°C, and 110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 8. Temperature-power derating for all types $R_{\theta JA}$ (TO-5, TO-39, UA, and U4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 9. Temperature-power derating for 2N3439UA and 2N3440UA.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at $\leq T_J$ specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 10. Temperature-power derating for 2N3439U4 and 2N3440U4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 11. Temperature-power derating for 2N3439, 2N3439L, 2N3440, and 2N3440L.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature ($T_J \leq 200°C$) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at $T_J \leq 150°C$, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at $T_J \leq 125°C$, and 110°C to show power rating where most users want to limit T_J in their application.

* FIGURE 12. Temperature-power derating for 2N3439UB, 2N3439UBC, 2N3440UB, and 2N3440UBC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance




T_A = +25°C, P_T = 0.8W, thermal resistance $R_{\theta JA}$ = 175°C/W.

* FIGURE 13. Thermal impedance graph ($R_{\theta JA}$) for 2N3439, 2N3439L, 2N3440, and 2N3440L (TO-5, TO-39, U4, and UA).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance




T_C = +25°C, P_T = 5.0W, thermal resistance $R_{\theta JC}$ = 30°C/W, steel.

* FIGURE 14. Thermal impedance graph ($R_{\theta JC}$) for 2N3439, 2N3439L, 2N3440, and 2N3440L (TO-5 and TO-39).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance




T_C = +25°C, thermal resistance $R_{\theta JSP}$ = 70°C/W, Pdiss = 2W.

* FIGURE 15. Thermal impedance graph ($R_{\theta JSP}$) for 2N3439UA and 2N3440UA.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.


Maximum Thermal Impedance



Solder mounted to copper heatsink at T_C = +25C. Thermal resistance $R_{\theta JC}$ = 8.0 C/W

* FIGURE 16. Thermal impedance graph ($R_{\theta JC}$) for 2N3439U4, and 2N3440U4 (U4).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.



T_A = +25°C, P_T = 0.5W, thermal resistance $R_{\theta JA}$ = 175°C/W.

* FIGURE 17. Thermal impedance graph ($R_{\theta JA}$) for 2N3439UB, 2N3439UBC, and 2N3440UB 2N3440UBC.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.




NOTES:

1. The rise time (t_r) and fall time (t_f) of applied pulse shall be ≤ 20 ns, duty cycle ≤ 2 percent, generator source impedance shall be 50 ohms, pulse width = 20 μs.
2. Output sampling oscilloscope: Z_{IN} ≥ 100 kΩ, C_{IN} ≤ 50 pF, and rise time ≤ 1.0 μs.

* FIGURE 18. Pulse response test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.



NOTE: Also applies to the corresponding "L" and "UA" suffix devices.

* FIGURE 19. Maximum safe operating graph (continuous dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete Part or Identifying Number (PIN), see 1.5 and 6.5.

e. For acquisition of RHA designed devices, table II, subgroup 1 testing of group D is optional. If subgroup 1 testing is desired, it should be specified in the contract.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.


6.4 Suppliers of JANHC and JANKC die. The qualified JANHC and JANKC suppliers with the applicable letter version (example JANHCA2N3439) will be identified on the QML.

PIN	Die ordering information		
	Manufacturer	Manufacturer	Manufacturer
	43611	34156	52GC4
2N3439	JANHCB2N3439 JANKCB2N3439	JANHCC2N3439 JANKCC2N3439	JANHCD2N3439 JANKCD2N3439
2N3440	JANHCB2N3440 JANKCB2N3440	JANHCC2N3440 JANKCC2N3440	JANHCD2N3440 JANKCD2N3440


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

6.5 PIN construction example.

6.5.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



6.5.2 Unencapsulated devices. The PINs for un-encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

6.6 List of PINs. The following is a list of possible PINs available on this specification sheet.

PINs for devices of the base quality level	PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level	PINs for devices of the "S" quality level (1)
JAN2N3439	JANTX2N3439	JANTXV2N3439	JANS#2N3439
JAN2N3439L	JANTX2N3439L	JANTXV2N3439L	JANS#2N3439L
JAN2N3439UA	JANTX2N3439UA	JANTXV2N3439UA	JANS#2N3439UA
JAN2N3439U4	JANTX2N3439U4	JANTXV2N3439U4	JANS#2N3439U4
JAN2N3439UB	JANTX2N3439UB	JANTXV2N3439UB	JANS#2N3439UB
JAN2N3439UBC	JANTX2N3439UBC	JANTXV2N3439UBC	JANS#2N3439UBC
JAN2N3440	JANTX2N3440	JANTXV2N3440	JANS#2N3440
JAN2N3440L	JANTX2N3440L	JANTXV2N3440L	JANS#2N3440L
JAN2N3440UA	JANTX2N3440UA	JANTXV2N3440UA	JANS#2N3440UA
JAN2N3440U4	JANTX2N3440U4	JANTXV2N3440U4	JANS#2N3440U4
JAN2N3440UB	JANTX2N3440UB	JANTXV2N3440UB	JANS#2N3440UB
JAN2N3440UBC	JANTX2N3440UBC	JANTXV2N3440UBC	JANS#2N3440UBC

Quality level HC	Quality level KC (1)
JANHCB2N3439	JANKCB#2N3439
JANHCB2N3440	JANKCB#2N3440
JANHCC2N3439	JANKCC#2N3439
JANHCC2N3440	JANKCC#2N3440
JANHCD2N3439	JANKCD#2N3439
JANHCD2N3440	JANKCD#2N3440

(1) The number sign (#) represent one of eight RHA designators available (M, D, P, L, R, F, G, or H). The PIN is also available without a RHA designator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.

6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
Navy - SH
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, MC
Air Force - 19

Preparing activity:
DLA - CC

(Project 5961-2023-074)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:03Z
Check the source to verify that this is the current version before use.