INCH-POUND

The documentation and process conversion measures necessary to comply with this document shall be completed by 25 May 2018.

MIL-PRF-19500/370J
26 February 2018
SUPERSEDING
MIL-PRF-19500/370H
19 February 2013

PERFORMANCE SPECIFICATION SHEET

TRANSISTOR, NPN, SILICON, HIGH-POWER,
TYPE 2N3442, JAN, JANTX, AND JANTXV

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for NPN silicon, high-power transistor. Three levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. The device package style is TO-204AA (formerly TO-3) in accordance with figure 1.

1.3 Maximum ratings. Unless otherwise specified, T_C = +25°C.

Type	P_T (1) T_A = +25°C	P_T (2) T_C = +25°C	$R_{\theta JC}$ (3)	V_{CBO}	V_{CEO}	V_{EBO}	V_{CER}	I_B	I_C	T_J and T_{STG}
	W	W	°C/W	V dc	V dc	V dc	V dc	A dc	A dc	°C
2N3442	6.0	117	1.5	160	140	7	150	7	10	-65 to +200

(1) Derate linearly 34.2 mW/°C above T_A = +25°C.
(2) See figure 2 for temperature-power derating curves.
(3) See figure 3 for transient thermal impedance graph.

1.4 Primary electrical characteristics. Unless otherwise specified, T_C =+25°C.

	h_{FE1} (1)	$V_{CE(sat)}$ (1)	h_{fe}
Limits	V_{CE} = 4 V dc I_C = 3 A dc	I_C = 3 A dc I_B = 300 mA dc	V_{CE} = 4 V dc I_C = 3 A dc, f = 100 kHz
		V dc	
Min	20		1.0
Max	70	1.0	

(1) Pulsed (see 4.5.1).

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218–3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.




FIGURE 1. Physical dimensions (TO-204AA, formerly TO-3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
CD		.875		22.23	3
CH	.250	.450	6.35	11.43	
HR	.495	.525	12.57	13.34	
HR_1	.131	.188	3.33	4.78	4
HT	.060	.135	1.52	3.43	
L_1		.050		1.27	5, 6
LD	.038	.043	0.97	1.09	5, 6
LL	.312	.500	7.92	12.70	5
MHD	.151	.161	3.84	4.09	4
MHS	1.177	1.197	29.90	30.40	
PS	.420	.440	10.67	11.18	7
PS_1	.205	.225	5.21	5.72	7
S_1	.655	.675	16.64	17.15	7

NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
2. Terminal 1 is the emitter; terminal 2 is the base; and the collector shall be electrically connected to the case.
3. Body contour is optional within zone defined by dimension CD.
4. Applies to both ends.
5. Applies to both terminals.
6. Dimension LD applies between L_1 and LL. Lead diameter shall not exceed twice dimension LD within dimension L_1. Diameter is uncontrolled in dimension L_1.
7. These dimensions shall be measured at points .050 inch (1.27 mm) to .055 inch (1.4 mm) below the seating plane. When gauge is not used, measurement will be made at the seating plane.
8. The seating plane of the header shall be flat within .001 inch (0.03 mm) concave to .004 inch (0.10 mm) convex inside a .930 inch (23.62 mm) diameter circle on the center of the header and flat within .001 inch (0.03 mm) concave to .006 inch (0.15 mm) convex overall.
9. In accordance with ASME Y14.5M, diameters are equivalent to ϕx symbology.

FIGURE 1. Physical dimensions ((TO-204AA, formerly TO-3) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

* 1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

* 1.5.1 JAN certification mark and quality level.

* 1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: "JAN", "JANTX", and "JANTXV".

* 1.5.2 Device type. The designation system for the device types of semiconductors covered by this specification sheet are as follows.

* 1.5.2.1 First number and first letter symbols. The semiconductors of this specification sheet use the first number and letter symbols "2N".

* 1.5.2.2 Second number symbols. The second number symbols for the semiconductors covered by this specification sheet are as follows: "3442".

1.5.3 Suffix symbols. Suffix symbols are not applicable to this specification.

* 1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

2. APPLICABLE DOCUMENTS

* 2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at http://quicksearch.dla.mil/).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. The interface requirements and physical dimensions shall be as specified in MIL-PRF-19500 and on figure 1 (TO-204AA, formerly TO-3) herein.

3.4.1 Lead finish. Unless otherwise specified, the lead finish shall be solderable in accordance with MIL-STD-750, MIL-PRF-19500, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Polarity. The identification of terminals of the device package shall be as shown on figure 1. Terminal 1 shall be connected to the emitter, terminal 2 shall be connected to the base, and the collector shall be electrically connected to the case.

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in table I.

3.7 Marking. Marking shall be in accordance with MIL-PRF-19500.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

4.3 Screening (quality levels JANTX and JANTXV only). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen (see table E-IV of MIL-PRF-19500)	Measurement
	JANTX and JANTXV levels only
3c (1)	Thermal impedance (transient), see 4.3.1.
11	h_{FE1}, I_{CEX}
12	See 4.3.2.
13	See table I, subgroup 2 herein. ΔI_{CEX} = 100 percent or 2 μA dc whichever is greater; Δh_{FE1} = 25 percent of initial value.

(1) Thermal impedance shall be performed anytime after temperature cycling (screen 3a) and does not need to be repeated in screening requirements.

4.3.1 Thermal impedance. The thermal impedance measurements shall be performed in accordance with test method 3131 of MIL-STD-750 using the guidelines in that test method for determining I_H, I_M, t_H, t_{SW} (and V_H where appropriate). Measurement delay time (t_{MD}) = 70 μs maximum. The thermal impedance limit used in screen 3c and table I, subgroup 2 herein shall be set statistically by the supplier. See table II, subgroup 4 (group E) herein.

4.3.2 Power burn-in conditions. The power burn-in conditions shall be as follows: T_J = +187.5°C ±12.5°C; V_{CB} = 10 to 30 V dc; T_A ≤ +35°C. With approval of the qualifying activity and preparing activity, alternate burn-in criteria (hours, bias conditions, T_J, and mounting conditions) may be used. A justification demonstrating equivalence is required. In addition, the manufacturing site's burn-in data and performance history will be essential criteria for burn-in modification approval.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500, and as specified herein. If alternate screening is being performed in accordance with MIL-PRF-19500, a sample of screened devices shall be submitted to and pass the requirements of table I, subgroup 1 and 2. Table E-VIB, subgroup 1 of MIL-PRF-19500 is not required to be performed again if group B has already been satisfied in accordance with 4.4.2.

* 4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500 and table I herein.

* 4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the test methods and conditions specified for subgroup testing in table E-VIB of MIL-PRF-19500 and as follows. Delta measurements shall be in accordance with the applicable step of 4.6 herein.

Subgroup	Method	Conditions
B3	1037	For solder die attach: 2,000 cycles; V_{CB} = 10 - 30 V dc, T_A ≤ +35°C.
	or	
	1026	For eutectic die attach: V_{CB} = 10 to 30 V dc, T_A ≤ +35°C, adjust P_T to achieve T_J = +175°C minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

* 4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows herein. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

Subgroup	Method	Conditions
C2	2036	Test condition A, weight = 10 pounds ±10 ounce (4.5Kg ±0.28Kg), t = 15 s.
C5	3131	See 1.3 and 3.4.1, $R_{\theta JC}$ = 1.5°C/W.
C6	1037	For solder die attach: 6,000 cycles; V_{CB} = 10 to 30 V dc, $T_A \leq +35°C$.
	or	
	1026	For eutectic die attach: V_{CB} = 10 to 30 V dc, $T_A \leq +35°C$, adjust P_T to achieve $T_J = +175°C$ minimum.

* 4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in appendix E, table E-IX of MIL-PRF-19500 and as specified in table II herein. Delta requirements shall be in accordance with the applicable step of 4.6 herein.

4.5 Method of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Pulse response measurements. The conditions for the pulse response measurement shall be as specified in section 4 of MIL-STD-750.

4.6 Delta measurements. The delta measurements for groups B, C, and E shall be as specified below. (1) (2) (3)

Step	Inspection	MIL-STD-750		Symbol	Limits		Unit
		Method	Conditions		Min	Max	
1	Collector to base cutoff current	3041	Bias condition A; V_{CE} = 125 V dc V_{EB} = 1.5 V dc	ΔI_{CEX} (4)	100 percent of initial reading or 2 µA dc, whichever is greater.		

(1) The delta measurements for group B, product assurance levels JAN, JANTX and JANTXV as follows:
   a. In addition to the measurements specified for subgroup 3 of table E-VIB of MIL-PRF-19500, the measurements of step 1 shall also be taken.
   b. In addition to the measurements specified for subgroup 6 of table E-VIB of MIL-PRF-19500, the measurements of step 1 also be taken.

(2) The delta measurements for group C, all product assurance levels, shall be as follows: In addition to the measurements specified for subgroup 6 of table E-VII of MIL-PRF-19500, the measurements of step 1 shall also be taken.

(3) The delta measurements for group E, all product assurance levels, shall be as follows: In addition to the measurements specified for subgroups 1 and 2 of table E-IX of MIL-PRF-19500, the measurements of step 1 shall also be taken.

(4) Devices which exceed the table I (group A) limits for this test shall not be accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance	3131	See 4.3.1	$Z_{\theta JC}$			°C/W
Breakdown voltage, collector to emitter	3011	Bias condition D; I_C = 3 A dc, pulsed (see 4.5.1), see figure 4	$V_{(BR)CEO}$	140		V dc
Breakdown voltage, collector to emitter	3011	Bias condition B; I_C = 1.5 A dc, R_{BE} = 100 Ω, see figure 4	$V_{(BR)CER}$	150		V dc
Breakdown voltage, collector to emitter	3011	Bias condition A; I_C = 1.5 A dc, V_{EB} = 1.5 V dc, see figure 4	$V_{(BR)CEX}$	160		V dc
Collector to emitter cutoff current	3041	Bias condition A; V_{CE} = 125 V dc, V_{EB} = 1.5 V dc	I_{CEX}		0.01	mA dc
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 140 V dc	I_{CBO1}		0.1	mA dc
Emitter to base cutoff current	3061	Condition D; V_{EB} = 7 V dc	I_{EBO}		1	mA dc
Base emitter voltage (nonsaturated)	3066	Test condition B; pulsed (see 4.5.1), I_C = 3 A dc, V_{CE} = 4.0 V dc	V_{BE}		1.7	V dc
Saturation voltage and resistance	3071	Pulsed (see 4.5.1), I_C = 3 A dc, I_B = 300 mA dc	$V_{CE(sat)}$		1.0	V dc
Forward-current transfer ratio	3076	V_{CE} = 4 V dc, I_C = 3 A dc, pulsed (see 4.5.1)	h_{FE1}	20	70	

See footnote at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit		Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		T_A = +150°C				
Collector to base cutoff current	3036	Bias condition D; V_{CB} = 140 V dc	I_{CBO2}		1.0	mA dc
Low temperature operation		T_A = -55°C				
Forward-current transfer ratio	3076	V_{CE} = 4 V dc, I_C = 3 A dc, pulsed (see 4.5.1)	h_{FE2}	15		
Subgroup 4						
Small-signal, short circuit forward-current transfer ratio	3306	V_{CE} = 4 V dc, I_C = 3 A dc, f = 100 kHz	h_{fe}	1		
Subgroup 5						
Safe operating area (continuous dc)	3051	T_C = +25°C; t = 1 s, see figure 5				
Test 1		V_{CE} = 11.7 V dc, I_C = 10 A dc				
Test 2		V_{CE} = 78 V dc, I_C = 1.5 A dc				
Test 3		V_{CE} = 125 V dc, I_C = 0.5 A dc				
Electrical measurements		See subgroup 2 of this table				
Subgroups 6 and 7						
Not applicable						


1/ For sampling plan, see MIL-PRF-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) - for qualification and re-qualification only.

Inspection	MIL-STD-750		Qualification sample plan
	Method	Conditions	
Subgroup 1			45 devices c = 0
Temperature cycling (air to air)	1051	Test condition G, 500 cycles.	
Hermetic seal	1071		
Fine leak Gross leak			
Electrical measurements		See table I, subgroup 2 and 4.6 herein.	
Subgroup 2			45 devices c = 0
Blocking life	1048	Test temperature = +125°C; V_{CB} = 80 percent of rated voltage; t = 1,000 hours.	
Electrical measurements		See table I, subgroup 2 and 4.6 herein.	
Subgroup 4			Sample size N/A
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 8			45 devices c = 0
Reverse voltage leakage stability	1033	Condition B for devices < 400 V.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.




NOTES:

1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate power for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperature (T_J ≤ +200°C) and power rating specified. (See 1.3 herein.)
3. Derate design curve chosen at T_J ≤ +150°C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ +125°C, and +110°C to show power rating where most users want to limit T_J in their application.

FIGURE 2. Temperature-power derating graph for device type 2N3442 (TO-204AA, formerly TO-3).


Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.




T_C = +25°C. Thermal resistance = 1.5°C/W.

FIGURE 3. Transient thermal impedance graph for device type 2N3442.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.





NOTE: The voltages, V_{CEO}, V_{CER}, or V_{CEX} are acceptable when the trace falls to the right and above point "A".

FIGURE 4. Test circuit for V_{CEO}, V_{CER}, and V_{CEX}.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.




FIGURE 5. Maximum safe operating graph (dc).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

* 6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).


c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.4.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML 19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

* 6.4 PIN construction example.

* 6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.

* 6.5 List of PINs. The following is a list of possible PINs available on this specification sheet.

PINs for devices in the TO-204AA package			
JAN2N3442	JANTX2N3442	JANTXV2N3442	JANS2N3442

* 6.6 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, MC
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5961-2018-017)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T15:15Z
Check the source to verify that this is the current version before use.