NOT MEASUREMENT SENSITIVE


MIL-D-3943/46C
28 May 1991
SUPERSEDING
MIL-D-3943/46B
31 March 1987

MILITARY SPECIFICATION SHEET

Decoration, Exceptional Civilian Award, Civil Service, Army

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

DASH NO:
-1: Regular size
-2: Miniature size

MATERIAL: Red Brass

DIMENSIONS:
HEIGHT (Include Lug):
-1: 1-19/32 inch (4.05 cm) (REF)
-2: 13/16 inch (2.06 cm) (REF)
WIDTH (Overall):
-1: 1-1/2 inch (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)
THICKNESS (At thickest point):
-1: .145 inch ± .005 inch (0.368 cm ± 0.012 cm)
-2: .095 inch ± .005 inch (0.241 cn ± 0.012 cm)

FINISH: Gold plated, matte finish, polished highlights.

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T23:04Z
Check the source to verify that this is the current version before use.

NOTES:
1. Type I decoration set shall consist of a regular size medal, service ribbon and lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XVI with a Class 1 pad.

2. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/60.

3. The lapel button shall conform to MIL-L-11484/180.

Custodian:
Army - IH

Review Activity:
DLA - CT

Preparing Activity:
Army - IH

(Projected No. 8455-A590)

AMSC N/A

FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-16T23:04Z
Check the source to verify that this is the current version before use.