NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/47F
11 May 1999
SUPERSEDING
MIL-DTL-3943/47E
1 May 1997

DETAIL SPECIFICATION SHEET

DECORATION, MEDAL FOR MERIT

Inactive for new design after 14 January 1999.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Gilding Metal

FINISH: Hard Enameled, Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:05Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

PENDANT:
HEIGHT (overall):
-1: 1-7/8 inches (REF)
-2: (including suspense ring): 1-1/2 inches (REF)
WIDTH (overall):
-1: 1-1/2 inches (REF)
-2: 3/4 inch (REF)
THICKNESS (at thickest point):
-1: 0.195 inch ± 0.010 inch
-2: 0.115 inch ± 0.010 inch

SUSPENSION BAR: (See Note 2)
HEIGHT (including hinged joint): 19/32 inch(REF)
WIDTH (overall): 19/32 inch (REF)
THICKNESS (at thickest point): 0.100 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The suspension bar for the Dash No. -2 decoration is an integral part of the pendant. Therefore, dimensions given for the suspension bar are for the Dash No. -1 decoration only.

3. Pierced areas shall be as indicated.

4. Enamel colors shall be as indicated. The colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below.

COLOR	CHIP NO.
Green	11
Blue	18
White	28

5. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

6. The pendant ribbon ring for Dash No. -1 shall be soldered to the top of the wreath. The ring shall have an outside diameter of 13/32 inch + 1/32 inch - 0 and shall be formed from 0.045 inch ± 0.002 inch in diameter brass wire.

7. Decoration set shall consist of a regular size medal, a service ribbon, and a rosette all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:05Z
Check the source to verify that this is the current version before use.

8. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/86.

9. The rosette shall conform to MIL-DTL-14649/11.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 45
Navy - NU

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

(Project No. 8455-0978)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T23:05Z
Check the source to verify that this is the current version before use.