

MILITARY SPECIFICATION SHEET

CONNECTOR, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, 8 HOLE SURFACE LAUNCH RIGHT ANGLE RECEPTACLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-83517.





INCH	MM	INCH	MM
.001	.03	.085	2.16
.002	.05	.100	2.54
.003	.08	.120	3.05
.004	.10	.125	3.18
.005	.13	.250	6.35
.010	.25	.340	8.64
.015	.38	.4375	11.11
.0355	.90	.438	11.13
.0370	.94	.475	12.07
.050	1.27	.480	12.19
.060	1.52	.570	14.48
.072	1.83		


DETAIL
TRANSITION END

PART NO.	"A" DIM	TRANSMISSION LINE THICKNESS
-31001	.060±.003	.125
-31002	.120±.003	.250

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1 inch = 25.4 mm.
3. All undimensioned pictorial configurations are for reference purposes only.

FIGURE 1. Series SMA, socket contact, surface launch, right angle, receptacle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.



INCHES	MM
.002	.05
.005	.13
.010	.25
.015	.38
.030	.76
.0355	90
.0370	.94
.045	1.14
.049	1.24
.051	1.30
.074	1.88
.078	1.98
.115	2.82
.168	4.27
.170	4.32
.1810	4.60
.208	5.28
.216	5.49
.218	5.54
.250	6.35

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. All undimensioned pictorial configurations are for reference purposes only.

FIGURE 2. Mating dimensions for socket termination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

ENGINEERING PARAMETERS:

Nominal impedance: 50 ohms.

Voltage rating: 600 Vrms maximum at sea level.

150 Vrms maximum at 70,000 feet.

Frequency range: 0 to 12.4 GHz.

Temperature rating: -65° to 105°C.

REQUIREMENTS:

Design and construction: See figures 1 and 2 and table I.

Force to engage and disengage:

Torque - 2 inch-pounds maximum.

Longitudinal force - Not applicable.

Coupling proof torque: Not applicable.

Inspection note: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Contact gaging: See figure 3.

Contacts with spring members:

Center contact (socket)

Oversize test pin - .0375 +.0001

Test pin finish - 16 microinches.

Insertion depth - .030/.045.

Number of insertions - 3.

Insertion force test: Steel test pin diameter .0370 +.0001.

Insertion depth - .050/.075.

Test pin finish - 16 microinches.

Insertion force - 3 pounds maximum.

Withdrawal force test: Steel test pin diameter .0355 - .0001.

Insertion depth - .050/.075.

Withdrawal force - 1 ounce minimum.

Test pin finish - 16 microinches.




FIGURE 3. Test pin data.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

TABLE I. Part number and characteristics.

Part no. M83517/08-	Connector figure no.	Characteristics
31001	1	Strip transmission line surface launch, right angle receptacle for 1/8" strip transmission line.
31002	1	Strip transmission line surface launch, right angle receptacle, for 1/4" strip transmission line

Permeability of nonmagnetic materials Applicable.

Seal:

Hermetic sealed connectors: Not applicable.

Pressurized and weatherproof connectors: Not applicable.

Insulation resistance 5,000 megohms minimum.

Center contact retention (excluding transition end):

Axial force: 6 pounds minimum.

Torque: 4 inch-ounces minimum.

Dielectric withstanding voltage: Applicable, test condition I.

Test voltage 1,000 Vrms.

Corrosion Applicable, test condition B.

Voltage standing wave ratio (VSWR):

Test frequency range: From .5 to 12.4 GHz.

Swept frequency VSWR test setup:

Step 1: See basic specification.

Step 2: VSWR shall be less than 1.080 +.005 frequency (frequency in GHz).

Item 11p VSWR shall be less than 1.025 + .002 frequency (frequency in GHz).

Item 11j VSWR shall be less than 1.025 + .002 frequency (frequency in GHz).

Step 3. VSWR shall be less than (to be determined).

Test fixture - See figure 1 of basic specification.

Step 4: VSWR test shall be less than (to be determined).

RF transmission loss: (To be determined).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

RF leakage: Not applicable.

Connector durability:

Interface:

500 cycles minimum at 12 cycles/minute maximum rate.

Connector shall meet contact gaging and force to engage and disengage requirements.

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact	3.0	4.0
Outer contact:	2.0	Not applicable

Thermal shock: Applicable, test condition A.

Moisture resistance: Method 106 of MIL-STD-202.

No measurements at high humidity. Insulation resistance shall be at least 200 megohms within 5 minutes after removal from humidity.

RF high potential withstanding voltage:

At a frequency between 5 to 7.5 MHz.

Leakage current - Not applicable.

RF voltage - 1,000 Vrms.

Coupling mechanism retention force: Not applicable.

Part number: M83517/8-(dash number from table I.)

Group qualification: See table II.

TABLE II. Group qualification.

Group	Submission and qualification of any of the following connectors 1/2/	Qualifies the following connectors
I	3†001	3†001 3†002

1/ Individual connectors other than listed are self qualifying only.

2/ Qualification of connectors qualifies connectors of the same material only.

† Denotes finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

Custodians.
Army - CR
Navy - EC
Air Force - 85

Review activities.
Army - AR, MI, AT
Navy - SH, AS
Air Force - 11, 99
DLA - ES

User activities:
Navy - MC
Air Force - 19

Preparing activity:
Air Force - 85

(Project 5935-3159-8)

☆U.S. GOVERNMENT PRINTING OFFICE: 1993—605-034/48997

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-83517/8 - Connector, Coaxial

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 1 OCT 76 PREVIOUS EDITION WILL BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE AIR FORCE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO 73236 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

AFALD/PTS Standardization
Gentile AFS OH 45444

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.