INCH-POUND

MIL-DTL-83723/20C
w/AMENDMENT 3
01 March 2021
SUPERSEDING
MIL-DTL-83723/20C
w/AMENDMENT 2
16 May 2011


DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), RECEPTACLE, (WALL MOUNT, THREADED COUPLING, CRIMP PIN CONTACTS), (SERIES II, CLASSES A, G, K, AND R)

Inactive for new design after 13 July 1976. For new design, use SAE-AS34501 and SAE-AS50151.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83723.



Inches	mm
.005	0.13
.108	2.74
.215	5.46

FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

Shell size	SAE-AS50151 shell size	C	E max (see note 4)	G max	H Thread class 2A	K max	L max	M	R BSC	S max	T
08	8S	.056 (1.422)	.400 (10.16)	.375 (9.525)	.4375-28UNEF	.110 (2.794)	1.135 (28.829)	.577 (14.655) .562 (14.274)	.594 (15.087)	.906 (23.012)	.130 (3.302) .115 (2.921)
10	10S	.056 (1.422)	.400 (10.16)	.375 (9.525)	.500-28UNEF	.110 (2.794)	1.135 (28.829)	.577 (14.655) .562 14.274)	.719 (18.262)	1.031 (26.187)	.130 (3.302) .115 2.921)
11	10SL	.056 (1.422	.400 (10.16)	.375 (9.525)	.5625-24UNEF	.110 (2.794)	1.135 (28.829)	.577 (14.655) .562 (14.274)	.719 (18.262)	1.031 (26.187)	.130 (3.302) .115 (2.921)
13	12S	.041 (1.041)	.400 (10.16)	.375 (9.525)	.625-24UNEF	.130 (3.302)	1.135 (28.829)	.577 (14.655) .562 (14.274)	.812 (20.624)	1.125 (28.575)	.130 (3.302) .115 (2.921)
12	12	.072 (1.828)	.317 (8.051)	.375 (9.525)	.625-24UNEF	.130 (3.302)	1.495 (37.973)	.765 (19.431) .750 (19.05)	.812 (20.624)	1.125 (28.575)	.130 (3.302) .115 (2.921)
15	14S	.041 (1.041)	.400 (10.16)	.375 (9.525)	.750-20UNEF	.130 (3.302)	1.135 (28.829)	.577 (14.655 .562 (14.274)	.906 (23.012)	1.219 (30.962)	.130 (3.302) .115 (2.921)
14	14	.072 (1.828)	.317 (8.051)	.375 (9.525)	.750-20UNEF	.130 (3.302)	1.495 (37.973)	.765 (19.431) .750 (19.05)	.906 (23.012)	1.219 (30.962)	.130 (3.302) .115 (2.921)
17	16S	.041 (1.041)	.400 (10.16)	.375 (9.525)	.875-20UNEF	.130 (3.302)	1.135 (28.829)	.577 (14.655) .562 (14.274)	.969 (24.612)	1.312 (33.324)	.130 (3.302) .115 (2.921)
16	16	.072 (1.828)	.317 (8.051)	.375 (9.525)	.875-20UNEF	.130 (3.302)	1.495 (37.973)	.765 (19.431) .750 19.05)	.969 (24.612)	1.312 (33.324)	.130 (3.302) .115 2.921
18	18	.072 (1.828)	.380 (9.652)	.500 (12.7)	1.000-20UNEF	.160 (4.064)	1.495 (37.973)	.765 (19.431) .750 (19.05)	1.062 (26.974)	1.406 (35.712)	.130 (3.302) .115 (2.921)
22	22	.056 (1.422)	.380 (9.652)	.500 (12.7)	1.250-18UNEF	.160 (4.064)	1.495 (37.973)	.765 (19.431) .750 (19.05)	1.250 (31.75)	1.656 (42.062)	.130 (3.302) .115 (2.921)

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

Shell size	SAE-AS50151 shell size	C	E max (see note 4)	G max	H Thread class 2A	K max	L max	M	R BSC	S max	T
24	24	.041 (1.041)	.315 (8.001)	.500 (12.7)	1.375-18UNEF	.160 (4.064)	1.556 (39.522)	.827 (21.005) .812 (20.624)	1.375 (34.925)	1.781 (45.237)	.157 (3.987) .142 (3.606)
28	28	.041 (1.041)	.315 (8.001)	.500 (12.7)	1.625-18UNEF	.160 (4.064)	1.556 (39.522)	.827 (21.005) .812 (20.624)	1.562 (39.674)	2.031 (51.587)	.157 (3.987) .142 (3.606)
32	32		.260 (6.604)	.531 (13.487)	1.875-16UN	.160 (4.064)	1.620 (41.148)	.890 (22.606) .875 22.225)	1.750 (44.45)	2.281 (57.937)	.183 (4.648) .168 (4.267)
36	36		.260 (6.604)	.531 (13.487)	2.125-16UN	.160 (4.064)	1.620 (41.148)	.890 (22.606) .875 22.225)	1.938 (49.225)	2.531 (64.287)	.183 (4.648) .168 (4.267)
40	40		.260 (6.604)	.531 (13.487)	2.375-16UN	.160 (4.064)	1.620 (41.148)	.890 (22.606) .875 (22.225)	2.188 (55.575)	2.781 (70.637)	.183 (4.648) .168 (4.267)

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

Detail B dimensions								
Shell size	A	B	C	D	E	F	G	R
8S	.280 (7.112) .271 (6.883)	.250 (6.35) .237 (6.019)	.245 (6.223) .232 (5.892)	.180 (4.572) .167 (4.241)	.427 (10.845) .401 (10.185)	.342 (8.686) .326 (8.280)	.286 (7.246) .276 (7.010)	
10S	.340 (8.636) .332 (8.432)	.312 (7.924) .299 (7.594)	.298 (7.569) .285 (7.239)	.242 (6.146) .229 (7.544)	.420 (10.668 .397 (10.083)	.335 (8.509) .322 (8.178)	.272 (6.908) .262 (6.654)	
10SL	.409 (10.388) .401 (10.185)	.380 (9.652) .367 (9.321)	.378 (9.601) .365 (9.271)	.310 (7.874) .297 (7.543)	.430 (10.922) .407 (10.337)	.335 (8.509) .322 (8.178)	.237 (6.019) .227 (5.765)	
12 & 12S	.460 (11.684) .452 (11.480)	.432 (10.972) .419 10.642)	.403 (10.236) .390 (9.906	.355 (9.017) .342 (8.686)	.419 (10.642) .396 (10.058)	.340 (8.636) .326 (8.280)	.270 (6.858) .260 (6.604)	
14 & 14S	.563 (14.300) .550 (13.97)	.518 (13.157) .505 (12.827)	.485 (12.319) .472 (11.988)	.448 (11.379) .435 (11.049)	.414 (10.515) .391 (9.931)	.339 (8.610) .326 (8.280)	.261 (6.629) .251 (6.375)	.040 (1.016) .020 (.508)
16 & 16S	.689 (17.500) .676 (17.170)	.644 (13.357) .631 (16.027)	.605 (15.367) .592 (15.036)	.574 (14.579) .561 (14.249)	.424 (10.769) .401 (10.185)	.339 (8.610) .326 (8.280)	.266 (6.756) .256 (6.502)	.040 (1.016) .020 (.508)
18	.806 (20.472) .793 (20.142)	.760 (19.304) .747 (18.973)	.725 (18.415) .712 (18.084)	.690 (17.526) .677 (9.575)	.574 (14.579) .551 (13.995)	.449 (11.404) .436 (11.074)	.371 (9.423) .361 (9.169)	.060 (1.524) .040 (1.016)
20	.941 (23.901) .928 (23.571)	.894 (22.707) .881 (22.377)	.863 (21.920) .850 (21.59	.814 (20.675) .801 (20.345)	.573 (14.554) .550 (13.97)	.458 (11.633) .445 (11.303)	.385 (9.779) .375 (9.525)	.060 (1.524) .040 (1.016)

FIGURE 1. Dimensions and configurations – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

Detail B dimensions								
Shell size	A	B	C	D	E	F	G	R
22	1.059 (26.989) 1.046 (26.568)	.982 (24.942) .969 (24.612)	.973 (24.714) .960 (24.384)	.902 (22.910) .889 (22.580)	.551 (13.995) .528 (13.411)	.456 (11.582) .443 (11.252)	.389 (9.880) .379 (9.626)	.060 (1.524) .040 (1.016)
24	1.170 (29.718) 1.157 (29.387)	1.106 (28.092) 1.093 (27.762)	1.085 (27.559) 1.072 (27.228)	1.026 (26.060) 1.013 (25.730)	.547 (13.893) .524 (13.309)	.457 (11.607) .444 (11.277)	.385 (9.779) .375 (9.525)	.060 (1.524) .040 (1.016)
36	1.860 (47.244) 1.847 (46.913)	1.796 (45.618) 1.783 (45.288)	1.751 (44.475) 1.738 (44.145)	1.653 (41.986) 1.640 (41.656)	.573 (14.554) .550 (13.97)	.463 (11.760) .450 (11.43)	.355 (9.017) .345 (8.763)	.060 (1.524) .040 (1.016)
40	2.105 (53.467) 2.092 (53.136)	2.000 (50.8) 1.989 (50.520)		1.905 (48.387) 1.892 (48.056)	.823 (20.904) .800 (20.32)		.379 (9.626) .278 (7.061)	

NOTES:
1. All dimensions are in inches. Metric equivalents are given for information only.
2. All dimensions are after plating.
3. For details of connector front end configuration, see procurement specification.
4. When insulator arrangement sizes 18 thru 40 contain one or more size No. 0 contacts, E dimension will increase .150 max.

FIGURE 1. Dimensions and configurations – Continued.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

This receptacle mates with MIL-DTL-83723/23.

For insert arrangements, see MIL-STD-1651.


Rear hardware as specified in MIL-DTL-83723/27, /35, or /50 must be used for correct wire sealing.

Insert positions and alternate rotations: The letter N indicates normal (or standard) insert position. Alternate positions are identified in MIL-STD-1651.

Qualification is not required. When specified in the contract, a sample shall be subjected to first article inspection. The first article testing shall consist of the qualification inspections specified in MIL-DTL-83723.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN) example:



Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation.

Referenced documents. In addition to MIL-DTL-83723, this document references the following:

MIL-DTL-83723/23
MIL-DTL-83723/27
MIL-DTL-83723/35
MIL-DTL-83723/50
MIL-STD-1651
SAE-AS34501
SAE-AS50151

CONCLUDING MATERIAL

Custodians:
Air Force – 85
DLA – CC

Preparing activity:
DLA - CC

Review activities:
Air Force – 19

(Project 5935-2020-116)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.