MILITARY SPECIFICATION
CARTRIDGE, DELAY: XM271, ASSEMBLY

This amendment forms a part of Military Specification MIL-C-60872(MU) dated 25 April 1968.

Paragraph 2.1 Under STANDARDS: Delete

"MIL-STD-639 - Surface Roughness Values Preferred for Army Ordnance Materiel"

Following the parenthetical note of paragraph 2.1, add the following:

"2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016)"

Paragraph 4.2.1, line 5: Delete "30 cartridges for ballistic tests" and substitute "21 cartridges for ballistic tests".

Table II: under column marked Sample Size delete "30" and substitute "21" for ballistic test.

Paragraph 4.2.1.2, Table III: under column marked Not Vibrated at each temperature delete "6" and substitute "3" at each temperature.

Paragraph 4.3.3.4, line 1: delete "30 assembled X-rayed cartridges" and substitute "21 assembled X-rayed cartridges".

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.

Paragraph 4.3.3.6.1, line 1: delete "30 assembled cartridges" and substitute "21 assembled cartridges".

Table VI: under column marked Sample Size at each temperature delete "10" and substitute "7" at each temperature.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A282

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:02Z
Check the source to verify that this is the current version before use.