MIL-C-62326B
2 March 1988
SUPERSEDING
MIL-C-62326A
12 March 1984

MILITARY SPECIFICATION

CARRIERS, CARGO AND PASSENGER, FULL TRACKED, ALL-TERRAIN, GASOLINE ENGINE DRIVEN, COMMERCIAL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This specification covers gasoline engine driven cargo and passenger carrying, full tracked, all-terrain vehicles with a payload as defined in Table I. Vehicles procured under this specification are commercial items which shall be warranted by the manufacturer as specified in acquisition documents.

* 1.2 Classification. The carriers shall be one of the following types as specified (see 6.2).

Type I - Carrier, cargo, flatbed, with 2-man cab.
Type II - Carrier, cargo and passenger, fully enclosed, with driver, passenger, and 2-place seating length (6 to 8 man capacity).
Type III - Carrier, cargo, flatbed, with 2-man cab and 3-man crew cab.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS), and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Tank-Automotive Command, ATTN: AMSTA-UED, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC-2350

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-393 - Extinguisher, Fire, Dry-Chemical (Portable).

MILITARY

* MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.

STANDARDS

FEDERAL

FED-STD-297 - Rustproofing of Commercial (Nontactical) Vehicles.

MILITARY

MIL-STD-210 - Climatic Extremes for Military Equipment.

MIL-STD-1223 - Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Plate Standards.

MIL-STD-1474 - Noise Limits for Army Material.

* 2.1.2 Other Government documents. The following other Government documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DEPARTMENT OF TRANSPORTATION (DoT)

Federal Motor Carrier Safety Regulations.

Federal Motor Vehicle Safety Standards.

(Application for copies of DoT publications should reference the Code of Federal Regulations, 49 CFR, and the Federal Register, and should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

Control of Air Pollution from New Motor Vehicles and New Motor Vehicle Engines.

Noise Emission Standards for Transportation Equipment - Medium and Heavy Trucks.

(Application for copies of EPA publications should reference the Code of Federal Regulations, 40 CFR, and the Federal Register and should be addressed to the Superintendent of Documents, U.S. Government Printing office, Washington. D.C. 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

TEST OPERATION PROCEDURES

TOP 2-2-614 - Toxic and Hazard Test for Vehicles and other Equipment.

(Application for copies of Test Operation Procedures publications should be addressed to Defense Technical Information Center, Cameron Station, Alexandria, VA 22304-6145.)

(Copies of specifications, standards and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the non-Government document which is current on the date of the solicitation.

SAE, INC.

SAE Standards and Recommended Practices

J350 - Spark Arrester, Test Procedure for Medium Size Engines (DoD adopted).

J551 - Performance Levels and Methods of Measurement of Electromagnetic Radiation from Vehicles and Devices (30-1,000 MHz).

* J706 - Rating of winches.

(Application for copies of SAE publications should be addressed to SAE, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

* UNDERWRITERS' LABORATORIES, INC. (UL)

Fire Protection Equipment List.

(Application for copies of UL publications should be addressed to the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

* 3.1 Standard vehicle and accessories. Except as specified in 3.1.1 through 3.1.1.4, the vehicle, components, assemblies, and accessories to be delivered under the contract shall be standard or optional items which meet or exceed the requirements of this specification. All chassis items shall be as represented in the chassis manufacturer's technical data, and special bodies or mounted equipment shall be as represented in the body and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components and shall be available in the engineering offices of the procuring activity, prior to delivery of the items. The chassis model furnished shall be not older than the chassis manufacturer's current model on the date of invitation for bids.

3.1.1 Special requirements. In addition to the standard vehicle and components specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

* 3.1.1.1 Painting and marking. The vehicle shall be treated, painted and marked in accordance with MIL-STD-1223. As specified, by the procuring activity for the appropriate military service (see 6.2), the exterior color and the identification markings shall be in accordance with MIL-STD-1223.

* 3.1.1.2 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with the truck requirements of FED-STD-297.

* 3.1.1.3 Instruction plates. The equipment shall be provided with instruction plates describing special or important procedures for operating and servicing equipment and warnings of hazardous procedures. Each control lever shall be marked with a plate depicting the function of the control. Individual markings shall be adjacent to each control. The plates shall be durable and legible throughout the life of the equipment. The plates shall be conspicuously located. Plates and markings shall conform to composition A (class l or 2) or composition C of MIL-P-514.

3.1.1.4 Spark arrester muffler. As specified herein (see 3.4.16), the vehicle shall be furnished with an exhaust system spark arrester muffler.

3.2 General design.

3.2.1 Federal Motor Vehicle Safety Standards. The vehicle and all furnished accessories shall comply with all Federal Motor Vehicle Safety Standards in effect on the date of manufacture.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

* 3.2.2 Sound level. The vehicle interior sound level shall conform to the requirements of MIL-STD-1474, table 2, category D (less than 85 dB(A)).

* 3.2.3 Curb weight. The curb weight shall include the weight of the chassis and cab, with all attachments, accessories, and equipment (whether standard or manufacturer's option); the body; and a full complement of fuel, lubricants and coolant.

* 3.2.4 Payload. The payload shall be only the weight of the driver, passengers and cargo being transported. No part of the vehicle shall be included in the payload weight.

* 3.2.5 Vehicle weights and dimensions. Vehicle weights and dimensions shall be as specified in table I.

TABLE I. Weights and dimensions.

Feature	Type I	Type II	Type III
Weights			
Vehicle gross weight (nominal, pounds)	7,400	7,400	7,400
Vehicle curb weight (empty) (nominal, pounds)	5,000	5,600	5,300
Payload (minimum, pounds)	2,400	1,800	2,100
Ground pressure (at zero penetration)			
(1) At curb weight (maximum, pounds per square inch)	.79	.88	.84
(2) Loaded (maximum, pounds per square inch)	1.17	1.17	1.17
Dimensions:			
Overall length (nominal, inches)	144	154	144
Overall width (maximum, inches)	98	98	98
Height (without lights) (maximum, inches)	84	84	84
Ground clearance (minimum, inches)	9	9	9
Ground clearance with drop box guards (minimum, inches)	7	7	7
Track width (minimum, inches)	36	36	36
Track footprint area (at zero penetration) (minimum square inches)	6400	6400	6400

* 3.2.6 Accessibility. The design of the vehicle and optional equipment shall permit access for routine servicing and shall permit access for replacement and adjustment of component parts and accessories with minimal disturbance of other components and systems.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

3.3 Performance.

* 3.3.1 Speed. The vehicle shall transport the minimum payload over smooth, level, hard surfaces at speeds up to 20 miles per hour (mph).

* 3.3.2 Temperature variance. The vehicle shall operate in ambient air temperatures of plus 120 degrees Fahrenheit (°F) to minus 65°F. When in storage, the vehicle shall withstand climatic extremes as specified in MIL-STD-210, without deterioration that could cause failure of any component part of the vehicle.

* 3.3.3 Obstacles. With the minimum payload specified in table I, the vehicle shall climb, either in a head-on or diagonal approach, a vertical barrier 10 inches in height. The vehicle shall ford streams and open water up to 14 inches deep.

3.3.4 Climbing ability. With the minimum payload specified in table I, the vehicle shall climb a hard surface grade of not less than 75 percent without stalling or damaging the power plant or running gear. Side hill ability shall be not less than 55 percent on hard surface grades.

3.3.5 Turning radius. The carrier shall be capable of short radius turns to the right and left which shall be not more than a radius of 10 feet, as measured from the pivot point to the inside edge of the inner track.

3.4 Chassis components.

* 3.4.1 Engine. The intermittent brake horsepower and speed rating of the engine shall be in excess of that required to meet the operational requirements of the vehicle. The engine shall be an air- or a water-cooled, four-stroke cycle, gasoline type of not less than 120 horsepower. The engine shall be of a commercial design that has been proven satisfactory in extensive use, and for which repair parts are readily obtainable. The cooling system shall be such that the engine will operate satisfactorily in ambient temperatures between minus 65°F and plus 120°F. The engine shall have not less than six cylinders and not less than a 258 cubic inch displacement. Engine hood insulation shall be provided to decrease heat transfer from the engine compartment to the driver. Insulation shall be standard type used in automobiles and trucks; carpet; or a combination thereof. The design of the insulation shall take into account any potential fire hazard. The engine shall be complete with all accessories normally furnished with the engine, including a fuel filter located between the fuel tank and the carburetor. A hand throttle sufficient to run the engine steadily at any set speed from idle to maximum shall be furnished. A speed limiting system which provides engine overspeed protection shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

* 3.4.1.1 Power plant, transmission and drive unit heaters. A coolant heater, an engine oil heater, a transmission heater and a drive unit heater shall be provided. Unless otherwise specified (see 6.2), a battery heater shall be provided. Heaters shall operate on 110 volts alternating current (ac), and shall be wired through a junction block to a single three-pronged (male), weatherproof, slave receptacle for receiving external power and grounding the vehicle. A three-wire connecting cable, 25 feet long and of adequate line capacity to supply power for all heater units simultaneously, shall be furnished. Connecting cable shall include a matching female connector at the vehicle end and a standard, three-pronged (two power plus one ground) male connector at the other end. Electrical apparatus shall conform to Federal Motor Carrier Safety Regulation 393.77(c)(7). Electrical insulation of connecting cable shall withstand normal operating stresses in low ambient air temperatures (down to minus 60ºF) without cracking or loss of dielectric capacity. All heater lead wires shall be installed without interfering with vehicle component operation and without loose excess wire. Provisions for stowage of the cable shall be provided in the vehicle cab. Heaters shall be furnished as follows:

(a) A coolant heater, 1,500-watt minimum rating, shall be installed in the engine block or in the lower coolant inlet hose. An engine thermostat with an operating range of 170 ºF to 195°F shall be installed
(b) An immersion type engine oil heater, 300-watt minimum rating, with 170°F to 195°F thermostat, shall be installed in the engine oil pan through any convenient opening
(c) An immersion type oil heater, 300-watt minimum rating with 170°F to 195°F thermostat, shall be installed in the transmission lower pan
(d) An immersion type oil heater, 300-watt minimum rating with 170°F to 195°F thermostat, shall be installed in the drive unit
(e) A battery heater with a capacity adequate to maintain the battery electrolyte at a temperature of not less than 10°F during vehicle exposure in ambient air temperature as low as minus 60°F, and with a thermostat to limit the temperature of the electrolyte to not more than 80ºF.

* 3.4.2 Electrical system. The electrical system shall be of 12-volt direct current (dc) potential. The manufacturer's standard commercial storage battery(s), dry charged and moisture sealed, shall be provided. Electrolyte shall not be furnished. An alternator with a rating of not less than 60 amperes shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

3.4.2.1 Starting system. A 12-volt dc electrical starting system shall be provided.

3.4.2.2 Lighting. The lighting shall include two high and low sealed-beam driving lights, brake lights, back-up lights, interior dome and dash lights, and reflectors. Switches for operating and dimming shall be located convenient to the driver. The dash light(s) shall be located or shielded to eliminate a reflection on the carrier windshield. All exterior lights shall be rigidly mounted. The driving lights shall be protected against damage from brush and tree limbs by a brushguard. When specified (see 6.2), an adjustable, roof-mounted spotlight shall be provided.

3.4.2.3 Radio interference suppression. The vehicle shall be suppressed to limit electromagnetic radiation in accordance with SAE J551. Any body equipment emitting electromagnetic radiation shall be suppressed to the same level as the vehicle chassis.

* 3.4.3 Fuel tank. A fuel tank with a minimum capacity of 29 gallons shall be furnished. The tank shall provide easy access for refueling. If the tank is inside the cab or body, the tank vent and filler lines shall be conveniently located to provide for exterior filling of the tank and to prevent the danger of fumes or leakage inside the vehicle.

* 3.4.4 Transmission. An automatic transmission shall be furnished. The transmission shall include a hydraulic torque converter and shall provide not less than three forward speeds and one reverse speed. The input torque capacity of the transmission shall be at least equal to the maximum torque delivered by the engine.

* 3.4.5 Suspension system. The design of the suspension assembly shall permit the articulation in a vertical plane of the wheel and tire assemblies so that a constant downward pressure is applied when the vehicle is operated on uneven surfaces and the track guides are retained in one vertical plane. A track adjusting assembly shall be provided for adjustment of track tension.

3.4.6 Wheel and tire assemblies. The wheel and tire assemblies shall be standard automotive or trailer type and shall provide adequate support for the vehicle and the tracks.

3.4.6.1 Tires. Tires shall be pneumatic tube or tubeless type. The tires shall have a rated capacity at least equal to the load imposed on each tire under all conditions of service with the vehicle loaded with a payload not less than as specified in table I. When specified (see 6.2), urethane filled tires shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

* 3.4.6.2 Spare tire assembly. Unless otherwise specified (see 6.2), an inflated spare tire mounted on a spare wheel or rim shall be provided. The spare tire and spare wheel or rim shall be identical to those furnished on the vehicle. When specified (see 6.2), the spare tire assembly shall be mounted on the vehicle. Threaded fasteners, when used to mount the spare tire assembly on the vehicle, shall be constructed of or plated with corrosion-resistant material.

* 3.4.7 Tracks. Track assemblies shall be not less than 36 inches in width and shall be capable of continued use over snow, barren frozen ground, rocks, mud or sand without undue damage or excessive wear to drive sprockets, tire guides or grousers. Grousers shall be of heat treated steel. Aluminum grousers are unacceptable.

* 3.4.8 Brakes. Brakes capable of completely stopping the vehicle under all conditions shall be furnished. The braking system shall include a separate emergency brake on the driveline.

3.4.9 Cab. The vehicle shall be furnished with a full width cab constructed to withstand not less than two times the vehicle weight based on ultimate strength of the material. Cab doors shall be equipped with locks operable from inside the cab through mechanical linkage and with at least one door equipped with an external, key-operated lock. Grab handles shall be provided on each side of the cab. Separate driver and passenger doors shall be furnished and shall have movable, sliding glass windows to provide ventilation. Two seats shall be located in front, for the driver and a passenger. These seats shall be cushioned and contoured. The driver's seat shall be adjustable forward and rearward. Seats shall conform to Federal Motor Vehicle Safety Standards 207 and 302. Manufacturer's standard seat belts shall be installed. All cab glass shall be of the safety type. The cab shall be fully insulated. Drip rails shall be installed above the cab doors.

3.4.10 Skid plate. A skid plate shall be provided to cover and protect at least the rearmost 36 inches of the vehicle. The skid plate shall be of not less than 1/4-inch hot rolled steel.

3.4.11 Controls and operating mechanisms. All controls and operating mechanisms shall be located for left hand drive. Controls shall be complete and conveniently operable by the driver. Lever controls shall be designed and located to permit easy entrance and exit of the operator to and from the driver's compartment. Instruments and controls shall be identified as to their function and installed in a manner to facilitate removal and servicing. All instruments shall be visible to the driver when seated in the driving position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

* 3.4.12 Heaters and defroster. The vehicle shall be furnished with a combination heater and defroster for heating the cab and defrosting both the left and right hand windshields. The rating of the combination heater and defroster shall be not less than 40,000 British thermal units (Btu). When specified for type II and III vehicles (see 6.2), an additional heater for heating the full cab or crew cab (using engine coolant heat) shall be furnished. The rating of the additional heater shall be not less than 28,000 Btu. The combination heater and defroster and, when provided, the additional heater shall be complete with blower and mounted controls convenient to the driver.

3.4.13 Radiator shutters. When specified (see 6.2), radiator shutters shall be provided.

* 3.4.14 Steering. Hydraulic assist steering shall be furnished.

3.4.15 Windshield washers and wipers. The vehicle shall be equipped with dual windshield washers and heavy duty dual windshield wipers. Windshield wipers shall be operated by electric motor(s).

* 3.4.16 Exhaust system. The exhaust system shall be installed in a manner that will ensure that the concentration of oxides of nitrogen (NO_x) shall not exceed 5 parts per million (ppm), the concentration of carbon monoxide (CO) shall not exceed 50 ppm and the concentration of sulfur dioxide ($S0_2$) shall not exceed 5 ppm in the vehicle, after eight hours of operation with all windows and doors closed, with cab air intakes open, with and without all heaters operating, and with the engine at idle speed. A spark arrester muffler, with at least an 80 percent efficiency rating when tested in accordance with SAE J350, shall be provided.

* 3.4.17 Winch. When specified (see 6.2), the vehicle shall be furnished with 2-volt dc electric winch, mounted on the front of the vehicle. The winch shall be of the single drum type and shall have one forward and one reverse speed. The winch shall be equipped with an automatic clutch enabling single man operation. The winch shall have a rated single line pull capacity of not less than 8,000 pounds on the bare drum. The winch shall conform to SAE J706. The winch shall be wound with not less than 150 feet of 5/16-inch diameter, preformed, improved plow-steel, independent wire rope core (IWRC) cable and shall be equipped with an end chain and hook. When specified for type I vehicles (see 6.2), a rear-mounted winch of the same construction shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

3.4.18 Gasoline can. When specified (see 6.2), a demountable gasoline can shall be provided on the vehicle. The can shall be of 5-gallon capacity and shall include a detachable spout of sufficient length and flexibility to provide completely enclosed passage of the fuel from the can to the fuel tank.

* 3.4.19 Accessories and equipment. Chassis equipment shall be complete with all accessories furnished as standard equipment by the manufacturer. The following minimum equipment shall be furnished:

(a) Key-operated ignition switch
(b) Ammeter, charging indicator or voltmeter
(c) Oil pressure gage or indicator
(d) Fuel gage
(e) Engine temperature gage or indicator
(f) Tachometer
(g) Engine hour meter
(h) Rear-mounted pintle hook
(i) Horn
(j) Rearview mirrors
(k) Solid front idler tires
(l) Headlight dimmer switch
(m) Track jacks
(n) Tools for replacing and adjusting tracks.

* 3.4.20 Fire extinguisher. When specified (see 6.2), a 5-pound, dry chemical fire extinguisher shall be furnished. The fire extinguisher shall have an Underwriter's Laboratory rating of 2A:10 B:C or more, shall include a metal safety pin and wire, and shall conform to size 5, type I or type II, class 1 of A-A-393. The fire extinguisher shall permit visual determination as to whether it is fully charged.

3.5 Vehicle types.

3.5.1 Type I. Type I vehicle shall include a 2-man cab and a flatbed. The cab shall conform to 3.4.9 and shall be furnished with a roll bar of not less than 3/16 inch thick steel in a 2 inch square tube. The flatbed shall be not less than 25 square feet in area and shall be of diamond tread aluminum or steel capable of supporting a payload of not less than 2,400 pounds over varied terrain without causing permanent deformation of any part of the bed. The flatbed shall include tiedown holes around its perimeter to help secure the payload during vehicle operation on uneven surfaces.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

3.5.2 Type II. Type II vehicle shall include a fully enclosed cab for cargo and passenger transport. The cab shall conform to 3.4.9 and shall include a rear door. The cab shall be furnished with a front roll bar as protection for the driver and front passenger. A second roll bar, located to the rear of the vehicle, shall be provided. Both front and rear roll bars shall be not less than 3/16 inch thick steel in a 2 inch square tube. The rear storage area shall be capable of transporting a payload not less than as specified in table I, minus driver and passenger weight (175 pounds each).

3.5.2.1 Seats. Seating for an additional four to six passengers in the rear of the cab shall be provided. Rear seats shall be of the cushioned bench type with seat belts and padded back rests. When specified (see 6.2), the seats shall be of the fold-up bench type. Seats shall fold flush to the walls permitting storage in the full rear of the cab.

* 3.5.3 Type III. Type III vehicle shall include a 2-man cab, a 3-men crew cab, and a flatbed. The 2-man cab shall conform to 3.4.9 and shall be furnished with a roll bar of not less than 3/16 inch thick steel in a 2 inch square tube. The crew cab shall be provided with a roll bar as specified above, and shall be furnished with seating for three passengers. At least one side door for access to the crew cab shall be furnished. The crew cab shall be furnished with a bench seat and shall be open to the front cab. The inside height shall be not less than 48 inches. The flatbed uncovered cargo area behind the crew cab shall be not less than 17 square feet in area and shall be capable of transporting a payload not less than as specified in table I, minus driver and passenger weights (175 pounds each).

* 3.5.4 Escape hatch. When specified (see 6.2), an escape hatch shall be provided in the roof of the vehicle. The escape hatch shall provide easy access for personnel and shall be of sufficient dimension to provide a quick, unimpaired exit from the vehicle.

3.6 Servicing and adjusting. Prior to acceptance of the vehicle by the Government, the contractor shall service and adjust the vehicle for operational use, including at least the following: alinement of lights; adjustment of the engine, electrical and brake systems; inflation of all tires; adjustment of track tension; complete lubrication of chassis and engine with grades of lubricants recommended for the ambient air temperature at the delivery point; servicing of the cooling system with a solution of 70 percent ethylene glycol type antifreeze and 30 percent water by volume; and servicing of the windshield washer reservoir with water and appropriate additives.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

3.7 Workmanship.

3.7.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. All bends shall be made by controlled means to ensure uniformity of size and shape.

3.7.2 Bolted connections. Bolt holes shall be accurate and true, and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts and screws shall be tight.

3.7.3 Riveted connections. All rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall completely fill the holes. Rivet heads shall be of a suitable shape and shall be concentric with the rivet. Rivet heads shall make full contact with the mating surface. The rivets shall be fabricated to develop a joint strength of not less than the design value.

3.7.4 Welding. Surfaces to be welded shall be free from foreign matter which would be injurious to the weld. Welding procedures shall be in accordance with a nationally recognized code. Welds shall be of sufficient size and shape to develop the full design strength of the parts connected by the welds. Welds shall transmit imposed stresses without permanent deformation or failure when subject to proof or service loadings.

3.7.5 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect which would reduce the casting's ability to perform its intended function.

3.7.6 Components. Defective components, or parts and assemblies which have been repaired or modified to overcome deficiencies, shall not be furnished.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility for assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Government verification. Quality assurance operations performed by the supplier will be subject to Government verification at unscheduled Intervals. Verification will consist of observation of the operations to determine that practices, methods, and procedures of the supplier's inspection are being properly applied. Failure of the supplier to promptly correct product deficiencies discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First production vehicle inspection. The first vehicle produced under the contract shall be inspected by the contractor at his plant under the direction and in the presence of Government representatives. The purpose of the inspection shall be to determine vehicle conformance to the contract. Acceptance of the first production vehicle shall not constitute a waiver by the Government of its rights under the provisions of the contract.

4.3.1 Road test. The first production vehicle shall be loaded with a minimum payload as defined in table I and driven for not less than 50 miles over snow, sand or dirt. During the road test, at least 20 short radius right turns, 20 short radius left turns, and 10 sudden stops shall be completed, and conformance to 3.3.3, 3.3.4, and 3.3.5 shall be determined. Throughout the test, the vehicle shall be observed as to its trackability, ease of handling and tendency to yaw or sway. Upon completion of the road tests, the vehicle shall be inspected for misalinement, distortion or other damage sustained as a result of the testing. Undesirable performance and any damage resulting from the tests shall be cause for rejection.

4.3.2 Ground pressure. The carrier, in both empty and loaded states, shall be weighed and examined to determine conformance to the ground pressure requirements of table I. Ground pressure shall be calculated by using the following formula:

$$\text{GP (psi)} = \frac{\text{Curb weight (lb.)}}{\text{Track area (sq. in.) in contact with ground.}}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

4.3.3 Servicing and restoration. Each unit tested shall be serviced and restored to a service condition equal to the original condition of the unit, neglecting nominal wear incurred during the tests. The restoration shall include paint touchup or repainting, as required for delivery.

* 4.3.4 Exhaust gas test. The vehicle shall be tested to determine the concentration of NO_x CO and SO_2 in the vehicle after 8 hours of engine operation. The tests shall be in accordance with TOP 2-2-614. The tests shall, be conducted with the vehicle stationary, with all cab windows and doors closed, with cab air intakes open, with all cab heaters operating at highest output, and with the engine operating at idle speed. The test shall be repeated except with the heater off. The allowable eight-hour, time weighted averages of TOP-2-614 shall not be exceeded.

* 4.3.6 Failure of first production vehicle. Failure to successfully complete the road test or to meet the requirements shall be cause for the Government to refuse acceptance of the vehicle pending corrective action and reinspect ion or retest. The necessity for replacement of any major component as a result of the road test may mandate a complete retest at the discretion of the Government. Rejection of the vehicle shall be for deficiencies, including but not limited to the following:

(a) Damage caused by collision
(b) Failure of any major component
(c) Vibration due to misalinement of wheels, tracks, drivetrain or frame
(d) Vibration due to type of construction or mounting
(e) Evidence of abnormal tire wear
(f) Failure of vehicular safety device such as brakes or electrical circuits
(g) Evidence of structural weakness in any part of the vehicle, vehicle component or accessory
(h) Loose mounting of parts or accessories due to workmanship or vehicle operation
(i) Fuel leakage.

4.4 Inspection of production vehicle. The contractor's inspection system shall, as a minimum, assure that the vehicle conforms to the physical and dimensional requirements and is capable of meeting performance requirements contained herein. For each vehicle under contract, the contractor shall make available to the Government, at the point of final acceptance, records acceptable to the Government indicating that the servicing and adjusting required by 3.6 have been accomplished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Vehicle processing. Full tracked cargo and passenger carriers shall be processed for shipment in accordance with the manufacturer's standard commercial practice.

6. NOTES

6.1 Intended use. The carriers covered by this specification are intended for general nontactical use in the transportation of passengers and cargo, and for towing of sleds and trailers over a variety of terrains and environments. The terrains encountered include swampy and frozen muskeg, hummocks, rocks, light and deep snows, narrow trenches, elopes, small tree and brush areas, sand, mud, and vertical objects.

* 6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of vehicle required (see 1.2).
(c) Identification of appropriate service for painting and marking (see 3.1.1.1).
(d) Rustproofing, if required (see 3.1.1.2).
(e) If a battery heater is not required (see 3.4.1.1).
(f) Roof-mounted, adjustable spotlight, if required (see 3.4.2.2).
(g) Urethane filled tires, if required (see 3.4.6.1).
(h) If a spare tire assembly is not required (see 3.4.6.2).
(i) Mounted spare tire assembly, if required (see 3.4.6.2).
(j) Additional cab heater, if required for type II and III vehicles (see 3.4.12).
(k) Radiator shutters, if required (see 3.4.13).
(l) Front-mounted winch, if required (see 3.4.17).
(m) Rear-mounted winch, if required for type I vehicles (see 3.4.17).
(n) Mounted gasoline can, if required (see 3.4.18).
(o) Fire extinguisher, if required (see 3.4.20).
(p) Fold-up, bench type seats, if required for type II vehicles (see 3.5.2.1).
(q) Escape hatch, if required (see 3.5.4).

* 6.3 Subject term (key word) listing.

Carrier, all terrain
Carrier, cargo and passenger
Carrier, flatbed
Carrier, full tracked
Tracked vehicle, commercial
Tracked vehicle, nontactical.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.

6.4 Changes from previous issue. The margins of this specification are marked with asterisks (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content regardless of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AT
Navy - YD

Preparing activity:
Army - AT

Project No. 2350-0387

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:32Z
Check the source to verify that this is the current version before use.