MILITARY SPECIFICATION

CARTRIDGE, 60MM, ILLUMINATING, XM721 LOADING, ASSEMBLING, AND PACKING

This Amendment forms a part of Military Specification MIL-C-70714 (AR), dated 28 August 1987 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add "(M721)" after "XM721"; and wherever XM721 appears in the specification.

PAGE 2

2.1.2, Government drawings: PRODUCT AND PACKAGING DRAWINGS: Change "XM776" to "M776"; and wherever XM776 appears in the specification.

INSPECTION EQUIPMENT DRAWINGS: Delete "7297287 - Chamber Gage" and "7257965 - Limit Check Gage" and add "7256348 - Alignment Gage."

PAGE 6

Table II, Examination or test: Change "Fast" to "First" and change under cartridge examination, the sample size (2 places) from "50" to "176"

PAGE 8

4.4.2.1, Major 107: Delete in its entirety.

PAGE 9

4.4.2.2, Major 103: Delete in its entirety.

PAGE 12

4.4.2.5, Major 101: Delete inspection method "Gage" and substitute "7256348"

AMSC N/A FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.8, Title: Change "Contained" to "Container"

PAGE 17

4.4.2.9, Title: Change "Contained" to "Container"

PAGE 20

4.4.3.5, Delete first sentence in its entirety and substitute the following:

"One hundred and seventy-six (176) sample cartridges shall be selected for first article testing and fifty sample cartridges shall be selected for production lot testing. The cartridges for first article testing shall be separated into three groups; one group (48 samples) conditioned for 24 hours at plus 145°F ± 2.5°F, one group (80 samples) conditioned for 24 hours at plus 70°F ± 2.5°F, and one group (48 samples) conditioned for 24 hours at minus 50° ± 2.5°F. Each group shall be separated into equal subgroups; one subgroup tested at charge zone 1 and one subgroup tested at charge zone 4. The cartridges for production lot testing shall be conditioned for 24 hours at plus 70°F ± 2.5°F."

PAGE 21

4.4.3.5.1, Delete paragraph in its entirety and substitute the following:

"4.4.3.5.1 Overall acceptance criteria. In addition to the individual accept/reject criteria of 4.4.3.5, the first article sample shall be rejected if a total of five or more major defects occur. The production lot sample shall be rejected if a total of three or more major defects occur."

PAGE 24

4.4.5.7, Line 19: Delete sentence starting with "the cartridges shall be conditioned ... "

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A447)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.