INCH-POUND

MIL-C-70714 (AR)
AMENDMENT 3
26 December 1990
SUPERSEDING
AMENDMENT 2
27 July 1990

MILITARY SPECIFICATION

CARTRIDGE, 60MM, ILLUMINATING, M721
LOADING, ASSEMBLING, AND PACKING

This Amendment forms a part of Military Specification MIL-C-70714 (AR), dated 28 August 1987 and is approved for use within the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add "(M721)" after "XM721"; and wherever XM721 appears in the specification.

PAGE 2

2.1.2, Government drawings: PRODUCT AND PACKAGING DRAWINGS: Change "XM776" to "M776"; and wherever XM776 appears in the specification.

INSPECTION EQUIPMENT DRAWINGS: Delete "7297287 - Chamber Gage" and "7257965 - Limit Check Gage" and add "7256348 - Alignment Gage."

PAGE 4

3.5.6, fuze times: Change, "19.0" to "21.0" (2 places) and "26.0" to "27.0" (2 places).

PAGE 6

Table II, Examination or test: Change "Fast" to "First" and change under cartridge examination, the sample size (2 places) from "50" to "176."

PAGE 8

4.4.2.1, Major 107: Delete in its entirety.

4.4.2.1, Add new major 108 as follows:

"108 Compression pad(s) missing or improperly placed... 0.40%...3.2...Visual."

AMSC N/A FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

PAGE 9

4.4.2.2., Major 103: Delete in its entirety.

PAGE 10

4.4.2.3, Major 106: Change "Visual" to "Gage."

PAGE 12

4.4.2.5, Major 101: Delete inspection method "Gage" and substitute "7256348."

* 4.4.2.5, Major 108: Delete inspection method "Visual" and substitute "Gage."

4.4.2.5, Major 109 and 110 and Note 1: Delete in their entirety.

PAGE 16

4.4.2.8, Title: Change "Contained" to "Container."

PAGE 17

4.4.2.9, Title: Change "Contained" to "Container."

PAGE 18

4.4.3.2.1.1, Change "85" to "200."

PAGE 19

4.4.3.3, Last sentence: Delete end of sentence as follows:

"made on the applicable...the rejected production."

PAGE 20

4.4.3.5, Delete first sentence in its entirety and substitute the following:

"One hundred and seventy-six (176) sample cartridges shall be selected for first article testing and fifty sample cartridges shall be selected for production lot testing. The cartridges for first article testing shall be separated into three groups; one group (48 samples) conditioned for 24 hour sat plus 145°F ±2.5°F, one group (80 samples) conditioned

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

for 24 hours at plus 70°F ±2.5°F, and one group (48 samples) conditioned for 24 hours at minus 50°F ± 2.5°F. Each group shall be separated into equal subgroups; one subgroup tested at charge zone 1 and one subgroup tested at charge zone 4. The cartridges for production lot testing shall be conditioned for 24 hours at plus 70°F ±2.5°F."

PAGE 21

4.4.3.5.1, Delete paragraph in its entirety and substitute the following:

"4.4.3.5.1 Overall acceptance criteria. In addition to the individual accept/reject criteria of 4.4.3.5, the first article sample shall be rejected if a total of five or more major defects occur. The production lot sample shall be rejected if a total of three or more major defects occur."

4.4.3.6, Delete in its entirety.

PAGE 24

4.4.5.7, Line 19: Delete sentence starting with "the cartridges shall be conditioned..."

4.4.5.7, test settings: Change "19.0" to "21.0" and "26.0" to "27.0."

* 4.4.5.7, add to paragraph as follows:

"Meteorological data should be checked prior to and during testing. If the wind conditions exceed the TECOM firing table TOP thresholds or following criteria, then the test should be halted until the conditions are favorable.

a. When firing to maximum ordinates below 1,500 meters:

1. Surface winds exceed 10 knots.

2. Gust winds exceed 5 knots.

b. When firing to maximum ordinates above 1,500 meters.

1. Surface winds exceed 20 knots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

2. If the wind speed changes by more than 15 knots or the wind direction changes by 800 mils when compared to two successive rawinsondes at a constant height. If the directional change exceeds 800 mils but the wind speed is less than 5 knots at the comparison height, firing may continue."

PAGE 25

4.4.5.8, Delete in its entirety.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A488)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.