MILITARY SPECIFICATION

LAUNCHER FOR ROCKET, HE, 66MM,
ANTI-TANK, M72, ASSEMBLY AND PACKING

This amendment forms a part of Military Specification MIL-L-60004A (MU), dated 13 June 1966, and is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 3

3.5.3, line 5: Delete "15 pounds" and substitute "19 pounds."

PAGE 22

4.3.2.39, Critical Defects: Add the following:

"2. Wall thickness, minimum ... Gage 40012."

PAGE 24

4.3.2.44, Critical Defects: Delete "None defined" and add the following:

"1. Wall thickness test marking missing ... Visual 45020."

PAGE 30

4.4.5, line 10: Delete "applied to the vail handle" and substitute "applied to the rear sight cover."

FSC: 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.

4.4.6.1: Delete in its entirety and substitute the following:

"4.4.6.1 Safe position (non-functioning). With the trigger safety handle in the "ON" position, the specified load shall be applied to the trigger in a direction perpendicular to the top surface of the trigger housing. The trigger safety shall be moved to the fully "OFF" position and returned to the"ON" position and the non-functioning load applied as before. The assembly shall be classed defective if the firing pin is released."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1340-A604

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:02Z
Check the source to verify that this is the current version before use.