MILITARY SPECIFICATION

TAPE READER: 10526192

This amendment forms a part of Military Specification MIL-T-60171(MU), dated 10 March 1965.

Paragraph 3.2.13: Change "Tape life" to "Tape reader life".

Paragraph 3.5.3(a) line 1: Delete "The free running speed at 72°F and nominal voltage" and substitute "The free running speed at standard ambient temperatures (60°F - 90°F) and 31 ± 7 vdc".

Following paragraph 4.1.1, add paragraphs 4.12, 4.1.2.1 and 4.1.2.2.

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) units manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected and a record of this inspection, including certificates of conformance for materials shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.2.3: Add the following sentence: "No lots shall be accepted until control samples have been satisfactorily tested."

Paragraph 4.3.2: Delete first sentence and substitute:

"The units shall be selected at random by a Government representative

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.

as control samples from each three (3) months production or portion thereof as follows:

3 Units per first 100 produced
5 units per 200
7 units per 300
9 units per 400
10 units per 500
12 units per 700
15 units per 1000
and 2 units for each 100 items produced in excess of 1000."

Paragraph 4.5.2.6 Tape life.- Delete and substitute:

"4.5.2.6 Tape reader life.- Prior to final acceptance, tape readers shall be randomly selected as specified in 4.3.2 and shall be operated as required to pass an eight level, thirty-six inch linear looped tape through the readers at maximum voltage (38V) for 500 hours. The tape readers shall run without major over-haul and only with normal maintenance. Upon completion of the life tests, the tape readers shall be tested to determine compliance with 4.5.3."

Paragraph 4.5.3.2: Delete and substitute the following:

"4.5.3.2 Operating speed.

a. With the tape reader operating as specified in 4.5.3.1, determine compliance with 3.5.3 by measuring the free running speed using a premeasured length of tape. Measure the length of time the tape passes through the tape reader by means of standard measuring equipment. The free running speed at standard ambient temperatures (60 - 90°F), with 24 vdc applied shall be at least 20 code lines per second. With 38 vdc applied, the running speed shall not exceed 35 code lines per second.

b. The free running speed at -40°F, with 24 vdc applied shall be at least 15 code lines per second. At +135°F, with 38 vdc applied, the free running speed shall not exceed 45 code lines per second.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A163

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:14Z
Check the source to verify that this is the current version before use.